

Package ‘DOSE’

October 12, 2021

Type Package

Title Disease Ontology Semantic and Enrichment analysis

Version 3.18.3

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description This package implements five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively for measuring semantic similarities among DO terms and gene products. Enrichment analyses including hypergeometric model and gene set enrichment analysis are also implemented for discovering disease associations of high-throughput biological data.

Depends R (>= 3.5.0)

Imports AnnotationDbi, BiocParallel, DO.db, fgsea, ggplot2, GOSemSim (>= 2.0.0), methods, qvalue, reshape2, stats, utils

Suggests prettydoc, clusterProfiler, knitr, rmarkdown, org.Hs.eg.db, testthat

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

Encoding UTF-8

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/GuangchuangYu/DOSE/issues>

biocViews Annotation, Visualization, MultipleComparison, GeneSetEnrichment, Pathways, Software

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/DOSE>

git_branch RELEASE_3_13

git_last_commit f01fef4

git_last_commit_date 2021-09-30

Date/Publication 2021-10-12

Author Guangchuang Yu [aut, cre],
 Li-Gen Wang [ctb],
 Vladislav Petyuk [ctb],
 Giovanni Dall'Olio [ctb],
 Erqiang Hu [ctb]

R topics documented:

DOSE-package	3
clusterSim	3
compareClusterResult-class	4
computeIC	5
DataSet	5
doSim	6
enrichDGN	6
enrichDGNv	7
enrichDO	9
enricher_internal	10
enrichNCG	11
enrichResult-class	12
EXTID2NAME	13
gene2DO	13
geneID	14
geneInCategory	14
geneSim	15
gseaResult-class	16
GSEA_internal	16
gseDGN	17
gseDO	18
gseNCG	19
gsfilter	20
mclusterSim	21
parse_ratio	21
rebuildAnnoData	22
setReadable	22
show	23
simplot	24
summary	25
theme_dose	25

Index

27

DOSE-package	<i>Disease Ontology Semantic and Enrichment analysis Implemented five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively for measuring DO semantic similarities, and hypergeometric test for enrichment analysis.</i>
--------------	--

Description

This package is designed to estimate DO-based semantic similarity measurement and enrichment analysis.

Details

Package:	DOSE
Type:	Package
Version:	2.3.5
Date:	2-27-2012
biocViews:	Bioinformatics, Annotation
Depends:	
Imports:	methods, AnnotationDbi, DO.db
Suggests:	clusterProfiler, GOSemSim
License:	Artistic-2.0

Author(s)

Guangchuang Yu, Li-Gen Wang

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com>

See Also

[enrichResult](#)

clusterSim	<i>clusterSim</i>
------------	-------------------

Description

semantic similarity between two gene clusters

Usage

```
clusterSim(cluster1, cluster2, measure = "Wang", combine = "BMA")
```

Arguments

cluster1	a vector of gene IDs
cluster2	another vector of gene IDs
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining

Details

given two gene clusters, this function calculates semantic similarity between them.

Value

similarity

Author(s)

Yu Guangchuang

Examples

```
cluster1 <- c("835", "5261", "241", "994")
cluster2 <- c("307", "308", "317", "321", "506", "540", "378", "388", "396")
clusterSim(cluster1, cluster2)
```

compareClusterResult-class

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Description

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Slots

compareClusterResult cluster comparing result
 geneClusters a list of genes
 fun one of groupGO, enrichGO and enrichKEGG
 gene2Symbol gene ID to Symbol
 keytype Gene ID type
 readable logical flag of gene ID in symbol or not.
 .call function call
 termsim Similarity between term
 method method of calculating the similarity between nodes

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[enrichResult](#)

computeIC

compute information content

Description

compute information content

Usage

```
computeIC(ont = "DO", organism = "human")
```

Arguments

ont	"DO"
organism	"human"

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

DataSet

Datasets

Description

Information content and DO term to entrez gene IDs mapping

doSim

*doSim***Description**

measuring similarities between two DO term vectors.

Usage

```
doSim(DOID1, DOID2, measure = "Wang")
```

Arguments

DOID1	DO term vector
DOID2	DO term vector
measure	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".

Details

provide two DO term vectors, this function will calculate their similarities.

Value

score matrix

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

enrichDGN

Enrichment analysis based on the DisGeNET (<http://www.disgenet.org/>)

Description

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Usage

```
enrichDGN(  
  gene,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2,  
  readable = FALSE  
)
```

Arguments

gene	a vector of entrez gene id
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

References

Janet et al. (2015) DisGeNET: a discovery platform for the dynamical exploration of human diseases and their genes. *Database* bav028 <http://database.oxfordjournals.org/content/2015/bav028.long>

enrichDGNv

enrichDGN

Description

Enrichment analysis based on the DisGeNET (<http://www.disgenet.org/>)

Usage

```
enrichDGNv(  
  snp,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2,  
  readable = FALSE  
)
```

Arguments

snp	a vector of SNP
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Details

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

References

Janet et al. (2015) DisGeNET: a discovery platform for the dynamical exploration of human diseases and their genes. *Database* bav028 <http://database.oxfordjournals.org/content/2015/bav028.long>

enrichDO	<i>DO Enrichment Analysis</i>
----------	-------------------------------

Description

Given a vector of genes, this function will return the enrichment DO categories with FDR control.

Usage

```
enrichDO(  
  gene,  
  ont = "DO",  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2,  
  readable = FALSE  
)
```

Arguments

gene	a vector of entrez gene id
ont	one of DO or DOLite.
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

See Also

[enrichResult-class](#)

Examples

```
data(geneList)
gene = names(geneList)[geneList > 1]
yy = enrichDO(gene, pvalueCutoff=0.05)
summary(yy)
```

enricher_internal	<i>enrich.internal</i>
-------------------	------------------------

Description

internal method for enrichment analysis

Usage

```
enricher_internal(
  gene,
  pvalueCutoff,
  pAdjustMethod = "BH",
  universe = NULL,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  USER_DATA
)
```

Arguments

gene	a vector of entrez gene id.
pvalueCutoff	Cutoff value of pvalue.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	cutoff of qvalue
USER_DATA	ontology information

Details

using the hypergeometric model

Value

A enrichResult instance.

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

enrichNCG

enrichNCG

Description

Enrichment analysis based on the Network of Cancer Genes database (<http://ncg.kcl.ac.uk/>)

Usage

```
enrichNCG(  
  gene,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2,  
  readable = FALSE  
)
```

Arguments

gene	a vector of entrez gene id
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Details

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

enrichResult-class	<i>Class "enrichResult" This class represents the result of enrichment analysis.</i>
--------------------	--

Description

Class "enrichResult" This class represents the result of enrichment analysis.

Slots

result enrichment analysis
 pvalueCutoff pvalueCutoff
 pAdjustMethod pvalue adjust method
 qvalueCutoff qvalueCutoff
 organism only "human" supported
 ontology biological ontology
 gene Gene IDs
 keytype Gene ID type
 universe background gene
 gene2Symbol mapping gene to Symbol
 geneSets gene sets
 readable logical flag of gene ID in symbol or not.
 termsim Similarity between term
 method method of calculating the similarity between nodes

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[enrichDO](#)

EXTID2NAME	<i>EXTID2NAME</i>
------------	-------------------

Description

mapping gene ID to gene Symbol

Usage

EXTID2NAME(OrgDb, geneID, keytype)

Arguments

OrgDb	OrgDb
geneID	entrez gene ID
keytype	keytype

Value

gene symbol

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

gene2DO	<i>convert Gene ID to DO Terms</i>
---------	------------------------------------

Description

provide gene ID, this function will convert to the corresponding DO Terms

Usage

gene2DO(gene)

Arguments

gene	entrez gene ID
------	----------------

Value

DO Terms

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

geneID	<i>geneID generic</i>
--------	-----------------------

Description

geneID generic

Usage

geneID(x)

Arguments

x enrichResult object

Value

'geneID' return the 'geneID' column of the enriched result which can be converted to data.frame via 'as.data.frame'

Examples

```
data(geneList, package="DOSE")
de <- names(geneList)[1:100]
x <- enrichDO(de)
geneID(x)
```

geneInCategory	<i>geneInCategory generic</i>
----------------	-------------------------------

Description

geneInCategory generic

Usage

geneInCategory(x)

Arguments

x enrichResult

Value

'geneInCategory' return a list of genes, by splitting the input gene vector to enriched functional categories

Examples

```
data(geneList, package="DOSE")
de <- names(geneList)[1:100]
x <- enrichDO(de)
geneInCategory(x)
```

*geneSim**geneSim*

Description

measuring similarities between two gene vectors.

Usage

```
geneSim(geneID1, geneID2 = NULL, measure = "Wang", combine = "BMA")
```

Arguments

geneID1	entrez gene vector
geneID2	entrez gene vector
measure	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple DO terms associated with gene/protein.

Details

provide two entrez gene vectors, this function will calculate their similarity.

Value

score matrix

Author(s)

Guangchuang Yu <http://ygc.name>

gseaResult-class	<i>Class "gseaResult" This class represents the result of GSEA analysis</i>
------------------	---

Description

Class "gseaResult" This class represents the result of GSEA analysis

Slots

result GSEA analysis
 organism organism
 setType setType
 geneSets geneSets
 geneList order rank geneList
 keytype ID type of gene
 permScores permutation scores
 params parameters
 gene2Symbol gene ID to Symbol
 readable whether convert gene ID to symbol

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

GSEA_internal	<i>GSEA_internal</i>
---------------	----------------------

Description

generic function for gene set enrichment analysis

Usage

```
GSEA_internal(
  geneList,
  exponent,
  minGSSize,
  maxGSSize,
  eps,
  pvalueCutoff,
  pAdjustMethod,
  verbose,
  seed = FALSE,
```



```

    USER_DATA,
    by = "fgsea",
    ...
  )

```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	p value Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	set seed inside the function to make result reproducible. FALSE by default.
USER_DATA	annotation data
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseDGN

DisGeNET Gene Set Enrichment Analysis

Description

perform gsea analysis

Usage

```

gseDGN(
  geneList,
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",

```

```

    verbose = TRUE,
    seed = FALSE,
    by = "fgsea",
    ...
)

```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseDO

DO Gene Set Enrichment Analysis

Description

perform gsea analysis

Usage

```

gseDO(
  geneList,
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  verbose = TRUE,
  seed = FALSE,
  by = "fgsea",
  ...
)

```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseNCG

NCG Gene Set Enrichment Analysis

Description

perform gsea analysis

Usage

```
gseNCG(
  geneList,
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  verbose = TRUE,
  seed = FALSE,
  by = "fgsea",
  ...
)
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gsfilter

gsfilter

Description

filter enriched result by gene set size or gene count

Usage

```
gsfilter(x, by = "GSSize", min = NA, max = NA)
```

Arguments

x	instance of enrichResult or compareClusterResult
by	one of 'GSSize' or 'Count'
min	minimal size
max	maximal size

Value

update object

Author(s)

Guangchuang Yu

mclusterSim	<i>mclusterSim</i>
-------------	--------------------

Description

Pairwise semantic similarity for a list of gene clusters

Usage

```
mclusterSim(clusters, measure = "Wang", combine = "BMA")
```

Arguments

- clusters A list of gene clusters
- measure one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".
- combine One of "max", "avg", "rmax", "BMA" methods, for combining semantic similarity scores of multiple DO terms associated with gene/protein.

Value

similarity matrix

Author(s)

Yu Guangchuang

Examples

```
cluster1 <- c("835", "5261", "241")
cluster2 <- c("578", "582")
cluster3 <- c("307", "308", "317")
clusters <- list(a=cluster1, b=cluster2, c=cluster3)
mclusterSim(clusters, measure="Wang")
```

parse_ratio	<i>parse_ratio</i>
-------------	--------------------

Description

parse character ratio to double value, such as 1/5 to 0.2

Usage

```
parse_ratio(ratio)
```

Arguments

ratio character vector of ratio to parse

Value

A numeric vector (double) of parsed ratio

Author(s)

Guangchuang Yu

rebuildAnnoData	<i>rebuilding annotation data</i>
-----------------	-----------------------------------

Description

rebuilding entrez and DO mapping datasets

Usage

```
rebuildAnnoData(file)
```

Arguments

file do_rif.human.txt

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

setReadable	<i>setReadable</i>
-------------	--------------------

Description

mapping geneID to gene Symbol

Usage

```
setReadable(x, OrgDb, keyType = "auto")
```

Arguments

x	enrichResult Object
OrgDb	OrgDb
keyType	keyType of gene

Value

enrichResult Object

Author(s)

Yu Guangchuang

show	<i>show method</i>
------	--------------------

Description

- show method for gseaResult instance
- show method for enrichResult instance

Usage

- show(object)
- show(object)

Arguments

- object A enrichResult instance.

Value

- message
- message

Author(s)

- Guangchuang Yu <https://guangchuangyu.github.io>
- Guangchuang Yu <https://guangchuangyu.github.io>

`simplot`*simplot*

Description

plotting similarity matrix

Usage

```
simplot(  
  sim,  
  xlab = "",  
  ylab = "",  
  color.low = "white",  
  color.high = "red",  
  labs = TRUE,  
  digits = 2,  
  labs.size = 3,  
  font.size = 14  
)
```

Arguments

<code>sim</code>	similarity matrix
<code>xlab</code>	xlab
<code>ylab</code>	ylab
<code>color.low</code>	color of low value
<code>color.high</code>	color of high value
<code>labs</code>	logical, add text label or not
<code>digits</code>	round digit numbers
<code>labs.size</code>	lable size
<code>font.size</code>	font size

Value

ggplot object

Author(s)

Yu Guangchuang

summary	<i>summary method</i>
---------	-----------------------

Description

summary method for gseaResult instance
summary method for enrichResult instance

Usage

```
summary(object, ...)  
  
summary(object, ...)
```

Arguments

object	A enrichResult instance.
...	additional parameter

Value

A data frame
A data frame

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>
Guangchuang Yu <http://guangchuangyu.github.io>

theme_dose	<i>theme_dose</i>
------------	-------------------

Description

ggplot theme of DOSE

Usage

```
theme_dose(font.size = 14)
```

Arguments

font.size	font size
-----------	-----------

Value

ggplot theme

Examples

```
library(ggplot2)
qplot(1:10) + theme_dose()
```

Index

- * **classes**
 - compareClusterResult-class, 4
 - enrichResult-class, 12
 - gseaResult-class, 16
- * **datasets**
 - DataSet, 5
- * **manip**
 - enrichDO, 9
 - enricher_internal, 10
 - gseDGN, 17
 - gseDO, 18
 - gseNCG, 19
- * **package**
 - DOSE-package, 3

clusterSim, 3

compareClusterResult-class, 4

computeIC, 5

DataSet, 5

DGN_EXTID2PATHID (DataSet), 5

DGN_PATHID2EXTID (DataSet), 5

DGN_PATHID2NAME (DataSet), 5

D02ALLEG (DataSet), 5

D02EG (DataSet), 5

D0IC (DataSet), 5

DOLite2EG (DataSet), 5

DOLiteTerm (DataSet), 5

DOSE (DOSE-package), 3

DOSE-package, 3

doSim, 6

dotbl (DataSet), 5

EG2ALLDO (DataSet), 5

EG2DO (DataSet), 5

EG2DOLite (DataSet), 5

enrichDGN, 6

enrichDGNv, 7

enrichDO, 9, 12

enricher_internal, 10

enrichNCG, 11

enrichResult, 3, 5

enrichResult-class, 12

EXTID2NAME, 13

gene2DO, 13

geneID, 14

geneInCategory, 14

geneList (DataSet), 5

geneSim, 15

GSEA_internal, 16

gseahResult-class (gseaResult-class), 16

gseaResult-class, 16

gseDGN, 17

gseDO, 18

gseNCG, 19

gsfilter, 20

mclusterSim, 21

NCG_EXTID2PATHID (DataSet), 5

NCG_PATHID2EXTID (DataSet), 5

NCG_PATHID2NAME (DataSet), 5

parse_ratio, 21

plot, compareClusterResult-method
(compareClusterResult-class), 4

rebuildAnnoData, 22

setReadable, 22

show, 23

show, compareClusterResult-method
(compareClusterResult-class), 4

show, enrichResult-method
(enrichResult-class), 12

show, gseaResult-method
(gseaResult-class), 16

simplot, 24

summary, 25

summary, compareClusterResult-method
(compareClusterResult-class), [4](#)

summary, enrichResult-method
(enrichResult-class), [12](#)

summary, gseaResult-method
(gseaResult-class), [16](#)

theme_dose, [25](#)

VDGN_EXTID2PATHID (DataSet), [5](#)

VDGN_PATHID2EXTID (DataSet), [5](#)

VDGN_PATHID2NAME (DataSet), [5](#)