

Package ‘InterCellar’

October 12, 2021

Title InterCellar: an R-Shiny app for interactive analysis and exploration of cell-cell communication in single-cell transcriptomics

Version 1.0.0

Description InterCellar is implemented as an R/Bioconductor Package containing a Shiny app that allows users to interactively analyze cell-cell communication from scRNA-seq data. Starting from precomputed ligand-receptor interactions, InterCellar provides filtering options, annotations and multiple visualizations to explore clusters, genes and functions. Finally, the user can define interaction-pairs modules and link them to significant functional terms from Pathways or Gene Ontology.

License MIT + file LICENSE

Imports config, golem, shiny, DT, shinydashboard, shinyFiles, shinycssloaders, data.table, fs, dplyr, tidyr, circlize, colourpicker, dendextend, factoextra, ggplot2, plotly, plyr, shinyFeedback, shinyalert, tibble, umap, visNetwork, wordcloud2, readxl, htmlwidgets, colorspace, signal, scales, htmltools, ComplexHeatmap, grDevices, stats, tools, utils, biomaRt, rlang, fmsb

Encoding UTF-8

RoxygenNote 7.1.1

Suggests testthat (>= 3.0.0), knitr, rmarkdown, glue, graphite, processx, attempt, BiocStyle, igraph

Config/testthat/edition 3

URL <https://github.com/martaint/InterCellar>

BugReports <https://github.com/martaint/InterCellar/issues>

VignetteBuilder knitr

biocViews Software, SingleCell, Visualization, GO, Transcriptomics

Depends R (>= 4.1)

git_url <https://git.bioconductor.org/packages/InterCellar>

git_branch RELEASE_3_13

git_last_commit 094f1da

git_last_commit_date 2021-05-19

Date/Publication 2021-10-12

Author Marta Interlandi [cre, aut] (<<https://orcid.org/0000-0002-6863-2552>>)

Maintainer Marta Interlandi <marta.interlandi01@gmail.com>

R topics documented:

annotateGO	3
annotatePathways	4
buildPairsbyFunctionMatrix	4
checkLL_RR	5
circlePlot	5
combineAnnotations	6
createBarPlot1_ggplot	6
createBarPlot2_CV	7
createBarPlot2_ggplot	7
createBarPlot_CV	8
createNetwork	8
dendroIntPairModules	9
elbowPoint	9
ensemblLink	10
getBack2BackBarplot	10
getBarplotDF	11
getBarplotDF2	11
getClusterNames	12
getClusterNetwork	12
getClusterSize	13
getDotPlot_selInt	13
getGeneTable	14
getGObiomaRt	14
getHitsf	15
getIntFlow	15
getNtermsBYdb	16
getNumLR	16
getRadarPlot	17
getRankedTerms	17
getSignificantFunctions	18
getSunburst	18
getUMAPipModules	19
getUniqueDotplot	20
goLink	20
input.data	21
read.CPDBv2	21
read.customInput	22
read.SCsignalR	22

annotateGO

3

run_app

23

subsetFuncMatBYFlow

24

swap.RLint

24

uniprotLink

25

updateInputLR

25

Index

26

annotateGO	<i>Perform GO annotation of input data</i>
------------	--

Description

Perform GO annotation of input data

Usage

```
annotateGO(  
  input_select_ensembl,  
  input_go_evidence_exclude,  
  input_go_sources_checkbox,  
  input.data  
)
```

Arguments

- input_select_ensembl

ensembl version selected by user
- input_go_evidence_exclude

evidence codes to exclude by user
- input_go_sources_checkbox

GO sources to use by user
- input.data

preprocessed input data

Value

GO_annotation

annotatePathways	<i>Annotate pathways for input data</i>
------------------	---

Description

Annotate pathways for input data

Usage

```
annotatePathways(selected.db, input.data)
```

Arguments

selected.db	pathways sources to use
input.data	filtered input data

Value

pathways_annotation

buildPairsbyFunctionMatrix	<i>Build binary matrix with int-pairs in rows, functions in cols</i>
----------------------------	--

Description

Build binary matrix with int-pairs in rows, functions in cols

Usage

```
buildPairsbyFunctionMatrix(functions_df)
```

Arguments

functions_df	annotated df (GO/path/combined)
--------------	---------------------------------

Value

binary matrix

checkLL_RR	<i>Manually change the annotation of L-L and R-R pairs</i>
------------	--

Description

Manually change the annotation of L-L and R-R pairs

Usage

```
checkLL_RR(input.data)
```

Arguments

input.data preprocessed table

Value

input.data

Examples

```
data(input.data)
checked.input.data <- checkLL_RR(input.data)
```

circlePlot	<i>Plot circle plot</i>
------------	-------------------------

Description

Plot circle plot

Usage

```
circlePlot(data, cluster_colors, ipm_color, int_flow, link.color)
```

Arguments

data subset of input data by flow / intpair module
cluster_colors global
ipm_color single color for chosen int-pair module
int_flow string specifying the flow
link.color string specifying variable by which to color links

Value

circle plot

combineAnnotations	<i>Combine GO annotation and pathways in a unique object</i>
--------------------	--

Description

Combine GO annotation and pathways in a unique object

Usage

```
combineAnnotations(GO_annotation, pathways_annotation)
```

Arguments

GO_annotation	data
pathways_annotation	data

Value

combined annotation dataframe

createBarPlot1_ggplot	<i>Create ggplot barplot to be saved in tiff</i>
-----------------------	--

Description

Create ggplot barplot to be saved in tiff

Usage

```
createBarPlot1_ggplot(barplotDF, input_cluster_selected_checkbox)
```

Arguments

barplotDF	dataframe with N interactions per cluster (auto/para)
input_cluster_selected_checkbox	checkbox input

Value

ggplot barplot

createBarPlot2_CV	Create barplot of number of interaction for selected cluster
-------------------	--

Description

Create barplot of number of interaction for selected cluster

Usage

```
createBarPlot2_CV(  
  barplotDF2,  
  input_cluster_selected_checkbox,  
  input_clust_barplot2  
)
```

Arguments

barplotDF2	dataframe with barplot data
input_cluster_selected_checkbox	selected clusters to keep
input_clust_barplot2	selected cluster to plot

Value

plotly fig

createBarPlot2_ggplot	Create ggplot barplot of Nint per cluster selected
-----------------------	--

Description

Create ggplot barplot of Nint per cluster selected

Usage

```
createBarPlot2_ggplot(  
  barplotDF2,  
  input_cluster_selected_checkbox,  
  input_clust_barplot2  
)
```

Arguments

barplotDF2 dataframe with barplot data
input_cluster_selected_checkbox
 selected clusters to keep
input_clust_barplot2
 selected cluster to plot

Value

ggplot barplot

createBarPlot_CV	<i>Create Barplot cluster-verse</i>
------------------	-------------------------------------

Description

Create Barplot cluster-verse

Usage

```
createBarPlot_CV(barplotDF, input_cluster_selected_checkbox)
```

Arguments

barplotDF dataframe with N interactions per cluster (auto/para)
input_cluster_selected_checkbox
 checkbox input

Value

plotly barplot

createNetwork	<i>Create Network of clusters</i>
---------------	-----------------------------------

Description

Create Network of clusters

Usage

```
createNetwork(data.filt.cluster)
```


Arguments

data.filt.cluster
filtered input data (by clusters)

Value

list containing nodes and edges for network

dendroIntPairModules	<i>Get dendrogram of int pair modules</i>
----------------------	---

Description

Get dendrogram of int pair modules

Usage

dendroIntPairModules(pairs_func_matrix)

Arguments

pairs_func_matrix
binary matrix pairs x functions

Value

list with dendrogram, hclust and umap

elbowPoint	<i>Determine the elbow point on a curve (from package akmedoids)</i>
------------	--

Description

Given a list of x, y coordinates on a curve, function determines the elbow point of the curve.

Usage

elbowPoint(x, y)

Arguments

x vector of x coordinates of points on the curve
y vector of y coordinates of points on the curve

Details

highlight the maximum curvature to identify the elbow point (credit: 'github.com/agentlans')

Value

an x, y coordinates of the elbow point.

ensemblLink	<i>Get html link to ensembl</i>
-------------	---------------------------------

Description

Get html link to ensembl

Usage

ensemblLink(ensembl)

Arguments

ensembl symbol

Value

html link to website

getBack2BackBarplot	<i>Get back-to-back barplot for 2 conditions comparison</i>
---------------------	---

Description

Get back-to-back barplot for 2 conditions comparison

Usage

getBack2BackBarplot(tab_c1, tab_c2, lab_c1, lab_c2)

Arguments

tab_c1	table from csv file (barplot#1) containing data for condition 1
tab_c2	table from csv file (barplot#1)containing data for condition 2
lab_c1	label for condition 1
lab_c2	label for condition 2

Value

ggplot object

getBarplotDF	<i>Get dataframe for plotting barplot (all clusters)</i>
--------------	--

Description

Get dataframe for plotting barplot (all clusters)

Usage

```
getBarplotDF(data.filt.bar, input_cluster_selected_checkbox)
```

Arguments

data.filt.bar filtered object (checkbox auto/para)
input_cluster_selected_checkbox
checkbox input

Value

dataframe with number of interactions per cluster auto/para

getBarplotDF2	<i>Get dataframe for barplot (by cluster)</i>
---------------	---

Description

Get dataframe for barplot (by cluster)

Usage

```
getBarplotDF2(filt.data, input_cluster_selected_checkbox, input_clust_barplot2)
```

Arguments

filt.data input data filtered in cluster-verse
input_cluster_selected_checkbox
selected clusters to keep
input_clust_barplot2
selected cluster to plot

Value

dataframe with num int per cluster

getClusterNames	<i>Get clusters names from initial input data</i>
-----------------	---

Description

Get clusters names from initial input data

Usage

```
getClusterNames(input.data)
```

Arguments

input.data	preprocessed input data
------------	-------------------------

Value

named list of clusters

Examples

```
data(input.data)
cluster_list <- getClusterNames(input.data)
```

getClusterNetwork	<i>Creating edges dataframe for network of clusters</i>
-------------------	---

Description

Creating edges dataframe for network of clusters

Usage

```
getClusterNetwork(input.data)
```

Arguments

input.data	preprocessed input data
------------	-------------------------

Value

edges dataframe

getClusterSize	<i>Get Clusters size</i>
----------------	--------------------------

Description

Get Clusters size

Usage

```
getClusterSize(cl, edges.df)
```

Arguments

cl	cluster name
edges.df	dataframe with edges for network

Value

sum of interactions for that cluster

getDotPlot_selInt	<i>Functions to plot DotPlots</i>
-------------------	-----------------------------------

Description

Functions to plot DotPlots

Usage

```
getDotPlot_selInt(  
  selected_tab,  
  clust.order,  
  low_color = "aquamarine",  
  high_color = "#131780"  
)
```

Arguments

selected_tab	table of selected rows from gene tableeeeeeee
clust.order	how to order clusters
low_color	of dotplot
high_color	of dotplot

Value

list with modified selected data and ggplot2 dotplot

getGeneTable	<i>Get table for gene-verse</i>
--------------	---------------------------------

Description

Get table for gene-verse

Usage

```
getGeneTable(input.data)
```

Arguments

input.data	preprocessed input data
------------	-------------------------

Value

gene table with unique intpairs (no connection to clusters)

Examples

```
data(input.data)
gene_table <- getGeneTable(input.data)
```

getGObiomaRt	<i>Connection to Ensembl via biomaRt to get GO terms</i>
--------------	--

Description

Connection to Ensembl via biomaRt to get GO terms

Usage

```
getGObiomaRt(input_select_ensembl, input.data)
```

Arguments

input_select_ensembl	chosen version of Ensembl
input.data	filtered input data

Value

dataframe with GO annotation

getHitsf	<i>Subfunction to calculate significant functions by permutation test</i>
----------	---

Description

Subfunction to calculate significant functions by permutation test

Usage

```
getHitsf(mat, gpModules_assign)
```

Arguments

mat	binary matrix of functional terms by int-pairs
gpModules_assign	assignment of intpairs to modules

Value

matrix with hits

getIntFlow	<i>Get subset of interactions corresponding to a certain viewpoint and flow</i>
------------	---

Description

Get subset of interactions corresponding to a certain viewpoint and flow

Usage

```
getIntFlow(vp, input.data, flow)
```

Arguments

vp	viewpoint cluster
input.data	preprocessed/filtered input data
flow	one among directed_out, directed_in or undirected

Value

subset of data

Examples

```
data(input.data)
caf_out <- getIntFlow(vp = "CAF", input.data, flow = "directed_out")
```

getNtermsBYdb	<i>Calculate number of terms of a database</i>
---------------	--

Description

Calculate number of terms of a database

Usage

```
getNtermsBYdb(annotation)
```

Arguments

annotation	data from either pathways, GO or combined
------------	---

Value

number of terms by dataset

getNumLR	<i>Get number of unique ligands and receptors</i>
----------	---

Description

Get number of unique ligands and receptors

Usage

```
getNumLR(gene.table, type)
```

Arguments

gene.table	gene table of unique int-pairs
type	either L or R

Value

number of L or R genes

getRadarPlot	<i>Get radar plot of relative numbers of interactions for a certain cell type</i>
--------------	---

Description

Get radar plot of relative numbers of interactions for a certain cell type

Usage

```
getRadarPlot(tab_c1, tab_c2, lab_c1, lab_c2, cell_name)
```

Arguments

tab_c1	table from csv file (barplot#2) containing data for condition 1
tab_c2	table from csv file (barplot#2) containing data for condition 2
lab_c1	label for condition 1
lab_c2	label for condition 2
cell_name	label of cell type of interest

Value

plot

getRankedTerms	<i>Get table with ranked functional terms</i>
----------------	---

Description

Get table with ranked functional terms

Usage

```
getRankedTerms(data.fun.annot, gene.table)
```

Arguments

data.fun.annot	annotated df (GO/path/combined)
gene.table	of unique intpairs

Value

table with ranking

```
getSignificantFunctions
```

Calculate significant function per intpair module

Description

Calculate significant function per intpair module

Usage

```
getSignificantFunctions(
  subGenePairs_func_mat,
  gpModules_assign,
  rank.terms,
  input_maxPval
)
```

Arguments

subGenePairs_func_mat	subset of binary mat
gpModules_assign	assignment of intpairs to modules
rank.terms	table of ranked functions
input_maxPval	threshold of significance

Value

table with significant functions

```
getSunburst
```

Get Sunburst plot of selected functional terms

Description

Get Sunburst plot of selected functional terms

Usage

```
getSunburst(sel.data, func_selected, int_p_fun, cluster.colors)
```

Arguments

`sel.data` dataframe of selected functions
`func_selected` the selected functional term
`int_p_fun` dataframe with int pairs annotated to this function
`cluster.colors` for plotting

Value

plotly figure

getUMAPipModules	<i>Get UMAP for IP modules</i>
------------------	--------------------------------

Description

Get UMAP for IP modules

Usage

```
getUMAPipModules(
  intPairs.dendro,
  gpModules_assign,
  gene.table,
  ipm_colors,
  input_ipM_UMAPcolors
)
```

Arguments

`intPairs.dendro` list output of dendrogram
`gpModules_assign` named vector of module assignment
`gene.table` unique intpairs table
`ipm_colors` for intpair modules
`input_ipM_UMAPcolors` user choice for coloring umap

Value

plotly umap

getUniqueDotplot	<i>Plot dotplot containing only unique int-pair/cluster pairs with many conditions</i>
------------------	--

Description

Plot dotplot containing only unique int-pair/cluster pairs with many conditions

Usage

```
getUniqueDotplot(data_dotplot)
```

Arguments

data_dotplot table with selected int_pairs for multiple conditions

Value

ggplot object

goLink	<i>Get GO link</i>
--------	--------------------

Description

Get GO link

Usage

```
goLink(go_id)
```

Arguments

go_id string

Value

html link to website

input.data

*Input Data example***Description**

A dataset obtained from Tirosh et al melanoma dataset, running CellPhoneDBv2. This data is generated by InterCellar running read.CPDBv2()

Usage

input.data

Format

A data frame with 5638 rows and 11 variables:

int_pair interaction pair name, geneA & geneB

geneA name, hgnc_symbol

geneB name, hgnc_symbol

typeA molecular type of geneA, either L (ligand) or R (receptor)

typeB molecular type of geneB, either L (ligand) or R (receptor)

clustA name of first cluster, either character or number

clustB name of second cluster, either character or number

score int-pair score as avg expression of geneA and geneB over clustA and clustB, decimal

p_value int-pair pvalue, decimal

annotation_strategy database from which the int-pair was retrieved

int.type either autocrine or paracrine

read.CPDBv2

*Read output from CellPhoneDB v2.***Description**

Output is a folder containing 4 .txt files - deconvoluted.txt: containing list of single genes and their mean expression in each cluster (not considered); - means.txt: containing list of interacting pairs with info regarding L/R, annotation strategy and mean value of all pairs over cluster couples. - pvalues.txt: same as means, but containing pvalue of each pair, for each cluster couple. - significant_means.txt: only means of those pairs that have pvalue < 0.05. Has one more column:rank. If the statistical analysis is not run, the folder would contain only deconvoluted and means

Usage

read.CPDBv2(folder)

Arguments

folder folder containing output

Value

input.data which is the pre-processed object with annotated L-R pairs

read.customInput	<i>Read custom input file and re-structure it with InterCellar format</i>
------------------	---

Description

Read custom input file and re-structure it with InterCellar format

Usage

read.customInput(tab, separator)

Arguments

tab custom input table
separator character that separates two elements of an interaction pair

Value

preprocessed table

read.SCSignalR	<i>Read output from SingleCellSignalR</i>
----------------	---

Description

SCSR description: the output folder is a collection of txt files, one for each clusters pair considered. The "paracrine" option looks for ligands expressed in cluster A and their associated receptors according to LRdb that are expressed in any other cluster but A. These interactions are labelled "paracrine". The interactions that involve a ligand and a receptor, both differentially expressed in their respective cell clusters according to the **edgeR** analysis performed by the **cluster_analysis()** function, are labelled "specific". The "autocrine" option searches for ligands expressed in cell cluster A and their associated receptors also expressed in A. These interactions are labelled "autocrine". Additionally, it searches for those associated receptors in the other cell clusters (not A) to cover the part of the signaling that is "autocrine" and "paracrine" simultaneously. These interactions are labelled "autocrine/paracrine". This file is a 4-column table: ligands, receptors, interaction types ("paracrine", "autocrine", "autocrine/paracrine" and "specific"), and the associated LRscore. InterCellar: rename autocrinelparacrine to paracrine

Usage

```
read.SCSignalR(folder)
```

Arguments

folder containing output from SingleCellSignalR, named cell-signaling

Value

input.data: preprocessed object with annotated L-R pairs

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

Description

Run the Shiny Application

Usage

```
run_app(reproducible = TRUE)
```

Arguments

reproducible boolean for setting a seed, making plots reproducible

Value

a running instance of InterCellar

Examples

```
## Not run:  
run_app()  
  
## End(Not run)
```

subsetFuncMatBYFlow	<i>Subset pairs-function matrix by selected flow</i>
---------------------	--

Description

Subset pairs-function matrix by selected flow

Usage

```
subsetFuncMatBYFlow(pairs_func_matrix, flow_df)
```

Arguments

pairs_func_matrix	binary
flow_df	subset of input data by flow

Value

subset of binary mat

swap.RLint	<i>Swaps interaction pairs that are R-L to L-R</i>
------------	--

Description

Swaps interaction pairs that are R-L to L-R

Usage

```
swap.RLint(RLint)
```

Arguments

RLint	subset of R-L interactions
-------	----------------------------

Value

input data with ordered L-R pairs and L-L/R-R

uniprotLink	<i>Get html link to uniprot</i>
-------------	---------------------------------

Description

Get html link to uniprot

Usage

```
uniprotLink(uniprot)
```

Arguments

uniprot	symbol
---------	--------

Value

html link to website

updateInputLR	<i>Function that orders all interaction pairs as L-R. Leaves unchanged the R-R and L-L</i>
---------------	--

Description

Function that orders all interaction pairs as L-R. Leaves unchanged the R-R and L-L

Usage

```
updateInputLR(input.data)
```

Arguments

input.data	uploaded data
------------	---------------

Value

ordered input data

Index

* datasets

input.data, [21](#)

annotateGO, [3](#)
annotatePathways, [4](#)

buildPairsbyFunctionMatrix, [4](#)

checkLL_RR, [5](#)
circlePlot, [5](#)
combineAnnotations, [6](#)
createBarPlot1_ggplot, [6](#)
createBarPlot2_CV, [7](#)
createBarPlot2_ggplot, [7](#)
createBarPlot_CV, [8](#)
createNetwork, [8](#)

dendroIntPairModules, [9](#)

elbowPoint, [9](#)
ensemblLink, [10](#)

getBack2BackBarplot, [10](#)
getBarplotDF, [11](#)
getBarplotDF2, [11](#)
getClusterNames, [12](#)
getClusterNetwork, [12](#)
getClusterSize, [13](#)
getDotPlot_selInt, [13](#)
getGeneTable, [14](#)
getGObiomaRt, [14](#)
getHitsf, [15](#)
getIntFlow, [15](#)
getNtermsBYdb, [16](#)
getNumLR, [16](#)
getRadarPlot, [17](#)
getRankedTerms, [17](#)
getSignificantFunctions, [18](#)
getSunburst, [18](#)
getUMAPipModules, [19](#)
getUniqueDotplot, [20](#)

goLink, [20](#)

input.data, [21](#)

read.CPDBv2, [21](#)
read.customInput, [22](#)
read.SCsignalR, [22](#)
run_app, [23](#)

subsetFuncMatBYFlow, [24](#)
swap.RLint, [24](#)

uniprotLink, [25](#)
updateInputLR, [25](#)