

Package ‘SynMut’

October 10, 2021

Type Package

Title SynMut: Designing Synonymously Mutated Sequences with Different Genomic Signatures

Version 1.8.0

Description There are increasing demands on designing virus mutants with specific dinucleotide or codon composition.

This tool can take both dinucleotide preference and/or codon usage bias into account while designing mutants.

It is a powerful tool for in silico designs of DNA sequence mutants.

License GPL-2

Encoding UTF-8

Suggests BiocManager, knitr, rmarkdown, testthat, devtools, prettydoc, glue

VignetteBuilder knitr

Imports seqinr, methods, Biostrings, stringr, BiocGenerics

RoxygenNote 6.1.1

Collate 'regioned_dna_Class.R' 'codon_mimic.R' 'input_seq.R' 'codon_random.R' 'codon_to.R' 'dinu_to.R' 'distance_analysis.R' 'region_related.R' 'seq_random.R' 'zzz.R'

biocViews SequenceMatching, ExperimentalDesign, Preprocessing

BugReports <https://github.com/Koohoko/SynMut/issues>

URL <https://github.com/Koohoko/SynMut>

git_url <https://git.bioconductor.org/packages/SynMut>

git_branch RELEASE_3_13

git_last_commit ea7c78c

git_last_commit_date 2021-05-19

Date/Publication 2021-10-10

Author Haogao Gu [aut, cre],
Leo L.M. Poon [led]

Maintainer Haogao Gu <hggu@connect.hku.hk>

R topics documented:

codon_dist	2
codon_mimic	3
codon_random	4
codon_to	5
dinu_dist	6
dinu_to	7
get_cu	8
get_dna	9
get_du	9
get_freq	10
get_nu	11
get_region	12
get_rscu	12
input_seq	13
regioned_dna-class	14
seq_random	15
Index	16

codon_dist	<i>Calculating the codon usage difference between sequences</i>
------------	---

Description

We use a least squares approach to estimate the codon usage difference between DNA sequences.

Usage

```
codon_dist(seq, ref)

## S4 method for signature 'ANY'
codon_dist(seq, ref)
```

Arguments

- seq the input DNA sequece of DNASTringSet or regioned_dna class.
- ref the reference DNA sequece of DNASTringSet or regioned_dna class.

Details

idea inspired by "Daniel Macedo de Melo Jorge, Ryan E. Mills, Adam S. Lauring, CodonShuffle: a tool for generating and analyzing synonymously mutated sequences, Virus Evolution, Volume 1, Issue 1, March 2015, vev012, <https://doi.org/10.1093/ve/vev012>"

Value

vector

Examples

```

filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)

mut.seq <- codon_random(rgd.seq)
codon_dist(mut.seq, rgd.seq)
mut.seq2 <- codon_random(rgd.seq, keep = TRUE)
codon_dist(mut.seq2, rgd.seq)

```

codon_mimic	<i>Mimic a target codon usage bias</i>
-------------	--

Description

Mutating the current DNA sequences in the regioned_dna object to mimic a target codon usage pattern.

Usage

```

codon_mimic(object, alt, ...)

## S4 method for signature 'regioned_dna,vector'
codon_mimic(object, alt)

## S4 method for signature 'regioned_dna,DNAStringSet'
codon_mimic(object, alt)

## S4 method for signature 'DNAStringSet,DNAStringSet'
codon_mimic(object, alt)

```

Arguments

object	regioned_dna object
alt	target codon usage vector or DNAStringSet object representing target codon usage
...	...

Details

The ideas for codon_mimic is similar to [codon_to](#): first extract the mutable regions and then do the mutation. However the codons in the fixed (not mutable) regions will also alter the final codon usage, thus we have to adjust for the fixed codons when introducing synonymous codons. The ideal design for codon_mimic is not unique as the swap between positions of the synonymous codons will not change the codon usage bias.

Details please refer to: <https://koohoko.github.io/SynMut/algorithm.html>

Value

regioned_dna

See Also

[input_seq](#), [codon_to](#), [codon_random](#), [dinu_to](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
target <- get_cu(rgd.seq)[2,]
new <- codon_mimic(rgd.seq, alt = target)
get_cu(new) - get_cu(rgd.seq)

target <- Biostrings::DNASTringSet("TTGAAAA-CTC-N--AAG")
new <- codon_mimic(rgd.seq, alt = target)
get_cu(new) - get_cu(rgd.seq)
get_freq(new) - get_freq(rgd.seq)
get_rscu(new) - get_rscu(rgd.seq)
```

codon_random	<i>Generate random synonymous mutations</i>
--------------	---

Description

Generating random synonymous mutations (in user-defined region), with optionally keeping/not keeping the original codon usage bias.

Usage

```
codon_random(object, n = 1, keep = FALSE, ...)

## S4 method for signature 'regioned_dna'
codon_random(object, n, keep)

## S4 method for signature 'DNASTringSet'
codon_random(object, n, keep)
```

Arguments

object	A regioned_dna object.
n	Optional n parameter specifying what proportion of the codons to be mutate. Default value: 1.
keep	Logical parameter controlling whether keeping the codon usage bias of the original sequence. Default value: FALSE.
...	...

Details

This method randomly sample synonymous codons for n propotion of every mutable codons in the sequences. This process will be likely to alter the codon usage bias of the original sequences. However the keep = TRUE argument help to preserve the codon usage bias. It is done via the synsequence function in seqinr package. The synsequence function essentially swaps the position of the synonymous codons without introducing new codons into the original sequences.

Value

A regioned_dna object containing the mutants; Or a DNASTringSet object if the input is a DNASTringSet object.

See Also

[input_seq](#), [dinu_to](#), [codon_to](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
set.seed(2019)
get_cu(codon_random(rgd.seq, n = 0.5))
get_cu(codon_random(rgd.seq))
```

codon_to

Maximize or minimize the usage of certain codon.

Description

Input string of a codon to either the "max.codon = " or "min.codon = " parameter to maximize or minimize the usage of certain codon in the sequence.

Usage

```
codon_to(object, max.codon = NA, min.codon = NA, ...)
```

```
## S4 method for signature 'regioned_dna'
codon_to(object, max.codon, min.codon)
```

Arguments

object	A regioned_dna object.
max.codon	A string of a codon.
min.codon	A string of a codon.
...	...

Details

The ideas for this function is simple. We first extract the mutable regions for every sequences, then mutated the synonymous codons of the input to the desired. There will be only one ideal design for the maximization problem, however there may be numerous comparable designs having the same minimal usage of certain codon, as we randomly sample synonymous codon for substitution when solving the minimization problem.

Value

A `regioned_dna` object.

See Also

[input_seq](#), [dinu_to](#), [codon_random](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(codon_to(rgd.seq, max.codon = "AAC")) - get_cu(rgd.seq)
get_cu(codon_to(rgd.seq, min.codon = "AAC")) - get_cu(rgd.seq)
```

dinu_dist

Calculating the dinucleotide usage difference between sequences

Description

We use a least squares approach to estimate the dinucleotide usage difference between DNA sequences

Usage

```
dinu_dist(seq, ref)

## S4 method for signature 'ANY'
dinu_dist(seq, ref)
```

Arguments

<code>seq</code>	the input DNA sequence of <code>DNAStringSet</code> or <code>regioned_dna</code> class.
<code>ref</code>	the reference DNA sequence of <code>DNAStringSet</code> or <code>regioned_dna</code> class.

Details

similar method that applied in "Daniel Macedo de Melo Jorge, Ryan E. Mills, Adam S. Luring, CodonShuffle: a tool for generating and analyzing synonymously mutated sequences, Virus Evolution, Volume 1, Issue 1, March 2015, vev012, <https://doi.org/10.1093/ve/vev012>"

Value

vector

Examples

```

filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)

mut.seq <- codon_random(rgd.seq)
dinu_dist(mut.seq, rgd.seq)

```

dinu_to

*Maximize or minimize the usage of certain dinucleotide.***Description**

Input string of a dinucleotide to either the "max.dinu = " or "min.codon = " parameter to maximize or minimize the usage of certain codon in the sequence. Using a greedy algorithm with priority given to dinucleotide12 or dinucleotide23.

Usage

```

dinu_to(object, max.dinu = NA, min.dinu = NA, keep = FALSE, ...)

```

```

## S4 method for signature 'regioned_dna'
dinu_to(object, max.dinu, min.dinu, keep)

```

Arguments

object	A regioned_dna object.
max.dinu	A string of a dinucleotide.
min.dinu	A string of a dinucleotide.
keep	A logical varibale stating if the codon usage of the original sequences should be keep. Default: False.
...	...

Details

The detail strategy for this function please refer to: <https://koohoko.github.io/SynMut/algorithm.html>

Value

regioned_dna

See Also

[input_seq](#), [codon_to](#), [codon_random](#), [codon_mimic](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_du(dinu_to(rgd.seq, max.dinu = "cg")) - get_du(rgd.seq)
get_du(dinu_to(rgd.seq, min.dinu = "AA")) - get_du(rgd.seq)
get_du(dinu_to(rgd.seq, max.dinu = "cg", keep = TRUE)) - get_du(rgd.seq)
get_cu(dinu_to(rgd.seq, max.dinu = "CG", keep = TRUE)) - get_cu(rgd.seq)
```

get_cu

Get codon usage matrix

Description

Access the codon usage matrix

Usage

```
get_cu(object, ...)
```

S4 method for signature 'regioned_dna'

```
get_cu(object)
```

S4 method for signature 'DNAStrngSet'

```
get_cu(object)
```

Arguments

object	regioned_dna / DNAStrngSet
...	...

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_nu](#), [get_du](#), [get_freq](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_cu(rgd.seq)
```

get_dna	<i>Get the DNASTringSet data</i>
---------	----------------------------------

Description

Access the DNA sequence data in DNASTringSet.

Usage

```
get_dna(object, ...)  
  
## S4 method for signature 'regioned_dna'  
get_dna(object)
```

Arguments

object	A regioned_dna object.
...	...

Value

DNASTringSet

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")  
rgd.seq <- input_seq(filepath)  
get_dna(rgd.seq)
```

get_du	<i>Get dinucleotide usage matrix</i>
--------	--------------------------------------

Description

Access the dinucleotide usage matrix

Usage

```
get_du(object, ...)  
  
## S4 method for signature 'regioned_dna'  
get_du(object)  
  
## S4 method for signature 'DNASTringSet'  
get_du(object)
```

Arguments

object	regioned_dna / DNAStrngSet
...	...

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_nu](#), [get_cu](#), [get_freq](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_du(rgd.seq)
```

get_freq	<i>Get codon usage frequency of synonymous codons</i>
----------	---

Description

Access the synonymous codon usage frequency

Usage

```
get_freq(object, ...)
```

S4 method for signature 'regioned_dna'

```
get_freq(object)
```

S4 method for signature 'DNAStrngSet'

```
get_freq(object)
```

S4 method for signature 'matrix'

```
get_freq(object)
```

S4 method for signature 'vector'

```
get_freq(object)
```

Arguments

object	regioned_dna / DNAStrngSet / codon usage matrix (vector)
...	...

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_freq(rgd.seq)
```

get_nu

Get nucleotide usage matrix

Description

Access the nucleotide usage matrix

Usage

```
get_nu(object, ...)
```

S4 method for signature 'regioned_dna'

```
get_nu(object)
```

S4 method for signature 'DNAStrngSet'

```
get_nu(object)
```

Arguments

object	regioned_dna / DNAStrngSet
...	...

Value

matrix

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_rscu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_nu(rgd.seq)
```

get_region	<i>Get the variable region</i>
------------	--------------------------------

Description

Access the variable regions

Usage

```
get_region(object, ...)  
  
## S4 method for signature 'regioned_dna'  
get_region(object)
```

Arguments

object	regioned_dna
...	...

Value

list

See Also

[input_seq](#), [get_cu](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")  
rgd.seq <- input_seq(filepath)  
get_region(rgd.seq)
```

get_rscu	<i>Get Relative Synonymous Codon Usage (rscu) of synonymous codons</i>
----------	--

Description

Access the Relative Synonymous Codon Usage rscu

Usage

```
get_rscu(object, ...)

## S4 method for signature 'regioned_dna'
get_rscu(object)

## S4 method for signature 'DNAStrngSet'
get_rscu(object)
```

Arguments

```
object          regioned_dna / DNAStrngSet / codon usage matrix (vector)
...             ...
```

Value

```
matrix
```

See Also

[input_seq](#), [get_region](#), [get_cu](#), [get_du](#), [get_freq](#)

Examples

```
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)
get_rscu(rgd.seq)
```

input_seq	<i>Import region / constructing regioned_dna object</i>
-----------	---

Description

Constructing regioned_dna from DNAStrngSet. Optionally input a region data.frame to define restricted amino-acid region for mutation.

Usage

```
input_seq(object, region = NA, ...)

## S4 method for signature 'character'
input_seq(object, region)

## S4 method for signature 'DNAStrngSet'
input_seq(object, region)

## S4 method for signature 'DNAStrng'
input_seq(object, region)
```

Arguments

object	Filepath or DNASTringSet. The input sequences is suggested to be in open reading frame(ORF).
region	NA. A data.frame specifying paticular regions (positions in amino acid sequence) that is allowed to be mutated in the sequences. Both 1 / 0 or TRUE / FALSE encoding is OK. Please refer to Examples below for reference.
...	...

Value

A regioned_dna-class object

See Also

[get_cu](#), [get_du](#), [get_region](#), [get_dna](#)

Examples

```
# Creating a input_seq class directly from system file
filepath <- system.file("extdata", "example.fasta", package = "SynMut")
rgd.seq <- input_seq(filepath)

# Optionally input with region dataframe
filepath.fasta <- system.file("extdata", "example.fasta", package = "SynMut")
fp.csv <- system.file("extdata", "target_regions.csv", package = "SynMut")
region <- read.csv(fp.csv)
rgd.seq <- input_seq(filepath.fasta, region)

# Creating from exsisting DNASTringSet object
seq <- Biostrings::DNASTringSet("ATCGATCGA")
rgd.seq <- input_seq(seq)
```

regioned_dna-class	<i>An S4 class to record DNA sequences and variable regions for mutations</i>
--------------------	---

Description

Recording codon DNA sequences and region.

Slots

dnaseq a DNASTingSet object recording the sequence(s)
 region a list specifying paticular regions in the sequences allowed to be mutated

Author(s)

Haogao Gu

See Also[input_seq](#), [get_cu](#), [get_region](#)

seq_random

*Generate n random DNA sequences of length m***Description**

Generate n random DNA sequences of length m, optional exclude stop codons.

Usage

```
seq_random(n = 1, m, no.stop.codon = FALSE, ...)
```

```
## S4 method for signature 'numeric,numeric'
```

```
seq_random(n, m, no.stop.codon)
```

Arguments

n	the number of the output sequence(s).
m	the length of the output sequence(s). Either a fixed number or a vector of different numbers.
no.stop.codon	Default FALSE. If TRUE, the stop codons in the frame 1 would be substituted to another random codon.
...	...

Value

a DNASTringSet object

Examples

```
seq_random(n = 1, m = 99)
seq_random(n = 10, m = 30)
seq_random(n = 10, m = 1:10)
seq.nsc <- seq_random(n = 10, m = 100, no.stop.codon = TRUE)
get_cu(seq.nsc)
```

Index

codon_dist, 2
codon_dist, ANY-method (codon_dist), 2
codon_mimic, 3, 5, 6, 8
codon_mimic, DNAStringSet, DNAStringSet-method
 (codon_mimic), 3
codon_mimic, regioned_dna, DNAStringSet-method
 (codon_mimic), 3
codon_mimic, regioned_dna, vector-method
 (codon_mimic), 3
codon_random, 4, 4, 6, 8
codon_random, DNAStringSet-method
 (codon_random), 4
codon_random, regioned_dna-method
 (codon_random), 4
codon_to, 3–5, 5, 8
codon_to, regioned_dna-method
 (codon_to), 5

dinu_dist, 6
dinu_dist, ANY-method (dinu_dist), 6
dinu_to, 4–6, 7
dinu_to, regioned_dna-method (dinu_to), 7

get_cu, 8, 10–15
get_cu, DNAStringSet-method (get_cu), 8
get_cu, regioned_dna-method (get_cu), 8
get_dna, 9, 14
get_dna, regioned_dna-method (get_dna), 9
get_du, 8, 9, 11, 13, 14
get_du, DNAStringSet-method (get_du), 9
get_du, regioned_dna-method (get_du), 9
get_freq, 8, 10, 10, 13
get_freq, DNAStringSet-method
 (get_freq), 10
get_freq, matrix-method (get_freq), 10
get_freq, regioned_dna-method
 (get_freq), 10
get_freq, vector-method (get_freq), 10
get_nu, 8, 10, 11
get_nu, DNAStringSet-method (get_nu), 11
get_nu, regioned_dna-method (get_nu), 11
get_region, 8, 10, 11, 12, 13–15
get_region, regioned_dna-method
 (get_region), 12
get_rscu, 8, 10, 11, 12
get_rscu, DNAStringSet-method
 (get_rscu), 12
get_rscu, regioned_dna-method
 (get_rscu), 12

input_seq, 4–6, 8, 10–13, 13, 15
input_seq, character-method (input_seq),
 13
input_seq, DNAString-method (input_seq),
 13
input_seq, DNAStringSet-method
 (input_seq), 13

regioned_dna-class, 14

seq_random, 15
seq_random, numeric, numeric-method
 (seq_random), 15