

Package ‘AnVILBilling’

April 7, 2022

Title Provide functions to retrieve and report on usage expenses in NHGRI AnVIL (anvilproject.org).

Date 2020-09-30

Version 1.4.0

Description AnVILBilling helps monitor AnVIL-related costs in R, using queries to a BigQuery table to which costs are exported daily. Functions are defined to help categorize tasks and associated expenditures, and to visualize and explore expense profiles over time. This package will be expanded to help users estimate costs for specific task sets.

License Artistic-2.0

Encoding UTF-8

LazyData true

Depends R (>= 4.1)

Imports methods, DT, shiny, bigrquery, shinytoastr, DBI, magrittr, dplyr, lubridate, plotly, ggplot2

Suggests testthat, knitr, BiocStyle, rmarkdown

RoxygenNote 7.1.1

VignetteBuilder knitr

biocViews Infrastructure, Software

BugReports <https://github.com/vjcitn/AnVILBilling/issues>

git_url <https://git.bioconductor.org/packages/AnVILBilling>

git_branch RELEASE_3_14

git_last_commit 54f05b3

git_last_commit_date 2021-10-26

Date/Publication 2022-04-07

Author BJ Stubbs [aut],
Vince Carey [aut, cre]

Maintainer Vince Carey <stvjc@channing.harvard.edu>

R topics documented:

ab_reckoning	2
browse_reck	3
browse_reck2	3
demo_rec	3
getBilling	4
getKeys	5
getSkus	5
getSubmissionCost	6
getSubmissionRam	6
getValues	7
reckon	7
reckoning	8
reckoning.avReckoning-method	8
setup_billing_request	9
subsetByKeyValue	10
subsetBySku	10
Index	12

ab_reckoning	<i>accessor for reckoning element</i>
--------------	---------------------------------------

Description

accessor for reckoning element

Usage

ab_reckoning(x)

Arguments

x an instance of avReckoning

Value

a tibble with one row for each expense type by time slice

Examples

dim(ab_reckoning(demo_rec))

browse_reck	<i>prototypical cost exploring app</i>
-------------	--

Description

prototypical cost exploring app

Usage

browse_reck()

Value

returns "NULL"

Examples

```
if (interactive()) browse_reck()
```

browse_reck2	<i>alternate app for AnVIL where htmlwidgets misbehaves</i>
--------------	---

Description

alternate app for AnVIL where htmlwidgets misbehaves

Usage

browse_reck2()

demo_rec	<i>a demonstration avReckoning object</i>
----------	---

Description

a demonstration avReckoning object

Usage

demo_rec

Format

avReckoning instance

Note

This is a snapshot of cost data collected for a specific project.

Examples

```
demo_rec
```

getBilling	<i>request billing data</i>
------------	-----------------------------

Description

request billing data

Usage

```
getBilling(  
  startDate,  
  endDate,  
  bqProject,  
  bqDataset,  
  bqTable,  
  bqBilling_code,  
  page_size = 50000  
)
```

Arguments

startDate	character(1) date of start of reckoning
endDate	character(1) date of end of reckoning
bqProject	character(1) GCP project id
bqDataset	character(1) GCP dataset id for billing data in BQ
bqTable	character(1) GCP table for billing data in BQ
bqBilling_code	character(1) GCP billing code
page_size	numeric(1) passed to dbConnect

Value

tbl_df

Note

On 21 August 2020 VJC changed condition on endDate to <=

Examples

```
if (interactive()) {  
  getBilling(startDate="2020-08-01",  
    endDate="2020-08-15", bqProject="bjbilling",  
    bqTable="gcp_billing_export_v1_015E39_38569D_3CC771",  
    bqDataset="anvilbilling", bqBilling_code="landmarkanvil2")  
}
```

getKeys	<i>return keys</i>
---------	--------------------

Description

return keys

Usage

```
getKeys(mybilling)
```

Arguments

mybilling tbl_df

Value

character()

getSkus	<i>List the available GCP product skus</i>
---------	--

Description

List the available GCP product skus

Usage

```
getSkus(mybilling)
```

Arguments

mybilling tbl_df

Value

character()

getSubmissionCost	<i>Calculate costs for a workflow submission by ID</i>
-------------------	--

Description

Calculate costs for a workflow submission by ID

Usage

```
getSubmissionCost(mybilling, submissionID)
```

Arguments

mybilling	tbl_df
submissionID	character(1) Terra submission ID

Value

numeric()

Examples

```
data(demo_rec) # makes rec
v = getValues(demo_rec@reckoning, "terra-submission-id")[1] # for instance
getSubmissionCost(demo_rec@reckoning,v)
```

getSubmissionRam	<i>Calculate ram usage for a workflow submission by ID</i>
------------------	--

Description

Calculate ram usage for a workflow submission by ID

Usage

```
getSubmissionRam(mybilling, submissionID)
```

Arguments

mybilling	tbl_df
submissionID	character(1) Terra submission ID

Value

data.frame

Examples

```
data(demo_rec) # makes rec
v = getValues(demo_rec@reckoning, "terra-submission-id")[1] # for instance
getSubmissionRam(demo_rec@reckoning,v)
```

getValues	<i>deal with nested tables in a reckoning</i>
-----------	---

Description

deal with nested tables in a reckoning

Usage

```
getValues(mybilling, mykey)
```

Arguments

mybilling	tbl_df from reckon()
mykey	character(1) key

Value

character()

Examples

```
if (interactive()) getValues(reckoning(demo_rec), "security")
```

reckon	<i>perform reckoning</i>
--------	--------------------------

Description

perform reckoning

Usage

```
reckon(obj)
```

Arguments

obj	instance of avReckoningRequest
-----	--------------------------------

Value

instance of avReckoning

Examples

```
data(demo_rec)
if (interactive()) reckon(demo_rec)
```

reckoning	<i>generic for accessor for reckoning component</i>
-----------	---

Description

generic for accessor for reckoning component

Usage

```
reckoning(x)
```

Arguments

x object inheriting from avReckoning

Value

tbl_df

Examples

```
if (interactive()) reckoning(reckon(demo_rec))
```

reckoning,avReckoning-method	<i>accessor for reckoning component</i>
------------------------------	---

Description

accessor for reckoning component

Usage

```
## S4 method for signature 'avReckoning'
reckoning(x)
```

Arguments

x instance of avReckoning

Value

tbl_df

Examples

```
if (interactive()) reckoning(reckon(demo_rec))
```

setup_billing_request *set up request object*

Description

set up request object

Usage

```
setup_billing_request(start, end, project, dataset, table, billing_code)
```

Arguments

start	character(1) date of start of reckoning
end	character(1) date of end of reckoning
project	character(1) GCP project id
dataset	character(1) GCP dataset id for billing data in BQ
table	character(1) GCP table for billing data in BQ
billing_code	character(1) GCP billing code

Value

instance of avReckoningRequest

Examples

```
lk1 = setup_billing_request("2020-08-01", "2020-08-15",  
  "bq-scoped-project", "bq_dataset", "bq_table", "billcode")  
lk1
```

subsetByKeyValue	<i>filter a reckoning by 'label' retaining records associated with a particular key-value pair</i>
------------------	--

Description

filter a reckoning by 'label' retaining records associated with a particular key-value pair

Usage

```
subsetByKeyValue(mybilling, mykey, myvalue)
```

Arguments

mybilling	instance of avReckoning
mykey	character(1)
myvalue	character(1)

Value

data.frame

Examples

```
example(reckon) # makes rec
v = getValues(ab_reckoning(demo_rec), "terra-submission-id")[1] # for instance
nt = subsetByKeyValue(ab_reckoning(demo_rec), "terra-submission-id", v)
head(nt)
dim(nt)
```

subsetBySku	<i>subset a billing object by sku</i>
-------------	---------------------------------------

Description

subset a billing object by sku

Usage

```
subsetBySku(mybilling, mysku)
```

Arguments

mybilling	tbl_df
mysku	character(1) GCP product sku

subsetBySku

11

Value

data.frame

Index

* **datasets**

demo_rec, [3](#)

ab_reckoning, [2](#)

browse_reck, [3](#)

browse_reck2, [3](#)

demo_rec, [3](#)

getBilling, [4](#)

getKeys, [5](#)

getSkus, [5](#)

getSubmissionCost, [6](#)

getSubmissionRam, [6](#)

getValues, [7](#)

reckon, [7](#)

reckoning, [8](#)

reckoning, avReckoning-method, [8](#)

setup_billing_request, [9](#)

subsetByKeyValue, [10](#)

subsetBySku, [10](#)