

Package ‘EWCE’

October 16, 2022

Type Package

Title Expression Weighted Celltype Enrichment

Version 1.4.0

Description Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies. The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

URL <https://github.com/NathanSkene/EWCE>

BugReports <https://github.com/NathanSkene/EWCE/issues>

License GPL-3

Depends R (>= 4.1), RNOmni (>= 1.0)

VignetteBuilder knitr

Imports stats, utils, methods, ewceData, dplyr, ggplot2, reshape2, limma, stringr, HGNCHELPER, Matrix, parallel, SingleCellExperiment, SummarizedExperiment, DelayedArray, BiocParallel, orthogene (>= 0.99.8), data.table

Suggests remotes, knitr, BiocStyle, rmarkdown, testthat (>= 3.0.0), readxl, memoise, markdown, sctransform, DESeq2, MAST, DelayedMatrixStats, cowplot, ggdendro, grDevices, grid, gridExtra, scales, magick, badger

biocViews GeneExpression, Transcription, DifferentialExpression, GeneSetEnrichment, Genetics, Microarray, mRNA Microarray, OneChannel, RNASeq, BiomedicalInformatics, Proteomics, Visualization, FunctionalGenomics, SingleCell

RoxygenNote 7.1.2

Encoding UTF-8

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/EWCE>

git_branch RELEASE_3_15

git_last_commit 306f434

git_last_commit_date 2022-04-26

Date/Publication 2022-10-16

Author Alan Murphy [cre] (<<https://orcid.org/0000-0002-2487-8753>>),

Brian Schilder [aut] (<<https://orcid.org/0000-0001-5949-2191>>),

Nathan Skene [aut] (<<https://orcid.org/0000-0002-6807-3180>>)

Maintainer Alan Murphy <alanmurph94@hotmail.com>

R topics documented:

EWCE-package	3
add_res_to_merging_list	4
bin_columns_into_quantiles	5
bin_specificity_into_quantiles	5
bootstrap_enrichment_test	6
check_ewce_genelist_inputs	8
check_percent_hits	10
controlled_geneset_enrichment	11
ctd_to_sce	13
drop_uninformative_genes	14
ewce_expression_data	16
ewce_plot	18
example_bootstrap_results	19
example_transcriptome_results	20
filter_genes_without_1to1_homolog	21
filter_nonorthologs	22
fix_bad_hgnc_symbols	23
fix_bad_mgi_symbols	24
fix_celltype_names	25
generate_bootstrap_plots	26
generate_bootstrap_plots_for_transcriptome	28
generate_celltype_data	31
get_celltype_table	34
is_delayed_array	34
is_matrix	35
is_sparse_matrix	35
list_species	36
load_rdata	36
merged_ewce	37
merge_ctd	38
merge_sce	40
merge_two_expfiles	41
plot_ctd	42
prep.dendro	43
sct_normalize	43
standardise_ctd	44

Description

Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies. The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

Details

EWCE: Expression Weighted Celltype Enrichment

Used to determine which cell types are enriched within gene lists. The package provides tools for testing enrichments within simple gene lists (such as human disease associated genes) and those resulting from differential expression studies.

The package does not depend upon any particular Single Cell Transcriptome dataset and user defined datasets can be loaded in and used in the analyses.

Author(s)

Maintainer: Alan Murphy <alanmurph94@hotmail.com> ([ORCID](#))

Authors:

- Brian Schilder <brian_schilder@alumni.brown.edu> ([ORCID](#))
- Nathan Skene <nathan.skene@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/NathanSkene/EWCE>
- Report bugs at <https://github.com/NathanSkene/EWCE/issues>

`add_res_to_merging_list`*Add to results to merging list*

Description

`add_res_to_merging_list` adds EWCE results to a list for merging analysis.

Usage

```
add_res_to_merging_list(full_res, existing_results = NULL)
```

Arguments

`full_res` Results list generated using [bootstrap_enrichment_test](#) or [ewce_expression_data](#) functions. Multiple results tables can be merged into one results table, as long as the 'list' column is set to distinguish them.

`existing_results` Output of previous rounds from adding results to list. Leave empty if this is the first item in the list.

Value

Merged results list.

Examples

```
# Load the single cell data
ctd <- ewceData::ctd()

# Load the data
tt_alzh <- ewceData::tt_alzh()
# tt_alzh_BA36 <- ewceData::tt_alzh_BA36()
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
# Run EWCE analysis
# tt_results <- ewce_expression_data(
#   sct_data = ctd, tt = tt_alzh, annotLevel = 1, thresh = thresh,
#   reps = reps, ttSpecies = "human", sctSpecies = "mouse"
# )
# tt_results_36 <- ewce_expression_data(
#   sct_data = ctd, tt = tt_alzh_BA36, annotLevel = 1, thresh = thresh,
#   reps = reps, ttSpecies = "human", sctSpecies = "mouse"
# )

# Fill a list with the results
results <- add_res_to_merging_list(tt_alzh)
# results <- add_res_to_merging_list(tt_alzh_BA36, results)
```

```
bin_columns_into_quantiles
      bin_columns_into_quantiles
```

Description

bin_columns_into_quantiles is an internal function used to convert a matrix of specificity (with columns of cell types) into a matrix of specificity quantiles

Usage

```
bin_columns_into_quantiles(
  matrixIn,
  numberOfBins = 40,
  defaultBin = as.integer(numberOfBins/2)
)
```

Arguments

matrixIn	The matrix of specificity values
numberOfBins	Number of quantile 'bins' to use (40 is recommended)
defaultBin	Which bin to assign when there's only one non-zero quantile. In situations where there's only one non-zero quantile, cut() throws an error. Avoid these situations by using a default quantile.

Value

A matrix with same shape as matrixIn but with columns storing quantiles instead of specificity

Examples

```
ctd <- ewceData::ctd()
ctd[[1]]$specificity_quantiles <- apply(ctd[[1]]$specificity, 2,
  FUN = bin_columns_into_quantiles,
  numberOfBins = 40
)
```

```
bin_specificity_into_quantiles
      bin_specificity_into_quantiles
```

Description

bin_specificity_into_quantiles is an internal function used to convert add '\$specificity_quantiles' to a ctd

Usage

```
bin_specificity_into_quantiles(
  ctdIN,
  numberOfBins,
  matrix_name = "specificity_quantiles",
  as_sparse = TRUE,
  verbose = TRUE
)
```

Arguments

ctdIN	A single annotLevel of a ctd, i.e. ctd[[1]] (the function is intended to be used via apply).
numberOfBins	Number of quantile 'bins' to use (40 is recommended).
matrix_name	Name of the specificity matrix to create (default: "specificity_quantiles").
as_sparse	Convert to sparseMatrix.
verbose	Print messages.

Value

A ctd with "specificity_quantiles" matrix in each level (or whatever matrix_name was set to.).

Examples

```
ctd <- ewceData::ctd()
ctd <- lapply(ctd, EWCE::bin_specificity_into_quantiles, numberOfBins = 40)
print(ctd[[1]]$specificity_quantiles[1:3, ])
```

bootstrap_enrichment_test

Bootstrap cell type enrichment test

Description

bootstrap_enrichment_test takes a genelist and a single cell type transcriptome dataset and determines the probability of enrichment and fold changes for each cell type.

Usage

```
bootstrap_enrichment_test(
  sct_data = NULL,
  hits = NULL,
  bg = NULL,
  genelistSpecies = NULL,
  sctSpecies = NULL,
  output_species = "human",
```

```

method = "homologene",
reps = 100,
no_cores = 1,
annotLevel = 1,
geneSizeControl = FALSE,
controlledCT = NULL,
mtc_method = "BH",
sort_results = TRUE,
verbose = TRUE
)

```

Arguments

sct_data	List generated using generate_celltype_data .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if <code>geneSizeControl=TRUE</code> .
bg	List of gene symbols containing the background gene list (including hit genes). If <code>bg=NULL</code> , an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
reps	Number of random gene lists to generate (<i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
no_cores	Number of cores to parallelise bootstrapping reps over.
annotLevel	An integer indicating which level of sct_data to analyse (<i>Default: 1</i>).
geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies (<i>Default: FALSE</i>). If set to TRUE, then hits must be from humans.
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
mtc_method	Multiple-testing correction method (passed to p.adjust).
sort_results	Sort enrichment results from smallest to largest p-values.
verbose	Print messages.

Value

A list containing three data frames:

- `results`: dataframe in which each row gives the statistics (p-value, fold change and number of standard deviations from the mean) associated with the enrichment of the stated cell type in the gene list
- `hit.cells`: vector containing the summed proportion of expression in each cell type for the target list
- `bootstrap_data`: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists

Examples

```
# Load the single cell data
ctd <- ewceData::ctd()
# Set the parameters for the analysis
# Use 3 bootstrap lists for speed, for publishable analysis use >=10,000
reps <- 3
# Load gene list from Alzheimer's disease GWAS
example_genelist <- ewceData::example_genelist()

# Bootstrap significance test, no control for transcript length or GC content
full_results <- EWCE::bootstrap_enrichment_test(
  sct_data = ctd,
  hits = example_genelist,
  reps = reps,
  annotLevel = 1,
  sctSpecies = "mouse",
  genelistSpecies = "human"
)
```

```
check_ewce_genelist_inputs
      check_ewce_genelist_inputs
```

Description

`check_ewce_genelist_inputs` Is used to check that hits and bg gene lists passed to EWCE are setup correctly. Checks they are the appropriate length. Checks all hits genes are in bg. Checks the species match and if not reduces to 1:1 orthologs.

Usage

```
check_ewce_genelist_inputs(
  sct_data,
  hits,
  bg = NULL,
  genelistSpecies = NULL,
```



```

    sctSpecies = NULL,
    output_species = "human",
    method = "homologene",
    geneSizeControl = FALSE,
    standardise = FALSE,
    verbose = TRUE
)

```

Arguments

sct_data	List generated using generate_celltype_data .
hits	List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if <code>geneSizeControl=TRUE</code> .
bg	List of gene symbols containing the background gene list (including hit genes). If <code>bg=NULL</code> , an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
geneSizeControl	Whether you want to control for GC content and transcript length. Recommended if the gene list originates from genetic studies (<i>Default: FALSE</i>). If set to TRUE, then hits must be from humans.
standardise	If <code>input_species==output_species</code> , should the genes be standardised using map_genes?
verbose	Print messages.

Value

A list containing

- hits: Array of MGI/HGNC gene symbols containing the target gene list.
- bg: Array of MGI/HGNC gene symbols containing the background gene list.

Examples

```
ctd <- ewceData::ctd()
example_genelist <- ewceData::example_genelist()

# Called from "bootstrap_enrichment_test()" and "generate_bootstrap_plots()"
checkedLists <- EWCE::check_ewce_genelist_inputs(
  sct_data = ctd,
  hits = example_genelist,
  sctSpecies = "mouse",
  genelistSpecies = "human"
)
```

check_percent_hits	<i>Get percentage of target cell type hits</i>
--------------------	--

Description

After you run [bootstrap_enrichment_test](#), check what percentage of significantly enriched cell types match an expected cell type.

Usage

```
check_percent_hits(
  full_results,
  target_celltype,
  mtc_method = "bonferroni",
  q_threshold = 0.05,
  verbose = TRUE
)
```

Arguments

full_results	bootstrap_enrichment_test results.
target_celltype	Substring to search to matching cell types (case-insensitive).
mtc_method	Multiple-testing correction method.
q_threshold	Corrected significance threshold.
verbose	Print messages.

Value

Report list.

Examples

```
## Bootstrap significance test,
## no control for transcript length or GC content
## Use pre-computed results to speed up example
full_results <- EWCE::example_bootstrap_results()

report <- EWCE::check_percent_hits(
  full_results = full_results,
  target_celltype = "microglia"
)
```

controlled_geneset_enrichment

Celltype controlled geneset enrichment

Description

controlled_geneset_enrichment tests whether a functional gene set is still enriched in a disease gene set after controlling for the disease gene set's enrichment in a particular cell type (the 'controlledCT')

Usage

```
controlled_geneset_enrichment(
  disease_genes,
  functional_genes,
  bg = NULL,
  sct_data,
  sctSpecies = NULL,
  output_species = "human",
  disease_genes_species = NULL,
  functional_genes_species = NULL,
  method = "homologene",
  annotLevel,
  reps = 100,
  controlledCT,
  use_intersect = FALSE,
  verbose = TRUE
)
```

Arguments

disease_genes Array of gene symbols containing the disease gene list. Does not have to be disease genes. Must be from same species as the single cell transcriptome dataset.

functional_genes Array of gene symbols containing the functional gene list. The enrichment of this gene set within the disease_genes is tested. Must be from same species as the single cell transcriptome dataset.

bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
sct_data	List generated using generate_celltype_data .
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
disease_genes_species	Species of the disease_genes gene set.
functional_genes_species	Species of the functional_genes gene set.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
annotLevel	An integer indicating which level of sct_data to analyse (<i>Default: 1</i>).
reps	Number of random gene lists to generate (<i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
controlledCT	[Optional] If not NULL, and instead is the name of a cell type, then the bootstrapping controls for expression within that cell type.
use_intersect	When species1 and species2 are both different from output_species, this argument will determine whether to use the intersect (TRUE) or union (FALSE) of all genes from species1 and species2.
verbose	Print messages.

Value

A list containing three data frames:

- p_controlled The probability that functional_genes are enriched in disease_genes while controlling for the level of specificity in controlledCT
- z_controlled The z-score that functional_genes are enriched in disease_genes while controlling for the level of specificity in controlledCT
- p_uncontrolled The probability that functional_genes are enriched in disease_genes WITHOUT controlling for the level of specificity in controlledCT
- z_uncontrolled The z-score that functional_genes are enriched in disease_genes WITHOUT controlling for the level of specificity in controlledCT
- reps=reps
- controlledCT
- actualOverlap=actual The number of genes that overlap between functional and disease gene sets

Examples

```

# See the vignette for more detailed explanations
# Gene set enrichment analysis controlling for cell type expression
# set seed for bootstrap reproducibility
set.seed(12345678)
## load merged dataset from vignette
ctd <- ewceData::ctd()
schiz_genes <- ewceData::schiz_genes()
hpsd_genes <- ewceData::hpsd_genes()
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3

res_hpsd_schiz <- EWCE::controlled_geneset_enrichment(
  disease_genes = schiz_genes,
  functional_genes = hpsd_genes,
  sct_data = ctd,
  annotLevel = 1,
  reps = reps,
  controlledCT = "pyramidal CA1"
)

```

ctd_to_sce

CellTypeDataset to SingleCellExperiment

Description

Copied from [scKirby](#), which is not yet on CRAN or Bioconductor.

Usage

```
ctd_to_sce(object, as_sparse = TRUE, as_DelayedArray = FALSE, verbose = TRUE)
```

Arguments

object	CellTypeDataset object.
as_sparse	Store SingleCellExperiment matrices as sparse.
as_DelayedArray	Store SingleCellExperiment matrices as DelayedArray.
verbose	Print messages.

Value

SingleCellExperiment

Examples

```

ctd <- ewceData::ctd()
sce <- EWCE::ctd_to_sce(ctd)

```

drop_uninformative_genes

Drop uninformative genes

Description

drop_uninformative_genes drops uninformative genes in order to reduce compute time and noise in subsequent steps. It achieves this through several steps, each of which are optional:

- Drop non-1:1 orthologs:
Removes genes that don't have 1:1 orthologs with the output_species ("human" by default).
- Drop non-varying genes:
Removes genes that don't vary across cells based on variance deciles.
- Drop non-differentially expressed genes (DEGs):
Removes genes that are not significantly differentially expressed across cell-types (multiple DEG methods available).

Usage

```
drop_uninformative_genes(  
  exp,  
  level2annot,  
  mtc_method = "BH",  
  adj_pval_thresh = 1e-05,  
  convert_orths = FALSE,  
  input_species = NULL,  
  output_species = "human",  
  non121_strategy = "drop_both_species",  
  method = "homologene",  
  as_sparse = TRUE,  
  as_DelayedArray = FALSE,  
  return_sce = FALSE,  
  no_cores = 1,  
  verbose = TRUE,  
  ...  
)
```

Arguments

exp	Expression matrix with gene names as rownames.
level2annot	Array of cell types, with each sequentially corresponding a column in the expression matrix.
mtc_method	Multiple-testing correction method used by DGE step. See p.adjust for more details.
adj_pval_thresh	Minimum differential expression significance that a gene must demonstrate across level2annot (i.e. cell types).

convert_orths	If input_species!=output_species and convert_orths=TRUE, will drop genes without 1:1 output_species orthologs and then convert exp gene names to those of output_species.
input_species	Which species the gene names in exp come from. See list_species for all available species.
output_species	Which species' genes names to convert exp to. See list_species for all available species.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> • "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (DEFAULT). • "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species. • "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species. • "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species. • "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs. • "sum", "mean", "median", "min" or "max" : When gene_df is a matrix and gene_output="rownames", these options will aggregate many-to-one gene mappings (input_species-to-output_species) after dropping any duplicate genes in the output_species.
method	R package to to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
as_sparse	Convert exp to sparse matrix.
as_DelayedArray	Convert exp to DelayedArray for scalable processing.
return_sce	Whether to return the filtered results as an expression matrix or a SingleCellExperiment .
no_cores	Number of cores to parallelise across. Set to NULL to automatically optimise.
verbose	Print messages.
...	Additional arguments to be passed to the selected DGE method.

Value

exp Expression matrix with gene names as row names.

Examples

```
cortex_mrna <- ewceData::cortex_mrna()
# Use only a subset of genes to keep the example quick
cortex_mrna$exp <- cortex_mrna$exp[1:300, ]

## Convert orthologs at the same time
exp2_orth <- drop_uninformative_genes(
  exp = cortex_mrna$exp,
  level2annot = cortex_mrna$annot$level2class,
  input_species = "mouse"
)
```

ewce_expression_data *Bootstrap cell type enrichment test for transcriptome data*

Description

ewce_expression_data takes a differential gene expression (DGE) results table and determines the probability of cell type enrichment in the up- and down- regulated genes.

Usage

```
ewce_expression_data(
  sct_data,
  annotLevel = 1,
  tt,
  sortBy = "t",
  thresh = 250,
  reps = 100,
  ttSpecies = NULL,
  sctSpecies = NULL,
  output_species = NULL,
  bg = NULL,
  method = "homologene",
  verbose = TRUE
)
```

Arguments

sct_data List generated using [generate_celltype_data](#).

annotLevel An integer indicating which level of sct_data to analyse (*Default: 1*).

tt	Differential expression table. Can be output of topTable function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes (Default: "t").
thresh	The number of up- and down- regulated genes to be included in each analysis (Default: 250).
reps	Number of random gene lists to generate (<i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
ttSpecies	The species the differential expression table was generated from.
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives <p>(slower but more species and genes) or "homologene" (faster but fewer species and genes).</p>
verbose	Print messages.

Value

A list containing five data frames:

- `results`: dataframe in which each row gives the statistics (p-value, fold change and number of standard deviations from the mean) associated with the enrichment of the stated cell type in the gene list. An additional column `*Direction*` stores whether it the result is from the up or downregulated set.
- `hit.cells.up`: vector containing the summed proportion of expression in each cell type for the target list.
- `hit.cells.down`: vector containing the summed proportion of expression in each cell type for the target list.
- `bootstrap_data.up`: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists.
- `bootstrap_data.down`: matrix in which each row represents the summed proportion of expression in each cell type for one of the random lists.

Examples

```

# Load the single cell data
ctd <- ewceData::ctd()

# Set the parameters for the analysis
# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
annotLevel <- 1 # <- Use cell level annotations (i.e. Interneurons)

# Load the top table
tt_alzh <- ewceData::tt_alzh()

tt_results <- EWCE::ewce_expression_data(
  sct_data = ctd,
  tt = tt_alzh,
  annotLevel = 1,
  thresh = thresh,
  reps = reps,
  ttSpecies = "human",
  sctSpecies = "mouse"
)

```

ewce_plot

Plot EWCE results

Description

ewce_plot generates plots of EWCE enrichment results

Usage

```

ewce_plot(
  total_res,
  mtc_method = "bonferroni",
  ctd = NULL,
  align = "v",
  rel_heights = c(0.3, 1),
  axis = "lr"
)

```

Arguments

total_res Results data.frame generated using [bootstrap_enrichment_test](#) or [ewce_expression_data](#) functions. Multiple results tables can be merged into one results table, as long as the 'list' column is set to distinguish them. Multiple testing correction is then applied across all merged results.

mtc_method	Method to be used for multiple testing correction. Argument is passed to p.adjust (DEFAULT: "bonferroni").
ctd	CellTypeDataset object. Should be provided so that the dendrogram can be taken from it and added to plots
align	(optional) Specifies whether graphs in the grid should be horizontally ("h") or vertically ("v") aligned. Options are "none" (default), "hv" (align in both directions), "h", and "v".
rel_heights	(optional) Numerical vector of relative rows heights. Works just as <code>rel_widths</code> does, but for rows rather than columns.
axis	(optional) Specifies whether graphs should be aligned by the left ("l"), right ("r"), top ("t"), or bottom ("b") margins. Options are "none" (default), or a string of any combination of l, r, t, and b in any order (e.g. "tblr" or "rlbt" for aligning all margins). Must be specified if any of the graphs are complex (e.g. faceted) and alignment is specified and desired. See align_plots() for details.

Value

A ggplot containing the plot

Examples

```
## Bootstrap significance test,
## no control for transcript length or GC content
## Use pre-computed results to speed up example
full_results <- EWCE::example_bootstrap_results()

## Generate the plot
print(EWCE::ewce_plot(
  total_res = full_results$results,
  mtc_method = "BH"
))
```

example_bootstrap_results

Example bootstrap enrichment results

Description

Example cell type enrichment results produced by [bootstrap_enrichment_test](#).

Usage

```
example_bootstrap_results(verbose = TRUE)
```

Arguments

verbose Print messages.

Value

List with 3 items.

Source

```
# Load the single cell data
ctd <- ewceData::ctd()
# Set the parameters for the analysis
# Use 3 bootstrap lists for speed, for publishable analysis use >=10,000
reps <- 3
# Load gene list from Alzheimer's disease GWAS
example_genelist <- ewceData::example_genelist()
# Bootstrap significance test, no control for transcript length or GC content
full_results <- EWCE::bootstrap_enrichment_test( sct_data = ctd, hits = example_genelist, reps =
reps, annotLevel = 1, sctSpecies = "mouse", genelistSpecies = "human" )
bootstrap_results <- full_results
save(bootstrap_results,file = "inst/extdata/bootstrap_results.rda")
```

Examples

```
full_results <- EWCE::example_bootstrap_results()
```

example_transcriptome_results

Example bootstrap celltype enrichment test for transcriptome data

Description

Example celltype enrichment results produced by [ewce_expression_data](#).

Usage

```
example_transcriptome_results(verbose = TRUE)
```

Arguments

verbose Print messages.

Value

List with 5 items.

Source

```
## Load the single cell data
ctd <- ewceData::ctd()
## Set the parameters for the analysis
## Use 3 bootstrap lists for speed, for publishable analysis use >10,000
reps <- 3
annotLevel <- 1 # <- Use cell level annotations (i.e. Interneurons)
## Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5
## Load the top table
tt_alzh <- ewceData::tt_alzh()
tt_results <- EWCE::ewce_expression_data( sct_data = ctd, tt = tt_alzh, annotLevel = 1, thresh =
thresh, reps = reps, ttSpecies = "human", sctSpecies = "mouse" )
save(tt_results, file = "inst/extdata/tt_results.rda")
```

Examples

```
tt_results <- EWCE::example_transcriptome_results()
```

```
filter_genes_without_1to1_homolog
  filter_genes_without_1to1_homolog
```

Description

Deprecated function. Please use [filter_nonorthologs](#) instead.

Usage

```
filter_genes_without_1to1_homolog(
  filenames,
  input_species = "mouse",
  convert_nonhuman_genes = TRUE,
  annot_levels = NULL,
  suffix = "_orthologs",
  verbose = TRUE
)
```

Arguments

filenames List of file names for sct_data saved as *.rda* files.
input_species Which species the gene names in exp come from.
convert_nonhuman_genes Whether to convert the exp row names to human gene names.
annot_levels [Optional] Names of each annotation level.
suffix Suffix to add to the file name (right before *.rda*).
verbose Print messages.

Details

Note: This function replaces the original `filter_genes_without_1to1_homolog` function. `filter_genes_without_1to1` is now a wrapper for `filter_nonorthologs`.

Value

List of the filtered CellTypeData file names.

Examples

```

# Load the single cell data
ctd <- ewceData::ctd()
tmp <- tempfile()
save(ctd, file = tmp)
fNames_ALLCELLS_orths <- EWCE::filter_nonorthologs(filenames = tmp)

```

`filter_nonorthologs` *Filter non-orthologs*

Description

`filter_nonorthologs` Takes the filenames of CellTypeData files, loads them, drops any genes which don't have a 1:1 orthologs with humans, and then convert the gene to human orthologs. The new files are then saved to disk, appending `'_orthologs'` to the file name.

Usage

```

filter_nonorthologs(
  filenames,
  input_species = NULL,
  convert_nonhuman_genes = TRUE,
  annot_levels = NULL,
  suffix = "_orthologs",
  method = "homologene",
  verbose = TRUE
)

```

Arguments

filenames	List of file names for sct_data saved as <i>.rda</i> files.
input_species	Which species the gene names in exp come from.
convert_nonhuman_genes	Whether to convert the exp row names to human gene names.
annot_levels	[Optional] Names of each annotation level.
suffix	Suffix to add to the file name (right before <i>.rda</i>).
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
verbose	Print messages.

Details

Note: This function replaces the original `filter_genes_without_1to1_homolog` function. `filter_genes_without_1to1` is now a wrapper for `filter_nonorthologs`.

Value

List of the filtered CellTypeData file names.

Examples

```
# Load the single cell data
ctd <- ewceData::ctd()
tmp <- tempfile()
save(ctd, file = tmp)
fNames_ALLCELLS_orths <- EWCE::filter_nonorthologs(filenames = tmp)
```

`fix_bad_hgnc_symbols` *fix_bad_hgnc_symbols*

Description

Given an expression matrix, wherein the rows are supposed to be HGNC symbols, find those symbols which are not official HGNC symbols, then correct them if possible. Return the expression matrix with corrected symbols.

Usage

```
fix_bad_hgnc_symbols(
  exp,
  dropNonHGNC = FALSE,
  as_sparse = TRUE,
  verbose = TRUE
)
```

Arguments

exp	An expression matrix where the rows are HGNC symbols or a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object.
dropNonHGNC	Boolean. Should symbols not recognised as HGNC symbols be dropped?
as_sparse	Convert exp to sparse matrix.
verbose	Print messages.

Value

Returns the expression matrix with the rownames corrected and rows representing the same gene merged. If a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object was inputted this will be returned with the corrected expression matrix under counts.

Examples

```
# create example expression matrix, could be part of a exp, annot list obj
exp <- matrix(data = runif(70), ncol = 10)
# Add HGNC gene names but add with an error:
# MARCH8 is a HGNC symbol which if opened in excel will convert to Mar-08
rownames(exp) <-
  c("MT-TF", "MT-RNR1", "MT-TV", "MT-RNR2", "MT-TL1", "MT-ND1", "Mar-08")
exp <- fix_bad_hgnc_symbols(exp)
# fix_bad_hgnc_symbols warns the user of this possible issue
```

fix_bad_mgi_symbols	<i>fix_bad_mgi_symbols - Given an expression matrix, wherein the rows are supposed to be MGI symbols, find those symbols which are not official MGI symbols, then check in the MGI synonym database for whether they match to a proper MGI symbol. Where a symbol is found to be an aliases for a gene that is already in the dataset, the combined reads are summed together.</i>
---------------------	--

Description

Also checks whether any gene names contain "Sep", "Mar" or "Feb". These should be checked for any suggestion that excel has corrupted the gene names.

Usage

```
fix_bad_mgi_symbols(
  exp,
  mrk_file_path = NULL,
  printAllBadSymbols = FALSE,
  as_sparse = TRUE,
  verbose = TRUE
)
```

Arguments

exp	An expression matrix where the rows are MGI symbols, or a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object.
mrk_file_path	Path to the MRK_List2 file which can be downloaded from www.informatics.jax.org/downloads/reports/informatics.jax.org/downloads/reports/mrk_list2
printAllBadSymbols	Output to console all the bad gene symbols
as_sparse	Convert exp to sparse matrix.
verbose	Print messages.

Value

Returns the expression matrix with the rownames corrected and rows representing the same gene merged. If no corrections are necessary, input expression matrix is returned. If a SingleCellExperiment (SCE) or other Ranged Summarized Experiment (SE) type object was inputted this will be returned with the corrected expression matrix under counts.

Examples

```
# Load the single cell data
cortex_mrna <- ewceData::cortex_mrna()
# take a subset for speed
cortex_mrna$exp <- cortex_mrna$exp[1:50, 1:5]
cortex_mrna$exp <- fix_bad_mgi_symbols(cortex_mrna$exp)
```

fix_celltype_names *Fix celltype names*

Description

Make sure celltypes don't contain characters that could interfere with downstream analyses. For example, the R package [MAGMA.Celltyping](#) cannot have spaces in celltype names because spaces are used as a delimiter in later steps.

Usage

```
fix_celltype_names(celltypes, replace_chars = "[~]|[.]|[ ]|[//]|[\\|/]" )
```

Arguments

celltypes Character vector of celltype names.
 replace_chars Regex string of characters to replace with "_" when renaming columns.

Value

Fixed celltype names.

Examples

```
ct <- c("microglia", "astrocytes", "Pyramidal SS")
ct_fixed <- fix_celltype_names(celltypes = ct)
```

generate_bootstrap_plots

Generate bootstrap plots

Description

generate_bootstrap_plots takes a gene list and a single cell type transcriptome dataset and generates plots which show how the expression of the genes in the list compares to those in randomly generated gene lists

Usage

```
generate_bootstrap_plots(
  sct_data = NULL,
  hits = NULL,
  bg = NULL,
  genelistSpecies = NULL,
  sctSpecies = NULL,
  output_species = "human",
  method = "homologene",
  reps = 100,
  annotLevel = 1,
  full_results = NA,
  listFileName = "",
  savePath = tempdir(),
  verbose = TRUE
)
```

Arguments

sct_data List generated using [generate_celltype_data](#).
 hits List of gene symbols containing the target gene list. Will automatically be converted to human gene symbols if geneSizeControl=TRUE.

bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
genelistSpecies	Species that hits genes came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
reps	Number of random gene lists to generate (<i>Default: 100</i> , but should be $\geq 10,000$ for publication-quality results).
annotLevel	An integer indicating which level of sct_data to analyse (<i>Default: 1</i>).
full_results	The full output of bootstrap_enrichment_test for the same gene list.
listFileName	String used as the root for files saved using this function.
savePath	Directory where the BootstrapPlots folder should be saved, default is a temp directory.
verbose	Print messages.

Value

Saves a set of pdf files containing graphs and returns the file where they are saved. These will be saved with the filename adjusted using the value of listFileName. The files are saved into the 'BootstrapPlot' folder. Files start with one of the following:

- qqplot_noText: sorts the gene list according to how enriched it is in the relevant cell type. Plots the value in the target list against the mean value in the bootstrapped lists.
- qqplot_wtGSym: as above but labels the gene symbols for the highest expressed genes.
- bootDists: rather than just showing the mean of the bootstrapped lists, a boxplot shows the distribution of values
- bootDists_LOG: shows the bootstrapped distributions with the y-axis shown on a log scale

Examples

```
## Load the single cell data
ctd <- ewceData::ctd()

## Set the parameters for the analysis
## Use 5 bootstrap lists for speed, for publishable analysis use >10000
reps <- 5
```

```

## Load the gene list and get human orthologs
hits <- ewceData::example_genelist()[1:100]

## Bootstrap significance test,
## no control for transcript length or GC content
## Use pre-computed results to speed up example
full_results <- EWCE::example_bootstrap_results()

### Skip this for example purposes
# full_results <- EWCE::bootstrap_enrichment_test(
#   sct_data = ctd,
#   hits = hits,
#   reps = reps,
#   annotLevel = 1,
#   sctSpecies = "mouse",
#   genelistSpecies = "human"
# )

plot_file_path <- EWCE::generate_bootstrap_plots(
  sct_data = ctd,
  hits = hits,
  reps = reps,
  full_results = full_results,
  listFileName = "Example",
  sctSpecies = "mouse",
  genelistSpecies = "human",
  annotLevel = 1,
  savePath = tempdir()
)

```

```

generate_bootstrap_plots_for_transcriptome
  Generate bootstrap plots

```

Description

Takes a gene list and a single cell type transcriptome dataset and generates plots which show how the expression of the genes in the list compares to those in randomly generated gene lists.

Usage

```

generate_bootstrap_plots_for_transcriptome(
  sct_data,
  tt,
  bg = NULL,
  thresh = 250,
  annotLevel = 1,
  reps = 100,

```

```

full_results = NA,
listFileName = "",
showGNameThresh = 25,
ttSpecies = NULL,
sctSpecies = NULL,
output_species = NULL,
sortBy = "t",
sig_only = TRUE,
sig_col = "q",
sig_thresh = 0.05,
celltype_col = "CellType",
plot_types = c("bootstrap", "bootstrap_distributions", "log_bootstrap_distributions"),
savePath = tempdir(),
method = "homologene",
verbose = TRUE
)

```

Arguments

sct_data	List generated using generate_celltype_data .
tt	Differential expression table. Can be output of topTable function. Minimum requirement is that one column stores a metric of increased/decreased expression (i.e. log fold change, t-statistic for differential expression etc) and another contains gene symbols.
bg	List of gene symbols containing the background gene list (including hit genes). If bg=NULL, an appropriate gene background will be created automatically.
thresh	The number of up- and down- regulated genes to be included in each analysis (Default: 250).
annotLevel	An integer indicating which level of sct_data to analyse (Default: 1).
reps	Number of random gene lists to generate (Default: 100, but should be >=10,000 for publication-quality results).
full_results	The full output of ewce_expression_data for the same gene list.
listFileName	String used as the root for files saved using this function.
showGNameThresh	Integer. If a gene has over X percent of it's expression proportion in a cell type, then list the gene name.
ttSpecies	The species the differential expression table was generated from.
sctSpecies	Species that sct_data came from (no longer limited to just "mouse" and "human"). See list_species for all available species.
output_species	Species to convert sct_data and hits to (Default: "human"). See list_species for all available species.
sortBy	Column name of metric in tt which should be used to sort up- from down-regulated genes (Default: "t").
sig_only	Should plots only be generated for cells which have significant changes?
sig_col	Column name in tt that contains the significance values.

sig_thresh	Threshold by which to filter tt by sig_col.
celltype_col	Column within tt that contains celltype names.
plot_types	Plot types to generate.
savePath	Directory where the <i>BootstrapPlots</i> folder should be saved, default is a temp directory.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
verbose	Print messages.

Value

Saves a set of PDF files containing graphs and returns the file where they are saved. These will be saved with the filename adjusted using the value of `listFileName`. The files are saved into the *BootstrapPlot* folder. Files start with one of the following:

- `qqplot_noText`: sorts the gene list according to how enriched it is in the relevant cell type. Plots the value in the target list against the mean value in the bootstrapped lists.
- `qqplot_wtGSym`: as above but labels the gene symbols for the highest expressed genes.
- `bootDists`: rather than just showing the mean of the bootstrapped lists, a boxplot shows the distribution of values
- `bootDists_LOG`: shows the bootstrapped distributions with the y-axis shown on a log scale

Examples

```
## Load the single cell data
ctd <- ewceData::ctd()

## Set the parameters for the analysis
## Use 3 bootstrap lists for speed, for publishable analysis use >10,000
reps <- 3
annotLevel <- 1 # <- Use cell level annotations (i.e. Interneurons)
## Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5

## Load the top table
tt_alzh <- ewceData::tt_alzh()

## See ?example_transcriptome_results for full code to produce tt_results
tt_results <- EWCE::example_transcriptome_results()

## Bootstrap significance test,
## no control for transcript length or GC content
savePath <- EWCE::generate_bootstrap_plots_for_transcriptome(
```

```

sct_data = ctd,
tt = tt_alzh,
thresh = thresh,
annotLevel = 1,
full_results = tt_results,
listFileName = "examples",
reps = reps,
ttSpecies = "human",
sctSpecies = "mouse",
# Only do one plot type for demo purposes
plot_types = "bootstrap"
)

```

generate_celltype_data

Generate CellTypeData (CTD) file

Description

generate_celltype_data takes gene expression data and cell type annotations and creates Cell-TypeData (CTD) files which contain matrices of mean expression and specificity per cell type.

Usage

```

generate_celltype_data(
  exp,
  annotLevels,
  groupName,
  no_cores = 1,
  savePath = tempdir(),
  file_prefix = "ctd",
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  normSpec = FALSE,
  convert_orths = FALSE,
  input_species = "mouse",
  output_species = "human",
  non121_strategy = "drop_both_species",
  method = "homologene",
  force_new_file = TRUE,
  specificity_quantiles = TRUE,
  numberOfBins = 40,
  dendrograms = TRUE,
  return_ctd = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

exp	Numerical matrix with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
annotLevels	List with arrays of strings containing the cell type names associated with each column in exp.
groupName	A human readable name for referring to the dataset being
no_cores	Number of cores that should be used to speedup the computation. <i>NOTE:</i> Use no_cores=1 when using this package in windows system.
savePath	Directory where the CTD file should be saved.
file_prefix	Prefix to add to saved CTD file name.
as_sparse	Convert exp to a sparse Matrix.
as_DelayedArray	Convert exp to DelayedArray.
normSpec	Boolean indicating whether specificity data should be transformed to a normal distribution by cell type, giving equivalent scores across all cell types.
convert_orths	If input_species!=output_species and convert_orths=TRUE, will drop genes without 1:1 output_species orthologs and then convert exp gene names to those of output_species.
input_species	The species that the exp dataset comes from. See list_species for all available species.
output_species	Species to convert exp to (Default: "human"). See list_species for all available species.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> • "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (<i>DEFAULT</i>). • "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species. • "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species. • "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species. • "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs.

- "sum", "mean", "median", "min" or "max" :
When gene_df is a matrix and gene_output="rownames", these options will aggregate many-to-one gene mappings (input_species-to-output_species) after dropping any duplicate genes in the output_species.

method	R package to to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
force_new_file	If a file of the same name as the one being created already exists, overwrite it.
specificity_quantiles	Compute specificity quantiles. Recommended to set to TRUE.
numberOfBins	Number of quantile 'bins' to use (40 is recommended).
dendrograms	Add dendrogram plots
return_ctd	Return the CTD object in a list along with the file name, instead of just the file name.
verbose	Print messages.
...	Additional arguments passed to convert_orthologs .

Value

File names for the saved CellTypeData (CTD) files.

Examples

```
# Load the single cell data
cortex_mrna <- ewceData::cortex_mrna()
# Use only a subset to keep the example quick
expData <- cortex_mrna$exp[1:100, ]
l1 <- cortex_mrna$annot$level1class
l2 <- cortex_mrna$annot$level2class
annotLevels <- list(l1 = l1, l2 = l2)
fNames_ALLCELLS <- EWCE::generate_celltype_data(
  exp = expData,
  annotLevels = annotLevels,
  groupName = "allKImouse"
)
```

get_celltype_table *get_celltype_table*

Description

get_celltype_table Generates a table that can be used for supplementary tables of publications. The table lists how many cells are associated with each cell type, the level of annotation, and the dataset from which it was generated.

Usage

```
get_celltype_table(annot)
```

Arguments

annot An annotation dataframe, which columns named 'level1class', 'level2class' and 'dataset_name'

Value

A dataframe with columns 'name', 'level', 'freq' and 'dataset_name'

Examples

```
# See PrepLDSC.Rmd for origin of merged_ALLCELLS$annot
cortex_mrna <- ewceData::cortex_mrna()
cortex_mrna$annot$dataset_name <- "cortex_mrna"
celltype_table <- EWCE::get_celltype_table(cortex_mrna$annot)
```

is_delayed_array *Assess whether an object is a DelayedArray.*

Description

Assess whether an object is a DelayedArray or one of its derived object types.

Usage

```
is_delayed_array(X)
```

Arguments

X Object.

Value

boolean

is_matrix	<i>Assess whether an object is a Matrix</i>
-----------	---

Description

Assess whether an object is a Matrix or one of its derived object types.

Usage

```
is_matrix(X)
```

Arguments

X Object.

Value

boolean

is_sparse_matrix	<i>Assess whether an object is a sparse matrix</i>
------------------	--

Description

Assess whether an object is a sparse matrix or one of its derived object types.

Usage

```
is_sparse_matrix(X)
```

Arguments

X Object.

Value

boolean

list_species	<i>List all species</i>
--------------	-------------------------

Description

List all species that EWCE can convert genes from/to. Wrapper function for [map_species](#).

Usage

```
list_species(verbose = TRUE)
```

Arguments

verbose Print messages.

Value

List of species EWCE can input/output genes as.

Examples

```
list_species()
```

load_rdata	load_rdata
------------	------------

Description

Load processed data (*.rda* format) using a function that assigns it to a specific variable (so you don't have to guess what the loaded variable name is).

Usage

```
load_rdata(fileName)
```

Arguments

fileName Name of the file to load.

Value

Data object.

Examples

```
tmp <- tempfile()
save(mtcars, file = tmp)
mtcars2 <- load_rdata(tmp)
```

`merged_ewce`*Multiple EWCE results from multiple studies*

Description

`merged_ewce` combines enrichment results from multiple studies targetting the same scientific problem

Usage

```
merged_ewce(results, reps = 100)
```

Arguments

<code>results</code>	a list of EWCE results generated using add_res_to_merging_list .
<code>reps</code>	Number of random gene lists to generate (Default=100 but should be $\geq 10,000$ for publication-quality results).

Value

dataframe in which each row gives the statistics (p-value, fold change and number of standard deviations from the mean) associated with the enrichment of the stated cell type in the gene list.

Examples

```
# Load the single cell data
ctd <- ewceData::ctd()

# Use 3 bootstrap lists for speed, for publishable analysis use >10000
reps <- 3
# Use 5 up/down regulated genes (thresh) for speed, default is 250
thresh <- 5

# Load the data
tt_alzh_BA36 <- ewceData::tt_alzh_BA36()
tt_alzh_BA44 <- ewceData::tt_alzh_BA44()

# Run EWCE analysis
tt_results_36 <- EWCE::ewce_expression_data(
  sct_data = ctd,
  tt = tt_alzh_BA36,
  thresh = thresh,
  annotLevel = 1,
  reps = reps,
  ttSpecies = "human",
  sctSpecies = "mouse"
)
tt_results_44 <- EWCE::ewce_expression_data(
  sct_data = ctd,
```

```

    tt = tt_alzh_BA44,
    thresh = thresh,
    annotLevel = 1,
    reps = reps,
    ttSpecies = "human",
    sctSpecies = "mouse"
  )

# Fill a list with the results
results <- EWCE::add_res_to_merging_list(tt_results_36)
results <- EWCE::add_res_to_merging_list(tt_results_44, results)

# Perform the merged analysis
# For publication reps should be higher
merged_res <- EWCE::merged_ewce(
  results = results,
  reps = 2
)
print(merged_res)

```

merge_ctd

Merge multiple CellTypeDataset references

Description

Import CellTypeDataset (CTD) references from a remote repository, standardize each, and then merge into one CTD.

Usage

```

merge_ctd(
  CTD_list,
  save_dir = tempdir(),
  standardise_CTD = FALSE,
  as_SCE = FALSE,
  gene_union = TRUE,
  merge_levels = seq(1, 5),
  save_split_SCE = FALSE,
  save_split_CTD = FALSE,
  save_merged_SCE = TRUE,
  force_new_quantiles = FALSE,
  numberOfBins = 40,
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  verbose = TRUE,
  ...
)

```

Arguments

CTD_list	(Named) list of CellTypeDatasets.
save_dir	The directory to save merged files in.
standardise_CTD	Whether to run standardise_ctd.
as_SCE	If =T, will return a the merged CTD as a SingleCellExperiment. Otherwise, will return a list of unmerged CTD.
gene_union	Whether to take the gene union or intersection when merging matrices (mean_exp,specificity, etc.).
merge_levels	Which CTD levels you want to merge. Can be a single value (e.g. merge_levels=5) or a list c(e.g. merge_levels=c(1:5)). If some CTD don't have the same number of levels, the maximum level depth available in that CTD will be used instead.
save_split_SCE	Whether to save individual SCE files in the subdirectory <i>standardized_CTD_SCE</i> .
save_split_CTD	Whether to save individual CTD files in the subdirectory <i>standardized_CTD</i> .
save_merged_SCE	Save the final merged SCE object, or simply to return it.
force_new_quantiles	If specificity quantiles matrix already exists, create a new one.
numberOfBins	Number of bins to compute specificity quantiles with.
as_sparse	Convert matrices to sparse matrix.
as_DelayedArray	Convert matrices to DelayedArray.
verbose	Print messages.
...	Additional arguments to be passed to standardise_ctd.

Details

Optionally, can return these as a merged SingleCellExperiment.

Value

List of CellTypeDatasets or SingleCellExperiments.

Examples

```
## Let's pretend these are different CTD datasets
ctd1 <- ewceData::ctd()
ctd2 <- ctd1
CTD_list <- list(ctd1, ctd2)
SCE_merged <- EWCE::merge_ctd(
  CTD_list = CTD_list,
  as_SCE = TRUE,
  gene_union = TRUE
)
```

`merge_sce`*Merge multiple SingleCellExperiment objects*

Description

Merge several `SingleCellExperiment` (SCE) objects from different batches/experiments. Extracted from the `scMerge` package.

Usage

```
merge_sce(  
  sce_list,  
  method = "intersect",  
  cut_off_batch = 0.01,  
  cut_off_overall = 0.01,  
  use_assays = NULL,  
  colData_names = NULL,  
  batch_names = NULL,  
  verbose = TRUE  
)
```

Arguments

<code>sce_list</code>	A list contains the <code>SingleCellExperiment</code> Object from each batch.
<code>method</code>	A string indicates the method of combining the gene expression matrix, either union or intersect. Default to <code>intersect</code> . union only supports matrix class.
<code>cut_off_batch</code>	A numeric vector indicating the cut-off for the proportion of a gene is expressed within each batch.
<code>cut_off_overall</code>	A numeric vector indicating the cut-off for the proportion of a gene is expressed overall data.
<code>use_assays</code>	A string vector indicating the expression matrices to be combined. The first assay named will be used to determine the proportion of zeros.
<code>colData_names</code>	A string vector indicating the <code>colData</code> that are combined.
<code>batch_names</code>	A string vector indicating the batch names for the output SCE object.
<code>verbose</code>	Print messages.

Value

A `SingleCellExperiment` object with the list of SCE objects combined.

Author(s)

Yingxin Lin (modified by Brian Schilder)

Source

[scMerge](#).

Examples

```
ctd <- ewceData::ctd()
sce_list <- EWCE::ctd_to_sce(object = ctd)
sce_combine <- merge_sce(sce_list = sce_list)
```

merge_two_expfiles *Merge two exp files*

Description

merge_two_expfiles Used to combine two single cell type datasets.

Usage

```
merge_two_expfiles(
  exp1,
  exp2,
  annot1,
  annot2,
  name1 = "",
  name2 = "",
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  verbose = TRUE
)
```

Arguments

exp1	Numerical expression matrix for dataset1 with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
exp2	Numerical expression matrix for dataset2 with row for each gene and column for each cell. Row names are gene symbols. Column names are cell IDs which can be cross referenced against the annot data frame.
annot1	Annotation data frame for dataset1 which contains three columns at least: cell_id, level1class and level2class
annot2	Annotation data frame for dataset2 which contains three columns at least: cell_id, level1class and level2class
name1	Name used to refer to dataset 1. Leave blank if it's already a merged dataset.
name2	Name used to refer to dataset 2. Leave blank if it's already a merged dataset.
as_sparse	Convert the merged exp to a sparse matrix.

as_DelayedArray Convert the merged exp to a DelayedArray.
 verbose Print messages.

Value

List containing merged exp and annot.

Examples

```
cortex_mrna <- ewceData::cortex_mrna()
exp1 <- cortex_mrna$exp[, 1:50]
exp2 <- cortex_mrna$exp[, 51:100]
annot1 <- cortex_mrna$annot[1:50, ]
annot2 <- cortex_mrna$annot[51:100, ]
merged_res <- EWCE::merge_two_expfiles(
  exp1 = exp1,
  exp2 = exp2,
  annot1 = annot1,
  annot2 = annot2,
  name1 = "dataset1",
  name2 = "dataset2"
)
```

 plot_ctd

Plot CellTypeData metrics

Description

Plot *CellTypeData* metrics such as mean_exp, specificity and/or specificity_quantiles.

Usage

```
plot_ctd(ctd, genes, level = 1, metric = "specificity", show_plot = TRUE)
```

Arguments

ctd CellTypeDataset.
 genes Which genes in ctd to plot.
 level Annotation level in ctd to plot.
 metric Which metric in the ctd to plot:

- "mean_exp"
- "specificity"
- "specificity_quantiles"

show_plot Whether to print the plot or simply return it.

Value

ggplot object.

Examples

```
ctd <- ewceData::ctd()
plt <- EWCE::plot_ctd(ctd, genes = c("ApoE", "Gfap", "Gapdh"))
```

prep.dendro	<i>prep.dendro</i>
-------------	--------------------

Description

prep_dendro adds a dendrogram to a CellTypeDataset (CTD).

Usage

```
prep.dendro(ctdIN)
```

Arguments

ctdIN	A single annotLevel of a ctd, i.e. ctd[[1]] (the function is intended to be used via apply).
-------	--

Value

A CellTypeDataset with dendrogram plotting info added.

sct_normalize	<i>Normalize expression matrix</i>
---------------	------------------------------------

Description

Normalize expression matrix by accounting for library size. Uses **sctransform**.

Usage

```
sct_normalize(exp, as_sparse = TRUE, verbose = TRUE)
```

Arguments

exp	Gene x cell expression matrix.
as_sparse	Convert exp to sparse matrix.
verbose	Print messages.

Value

Normalised expression matrix.

Examples

```
cortex_mrna <- ewceData::cortex_mrna()
exp_sct_normed <- EWCE::sct_normalize(exp = cortex_mrna$exp[1:300, ])
```

standardise_ctd	<i>Convert a CellTypeDataset into standardized format</i>
-----------------	---

Description

This function will take a CTD, drop all genes without 1:1 orthologs with the output_species ("human" by default), convert the remaining genes to gene symbols, assign names to each level, and convert all matrices to sparse matrices and/or DelayedArray.

Usage

```
standardise_ctd(
  ctd,
  dataset,
  input_species = NULL,
  output_species = "human",
  non121_strategy = "drop_both_species",
  method = "homologene",
  force_new_quantiles = TRUE,
  force_standardise = FALSE,
  remove_unlabeled_clusters = FALSE,
  numberOfBins = 40,
  keep_annot = TRUE,
  keep_plots = TRUE,
  as_sparse = TRUE,
  as_DelayedArray = FALSE,
  rename_columns = TRUE,
  make_columns_unique = FALSE,
  verbose = TRUE
)
```

Arguments

ctd	Input CellTypeData.
dataset	CellTypeData. name.
input_species	Which species the gene names in exp come from. See list_species for all available species.

output_species	Which species' genes names to convert exp to. See list_species for all available species.
non121_strategy	How to handle genes that don't have 1:1 mappings between input_species:output_species. Options include: <ul style="list-style-type: none"> • "drop_both_species" or "dbs" or 1 : Drop genes that have duplicate mappings in either the input_species or output_species (<i>DEFAULT</i>). • "drop_input_species" or "dis" or 2 : Only drop genes that have duplicate mappings in the input_species. • "drop_output_species" or "dos" or 3 : Only drop genes that have duplicate mappings in the output_species. • "keep_both_species" or "kbs" or 4 : Keep all genes regardless of whether they have duplicate mappings in either species. • "keep_popular" or "kp" or 5 : Return only the most "popular" interspecies ortholog mappings. This procedure tends to yield a greater number of returned genes but at the cost of many of them not being true biological 1:1 orthologs. • "sum", "mean", "median", "min" or "max" : When gene_df is a matrix and gene_output="rownames", these options will aggregate many-to-one gene mappings (input_species-to-output_species) after dropping any duplicate genes in the output_species.
method	R package to use for gene mapping: <ul style="list-style-type: none"> • "gprofiler" : Slower but more species and genes. • "homologene" : Faster but fewer species and genes. • "babelgene" : Faster but fewer species and genes. Also gives (slower but more species and genes) or "homologene" (faster but fewer species and genes).
force_new_quantiles	By default, quantile computation is skipped if they have already been computed. Set =TRUE to override this and generate new quantiles.
force_standardise	If ctd has already been standardised, whether to rerun standardisation anyway (Default: FALSE).
remove_unlabeled_clusters	Remove any samples that have numeric column names.
numberOfBins	Number of non-zero quantile bins.
keep_annot	Keep the column annotation data if provided.
keep_plots	Keep the dendrograms if provided.
as_sparse	Convert to sparse matrix.
as_DelayedArray	Convert to DelayedArray.

`rename_columns` Remove `replace_chars` from column names.
`make_columns_unique` Rename each columns with the prefix `dataset.species.celltype`.
`verbose` Print messages. Set `verbose=2` if you want to print all messages from internal functions as well.

Value

Standardised `CellTypeDataset`.

Examples

```
ctd <- ewceData::ctd()
ctd_std <- EWCE::standardise_ctd(
  ctd = ctd,
  input_species = "mouse",
  dataset = "Zeisel2016"
)
```

Index

`add_res_to_merging_list`, 4, 37
`align_plots()`, 19

`bin_columns_into_quantiles`, 5
`bin_specificity_into_quantiles`, 5
`bootstrap_enrichment_test`, 4, 6, 10, 18, 19, 27

`check_ewce_genelist_inputs`, 8
`check_percent_hits`, 10
`controlled_geneset_enrichment`, 11
`convert_orthologs`, 33
`ctd_to_sce`, 13

`drop_uninformative_genes`, 14

EWCE (EWCE-package), 3
EWCE-package, 3
`ewce_expression_data`, 4, 16, 18, 20, 29
`ewce_plot`, 18
`example_bootstrap_results`, 19
`example_transcriptome_results`, 20

`filter_genes_without_1to1_homolog`, 21
`filter_nonorthologs`, 21, 22
`fix_bad_hgnc_symbols`, 23
`fix_bad_mgi_symbols`, 24
`fix_celltype_names`, 25

`generate_bootstrap_plots`, 26
`generate_bootstrap_plots_for_transcriptome`, 28
`generate_celltype_data`, 7, 9, 12, 16, 26, 29, 31
`get_celltype_table`, 34

`is_delayed_array`, 34
`is_matrix`, 35
`is_sparse_matrix`, 35

`list_species`, 7, 9, 12, 15, 17, 27, 29, 32, 36, 44, 45

`load_rdata`, 36

`map_genes`, 9
`map_species`, 36
`merge_ctd`, 38
`merge_sce`, 40
`merge_two_expfiles`, 41
`merged_ewce`, 37

`p.adjust`, 7, 14, 19
`plot_ctd`, 42
`prep.dendro`, 43

`sct_normalize`, 43
`standardise_ctd`, 44

`topTable`, 17, 29