

Package ‘miRmine’

October 11, 2022

Type Package

Title Data package with miRNA-seq datasets from miRmine database as RangedSummarizedExperiment

Version 1.18.0

Date 2021-11-21

Description miRmine database is a collection of expression profiles from different publicly available miRNA-seq datasets, Panwar et al (2017) miRmine: A Database of Human miRNA Expression, prepared with this data package as RangedSummarizedExperiment.

Depends R (>= 3.4), SummarizedExperiment

Suggests BiocStyle, knitr, rmarkdown, DESeq2

License GPL (>= 3)

LazyData true

biocViews Homo_sapiens_Data, RNASeqData, SequencingData, ExpressionData

VignetteBuilder knitr

NeedsCompilation no

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/miRmine>

git_branch RELEASE_3_15

git_last_commit a03585d

git_last_commit_date 2022-04-26

Date/Publication 2022-10-11

Author Dusan Randjelovic [aut, cre]

Maintainer Dusan Randjelovic <dusan.randjelovic@sbgenomics.com>

R topics documented:

miRmine	2
Index	5

miRmine

*miRmine dataset***Description**

miRmine dataset, from Panwar et al (2017) miRmine: A Database of Human miRNA Expression

Usage

```
data("miRmine")
```

Format

miRmine A [RangedSummarizedExperiment](#) object.

For all the details on how this dataset was produced, see examples.

Source

Panwar et al (2017) miRmine: A Database of Human miRNA Expression

Examples

```
## Not run:
library(GenomicRanges)
library(rtracklayer)
library(SummarizedExperiment)
library(Biostrings)

ext.data <- system.file("extdata", package = "miRmine")
hsa.gff3.file = file.path(ext.data, "hsa.gff3")
mature.fa.file = file.path(ext.data, "mature.fa")
miRmine.info.file = file.path(ext.data, "miRmine-info.txt")
miRmine.tissues.file = file.path(ext.data, "miRmine-tissues.csv")
miRmine.cell.lines.file = file.path(ext.data, "miRmine-cell-lines.csv")

gffRangedData.all <- import.gff3(hsa.gff3.file, genome="GRCh38")
gffRangedData.all$source = "miRBase v21"
gffRangedData.all$UniqueName = gffRangedData.all$Name
for (id in seq_along(as.character(gffRangedData.all$ID))){
  name = gffRangedData.all[id, ]$Name
  derives_from = gffRangedData.all[id, ]$Derives_from
  if (!is.na(derives_from)){
    precursor =
      gffRangedData.all[gffRangedData.all$ID == derives_from, ]$Name
    gffRangedData.all[id, ]$UniqueName = paste(name, precursor, sep=".")
  }
}
gff = gffRangedData.all[gffRangedData.all$type == "miRNA"]
gff = sort(gff, by=~UniqueName)
```

```

tiss = read.csv(miRmine.tissues.file)
tiss$UniqueName =
  paste(tiss$Mature.miRNA.ID, tiss$Precursor.miRNA.ID, sep=".")
tiss = tiss[base::order(tiss$UniqueName), ]

diff.names = setdiff(tiss$UniqueName, gff$UniqueName) # 7 rows differ

cellines = read.csv(miRmine.cell.lines.file)
cellines$UniqueName =
  paste(cellines$Mature.miRNA.ID, cellines$Precursor.miRNA.ID, sep=".")
cellines = cellines[base::order(cellines$UniqueName), ]

setdiff(cellines$UniqueName, gff$UniqueName) # same 7 rows differ

tissue.mirnas.freq = base::sort(table(tiss$UniqueName))
gff.mirnas.freq = base::sort(table(gff$UniqueName))
setdiff(tissue.mirnas.freq, gff.mirnas.freq) # additional 2 rows duplicated
tissue.mirnas.freq[tissue.mirnas.freq > 1] # shows which rows are different

base::rownames(
  tiss[(tiss$UniqueName %in%
    c('hsa-miR-3142.hsa-mir-3142', 'hsa-miR-4487.hsa-mir-4487')),])

tiss = tiss[-c(624, 1213),]
tiss = tiss[!(tiss$UniqueName %in% diff.names), ]
cellines = cellines[-c(624, 1213),]
cellines = cellines[!(cellines$UniqueName %in% diff.names), ]

mirnas.unique.names = tiss$UniqueName
tiss.counts =
  tiss[, -which(names(tiss) %in%
    c("UniqueName", "Mature.miRNA.ID", "Precursor.miRNA.ID"))]
cellines.counts =
  cellines[, -which(names(cellines) %in%
    c("UniqueName", "Mature.miRNA.ID", "Precursor.miRNA.ID"))]
expression = as.matrix(cbind(tiss.counts, cellines.counts))
rownames(expression) = mirnas.unique.names

# add mirna sequences
library(Rsamtools)
fasta = FaFile(mature.fa.file)
mirna.string.set = scanFa(fasta)
newnames = strsplit(names(mirna.string.set), " ")
newnames = unlist(newnames)[ c(TRUE, rep(FALSE, 4)) ]
names(mirna.string.set) = newnames

dna.strings = list()
for (id in seq_along(gff)){
  name = gff[id, ]$Name
  unique_name = gff[id, ]$UniqueName
  dna.strings[[unique_name]] = mirna.string.set[[name]]
}

```

```
gff$mirna_seq = dna.strings

# construct RSE
meta = read.csv(miRmine.info.file, sep="\t")

miRmine =
  SummarizedExperiment(
    assays=SimpleList(counts=expression),
    rowData=NULL,
    rowRanges=gff,
    colData=meta
  )

## End(Not run)
```

Index

* **datasets**

miRmine, [2](#)

miRmine, [2](#)

RangedSummarizedExperiment, [2](#)