

# Package ‘TENxPBMCData’

October 11, 2022

**Title** PBMC data from 10X Genomics

**Version** 1.14.0

**Description** Single-cell RNA-seq data for on PBMC cells, generated by 10X Genomics.

**License** CC BY 4.0

**Depends** SingleCellExperiment, HDF5Array

**Imports** AnnotationHub, ExperimentHub

**Suggests** rmarkdown, knitr, BiocStyle, snow, BiocFileCache,  
BiocParallel

**VignetteBuilder** knitr

**biocViews** SequencingData, RNASeqData, ExpressionData, ExperimentHub,  
ExperimentData, SingleCellData

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/TENxPBMCData>

**git\_branch** RELEASE\_3\_15

**git\_last\_commit** e4b8854

**git\_last\_commit\_date** 2022-04-26

**Date/Publication** 2022-10-11

**Author** Kasper D. Hansen [aut],  
Davide Risso [aut],  
Milan Malfait [ctb],  
Jeroen Gilis [ctb],  
Theodore Killian [ctb],  
Murat Cem Kose [ctb],  
Chong Tang [ctb],  
Teun van den Brand [ctb],  
Dania Machlab [ctb],  
Stephanie Hicks [aut, cre]

**Maintainer** Stephanie Hicks <shicks19@jhu.edu>

## R topics documented:

TENxPBMCData . . . . . 2

---

TENxPBMCData	<i>10X PBMC Data</i>
--------------	----------------------

---

### Description

Various single-cell RNA-seq data on PBMC, generated by 10X Genomics.

### Usage

```
TENxPBMCData(dataset = c("pbmc4k", "pbmc68k",
                          "frozen_pbmc_donor_a", "frozen_pbmc_donor_b",
                          "frozen_pbmc_donor_c", "pbmc33k", "pbmc3k",
                          "pbmc6k", "pbmc8k", "pbmc5k-CITEseq"),
              as.sparse = TRUE)
```

### Arguments

dataset	Which PBMC dataset from 10X Genomics should be retrieved?
as.sparse	Logical, specifies whether the underlying HDF5 dataset should be treated as sparse or not - will be passed to the call to HDF5Array(). Defaults to TRUE, i.e. by using the DelayedArray infrastructure.

### Details

Single-cell RNA-seq and CITE-seq data were generated by 10X Genomics at various times, using different versions of CellRanger, different chemistries and different genome builds. For details, see the 10X website.

We obtained ‘filtered’ data and generated SingleCellExperiment containers with data stored as an HDF5 Assay.

As rowData we include ENSEMBL and Symbol\_TENx which are ENSEMBL gene ID and gene symbol provided by TENx genomics and a remapping of the Ensembl identifier to a Hugo gene symbol as columns Symbol using the org.Hs.eg.db package. The difference between Symbol and Symbol\_TENx is that the former has many missing values (for non-protein coding genes) whereas the later is technically not a Hugo gene symbol. In case of CITE-seq data, the rowData has an additional column Type specifying if the counts are "Gene Expression" or "Antibody Capture". Note that there is a separate rowData for the altExp.

### Value

A SingleCellExperiment object with a HDF5Matrix in the counts assay, which contains UMI counts for each gene in each cell. Row- and column-level metadata are also provided. In case of CITE-seq data, the "Antibody Capture" counts are stored in the altExp of the SingleCellExperiment.

**Author(s)**

Kasper D. Hansen, Stephanie Hicks, Davide Risso

**References**

10X Genomics (2017). 1.3 Million PBMC Cells from E18 Mice. [https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.3.0/1M\\_neurons](https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.3.0/1M_neurons)

**See Also**

[SingleCellExperiment](#)

**Examples**

```
sce <- TENxPBMCData()
sce
lib.size <- colSums(assay(sce))
hist(log10(lib.size))

# CITE-seq data
sce <- TENxPBMCData(dataset = "pbmc5k-CITEseq")
sce
altExp(sce)
```

# Index

SingleCellExperiment, [3](#)

TENxPBMCData, [2](#)