

# Package ‘CATALYST’

May 30, 2023

**Type** Package

**Title** Cytometry dATa anALYSis Tools

**Version** 1.24.0

**Depends** R (>= 4.2), SingleCellExperiment

**biocViews** Clustering, DataImport, DifferentialExpression,  
ExperimentalDesign, FlowCytometry, ImmunoOncology,  
MassSpectrometry, Normalization, Preprocessing, SingleCell,  
Software, StatisticalMethod, Visualization

**Description** Mass cytometry (CyTOF) uses heavy metal isotopes rather than fluorescent tags as reporters to label antibodies, thereby substantially decreasing spectral overlap and allowing for examination of over 50 parameters at the single cell level. While spectral overlap is significantly less pronounced in CyTOF than flow cytometry, spillover due to detection sensitivity, isotopic impurities, and oxide formation can impede data interpretability. We designed CATALYST (Cytometry dATa anALYSis Tools) to provide a pipeline for preprocessing of cytometry data, including i) normalization using bead standards, ii) single-cell deconvolution, and iii) bead-based compensation.

**Imports** circlize, ComplexHeatmap, ConsensusClusterPlus, cowplot,  
data.table, dplyr, drc, flowCore, FlowSOM, ggplot2, ggrepel,  
ggridges, graphics, grDevices, grid, gridExtra, magrittr,  
Matrix, matrixStats, methods, nnls, purrr, RColorBrewer,  
reshape2, Rtsne, SummarizedExperiment, S4Vectors, scales,  
scater, stats

**Suggests** BiocStyle, diffcyt, flowWorkspace, ggcyto, knitr, openCyto,  
rmarkdown, testthat, uwot

**URL** <https://github.com/HelenaLC/CATALYST>

**BugReports** <https://github.com/HelenaLC/CATALYST/issues>

**VignetteBuilder** knitr

**RoxygenNote** 7.2.3

**License** GPL (>=2)

**Encoding** UTF-8

**LazyData** true

**git\_url** <https://git.bioconductor.org/packages/CATALYST>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** f3e294e

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-05-30

**Author** Helena L. Crowell [aut, cre] (<<https://orcid.org/0000-0002-4801-1767>>),

Vito R.T. Zanotelli [aut],

Stéphane Chevrier [aut, dtc],

Mark D. Robinson [aut, fnd],

Bernd Bodenmiller [fnd]

**Maintainer** Helena L. Crowell <[helena.crowell@uzh.ch](mailto:helena.crowell@uzh.ch)>

## R topics documented:

|                              |    |
|------------------------------|----|
| adaptSpillmat . . . . .      | 3  |
| applyCutoffs . . . . .       | 4  |
| assignPrelim . . . . .       | 5  |
| clrDR . . . . .              | 6  |
| cluster . . . . .            | 9  |
| compCytof . . . . .          | 11 |
| computeSpillmat . . . . .    | 13 |
| data . . . . .               | 15 |
| estCutoffs . . . . .         | 16 |
| extractClusters . . . . .    | 18 |
| filterSCE . . . . .          | 19 |
| guessPanel . . . . .         | 20 |
| mergeClusters . . . . .      | 21 |
| normCytof . . . . .          | 22 |
| pbMDS . . . . .              | 24 |
| plotAbundances . . . . .     | 26 |
| plotClusterExprs . . . . .   | 28 |
| plotClusterHeatmap . . . . . | 29 |
| plotCodes . . . . .          | 30 |
| plotCounts . . . . .         | 31 |
| plotDiffHeatmap . . . . .    | 32 |
| plotDR . . . . .             | 35 |
| plotEvents . . . . .         | 37 |
| plotExprHeatmap . . . . .    | 38 |
| plotExprs . . . . .          | 41 |
| plotFreqHeatmap . . . . .    | 42 |
| plotMahal . . . . .          | 44 |
| plotMultiHeatmap . . . . .   | 45 |
| plotNRS . . . . .            | 48 |
| plotPbExprs . . . . .        | 49 |
| plotScatter . . . . .        | 51 |

|                         |           |
|-------------------------|-----------|
| <i>adaptSpillmat</i>    | 3         |
| plotSpillmat . . . . .  | 52        |
| plotYields . . . . .    | 53        |
| prepData . . . . .      | 55        |
| runDR . . . . .         | 57        |
| SCE-accessors . . . . . | 59        |
| sce2fcs . . . . .       | 61        |
| <b>Index</b>            | <b>63</b> |

---

|               |                               |
|---------------|-------------------------------|
| adaptSpillmat | <i>Adapt spillover matrix</i> |
|---------------|-------------------------------|

---

**Description**

This helper function adapts the columns of a provided spillover matrix such that it is compatible with data having the column names provided.

**Usage**

```
adaptSpillmat(  
  x,  
  out_chs,  
  isotope_list = CATALYST::isotope_list,  
  verbose = TRUE  
)
```

**Arguments**

- x a previously calculated spillover matrix.
- out\_chs the column names that the prepared output spillover matrix should have. Numeric names as well as names of the form MetalMass(Di), e.g. Ir191, Ir191Di or Ir191(Di), will be interpreted as masses with associated metals.
- isotope\_list named list. Used to validate the input spillover matrix. Names should be metals; list elements numeric vectors of their isotopes. See [isotope\\_list](#) for the list of isotopes used by default.
- verbose logical. Should warnings about possibly inaccurate spillover estimates be printed to the console?

**Details**

The rules how the spillover matrix is adapted are explained in [compCytof](#).

**Value**

An adapted spillover matrix with column and row names according to out\_chs.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch> & Vito RT Zanutelli

**Examples**

```
# estimate spillover matrix from
# single-stained control samples
data(ss_exp)
sce <- prepData(ss_exp)
bc_ms <- c(139, 141:156, 158:176)
sce <- assignPrelim(sce, bc_ms, verbose = FALSE)
sce <- applyCutoffs(estCutoffs(sce))
sce <- computeSpillmat(sce)

library(SingleCellExperiment)
sm1 <- metadata(sce)$spillover_matrix
sm2 <- adaptSpillmat(sm1, rownames(sce), verbose = FALSE)
all(dim(sm2) == ncol(sm1))
```

---

|              |                                    |
|--------------|------------------------------------|
| applyCutoffs | <i>Single-cell debarcoding (2)</i> |
|--------------|------------------------------------|

---

**Description**

Applies separation and mahalanobies distance cutoffs.

**Usage**

```
applyCutoffs(x, assay = "exprs", mhl_cutoff = 30, sep_cutoffs = NULL)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                                |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x           | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                       |
| assay       | character string specifying which assay data to use. Should be one of assayNames(x) and correspond to expression-like not count data.                                                                                                                                                                          |
| mhl_cutoff  | numeric mahalanobis distance threshold above which events should be unassigned; ignored if metadata(x)\$mhl_cutoff exists.                                                                                                                                                                                     |
| sep_cutoffs | non-negative numeric of length one or of same length as the number of rows in the bc_key(x). Specifies the distance separation cutoffs between positive and negative barcode populations below which events should be unassigned. If NULL (default), applyCutoffs will try to access metadata(x)\$sep_cutoffs. |

**Value**

the input SingleCellExperiment x is returned with updated colData columns "bc\_id" and "mhl\_dist", and an additional int\_metadata slot "mhl\_cutoff" containing the applied mahalanobies distance cutoff.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Zunder, E.R. et al. (2015). Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell deconvolution algorithm. *Nature Protocols* **10**, 316-333.

**Examples**

```
library(SingleCellExperiment)

# construct SCE
data(sample_ff, sample_key)
sce <- prepData(sample_ff)

# assign preliminary barcode IDs
# & estimate separation cutoffs
sce <- assignPrelim(sce, sample_key)
sce <- estCutoffs(sce)

# use estimated population-specific
# vs. global separation cutoff(s)
sce1 <- applyCutoffs(sce)
sce2 <- applyCutoffs(sce, sep_cutoffs = 0.35)

# compare yields after applying cutoff(s)
c(global = mean(sce1$bc_id != 0),
  specific = mean(sce2$bc_id != 0))
```

---

|              |                                    |
|--------------|------------------------------------|
| assignPrelim | <i>Single-cell debarcoding (1)</i> |
|--------------|------------------------------------|

---

**Description**

Assigns a preliminary barcode ID to each event.

**Usage**

```
assignPrelim(x, bc_key, assay = "exprs", verbose = TRUE)
```

**Arguments**

|        |                                                                                                                                                                                                                                                                                   |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                          |
| bc_key | the debarcoding scheme. A binary matrix with sample names as row names and numeric masses as column names OR a vector of numeric masses corresponding to barcode channels. When the latter is supplied, ‘assignPrelim’ will create a scheme of the appropriate format internally. |

assay                character string specifying which assay to use.

verbose             logical. Should extra information on progress be reported?

### Value

a SingleCellExperiment structured as follows:

**assays**    • counts - raw counts  
              • exprs - arcsinh-transformed counts  
              • scaled - population-wise scaled expression using (95%)-quantiles as boundaries

**colData**    • bc\_idnumeric vector of barcode assignments  
              • deltaseparation between positive and negative barcode populations

**metadata**    • bc\_keythe input debarcoding scheme

### Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

### References

Zunder, E.R. et al. (2015). Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell deconvolution algorithm. *Nature Protocols* **10**, 316-333.

### Examples

```
data(sample_ff, sample_key)
sce <- prepData(sample_ff)
sce <- assignPrelim(sce, sample_key)
table(sce$bc_id)
```

---

clrDR

*DR plot on CLR of proportions*

---

### Description

Computes centered log-ratios (CLR) on cluster/sample proportions across samples/clusters, and visualizes them in a lower-dimensional space, highlighting differences in composition between samples/clusters.

**Usage**

```

clrDR(
  x,
  dr = c("PCA", "MDS", "UMAP", "TSNE", "DiffusionMap"),
  by = c("sample_id", "cluster_id"),
  k = "meta20",
  dims = c(1, 2),
  base = 2,
  arrows = TRUE,
  point_col = switch(by, sample_id = "condition", "cluster_id"),
  arrow_col = switch(by, sample_id = "cluster_id", "condition"),
  arrow_len = 0.5,
  arrow_opa = 0.5,
  label_by = NULL,
  size_by = TRUE,
  point_pal = NULL,
  arrow_pal = NULL
)

```

**Arguments**

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                    | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                            |
| dr                   | character string specifying which dimension reduction to use.                                                                                                                                                                                                                                                                                                                                                       |
| by                   | character string specifying across which IDs to compute CLRs <ul style="list-style-type: none"> <li>• by = "sample_id" compute CLRs across relative abundances of samples across clusters; each point in the embedded space represents a sample.</li> <li>• by = "cluster_id" compute CLRs across relative abundances of clusters across samples; each point in the embedded space represents a cluster.</li> </ul> |
| k                    | character string specifying which clustering to use; valid values are <code>names(cluster_codes(x))</code> .                                                                                                                                                                                                                                                                                                        |
| dims                 | two numeric scalars indicating which dimensions to plot.                                                                                                                                                                                                                                                                                                                                                            |
| base                 | integer scalar specifying the logarithm base to use.                                                                                                                                                                                                                                                                                                                                                                |
| arrows               | logical specifying whether to include arrows for PC loadings.                                                                                                                                                                                                                                                                                                                                                       |
| point_col, arrow_col | character string specifying a non-numeric cell metadata column to color points and PC loading arrows by; valid values are <code>names(colData(x))</code> .                                                                                                                                                                                                                                                          |
| arrow_len            | non-zero single numeric specifying the length of loading vectors relative to the largest xy-coordinate in the embedded space; NULL for no re-sizing (see details).                                                                                                                                                                                                                                                  |
| arrow_opa            | single numeric in [0,1] specifying the opacity (alpha) of PC loading arrows when they are grouped; 0 will hide individual arrows.                                                                                                                                                                                                                                                                                   |
| label_by             | character string specifying a non-numeric sample metadata variable to label points by; valid values are <code>names(colData(x))</code> .                                                                                                                                                                                                                                                                            |
| size_by              | logical specifying whether to scale point sizes by the number of cells in a given sample/cluster (for by = "sample/cluster_id").                                                                                                                                                                                                                                                                                    |

point\_pal, arrow\_pal

character string of colors to use for points and PC loading arrows. Arguments default to `CATALYST:::cluster_cols` for clusters, and `brewer.pal`'s "Set3" for samples.

## Details

**The centered log-ratio (CLR)** Let  $k$  be one of  $S$  samples,  $k$  one of  $K$  clusters, and  $p(s, k)$  be the proportion of cells from  $s$  in  $k$ . The centered log-ratio (CLR) is defined as

$$clr(sk) = \log p(s, k) - \sum p(s, k) / K$$

and analogous for clusters replacing  $s$  by  $k$  and  $K$  by  $S$ . Thus, each sample/cluster gives a vector with length  $K/S$  and mean 0, and the CLRs computed across all instances can be represented as a matrix with dimensions  $S \times K$  (or  $K \times S$  for clusters) that we embed into a lower dimensional space.

**Dimensionality reduction** In principle, `clrDR` allows any dimension reduction to be applied on the CLRs. The default method (`dr = "PCA"`) will include the percentage of variance explained by each principal component (PC) in the axis labels.

Noteworthy, distances between points in the lower-dimensional space are meaningful only for linear DR methods (PCA and MDS), and results obtained from other methods should be interpreted with caution. Thus, the output plot's aspect ratio should be kept as is for PCA and MDS; non-linear DR methods can use `aspect.ratio = 1`, rendering a square plot.

**Interpreting PC loadings** For `dr = "PCA"`, PC loadings will be represented as arrows that may be interpreted as follows:  $0^\circ$  ( $180^\circ$ ) between vectors indicates a strong positive (negative) relation between them, while vectors that are orthogonal to each another ( $90^\circ$ ) are roughly independent.

When a vector points towards a given quadrant, the variability in proportions for the points within this quadrant are largely driven by the corresponding variable. Here, only the relative orientation of vectors to one another and to the PC axes is meaningful; however, the sign of loadings (i.e., whether an arrow points left or right) can be flipped when re-computing PCs.

When `arrow_len` is specified, PC loading vectors will be re-scaled to improve their visibility. Here, a value of 1 will stretch vectors such that the largest loading will touch on the outer most point. Importantly, while absolute arrow lengths are not interpretable, their relative length is.

## Value

a `ggplot` object.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## Examples

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)
```



```
# CLR on sample proportions across clusters
# (1st vs. 3rd PCA; include sample labels)
clrDR(sce, by = "sample_id", k = "meta12",
      dims = c(1, 3), label_by = "sample_id")

# CLR on cluster proportions across samples
# (use custom colors for both points & loadings)
clrDR(sce, by = "cluster_id",
      point_pal = hcl.colors(10, "Spectral"),
      arrow_pal = c("royalblue", "orange"))
```

---

|         |                                                                        |
|---------|------------------------------------------------------------------------|
| cluster | FlowSOM <i>clustering</i> & ConsensusClusterPlus <i>metaclustering</i> |
|---------|------------------------------------------------------------------------|

---

## Description

cluster will first group cells into xdimxydim clusters using **FlowSOM**, and subsequently perform metaclustering with **ConsensusClusterPlus** into 2 through maxK clusters.

## Usage

```
cluster(
  x,
  features = "type",
  xdim = 10,
  ydim = 10,
  maxK = 20,
  verbose = TRUE,
  seed = 1
)
```

## Arguments

|            |                                                                                                                                                                                                                                   |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x          | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                          |
| features   | a character vector specifying which features to use for clustering; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |
| xdim, ydim | numeric specifying the grid size of the self-organizing map; passed to <a href="#">BuildSOM</a> . The default 10x10 grid will yield 100 clusters.                                                                                 |
| maxK       | numeric specifying the maximum number of clusters to evaluate in the metaclustering; passed to <a href="#">ConsensusClusterPlus</a> . The default (maxK = 20) will yield 2 through 20 metaclusters.                               |
| verbose    | logical. Should information on progress be reported?                                                                                                                                                                              |
| seed       | numeric. Sets the random seed for reproducible results in <a href="#">ConsensusClusterPlus</a> .                                                                                                                                  |

## Details

The delta area represents the amount of extra cluster stability gained when clustering into  $k$  groups as compared to  $k-1$  groups. It can be expected that high stability of clusters can be reached when clustering into the number of groups that best fits the data. The "natural" number of clusters present in the data should thus corresponds to the value of  $k$  where there is no longer a considerable increase in stability (plateau onset).

## Value

a SingleCellExperiment with the following newly added data:

- colData
  - cluster\_id: each cell's cluster ID as inferred by FlowSOM. One of 1, ...,  $x_{dim} \times y_{dim}$ .
- rowData
  - marker\_class: added when previously unspecified. "type" when an antigen has been used for clustering, otherwise "state".
  - used\_for\_clustering: logical indicating whether an antigen has been used for clustering.
- metadata
  - SOM\_codes: a table with dimensions  $K \times (\# \text{ cell type markers})$ , where  $K = x_{dim} \times y_{dim}$ . Contains the SOM codes.
  - cluster\_codes: a table with dimensions  $K \times (\max K + 1)$ . Contains the cluster codes for all metaclustering.
  - delta\_area: a [ggplot](#) object (see details).

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```
# construct SCE
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)

# run clustering
(sce <- cluster(sce))

# view all available clustering
names(cluster_codes(sce))

# access specific clustering resolution
```

```
table(cluster_ids(sce, "meta8"))

# view delta area plot
delta_area(sce)
```

---

compCytOf

Compensate CyTOF data

---

## Description

Compensates a mass spectrometry based experiment using a provided spillover matrix & assuming a linear spillover in the experiment.

## Usage

```
compCytOf(
  x,
  sm = NULL,
  method = c("nnls", "flow"),
  assay = "counts",
  overwrite = TRUE,
  transform = TRUE,
  cofactor = NULL,
  isotope_list = CATALYST::isotope_list
)
```

## Arguments

|           |                                                                                                                                                                                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x         | a <a href="#">SingleCellExperiment</a> OR a character string specifying the location of FCS files that should be compensates.                                                                                                                                                      |
| sm        | a spillover matrix.                                                                                                                                                                                                                                                                |
| method    | "flow" or "nnls".                                                                                                                                                                                                                                                                  |
| assay     | character string specifying which assay data to use; should be one of assayNames(x) and correspond to count-like data, as linearity assumptions underlying compensation won't hold otherwise.                                                                                      |
| overwrite | logical; should the specified assay slot (and exprs, when transform = TRUE) be overwritten with the compensated data? If FALSE, compensated counts (and expressions, if transform = TRUE) will be stored in assay(s) compcounts/exprs, respectively.                               |
| transform | logical; should normalized counts be arcsinh-transformed with the specified cofactor(s)?                                                                                                                                                                                           |
| cofactor  | numeric cofactor(s) to use for optional arcsinh-transformation when transform = TRUE; single value or a vector with channels as names. If NULL, compCytOf will try and access the cofactor(s) stored in int_metadata(x), thus re-using the same transformation applied previously. |

**isotope\_list**      named list. Used to validate the input spillover matrix. Names should be metals; list elements numeric vectors of their isotopes. See [isotope\\_list](#) for the list of isotopes used by default.

## Details

If the spillover matrix (SM) does not contain the same set of columns as the input experiment, it will be adapted according to the following rules:

1. columns present in the SM but not in the input data will be removed from it
2. non-metal columns present in the input but not in the SM will be added such that they do neither receive nor cause spill
3. metal columns that have the same mass as a channel present in the SM will receive (but not emit) spillover according to that channel
4. if an added channel could potentially receive spillover (as it has +/-1M or +16M of, or is of the same metal type as another channel measured), a warning will be issued as there could be spillover interactions that have been missed and may lead to faulty compensation

## Value

Compensates the input [flowFrame](#) or, if x is a character string, all FCS files in the specified location.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch> & Vito RT Zanutelli

## Examples

```
# deconvolute single-stained control samples
data(ss_exp)
sce <- prepData(ss_exp)
bc_ms <- c(139, 141:156, 158:176)
sce <- assignPrelim(sce, bc_ms)
sce <- applyCutoffs(estCutoffs(sce))

# estimate spillover matrix
sce <- computeSpillmat(sce)

# compensate & store compensated data in separate assays
sce <- compCytotf(sce, overwrite = FALSE)
assayNames(sce)

# bscatter before vs. after compensation
chs <- c("Dy162Di", "Dy163Di")
m <- match(chs, channels(sce))
i <- rownames(sce)[m][1]
j <- rownames(sce)[m][2]

par(mfrow = c(1, 2))
for (a in c("exprs", "compexprs")) {
  es <- assay(sce, a)
```

```

plot(es[i, ], es[j, ], cex = 0.2, pch = 19,
     main = a, xlab = i, ylab = j)
}

```

---

|                 |                                 |
|-----------------|---------------------------------|
| computeSpillmat | <i>Compute spillover matrix</i> |
|-----------------|---------------------------------|

---

## Description

Computes a spillover matrix from priorly identified single-positive populations.

## Usage

```

computeSpillmat(
  x,
  assay = "counts",
  interactions = c("default", "all"),
  method = c("default", "classic"),
  trim = 0.5,
  th = 1e-05
)

```

## Arguments

|                           |                                                                                                                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>            | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                     |
| <code>assay</code>        | character string specifying which assay to use; should be one of <code>assayNames(x)</code> and correspond to count-like data, as linearity assumptions underlying spillover estimation won't hold otherwise.                                |
| <code>interactions</code> | "default" or "all". Specifies which interactions spillover should be estimated for. The default exclusively takes into consideration interactions that are sensible from a chemical and physical point of view (see below for more details). |
| <code>method</code>       | "default" or "classic". Specifies the function to be used for spillover estimation (see below for details).                                                                                                                                  |
| <code>trim</code>         | numeric. Specifies the trim value used for estimation of spill values. Note that <code>trim = 0.5</code> is equivalent to using medians.                                                                                                     |
| <code>th</code>           | single non-negative numeric. Specifies the threshold value below which spill estimates will be set to 0.                                                                                                                                     |

## Details

The default method estimates the spillover as the median ratio between the unstained spillover receiving and the stained spillover emitting channel in the corresponding single stained populations. `method = "classic"` will compute the slope of a line through the medians (or trimmed means) of stained and unstained populations. The medians (or trimmed means) computed from events that

are i) negative in the respective channels; and, ii) not assigned to interacting channels; and, iii) not unassigned are subtracted as to account for background.

interactions="default" considers only expected interactions, that is,  $M \pm 1$  (detection sensitivity),  $M+16$  (oxide formation) and channels measuring metals that are potentially contaminated by isotopic impurities (see reference below and [isotope\\_list](#)).

interaction="all" will estimate spill for all  $n \times n - n$  interactions, where  $n$  denotes the number of single-color controls (`= nrow(bc_key(re))`).

## Value

Returns a square compensation matrix with dimensions and dimension names matching those of the input flowFrame. Spillover is assumed to be linear, and, on the basis of their additive nature, spillover values are computed independently for each interacting pair of channels.

## Author(s)

Helena L Crowell <[helena.crowell@uzh.ch](mailto:helena.crowell@uzh.ch)>

## References

Coursey, J.S., Schwab, D.J., Tsai, J.J., Dragoset, R.A. (2015). Atomic weights and isotopic compositions, (available at <http://physics.nist.gov/Comp>).

## Examples

```
# construct SCE from single-stained control samples
data(ss_exp)
sce <- prepData(ss_exp)

# specify mass channels stained for
bc_ms <- c(139, 141:156, 158:176)

# debarcode single-positive populations
sce <- assignPrelim(sce, bc_ms)
sce <- estCutoffs(sce)
sce <- applyCutoffs(sce)

# estimate & extract spillover matrix
sce <- computeSpillmat(sce)

library(SingleCellExperiment)
head(metadata(sce)$spillover_matrix)
```

data

*Example data sets***Description**

- Concatenation & Normalization

`raw_data` a `flowSet` with 3 experiments, each containing 2'500 raw measurements with a variation of signal over time. Samples were mixed with DVS beads capture by mass channels 140, 151, 153, 165 and 175.

- Debarcoding

`sample_ff` a `flowFrame` following a 6-choose-3 barcoding scheme where mass channels 102, 104, 105, 106, 108, and 110 were used for labeling such that each of the 20 individual barcodes are positive for exactly 3 out of the 6 barcode channels.

`sample_key` a `data.frame` of dimension 20 x 6 with sample names as row and barcode masses as column names. Contains a binary code of length 6 for each sample in `sample_ff`, e.g. 111000, as its unique identifier.

- Compensation

`ss_exp` a `flowFrame` with 20'000 events. Contains 36 single-antibody stained controls where beads were stained with antibodies captured by mass channels 139, 141 through 156, and 158 through 176, respectively, and pooled together.

`mp_cells` a `flowFrame` with 5000 spill-affected multiplexed cells and 39 measurement parameters.

`isotope_list` a named list of isotopic compositions for all elements within 75 through 209 u corresponding to the CyTOF mass range at the time of writing.

- Differential Analysis

`PBMC_fs` a `flowSet` with PBMCs samples from 6 patients. For each sample, the expression of 10 cell surface and 14 signaling markers was measured before (REF) and upon BCR/FcR-XL stimulation (BCRXL) with B cell receptor/ Fc receptor crosslinking for 30', resulting in a total of 12 samples.

`PBMC_panel` a 2 column `data.frame` that contains each marker's column name in the FCS file, and its targeted protein marker.

`PBMC_md` a `data.frame` where each row corresponds to a sample, and with columns describing the experimental design.

`merging_table` a 20 x 2 table with "old\_cluster" IDs and "new\_cluster" labels to exemplify manual cluster merging and cluster annotation.

**Value**

see descriptions above.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

## References

Bodenmiller, B., Zunder, E.R., Finck, R., et al. (2012). Multiplexed mass cytometry profiling of cellular states perturbed by small-molecule regulators. *Nature Biotechnology* **30**(9): 858-67.

Coursey, J.S., Schwab, D.J., Tsai, J.J., Dragoset, R.A. (2015). Atomic weights and isotopic compositions, (available at <http://physics.nist.gov/Comp>).

## Examples

```
### example data for concatenation & normalization:
# raw measurement data
data(raw_data)

### example data for debarcoding:
# 20 barcoded samples
data(sample_ff)
# 6-choose-3 barcoding scheme
data(sample_key)

### example data for compensation:
# single-stained control samples
data(ss_exp)
# multiplexed cells
data(mp_cells)

### example data for differential analysis:
# REF vs. BCRXL samples
data(PBMC_fs)
# antigen panel & experimental design
data(PBMC_panel, PBMC_md)
# exemplary manual merging table
data(merging_table)
```

---

estCutoffs

*Estimation of distance separation cutoffs*

---

## Description

For each sample, estimates a cutoff parameter for the distance between positive and negative barcode populations.

## Usage

```
estCutoffs(x)
```

## Arguments

x                      a [SingleCellExperiment](#).



## Details

For the estimation of cutoff parameters, we considered yields upon debarcoding as a function of the applied cutoffs. Commonly, this function will be characterized by an initial weak decline, where doublets are excluded, and subsequent rapid decline in yields to zero. In between, low numbers of counts with intermediate barcode separation give rise to a plateau. As an adequate cutoff estimate, we target the point that approximately marks the end of the plateau regime and the onset of yield decline. To facilitate robust cutoff estimation, we fit a linear and a three-parameter log-logistic function to the yields function:

$$f(x) = \frac{d}{1 + e^{b(\log(x) - \log(e))}}$$

The goodness of the linear fit relative to the log-logistic fit is weighed with:

$$w = \frac{RSS_{log-logistic}}{RSS_{log-logistic} + RSS_{linear}}$$

and the cutoffs for both functions are defined as:

$$c_{linear} = -\frac{\beta_0}{2\beta_1}$$

$$c_{log-logistic} = \operatorname{argmin}_x \left\{ \frac{|f'(x)|}{f(x)} > 0.1 \right\}$$

The final cutoff estimate is defined as the weighted mean between these estimates:

$$c = (1 - w) \cdot c_{log-logistic} + w \cdot c_{linear}$$

## Value

the input `SingleCellExperiment` is returned with an additional metadata slot `sep_cutoffs`.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Finney, D.J. (1971). Probit Analysis. *Journal of Pharmaceutical Sciences* **60**, 1432.

## Examples

```
library(SingleCellExperiment)

# construct SCE
data(sample_ff, sample_key)
sce <- prepData(sample_ff)

# assign preliminary barcode IDs
# & estimate separation cutoffs
sce <- assignPrelim(sce, sample_key)
sce <- estCutoffs(sce)
```

```
# access separation cutoff estimates
(seps <- metadata(sce)$sep_cutoffs)

# compute population yields
cs <- split(seq_len(ncol(sce)), sce$bc_id)
sapply(names(cs), function(id) {
  sub <- sce[, cs[[id]]]
  mean(sub$delta > seps[id])
})

# view yield plots including current cutoff
plotYields(sce, which = "A1")
```

---

|                 |                                                     |
|-----------------|-----------------------------------------------------|
| extractClusters | <i>Extract clusters from a SingleCellExperiment</i> |
|-----------------|-----------------------------------------------------|

---

## Description

Extracts clusters from a `SingleCellExperiment`. Populations will be either returned as a `flowSet` or written to FCS files, depending on argument `as`.

## Usage

```
extractClusters(
  x,
  k,
  clusters = NULL,
  as = c("flowSet", "fcs"),
  out_dir = ".",
  verbose = TRUE
)
```

## Arguments

|                       |                                                                                                                                          |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>        | a <a href="#">SingleCellExperiment</a> .                                                                                                 |
| <code>k</code>        | numeric or character string. Specifies the clustering to extract populations from. Must be one of <code>names(cluster_codes(x))</code> . |
| <code>clusters</code> | a character vector. Specifies which clusters to extract. <code>NULL</code> = all clusters.                                               |
| <code>as</code>       | "flowSet" or "fcs". Specifies whether clusters should be return as a <code>flowSet</code> or written to FCS files.                       |
| <code>out_dir</code>  | a character string. Specifies where FCS files should be written to. Defaults to the working directory.                                   |
| <code>verbose</code>  | logical. Should information on progress be reported?                                                                                     |

**Value**

a flowSet or character vector of the output file names.

**Author(s)**

Mark D Robinson & Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md, merging_table)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# merge clusters
sce <- mergeClusters(sce, k="meta20", table=merging_table, id="merging_1")
extractClusters(sce, k="merging_1", clusters=c("NK cells", "surface-"))
```

---

|           |                                       |
|-----------|---------------------------------------|
| filterSCE | SingleCellExperiment <i>filtering</i> |
|-----------|---------------------------------------|

---

**Description**

Filters cells/features from a SingleCellExperiment using conditional statements a la dplyr.

**Usage**

```
filterSCE(x, ..., k = NULL)
```

**Arguments**

|     |                                                                                                                                                                      |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x   | a <a href="#">SingleCellExperiment</a> .                                                                                                                             |
| ... | conditional statements separated by comma. Only rows/columns where the condition evaluates to TRUE are kept.                                                         |
| k   | numeric or character string. Specifies the clustering to extract populations from. Must be one of names(cluster_codes(x)). Defaults to the 1st clustering available. |

**Value**

a SingleCellExperiment.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

## Examples

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md, merging_table)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# one condition only, remove a single sample
filterSCE(sce, condition == "Ref", sample_id != "Ref1")

# keep only a subset of clusters
filterSCE(sce, cluster_id %in% c(7, 8, 18), k = "meta20")
```

---

guessPanel

*Guess parameter panel*

---

## Description

Helper function to parse information from the parameters slot of a flowFrame/flowSet.

## Usage

```
guessPanel(x, sep = "_")
```

## Arguments

|     |                                                                                                                                                                                                                                                                                           |
|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x   | a <a href="#">flowFrame</a> .                                                                                                                                                                                                                                                             |
| sep | character string specifying how channel descriptions should be parsed. E.g., if pData(x)\$desc contains both channel and antigens formatted as, 155Gd_CD73, descriptions will be split according to sep and everything after the first sep will be used as the antigen name (here, CD73). |

## Value

a data.frame with the following columns:

- name: the parameter name as extracted from the input flowFrame,
- desc: the parameter description as extracted from the input flowFrame,
- antigen: the targeted protein markers, and
- use\_channel: logical. If TRUE, the channel is expected to contain a marker and will be kept.

## Author(s)

Mark D Robinson & Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
# exemplary data with Time, DNA, BC channels, etc.
data(raw_data)
guessPanel(raw_data[[1]])
```

---

|               |                               |
|---------------|-------------------------------|
| mergeClusters | <i>Manual cluster merging</i> |
|---------------|-------------------------------|

---

**Description**

mergeClusters provides a simple wrapper to store a manual merging inside the input SingleCellExperiment.

**Usage**

```
mergeClusters(x, k, table, id, overwrite = FALSE)
```

**Arguments**

|           |                                                                                                                                     |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------|
| x         | a <a href="#">SingleCellExperiment</a> .                                                                                            |
| k         | character string specifying the clustering to merge; valid values are names(cluster_codes(x)).                                      |
| table     | merging table with 2 columns containing the cluster IDs to merge in the 1st, and the cluster IDs to newly assign in the 2nd column. |
| id        | character string used as a label for the merging.                                                                                   |
| overwrite | logical specifying whether to force overwriting should a clustering with name id already exist.                                     |

**Details**

in the following code snippets, x is a SingleCellExperiment object.

- merging codes are accesible through cluster\_codes(x)\$id
- all functions that ask for specification of a clustering (e.g. [plotAbundances](#), [plotMultiHeatmap](#)) take the merging ID as a valid input argument.

**Value**

a [SingleCellExperiment](#) with newly added cluster codes stored in cluster\_codes(.)\$id.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md, merging_table)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# merge clusters
sce <- mergeClusters(sce,
  k = "meta20",
  id = "merging",
  table = merging_table)

# tabulate manual merging
table(cluster_ids(sce, k = "merging"))

# visualize median type-marker expression
plotExprHeatmap(sce,
  features = "type",
  by = "cluster_id",
  k = "merging",
  bars = TRUE)
```

---

normCytof

*Bead-based normalization*


---

## Description

an implementation of Finck et al.'s normalization of mass cytometry data using bead standards with automated bead gating.

## Usage

```
normCytof(
  x,
  beads = c("dvs", "beta"),
  dna = c(191, 193),
  k = 500,
  trim = 5,
  remove_beads = TRUE,
  norm_to = NULL,
  assays = c("counts", "exprs"),
  overwrite = TRUE,
  transform = TRUE,
  cofactor = NULL,
  plot = TRUE,
  verbose = TRUE
)
```

**Arguments**

|              |                                                                                                                                                                                                                                                                                                                             |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x            | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                                    |
| beads        | "dvs" (for bead masses 140, 151, 153, 165, 175) or "beta" (for bead masses 139, 141, 159, 169, 175) or a numeric vector of masses.                                                                                                                                                                                          |
| dna          | numeric vector of masses corresponding to DNA channels (only one is required; output scatter plot (see Value section) will be generated using the first matching channel).                                                                                                                                                  |
| k            | integer width of the median window used for bead smoothing (affects visualizations only!).                                                                                                                                                                                                                                  |
| trim         | a single non-negative numeric. A <i>median+/-trim*mad</i> rule is applied to preliminary bead populations to remove bead-bead doublets and low signal beads prior to estimating normalization factors.                                                                                                                      |
| remove_beads | logical. If TRUE, bead events will be removed from the input <code>SingleCellExperiment</code> and returned as a separate object?                                                                                                                                                                                           |
| norm_to      | a <a href="#">flowFrame</a> or character string specifying an FCS file from which to compute baseline bead intensities, and to which the input data should be normalized to.                                                                                                                                                |
| assays       | length 2 character string specifying which assay data to use; both should be in <code>assayNames(x)</code> and correspond to count- and expression-like data, respectively.                                                                                                                                                 |
| overwrite    | logical; should the specified assays (both, when <code>transform = TRUE</code> ) be overwritten with the normalized data? If FALSE, normalized counts (and expressions, if <code>transform = TRUE</code> ) will be stored in <code>assay(s) normcounts/exprs</code> , respectively.                                         |
| transform    | logical; should normalized counts be arcsinh-transformed with the specified cofactor(s)?                                                                                                                                                                                                                                    |
| cofactor     | numeric cofactor(s) to use for optional arcsinh-transformation when <code>transform = TRUE</code> ; single value or a vector with channels as names. If NULL, <code>normCytof</code> will try and access the cofactor(s) stored in <code>int_metadata(x)</code> , thus re-using the same transformation applied previously. |
| plot         | logical; should bead vs. DNA scatters and smoothed bead intensities before vs. after normalization be included in the output?                                                                                                                                                                                               |
| verbose      | logical; should extra information on progress be reported?                                                                                                                                                                                                                                                                  |

**Value**

a list of the following `SingleCellExperiment`...

- data: The filtered input SCE (when `remove_beads = TRUE`); otherwise, `colData` columns `is_bead` and `remove` indicate whether an event has been identified as a bead or doublet. If `overwrite = FALSE`, `assays normcounts/exprs` are added; otherwise, the specified counts/exprs assays are overwritten.
- beads, removed: SCEs containing subsets of events identified as beads and that were removed, respectively. The latter includes bead-cell and cell-cell doublets)

...and `ggplot` objects:

- scatter: scatter plot of DNA vs. bead intensities with indication of the applied gates
- lines: running-median smoothed bead intensities before and after normalization

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Finck, R. et al. (2013). Normalization of mass cytometry data with bead standards. *Cytometry A* **83A**, 483-494.

**Examples**

```
data(raw_data)
sce <- prepData(raw_data)

# apply normalization & write normalized data to separate assays
res <- normCytob(sce, beads = "dvs", k = 80, overwrite = FALSE)

ncol(res$beads) # no. of bead events
ncol(res$removed) # no. of events removed

res$scatter # plot DNA vs. bead intensities including applied gates
res$lines # plot smoothed bead intensities before vs. after normalization

# filtered SCE now additionally includes
# normalized count & expression data
assayNames(res$data)
```

---

pbMDS

*Pseudobulk-level MDS plot*

---

**Description**

Pseudobulk-level Multi-Dimensional Scaling (MDS) plot computed on median marker expressions in each sample.

**Usage**

```
pbMDS(
  x,
  by = c("sample_id", "cluster_id", "both"),
  k = "meta20",
  dims = c(1, 2),
  features = NULL,
  assay = "exprs",
  fun = c("median", "mean", "sum"),
  color_by = switch(by, sample_id = "condition", "cluster_id"),
  label_by = if (by == "sample_id") "sample_id" else NULL,
  shape_by = NULL,
```



```

    size_by = is.null(shape_by),
    pal = if (color_by == "cluster_id") .cluster_cols else NULL
  )

```

## Arguments

|          |                                                                                                                                                                                                                                                            |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                   |
| by       | character string specifying whether to aggregate by sample_id, cluster_id or both.                                                                                                                                                                         |
| k        | character string specifying which clustering to use when by != "sample_id"; valid values are names(cluster_codes(x)).                                                                                                                                      |
| dims     | two numeric scalars indicating which dimensions to plot.                                                                                                                                                                                                   |
| features | character string specifying which features to include for computation of reduced dimensions; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |
| assay    | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                                                       |
| fun      | character string specifying which summary statistic to use.                                                                                                                                                                                                |
| color_by | character string specifying a non-numeric cell metadata column to color by; valid values are names(colData(x)).                                                                                                                                            |
| label_by | character string specifying a non-numeric cell metadata column to label by; valid values are names(colData(x)).                                                                                                                                            |
| shape_by | character string specifying a non-numeric cell metadata column to shape by; valid values are names(colData(x)).                                                                                                                                            |
| size_by  | logical specifying whether points should be sized by the number of cells that went into aggregation; i.e., the size of a give sample, cluster or cluster-sample instance.                                                                                  |
| pal      | character vector of colors to use; NULL for default ggplot2 colors.                                                                                                                                                                                        |

## Value

a ggplot object.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# sample-level pseudobulks
# including state-markers only
pbMDS(sce, by = "sample_id", features = "state")

# cluster-level pseudobulks
# including type-features only
pbMDS(sce, by = "cluster_id", features = "type")

# pseudobulks by cluster-sample
# including all features
pbMDS(sce, by = "both", k = "meta12",
      shape_by = "condition", size_by = TRUE)
```

---

plotAbundances

*Population frequencies across samples & clusters*


---

## Description

Plots the relative population abundances of the specified clustering.

## Usage

```
plotAbundances(
  x,
  k = "meta20",
  by = c("sample_id", "cluster_id"),
  group_by = "condition",
  shape_by = NULL,
  col_clust = TRUE,
  distance = c("euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski"),
  linkage = c("average", "ward.D", "single", "complete", "mcquitty", "median",
    "centroid", "ward.D2"),
  k_pal = CATALYST:::cluster_cols
)
```

## Arguments

|    |                                                                                                              |
|----|--------------------------------------------------------------------------------------------------------------|
| x  | a <a href="#">SingleCellExperiment</a> .                                                                     |
| k  | character string specifying which clustering to use; valid values are <code>names(cluster_codes(x))</code> . |
| by | a character string specifying whether to plot frequencies by samples or clusters.                            |

|           |                                                                                                                                                                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| group_by  | character string specifying a non-numeric cell metadata column to group by (determines the color coding); valid values are names(colData(x)) other than "sample_id" and "cluster_id".                                                         |
| shape_by  | character string specifying a non-numeric cell metadata column to shape by; valid values are names(colData(x)) other than "sample_id" and "cluster_id".                                                                                       |
| col_clust | for by = "sample_id", specifies whether to hierarchically cluster samples and reorder them accordingly. When col_clust = FALSE, samples are ordered according to levels(x\$sample_id) (or alphabetically, when x\$sample_id is not a factor). |
| distance  | character string specifying the distance metric to use for sample clustering; passed to <code>dist</code>                                                                                                                                     |
| linkage   | character string specifying the agglomeration method to use for sample clustering; passed to <code>hclust</code> .                                                                                                                            |
| k_pal     | character string specifying the cluster color palette; ignored when by = "cluster_id". If less than nlevels(cluster_ids(x, k)) are supplied, colors will be interpolated via <code>colorRampPalette</code> .                                  |

**Value**

a ggplot object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# plot relative population abundances
# by sample & cluster, respectively
plotAbundances(sce, k = "meta12")
plotAbundances(sce, k = "meta8", by = "cluster_id")

# use custom cluster color palette
plotAbundances(sce, k = "meta10",
  k_pal = c("lightgrey", "cornflowerblue", "navy"))
```

---

|                  |                                                 |
|------------------|-------------------------------------------------|
| plotClusterExprs | <i>Plot expression distributions by cluster</i> |
|------------------|-------------------------------------------------|

---

## Description

Plots smoothed densities of marker intensities by cluster.

## Usage

```
plotClusterExprs(x, k = "meta20", features = "type")
```

## Arguments

|          |                                                                                                                                                                                                                        |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                               |
| k        | character string specifying which clustering to use; valid values are names(cluster_codes(x)).                                                                                                                         |
| features | a character vector specifying which antigens to include; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |

## Value

a [ggplot](#) object.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

plotClusterExprs(sce, k = "meta8")
```

---

plotClusterHeatmap      *Plot cluster heatmap*


---

## Description

Plots expression & relative cluster abundances heatmaps summarizing a clustering and/or metaclustering.

## Usage

```
plotClusterHeatmap(
  x,
  hm2 = NULL,
  k = "meta20",
  m = NULL,
  fun = c("median", "mean"),
  cluster_anno = TRUE,
  split_by = NULL,
  scale = TRUE,
  draw_dend = TRUE,
  draw_freqs = FALSE,
  palette = rev(brewer.pal(11, "RdYlBu"))
)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x            | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                         |
| hm2          | character string. Specifies the right-hand side heatmap. One of: <ul style="list-style-type: none"> <li>• "abundances": cluster frequencies across samples</li> <li>• "state": median cell state marker expressions across clusters (analogous to the left-hand side heatmap)</li> <li>• a character string/vector corresponding to one/multiple marker(s): aggregated marker expressions across samples and clusters</li> </ul> |
| k            | character string specifying the clustering across which median marker expressions should be computed.                                                                                                                                                                                                                                                                                                                            |
| m            | character string specifying the metaclustering to be shown. (This is for display only and will not effect any computations!)                                                                                                                                                                                                                                                                                                     |
| fun          | character string specifying the function to use as summary statistic.                                                                                                                                                                                                                                                                                                                                                            |
| cluster_anno | logical specifying if clusters should be annotated.                                                                                                                                                                                                                                                                                                                                                                              |
| split_by     | deprecated.                                                                                                                                                                                                                                                                                                                                                                                                                      |
| scale        | logical specifying whether scaled values should be plotted.                                                                                                                                                                                                                                                                                                                                                                      |
| draw_dend    | logical specifying if the row dendrogram should be drawn.                                                                                                                                                                                                                                                                                                                                                                        |
| draw_freqs   | logical specifying whether to display cell counts and proportions.                                                                                                                                                                                                                                                                                                                                                               |
| palette      | character vector of colors to interpolate.                                                                                                                                                                                                                                                                                                                                                                                       |

## Details

Scaled values corresponds to cofactor arcsinh-transformed expression values scaled between 0 and 1 using 1 boundaries. Hierarchical clustering is performed on the unscaled data.

In its 1st panel, `plotClusterHeatmap` will display median (scaled, arcsinh-transformed) cell-type marker expressions (across all samples). Depending on argument `hm2`, the 2nd panel will contain one of:

- relative cluster abundances by sample
- median (scaled, arcsinh-transformed) cell-state marker expressions (across all samples)
- median (scaled, arcsinh-transformed) cell-state marker expressions by sample

## Value

a `HeatmapList-class` object.

## Author(s)

Helena Lucia Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

---

|           |                                  |
|-----------|----------------------------------|
| plotCodes | <i>tSNE and PCA on SOM codes</i> |
|-----------|----------------------------------|

---

## Description

Plots the tSNE and PCA representing the SOM codes as inferred by **FlowSOM**. Sizes are scaled to the total number of events assigned to each cluster, and points are color according to their cluster ID upon **ConsensusClusterPlus** metaclustering into k clusters.

## Usage

```
plotCodes(x, k = "meta20", k_pal = CATALYST:::cluster_cols)
```

## Arguments

|       |                                                                                                                                                                                           |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x     | a <code>SingleCellExperiment</code> .                                                                                                                                                     |
| k     | character string. Specifies the clustering to use for color coding.                                                                                                                       |
| k_pal | character string specifying the cluster color palette; If less than <code>nlevels(cluster_ids(x, k))</code> are supplied, colors will be interpolated via <code>colorRampPalette</code> . |

## Value

a ggplot object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

plotCodes(sce, k = "meta14")

# use custom cluster color palette
plotCodes(sce, k = "meta12",
  k_pal = c("lightgrey", "cornflowerblue", "navy"))
```

---

plotCounts

*Plot cell counts*


---

**Description**

Barplot of the number of cells measured for each sample.

**Usage**

```
plotCounts(x, group_by = "condition", color_by = group_by, prop = FALSE)
```

**Arguments**

|          |                                                                                                                                                                                |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                       |
| group_by | character string specifying a non-numeric cell metadata column to group by (determines x-axis ticks); valid values are names(colData(x)).                                      |
| color_by | character string specifying a non-numeric cell metadata column to color by (determines grouping of bars); valid values are names(colData(x)); NULL for no color.               |
| prop     | logical specifying whether to plot relative abundances (frequencies) for each group rather than total cell counts; bars will be stacked when prop = TRUE and dodged otherwise. |

**Value**

a `ggplot` object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

**Examples**

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)

# plot number of cells per sample, colored by condition
plotCounts(sce,
  group_by = "sample_id",
  color_by = "condition")

# same as above, but order by patient
plotCounts(sce,
  group_by = "patient_id",
  color_by = "condition")

# total number of cell per patient
plotCounts(sce,
  group_by = "patient_id",
  color_by = NULL)

# plot proportion of cells from each patient by condition
plotCounts(sce,
  prop = TRUE,
  group_by = "condition",
  color_by = "patient_id")
```

---

plotDiffHeatmap

*Plot differential heatmap*

---

**Description**

Heatmaps summarizing differential abundance & differential state testing results.



**Usage**

```
plotDiffHeatmap(
  x,
  y,
  k = NULL,
  top_n = 20,
  fdr = 0.05,
  lfc = 1,
  all = FALSE,
  sort_by = c("padj", "lfc", "none"),
  y_cols = list(padj = "p_adj", lfc = "logFC", target = "marker_id"),
  assay = "exprs",
  fun = c("median", "mean", "sum"),
  normalize = TRUE,
  col_anno = TRUE,
  row_anno = TRUE,
  hm_pal = NULL,
  fdr_pal = c("lightgrey", "lightgreen"),
  lfc_pal = c("blue3", "white", "red3")
)
```

**Arguments**

|         |                                                                                                                                                                                                                                                                                                               |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x       | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                      |
| y       | a SummarizedExperiment containing differential testing results as returned by one of <a href="#">testDA_edgeR</a> , <a href="#">testDA_voom</a> , <a href="#">testDA_GLMM</a> , <a href="#">testDS_limma</a> , or <a href="#">testDS_LMM</a> . Alternatively, a list as returned by <a href="#">diffcyt</a> . |
| k       | character string specifying the clustering in x from which y was obtained. If NULL, plotDiffHeatmap will try and guess it, which will be inaccurate if multiple clusterings share the same levels.                                                                                                            |
| top_n   | numeric. Number of top clusters (if type = "DA") or cluster-marker combinations (if type = "DS") to display.                                                                                                                                                                                                  |
| fdr     | numeric threshold on adjusted p-values below which results should be retained and considered to be significant.                                                                                                                                                                                               |
| lfc     | numeric threshold on logFCs above which to retain results.                                                                                                                                                                                                                                                    |
| all     | logical specifying whether all top_n results should be displayed. If TRUE, fdr, lfc filtering is skipped.                                                                                                                                                                                                     |
| sort_by | character string specifying the y column to sort by; "none" to retain original ordering. Adj. p-values will increase, logFCs will decreasing from top to bottom.                                                                                                                                              |
| y_cols  | named list specifying columns in y that contain adjusted p-values (padj), logFCs (lfc) and, for DS results, feature names (target). When only some y_cols differ from the defaults, specifying only these is sufficient.                                                                                      |
| assay   | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                                                                                                          |
| fun     | character string specifying the function to use as summary statistic for aggregation of assay data.                                                                                                                                                                                                           |

|                  |                                                                                                                                                                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| normalize        | logical specifying whether Z-score normalized values should be plotted. If y contains DA analysis results, frequencies will be arcsine-square-root scaled prior to normalization.                                                                            |
| col_anno         | logical specifying whether to include column annotations for all non-numeric cell metadata variables; or a character vector in names(colData(x)) to include only a subset of annotations. (Only variables that map uniquely to each sample will be included) |
| row_anno         | logical specifying whether to include a row annotation indicating whether cluster (DA) or cluster-marker combinations (DS) are significant, labeled with adjusted p-values, as well as logFCs.                                                               |
| hm_pal           | character vector of colors to interpolate for the heatmap. Defaults to brewer.pal's "RdYlBu" for DS, "RdBu" for DA results heatmaps.                                                                                                                         |
| fdr_pal, lfc_pal | character vector of colors to use for row annotations <ul style="list-style-type: none"> <li>• fdr_pallength 2 for (non-)significant at given fdr</li> <li>• lfc_pallength 3 for negative, zero and positive</li> </ul>                                      |

**Value**

a [Heatmap-class](#) object.

**Author(s)**

Lukas M Weber & Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce, verbose = FALSE)

## differential analysis
library(diffcyt)

# create design & contrast matrix
design <- createDesignMatrix(ei(sce), cols_design=2:3)
contrast <- createContrast(c(0, 1, 0, 0, 0))

# test for
# - differential abundance (DA) of clusters
# - differential states (DS) within clusters

da <- diffcyt(sce, design = design, contrast = contrast,
  analysis_type = "DA", method_DA = "diffcyt-DA-edgeR",
  clustering_to_use = "meta20", verbose = FALSE)

ds <- diffcyt(sce, design = design, contrast = contrast,
  analysis_type = "DS", method_DS = "diffcyt-DS-limma",
```

```

        clustering_to_use = "meta20", verbose = FALSE)

# extract result tables
da <- rowData(da$res)
ds <- rowData(ds$res)

# display test results for
# - top DA clusters
# - top DS cluster-marker combinations
plotDiffHeatmap(sce, da)
plotDiffHeatmap(sce, ds)

# visualize results for subset of clusters
sub <- filterSCE(sce, cluster_id %in% seq_len(5), k = "meta20")
plotDiffHeatmap(sub, da, all = TRUE, sort_by = "none")

# visualize results for selected feature
# & include only selected annotation
plotDiffHeatmap(sce["pp38", ], ds, col_anno = "condition", all = TRUE)

```

---

plotDR

*Plot reduced dimensions*


---

## Description

Dimension reduction plot colored by expression, cluster, sample or group ID.

## Usage

```

plotDR(
  x,
  dr = NULL,
  color_by = "condition",
  facet_by = NULL,
  ncol = NULL,
  assay = "exprs",
  scale = TRUE,
  q = 0.01,
  dims = c(1, 2),
  k_pal = CATALYST:::.cluster_cols,
  a_pal = hcl.colors(10, "Viridis")
)

```

## Arguments

|    |                                                                                                                                                |
|----|------------------------------------------------------------------------------------------------------------------------------------------------|
| x  | a <a href="#">SingleCellExperiment</a> .                                                                                                       |
| dr | character string specifying which dimension reduction to use. Should be one of <code>reducedDimNames(x)</code> ; default to the 1st available. |

|          |                                                                                                                                                                                                                                              |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| color_by | character string specifying the color coding; valid values are rownames(sce) and names(colData(x)).                                                                                                                                          |
| facet_by | character string specifying a non-numeric cell metadata column to facet by; valid values are names(colData(x)).                                                                                                                              |
| ncol     | integer scalar specifying number of facet columns; ignored unless coloring by multiple features without facetting or coloring by a single feature with facetting.                                                                            |
| assay    | character string specifying which assay data to use when coloring by marker(s); valid values are assayNames(x).                                                                                                                              |
| scale    | logical specifying whether assay data should be scaled between 0 and 1 using lower (1%) and upper (99%) expression quantiles; ignored if !all(color_by %in% rownames(x)).                                                                    |
| q        | single numeric in [0,0.5) determining the quantiles to trim when scale = TRUE.                                                                                                                                                               |
| dims     | length 2 numeric specifying which dimensions to plot.                                                                                                                                                                                        |
| k_pal    | character string specifying the cluster color palette; ignored when color_by is not one of names(cluster_codes(x)). If less than nlevels(cluster_ids(x, k)) are supplied, colors will be interpolated via <a href="#">colorRampPalette</a> . |
| a_pal    | character string specifying the assay data palette when coloring by feature(s), i.e. all(color_by %in% rownames(x)).                                                                                                                         |

**Value**

a ggplot object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)

# run clustering & dimension reduction
sce <- cluster(sce)
sce <- runDR(sce, dr = "UMAP", cells = 100)

# color by single marker, split by sample
plotDR(sce, color_by = "CD7", facet_by = "sample_id", ncol = 4)

# color by a set of markers using custom color palette
cdx <- grep("CD", rownames(sce), value = TRUE)
```

```

plotDR(sce, color_by = cdx, ncol = 4,
       a_pal = rev(hcl.colors(10, "Spectral"))))

# color by scaled expression for
# set of markers, split by condition
plotDR(sce,
       scale = TRUE,
       facet_by = "condition",
       color_by = sample(rownames(sce), 4))

# color by 8 metaclusters using custom
# cluster color palette, split by sample
p <- plotDR(sce,
            color_by = "meta8",
            facet_by = "sample_id",
            k_pal = c("lightgrey", "cornflowerblue", "navy"))
p$facet$params$ncol <- 4; p

```

plotEvents

*Event plot***Description**

Plots normalized barcode intensities for a given barcode.

**Usage**

```

plotEvents(
  x,
  which = "all",
  assay = "scaled",
  n = 1000,
  out_path = NULL,
  out_name = "event_plot"
)

```

**Arguments**

|          |                                                                                                                                                                                          |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                 |
| which    | "all", numeric or character specifying which barcode(s) to plot. Valid values are IDs that occur as rownames in the bc_key slot of the input SCE's metadata, or 0 for unassigned events. |
| assay    | character string specifying which assay data slot to use. One of assayNames(x).                                                                                                          |
| n        | single numeric specifying the number of events to plot.                                                                                                                                  |
| out_path | character string. If specified, events plots for all barcodes specified via which will be written to a single PDF file in this location.                                                 |
| out_name | character strings specifying the output's file name when !is.null(out_path); should be provided without(!) file type extension.                                                          |

**Details**

Plots intensities normalized by population for each barcode specified by which: Each event corresponds to the intensities plotted on a vertical line at a given point along the x-axis. Events are scaled to the 95% quantile of the population it has been assigned to. Barcodes with less than 50 event assignments will be skipped; it is strongly recommended to remove such populations or reconsider their separation cutoffs.

**Value**

a list of ggplot objects.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Zunder, E.R. et al. (2015). Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell deconvolution algorithm. *Nature Protocols* **10**, 316-333.

**Examples**

```
data(sample_ff, sample_key)
sce <- prepData(sample_ff, by_time = FALSE)
sce <- assignPrelim(sce, sample_key)
plotEvents(sce, which = "D1")
```

---

|                 |                                |
|-----------------|--------------------------------|
| plotExprHeatmap | <i>Plot expression heatmap</i> |
|-----------------|--------------------------------|

---

**Description**

Heatmap of marker expressions aggregated by sample, cluster, or both; with options to include annotation of cell metadata factors, clustering(s), as well as relative and absolute cell counts.

**Usage**

```
plotExprHeatmap(
  x,
  features = NULL,
  by = c("sample_id", "cluster_id", "both"),
  k = "meta20",
  m = NULL,
  assay = "exprs",
  fun = c("median", "mean", "sum"),
  scale = c("first", "last", "never"),
  q = 0.01,
```

```

row_anno = TRUE,
col_anno = TRUE,
row_clust = TRUE,
col_clust = TRUE,
row_dend = TRUE,
col_dend = TRUE,
bars = FALSE,
perc = FALSE,
bin_anno = FALSE,
hm_pal = rev(brewer.pal(11, "RdYlBu")),
k_pal = CATALYST:::.cluster_cols,
m_pal = k_pal,
distance = c("euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski"),
linkage = c("average", "ward.D", "single", "complete", "mcquitty", "median",
            "centroid", "ward.D2")
)

```

### Arguments

|                      |                                                                                                                                                                                                                                                                                                                                          |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                    | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                                                 |
| features             | character string specifying which features to include; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. When by = "both", only 1 feature is allowed.                                                                        |
| by                   | character string specifying whether to aggregate by sample, cluster, both.                                                                                                                                                                                                                                                               |
| k                    | character string specifying which clustering to use when by != "sample_id"; assay data will be aggregated across these cluster IDs.                                                                                                                                                                                                      |
| m                    | character string specifying a metaclustering to include as an annotation when by != "sample_id" and row_anno = TRUE.                                                                                                                                                                                                                     |
| assay                | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                                                                                                                                     |
| fun                  | character string specifying the function to use as summary statistic.                                                                                                                                                                                                                                                                    |
| scale                | character string specifying the scaling strategy: <ul style="list-style-type: none"> <li>• "first": scale &amp; trim then aggregate</li> <li>• "last": aggregate then scale &amp; trim</li> <li>• "never": aggregate only</li> </ul> If scale != "never", data will be scaled using lower (q%) and upper (1-q%) quantiles as boundaries. |
| q                    | single numeric in [0,0.5) determining the quantiles to trim when scale != "never".                                                                                                                                                                                                                                                       |
| row_anno, col_anno   | logical specifying whether to include row/column annotations (see details); when one axis corresponds to samples (by != "cluster_id"), this can be a character vector specifying a subset of names(colData(x)) to be included as annotations.                                                                                            |
| row_clust, col_clust | logical specifying whether rows/columns should be hierarchically clustered and re-ordered accordingly.                                                                                                                                                                                                                                   |

|                    |                                                                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| row_dend, col_dend | logical specifying whether to include the row/column dendrograms.                                                                              |
| bars               | logical specifying whether to include a barplot of cell counts per cluster as a right-hand side row annotation.                                |
| perc               | logical specifying whether to display percentage labels next to bars when bars = TRUE.                                                         |
| bin_anno           | logical specifying whether to display values inside bins.                                                                                      |
| hm_pal             | character vector of colors to interpolate for the heatmap.                                                                                     |
| k_pal, m_pal       | character vector of colors to interpolate for cluster annotations when by != "sample_id".                                                      |
| distance           | character string specifying the distance metric to use for both row and column hierarchical clustering; passed to <a href="#">Heatmap</a>      |
| linkage            | character string specifying the agglomeration method to use for both row and column hierarchical clustering; passed to <a href="#">Heatmap</a> |

### Details

By default (row/col\_anno = TRUE), for axes corresponding to samples (y-axis for by = "sample\_id" and x-axis for by = "both"), annotations will be drawn for all non-numeric cell metadata variables. Alternatively, a specific subset of annotations can be included for only a subset of variables by specifying row/col\_anno to be a character vector in names(colData(x)) (see examples).

For axes corresponding to clusters (y-axis for by = "cluster\_id" and "both"), annotations will be drawn for the specified clustering(s) (arguments k and m).

### Value

a [Heatmap-class](#) object.

### Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

### References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

### See Also

[plotMedExprs](#), [plotFreqHeatmap](#), [plotMultiHeatmap](#)

### Examples

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# median scaled & trimmed expression by cluster
```



```

plotExprHeatmap(sce,
  by = "cluster_id", k = "meta8",
  scale = "first", q = 0.05, bars = FALSE)

# scale each marker between 0 and 1
# after aggregation (without trimming)
plotExprHeatmap(sce,
  scale = "last", q = 0,
  bars = TRUE, perc = TRUE,
  hm_pal = hcl.colors(10, "YlGnBu", rev = TRUE))

# raw (un-scaled) median expression by cluster-sample
plotExprHeatmap(sce,
  features = "pp38", by = "both", k = "meta10",
  scale = "never", row_anno = FALSE, bars = FALSE)

# include only subset of samples
sub <- filterSCE(sce,
  patient_id != "Patient",
  sample_id != "Ref3")

# includes specific annotations &
# split into CDx & all other markers
is_cd <- grepl("CD", rownames(sce))
plotExprHeatmap(sub,
  rownames(sce)[is_cd],
  row_anno = "condition",
  bars = FALSE)
plotExprHeatmap(sub,
  rownames(sce)[!is_cd],
  row_anno = "patient_id",
  bars = FALSE)

```

---

plotExprs

*Expression densities*


---

## Description

Plots smoothed densities of marker intensities, with a density curve for each sample ID, and curves colored by a cell metadata variable of interest.

## Usage

```
plotExprs(x, features = NULL, color_by = "condition", assay = "exprs")
```

## Arguments

x                    a [SingleCellExperiment](#).

|          |                                                                                                                                                                                                                      |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| features | character vector specifying which features to include; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |
| color_by | character string specifying a non-numeric cell metadata column by which to color density curves for each sample; valid values are names(colData(x)).                                                                 |
| assay    | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                 |

**Value**

a `ggplot` object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

**Examples**

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
plotExprs(sce)
```

---

|                 |                                  |
|-----------------|----------------------------------|
| plotFreqHeatmap | <i>Cluster frequency heatmap</i> |
|-----------------|----------------------------------|

---

**Description**

Heatmap of relative cluster abundances (frequencies) by sample.

**Usage**

```
plotFreqHeatmap(
  x,
  k = "meta20",
  m = NULL,
  normalize = TRUE,
  row_anno = TRUE,
  col_anno = TRUE,
  row_clust = TRUE,
  col_clust = TRUE,
  row_dend = TRUE,
```

```

    col_dend = TRUE,
    bars = TRUE,
    perc = FALSE,
    hm_pal = rev(brewer.pal(11, "RdBu")),
    k_pal = CATALYST:::cluster_cols,
    m_pal = k_pal
  )

```

### Arguments

|                                   |                                                                                                                                                                                                                           |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>                    | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                  |
| <code>k</code>                    | character string specifying the clustering to use; valid values are <code>names(cluster_codes(x))</code> . Cell counts will be computed across these cluster IDs.                                                         |
| <code>m</code>                    | character string specifying a metaclustering to include as an annotation when <code>row_anno = TRUE</code> .                                                                                                              |
| <code>normalize</code>            | logical specifying whether to Z-score normalize.                                                                                                                                                                          |
| <code>row_anno, col_anno</code>   | logical specifying whether to include row/column annotations for clusters/samples; for <code>col_anno</code> , this can be a character vector specifying a subset of <code>names(colData(x))</code> to be included.       |
| <code>row_clust, col_clust</code> | logical specifying whether rows/columns (clusters/samples) should be hierarchically clustered and re-ordered accordingly.                                                                                                 |
| <code>row_dend, col_dend</code>   | logical specifying whether to include row/column dendrograms.                                                                                                                                                             |
| <code>bars</code>                 | logical specifying whether to include a barplot of cell counts per cluster as a right-hand side row annotation.                                                                                                           |
| <code>perc</code>                 | logical specifying whether to display percentage labels next to bars when <code>bars = TRUE</code> .                                                                                                                      |
| <code>hm_pal</code>               | character vector of colors to interpolate for the heatmap.                                                                                                                                                                |
| <code>k_pal, m_pal</code>         | character vector of colors to use for cluster and merging row annotations. If less than <code>nlevels(cluster_ids(x, k/m))</code> values are supplied, colors will be interpolated via <a href="#">colorRampPalette</a> . |

### Value

a [Heatmap-class](#) object.

### Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

### See Also

[plotAbundances](#), [plotExprHeatmap](#), [plotMultiHeatmap](#),

**Examples**

```

data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# complete
plotFreqHeatmap(sce, k = "meta12", m = "meta8")

# minimal
plotFreqHeatmap(sce, k = "meta10",
  normalize = FALSE, bars = FALSE,
  row_anno = FALSE, col_anno = FALSE,
  row_clust = FALSE, col_clust = FALSE)

# customize colors & annotations
plotFreqHeatmap(sce,
  k = "meta7", m = "meta4",
  col_anno = "condition",
  hm_pal = c("navy", "grey95", "gold"),
  k_pal = hcl.colors(7, "Set 2"),
  m_pal = hcl.colors(4, "Dark 3"))

```

plotMahal

*Biaxial plot***Description**

Histogram of counts and plot of yields as a function of separation cutoffs.

**Usage**

```
plotMahal(x, which, assay = "exprs", n = 1000)
```

**Arguments**

|       |                                                                 |
|-------|-----------------------------------------------------------------|
| x     | a <a href="#">SingleCellExperiment</a> .                        |
| which | character string. Specifies which barcode to plot.              |
| assay | character string specifying which assay to use.                 |
| n     | numeric. Number of cells to subsample; use NULL to include all. |

**Value**

Plots all inter-barcode interactions for the population specified by argument which. Events are colored by their Mahalanobis distance.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

## References

Zunder, E.R. et al. (2015). Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell deconvolution algorithm. *Nature Protocols* **10**, 316-333.

## Examples

```
data(sample_ff, sample_key)
sce <- prepData(sample_ff, by_time = FALSE)
sce <- assignPrelim(sce, sample_key)
sce <- estCutoffs(sce)
sce <- applyCutoffs(sce)
plotMahal(sce, which = "B3")
```

---

|                  |                                                        |
|------------------|--------------------------------------------------------|
| plotMultiHeatmap | <i>Multi-panel expression &amp; frequency heatmaps</i> |
|------------------|--------------------------------------------------------|

---

## Description

Combines expression and frequency heatmaps from [plotExprHeatmap](#) and [plotFreqHeatmap](#), respectively, into a [HeatmapList](#).

## Usage

```
plotMultiHeatmap(
  x,
  hm1 = "type",
  hm2 = "abundances",
  k = "meta20",
  m = NULL,
  assay = "exprs",
  fun = c("median", "mean", "sum"),
  scale = c("first", ifelse(hm2 == "state", "first", "last")),
  q = c(0.01, ifelse(hm2 == "state", 0.01, 0)),
  normalize = TRUE,
  row_anno = TRUE,
  col_anno = TRUE,
  row_clust = TRUE,
  col_clust = c(TRUE, hm2 == "state"),
  row_dend = TRUE,
  col_dend = c(TRUE, hm2 == "state"),
  bars = FALSE,
  perc = FALSE,
  hm1_pal = rev(brewer.pal(11, "RdYlBu")),
  hm2_pal = if (isTRUE(hm2 == "abundances")) rev(brewer.pal(11, "PuOr")) else hm1_pal,
  k_pal = CATALYST:::cluster_cols,
  m_pal = k_pal,
```

```

distance = c("euclidean", "maximum", "manhattan", "canberra", "binary", "minkowski"),
linkage = c("average", "ward.D", "single", "complete", "mcquitty", "median",
"centroid", "ward.D2")
)

```

## Arguments

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                    | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                                                                                                                                                                |
| hm1                  | character string specifying which features to include in the 1st heatmap; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features; and FALSE to omit the 1st heatmap altogether.                                                                                                                                   |
| hm2                  | character string. Specifies the right-hand side heatmap. One of: <ul style="list-style-type: none"> <li>• "abundances": cluster frequencies across samples</li> <li>• "state": median state-marker expressions across clusters (analogous to the left-hand side heatmap)</li> <li>• a character string/vector corresponding to one/multiple marker(s): median marker expressions across samples and clusters</li> </ul> |
| k                    | character string specifying which; valid values are names(cluster_codes(x)).                                                                                                                                                                                                                                                                                                                                            |
| m                    | character string specifying a metaclustering to include as an annotation when row_anno = TRUE.                                                                                                                                                                                                                                                                                                                          |
| assay                | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                                                                                                                                                                                                                    |
| fun                  | character string specifying the function to use as summary statistic.                                                                                                                                                                                                                                                                                                                                                   |
| scale                | character string specifying the scaling strategy; for expression heatmaps (see <a href="#">plotExprHeatmap</a> ).                                                                                                                                                                                                                                                                                                       |
| q                    | single numeric in [0,1) determining the quantiles to trim when scale != "never".                                                                                                                                                                                                                                                                                                                                        |
| normalize            | logical specifying whether to Z-score normalize cluster frequencies across samples; see <a href="#">plotFreqHeatmap</a> .                                                                                                                                                                                                                                                                                               |
| row_anno, col_anno   | logical specifying whether to include row/column annotations for cell metadata variables and clustering(s); see <a href="#">plotExprHeatmap</a> and <a href="#">plotFreqHeatmap</a> .                                                                                                                                                                                                                                   |
| row_clust, col_clust | logical specifying whether rows/columns should be hierarchically clustered and re-ordered accordingly.                                                                                                                                                                                                                                                                                                                  |
| row_dend, col_dend   | logical specifying whether to include the row/column dendrograms.                                                                                                                                                                                                                                                                                                                                                       |
| bars                 | logical specifying whether to include a barplot of cell counts per cluster as a right-hand side row annotation.                                                                                                                                                                                                                                                                                                         |
| perc                 | logical specifying whether to display percentage labels next to bars when bars = TRUE.                                                                                                                                                                                                                                                                                                                                  |
| hm1_pal, hm2_pal     | character vector of colors to interpolate for each heatmap.                                                                                                                                                                                                                                                                                                                                                             |
| k_pal, m_pal         | character vector of colors to use for cluster and merging row annotations. If less than nlevels(cluster_ids(x, k/m)) values are supplied, colors will be interpolated via <a href="#">colorRampPalette</a> .                                                                                                                                                                                                            |

|          |                                                                                                                    |
|----------|--------------------------------------------------------------------------------------------------------------------|
| distance | character string specifying the distance metric to use in <a href="#">dist</a> for hierarchical clustering.        |
| linkage  | character string specifying the agglomeration method to use in <a href="#">hclust</a> for hierarchical clustering. |

### Details

In its 1st panel, plotMultiHeatmap will display (scaled) type-marker expressions aggregated by cluster (across all samples). Depending on argument hm2, the 2nd panel will contain one of:

hm2 = "abundances" relative cluster abundances by cluster & sample

hm2 = "state" aggregated (scaled) state-marker expressions by cluster (across all samples; analogous to panel 1)

hm2 %in% rownames(x) aggregated (scaled) marker expressions by cluster & sample

### Value

a [HeatmapList-class](#) object.

### Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

### References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

### See Also

[plotMedExprs](#), [plotAbundances](#), [plotExprHeatmap](#), [plotFreqHeatmap](#)

### Examples

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# state-markers + cluster frequencies
plotMultiHeatmap(sce,
  hm1 = "state", hm2 = "abundances",
  bars = TRUE, perc = TRUE)

# type-markers + marker of interest
plotMultiHeatmap(sce, hm2 = "pp38", k = "meta12", m = "meta8")

# both, type- & state-markers
plotMultiHeatmap(sce, hm2 = "state")
```

```
# plot markers of interest side-by-side
# without left-hand side heatmap
plotMultiHeatmap(sce, k = "meta10",
  hm1 = NULL, hm2 = c("pS6", "pNFkB", "pBtk"),
  row_anno = FALSE, hm2_pal = c("white", "black"))
```

---

plotNRS

*Plot non-redundancy scores*


---

## Description

Plots non-redundancy scores (NRS) by feature in decreasing order of average NRS across samples.

## Usage

```
plotNRS(x, features = NULL, color_by = "condition", assay = "exprs")
```

## Arguments

|          |                                                                                                                                                                                                                                   |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                          |
| features | a character vector specifying which antigens to use for clustering; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |
| color_by | character string specifying the color coding; valid values are namescolData(x).                                                                                                                                                   |
| assay    | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                              |

## Value

a ggplot object.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)

plotNRS(sce, features = NULL) # default: all markers
plotNRS(sce, features = "type") # type-markers only
```



plotPbExprs

*Pseudobulk-level boxplot***Description**

Boxplot of aggregated marker data by sample or cluster, optionally colored and faceted by non-numeric cell metadata variables of interest.

**Usage**

```
plotPbExprs(
  x,
  k = "meta20",
  features = "state",
  assay = "exprs",
  fun = c("median", "mean", "sum"),
  facet_by = c("antigen", "cluster_id"),
  color_by = "condition",
  group_by = color_by,
  shape_by = NULL,
  size_by = FALSE,
  geom = c("both", "points", "boxes"),
  jitter = TRUE,
  ncol = NULL
)

plotMedExprs(
  x,
  k = "meta20",
  features = "state",
  facet_by = c("antigen", "cluster_id"),
  group_by = "condition",
  shape_by = NULL
)
```

**Arguments**

|          |                                                                                                                                                                                                                      |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> {SingleCellExperiment}.                                                                                                                                                       |
| k        | character string specifying which clustering to use; values are names(cluster_codes(x)). Ignored if facet_by = "antigen".                                                                                            |
| features | character vector specifying which features to include; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features. |
| assay    | character string specifying which assay data to use; valid values are assayNames(x).                                                                                                                                 |
| fun      | character string specifying the summary statistic to use.                                                                                                                                                            |

**facet\_by** "antigen" or "cluster\_id"; the latter requires having run `cluster`.  
**color\_by, group\_by, shape\_by** character string specifying a non-numeric cell metadata variable to color, group and shape by, respectively; valid values are `names(colData(x))` and `names(cluster_codes(x))` if `cluster` has been run.  
**size\_by** logical specifying whether to scale point sizes by the number of cells in a given sample or cluster-sample instance; ignored when `geom = "boxes"`.  
**geom** character string specifying whether to include only points, boxplots or both.  
**jitter** logical specifying whether to use `position_jitterdodge` in `geom_point` when `geom != "boxes"`.  
**ncol** integer scalar specifying number of facet columns.

### Value

a ggplot object.

### Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

### References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

### Examples

```

# construct SCE
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce, verbose = FALSE)

# plot median expressions by sample & condition
# ...split by marker
plotPbExprs(sce,
  shape_by = "patient_id",
  features = sample(rownames(sce), 6))

# ...split by cluster
plotPbExprs(sce, facet_by = "cluster_id", k = "meta6")

# plot median type-marker expressions by sample & cluster
plotPbExprs(sce, feature = "type", k = "meta6",
  facet_by = "antigen", group_by = "cluster_id", color_by = "sample_id",
  size_by = TRUE, geom = "points", jitter = FALSE, ncol = 5)

# plot median state-marker expressions
# by sample & cluster, split by condition
plotPbExprs(sce, k = "meta6", facet_by = "antigen",

```

```
group_by = "cluster_id", color_by = "condition", ncol = 7)
```

---

plotScatter

*Scatter plot*


---

## Description

Bivariate scatter plots including visualization of (group-specific) gates, their boundaries and percentage of selected cells.

## Usage

```
plotScatter(
  x,
  chs,
  color_by = NULL,
  facet_by = NULL,
  bins = 100,
  assay = "exprs",
  label = c("target", "channel", "both"),
  zeros = FALSE,
  k_pal = CATALYST:::.cluster_cols
)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                      |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                                             |
| chs      | character string specifying which channels to plot. Valid values are antigens: <code>rownames(x)</code> , channel names: <code>channels(x)</code> or non-mass channels stored in <code>names([int_]colData(x))</code> , and should correspond to numeric variables.                  |
| color_by | character string specifying a cell metadata column to color by; valid values are <code>names(colData(x))</code> , <code>names(int_colData(x))</code> ; <code>names(cluster_codes(x))</code> (if <a href="#">cluster</a> has been run); or <code>NULL</code> to color by density.     |
| facet_by | character string specifying a non-numeric cell metadata column to facet by; valid values are <code>names(colData(x))</code> . When <code>length(chs) == 1, 2</code> faceting variables may be provided, otherwise 1 only.                                                            |
| bins     | numeric of length 1 giving the number of bins for <a href="#">geom_hex</a> when coloring by density.                                                                                                                                                                                 |
| assay    | character string specifying which assay data to use. Should be one of <code>assayNames(x)</code> .                                                                                                                                                                                   |
| label    | character string specifying axis labels should include antigen targets, channel names, or a concatenation of both.                                                                                                                                                                   |
| zeros    | logical specifying whether to include 0 values.                                                                                                                                                                                                                                      |
| k_pal    | character string specifying the cluster color palette; ignored when <code>color_by</code> is not one of <code>names(cluster_codes(x))</code> . If less than <code>nlevels(cluster_ids(x, k))</code> are supplied, colors will be interpolated via <a href="#">colorRampPalette</a> . |

**Value**

a ggplot object.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
data(raw_data)
sce <- prepData(raw_data)

dna_chs <- c("DNA1", "DNA2")
plotScatter(sce, dna_chs, label = "both")

plotScatter(sce,
  chs = sample(rownames(sce), 4),
  color_by = "sample_id")

sce <- prepData(sample_ff)
ids <- sample(rownames(sample_key), 3)
sce <- assignPrelim(sce, sample_key[ids, ])
sce <- sce[, sce$bc_id %in% ids]

chs <- sample(rownames(sce), 5)
plotScatter(sce, chs, color_by = "bc_id")
plotScatter(sce, chs, color_by = "delta")
```

---

plotSpillmat

*Spillover matrix heatmap*


---

**Description**

Generates a heatmap of the spillover matrix annotated with estimated spill percentages.

**Usage**

```
plotSpillmat(
  x,
  sm = NULL,
  anno = TRUE,
  isotope_list = CATALYST::isotope_list,
  hm_pal = c("white", "lightcoral", "red2", "darkred"),
  anno_col = "black"
)
```

**Arguments**

|              |                                                                                                                                                                                                              |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x            | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                     |
| sm           | spillover matrix to visualize. If NULL, plotSpillmat will try and access metadata(x)\$spillover_matr                                                                                                         |
| anno         | logical. If TRUE (default), spill percentages are shown inside bins and rows are annotated with the total amount of spill received.                                                                          |
| isotope_list | named list. Used to validate the input spillover matrix. Names should be metals; list elements numeric vectors of their isotopes. See <a href="#">isotope_list</a> for the list of isotopes used by default. |
| hm_pal       | character vector of colors to interpolate.                                                                                                                                                                   |
| anno_col     | character string specifying the color to use for bin annotations.                                                                                                                                            |

**Value**

a ggplot2-object showing estimated spill percentages as a heatmap with colors ramped to the highest spillover value present.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
# get single-stained control samples & construct SCE
data(ss_exp)
sce <- prepData(ss_exp)

# debarcode single-positive populations
bc_ms <- c(139, 141:156, 158:176)
sce <- assignPrelim(sce, bc_ms, verbose = FALSE)
sce <- applyCutoffs(estCutoffs(sce))

# estimate & visualize spillover matrix
sce <- computeSpillmat(sce)
plotSpillmat(sce)
```

---

plotYields

*Yield plot*


---

**Description**

Plots the distribution of barcode separations and yields upon debarcoding as a function of separation cutoffs. If available, currently used separation cutoffs as well as their resulting yields will be indicated in the plot.

**Usage**

```
plotYields(x, which = 0, out_path = NULL, out_name = "yield_plot")
```

**Arguments**

|          |                                                                                                                                                                                                       |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                              |
| which    | 0, numeric or character. Specifies which barcode(s) to plot. Valid values are IDs that occur as row names of <code>bc_key(x)</code> ; 0 (the default) will generate a summary plot with all barcodes. |
| out_path | character string. If specified, yields plots for all barcodes specified via which will be written to a single PDF file in this location.                                                              |
| out_name | character strings specifying the output's file name when <code>!is.null(out_path)</code> ; should be provided without(!) file type extension.                                                         |

**Details**

The overall yield that will be achieved upon application of the specified set of separation cutoffs is indicated in the summary plot. Respective separation thresholds and their resulting yields are included in each barcode's plot. The separation cutoff value should be chosen such that it appropriately balances confidence in barcode assignment and cell yield.

**Value**

a list of ggplot objects.

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**References**

Zunder, E.R. et al. (2015). Palladium-based mass tag cell barcoding with a doublet-filtering scheme and single-cell deconvolution algorithm. *Nature Protocols* **10**, 316-333.

**Examples**

```
# construct SCE & apply arcsinh-transformation
data(sample_ff, sample_key)
sce <- prepData(sample_ff)

# deconvolute samples & estimate separation cutoffs
sce <- assignPrelim(sce, sample_key)
sce <- estCutoffs(sce)

# all barcodes summary plot
plotYields(sce, which = 0)

# plot for specific sample
plotYields(sce, which = "C1")
```

prepData

*Data preparation***Description**

Data preparation

**Usage**

```

prepData(
  x,
  panel = NULL,
  md = NULL,
  features = NULL,
  transform = TRUE,
  cofactor = 5,
  panel_cols = list(channel = "fcs_colname", antigen = "antigen", class = "marker_class"),
  md_cols = list(file = "file_name", id = "sample_id", factors = c("condition",
    "patient_id")),
  by_time = TRUE,
  FACS = FALSE,
  fix_chs = c("common", "all"),
  ...
)

```

**Arguments**

- |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a flowSet holding all samples or a path to a set of FCS files.                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| panel    | a data.frame containing, for each channel, its column name in the input data, targeted protein marker, and (optionally) class ("type", "state", or "none"). If 'panel' is unspecified, it will be constructed from the first input sample via <a href="#">guessPanel</a> .                                                                                                                                                                                                                                                   |
| md       | <p>a table with column describing the experiment. An exemplary metadata table could look as follows:</p> <ul style="list-style-type: none"> <li>• file_name: the FCS file name</li> <li>• sample_id: a unique sample identifier</li> <li>• patient_id: the patient ID</li> <li>• condition: brief sample description (e.g. reference/stimulated, healthy/diseased)</li> </ul> <p>If 'md' is unspecified, the flowFrame/Set <a href="#">identifier</a>(s) will be used as sample IDs with no additional metadata factors.</p> |
| features | a logical vector, numeric vector of column indices, or character vector of channel names. Specified which column to keep from the input data. Defaults to the channels listed in the input panel.                                                                                                                                                                                                                                                                                                                            |

|            |                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| transform  | logical. Specifies whether an arcsinh-transformation with cofactor cofactor should be performed, in which case expression values (transformed counts) will be stored in assay(x, "exprs").                                                                                                                                                                                                         |
| cofactor   | numeric cofactor(s) to use for optional arcsinh-transformation when transform = TRUE; single value or a vector with channels as names.                                                                                                                                                                                                                                                             |
| panel_cols | a names list specifying the panel column names that contain channel names, targeted protein markers, and (optionally) marker classes. When only some panel_cols deviate from the defaults, specifying only these is sufficient.                                                                                                                                                                    |
| md_cols    | a named list specifying the column names of md that contain the FCS file names, sample IDs, and factors of interest (batch, condition, treatment etc.). When only some md_cols deviate from the defaults, specifying only these is sufficient.                                                                                                                                                     |
| by_time    | logical; should samples be ordered by acquisition time? Ignored if !is.null(md) in which case samples will be ordered as they are listed in md[[md_cols\$file]]. (see details)                                                                                                                                                                                                                     |
| FACS       | logical; is this FACS / flow cytometry data? By default, prepData moves non-mass channels to the output SCE's int_colData; FACS = TRUE assures that all channels are kept as assay data. If FALSE, prepData will try and access the input flowFrame/Set's "\$CYT" descriptor (keyword(., "\$CYT")) to determine the data type; this may be inaccurate for some cytometer descriptors.              |
| fix_chs    | specifies the strategy to use in case of panel discrepancies. "common" will retain only channels present in all frames/FCS files; "all" will retain the union of channels across samples. In the latter case, a logical matrix with rows = channels and columns = samples will be stored under metadata slot chs_by_fcs specifying which channels were/n't (FALSE/TRUE) measured in which samples. |
| ...        | additional arguments passed to <a href="#">read.FCS</a> . E.g., channel_alias in case of panel discrepancies between frames/FCS files. By default, transformation = truncate_max_range = FALSE.                                                                                                                                                                                                    |

## Details

By default, non-mass channels (e.g., time, event lengths) will be removed from the output SCE's assay data and instead stored in the object's internal cell metadata (int\_colData) to assure these data are not subject to transformations or other computations applied to the assay data.

For more than 1 sample, prepData will concatenate cells into a single SingleCellExperiment object. Note that cells will hereby be order by "Time", regardless of whether by\_time = TRUE or FALSE. Instead, by\_time determines the sample (not cell!) order; i.e., whether samples should be kept in their original order, or should be re-ordered according to their acquisition time stored in keyword(flowSet, "\$BTIM").

When a metadata table is specified (i.e. !is.null(md)), argument by\_time will be ignored and sample ordering is instead determined by md[[md\_cols\$file]].

## Value

a [SingleCellExperiment](#).



**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
data(PBMC_fs, PBMC_panel, PBMC_md)
prepData(PBMC_fs, PBMC_panel, PBMC_md)

# channel-specific transformation
cf <- sample(seq_len(10)[-1], nrow(PBMC_panel), TRUE)
names(cf) <- PBMC_panel$fcs_colname
sce <- prepData(PBMC_fs, cofactor = cf)
int_metadata(sce)$cofactor

# input has different name for "condition"
md <- PBMC_md
m <- match("condition", names(md))
colnames(md)[m] <- "treatment"

# add additional factor variable batch ID
md$batch_id <- sample(c("A", "B"), nrow(md), TRUE)

# specify 'md_cols' that differ from defaults
factors <- list(factors = c("treatment", "batch_id"))
ei(prepData(PBMC_fs, PBMC_panel, md, md_cols = factors))

# without panel & metadata tables
sce <- prepData(raw_data)

# 'flowFrame' identifiers are used as sample IDs
levels(sce$sample_id)

# panel was guess with 'guessPanel';
# non-mass channels are set to marker class "none"
rowData(sce)
```

---

runDR

---

*Dimension reduction*


---

**Description**

Wrapper around dimension reduction methods available through scater, with optional subsampling of cells per each sample.

**Usage**

```
runDR(
  x,
```

```

dr = c("UMAP", "TSNE", "PCA", "MDS", "DiffusionMap"),
cells = NULL,
features = "type",
assay = "exprs",
...
)

```

## Arguments

|          |                                                                                                                                                                                                                                                                  |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                                                                                         |
| dr       | character string specifying which dimension reduction to use.                                                                                                                                                                                                    |
| cells    | single numeric specifying the maximal number of cells per sample to use for dimension reduction; NULL for all cells.                                                                                                                                             |
| features | a character vector specifying which antigens to use for dimension reduction; valid values are "type"/"state" for type/state_markers(x) if rowData(x)\$marker_class have been specified; a subset of rownames(x); NULL to use all features.                       |
| assay    | character string specifying which assay data to use for dimension reduction; valid values are assayNames(x).                                                                                                                                                     |
| ...      | optional arguments for dimension reduction; passed to <a href="#">runUMAP</a> , <a href="#">runTSNE</a> , <a href="#">runPCA</a> , <a href="#">runMDS</a> and <a href="#">runDiffusionMap</a> , respectively. See <code>?scater-red-dim-args</code> for details. |

## Value

a ggplot object.

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## References

Nowicka M, Krieg C, Crowell HL, Weber LM et al. CyTOF workflow: Differential discovery in high-throughput high-dimensional cytometry datasets. *F1000Research* 2017, 6:748 (doi: 10.12688/f1000research.11622.1)

## Examples

```

# construct SCE
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)

# run UMAP on <= 200 cells per sample
sce <- runDR(sce, features = type_markers(sce), cells = 100)

```

---

SCE-accessors[SingleCellExperiment](#) *accessors*

---

## Description

Various wrappers to conveniently access slots in a [SingleCellExperiment](#) created with [prepData](#), and that are used frequently during differential analysis.

## Usage

```
## S4 method for signature 'SingleCellExperiment'
ei(x)

## S4 method for signature 'SingleCellExperiment'
n_cells(x)

## S4 method for signature 'SingleCellExperiment'
channels(x)

## S4 method for signature 'SingleCellExperiment'
marker_classes(x)

## S4 method for signature 'SingleCellExperiment'
type_markers(x)

## S4 method for signature 'SingleCellExperiment'
state_markers(x)

## S4 method for signature 'SingleCellExperiment'
sample_ids(x)

## S4 method for signature 'SingleCellExperiment,missing'
cluster_ids(x, k = NULL)

## S4 method for signature 'SingleCellExperiment,character'
cluster_ids(x, k = NULL)

## S4 method for signature 'SingleCellExperiment'
cluster_codes(x)

## S4 method for signature 'SingleCellExperiment'
delta_area(x)
```

## Arguments

**x** a [SingleCellExperiment](#).

**k** character string specifying the clustering to extract. Valid values are `names(cluster_codes(x))`.

**Value**

`ei` extracts the experimental design table.

`n_cells` extracts the number of events measured per sample.

`channels` extracts the original FCS file's channel names.

`marker_classes` extracts marker class assignments ("type", "state", "none").

`type_markers` extracts the antigens used for clustering.

`state_markers` extracts antigens that were not used for clustering.

`sample_ids` extracts the sample IDs as specified in the metadata-table.

`cluster_ids` extracts the numeric vector of cluster IDs as inferred by [FlowSOM](#).

`cluster_codes` extracts a data.frame containing cluster codes for the [FlowSOM](#) clustering, the [ConsensusClusterPlus](#) metaclustering, and all mergings done through [mergeClusters](#).

`delta_area` extracts the delta area plot stored in the SCE's metadata by `cluster`

**Author(s)**

Helena L Crowell <helena.crowell@uzh.ch>

**Examples**

```
# construct SCE & run clustering
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce)

# view experimental design table
ei(sce)

# quick-access sample & cluster assignments
plot(table(sample_ids(sce)))
plot(table(cluster_ids(sce)))

# access specific clustering resolution
table(cluster_ids(sce, k = "meta8"))

# access marker information
channels(sce)
marker_classes(sce)
type_markers(sce)
state_markers(sce)

# get cluster ID correspondece between 2 clusterings
old_ids <- seq_len(20)
m <- match(old_ids, cluster_codes(sce)$`meta20`)
new_ids <- cluster_codes(sce)$`meta12`[m]
data.frame(old_ids, new_ids)

# view delta area plot (relative change in area
# under CDF curve vs. the number of clusters 'k')
delta_area(sce)
```

---

|         |                             |
|---------|-----------------------------|
| sce2fcs | <i>SCE to flowFrame/Set</i> |
|---------|-----------------------------|

---

## Description

If `split_by = NULL`, the input SCE is converted to a [flowFrame](#). Otherwise, it is split into a [flowSet](#) by the specified `colData` column. Any cell metadata (`colData`) and dimension reductions available in the SCE may be dropped or propagated to the output.

## Usage

```
sce2fcs(x, split_by = NULL, keep_cd = FALSE, keep_dr = FALSE, assay = "counts")
```

## Arguments

|                               |                                                                                                                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>                | a <a href="#">SingleCellExperiment</a> .                                                                                                                                                   |
| <code>split_by</code>         | <code>NULL</code> or a character string specifying a <code>colData(x)</code> column to split by.                                                                                           |
| <code>keep_cd, keep_dr</code> | logicals specifying whether cell metadata (stored in <code>colData(x)</code> ) and dimension reductions (stored in <code>reducedDims(x)</code> ), respectively, should be kept or dropped. |
| <code>assay</code>            | a character string specifying which assay data to use; valid values are <code>assayNames(x)</code> . When writing out FCS files, this should correspond to count-like data!                |

## Value

a [flowFrame](#) if `split_by = NULL`; otherwise a [flowSet](#).

## Author(s)

Helena L Crowell <helena.crowell@uzh.ch>

## Examples

```
# PREPROCESSING
data(sample_ff, sample_key)
sce <- prepData(sample_ff, by_time = FALSE)
sce <- assignPrelim(sce, sample_key, verbose = FALSE)

# split SCE by barcode population
fs <- sce2fcs(sce, split_by = "bc_id")

# do some spot checks
library(flowCore)
library(SingleCellExperiment)

length(fs) == nrow(sample_key)
all(fsApply(fs, nrow)[, 1] == table(sce$bc_id))
identical(t(exprs(fs[[1]])), assay(sce, "exprs")[, sce$bc_id == "A1"])
```

```
# DIFFERENTIAL ANALYSIS
data(PBMC_fs, PBMC_panel, PBMC_md)
sce <- prepData(PBMC_fs, PBMC_panel, PBMC_md)
sce <- cluster(sce, verbose = FALSE)

# split by 20 metacluster populations
sce$meta20 <- cluster_ids(sce, "meta20")
fs <- sce2fcs(sce, split_by = "meta20", assay = "exprs")
all(fsApply(fs, nrow)[, 1] == table(sce$meta20))
```

# Index

adaptSpillmat, [3](#)  
applyCutoffs, [4](#)  
assignPrelim, [5](#)  
  
BuildSOM, [9](#)  
  
channels (SCE-accessors), [59](#)  
channels, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
clrDR, [6](#)  
cluster, [9](#), [50](#), [51](#), [60](#)  
cluster\_codes (SCE-accessors), [59](#)  
cluster\_codes, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
cluster\_ids (SCE-accessors), [59](#)  
cluster\_ids, SingleCellExperiment, character-method  
    (SCE-accessors), [59](#)  
cluster\_ids, SingleCellExperiment, missing-method  
    (SCE-accessors), [59](#)  
colorRampPalette, [27](#), [30](#), [36](#), [43](#), [46](#), [51](#)  
compCytot, [3](#), [11](#)  
computeSpillmat, [13](#)  
ConsensusClusterPlus, [9](#), [60](#)  
  
data, [15](#)  
delta\_area (SCE-accessors), [59](#)  
delta\_area, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
diffcyt, [33](#)  
dist, [27](#), [47](#)  
  
ei (SCE-accessors), [59](#)  
ei, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
estCutoffs, [16](#)  
extractClusters, [18](#)  
  
filterSCE, [19](#)  
flowFrame, [12](#), [15](#), [20](#), [23](#), [61](#)  
flowSet, [15](#), [61](#)  
FlowSOM, [60](#)  
  
geom\_hex, [51](#)  
ggplot, [10](#), [28](#), [32](#), [42](#)  
guessPanel, [20](#), [55](#)  
  
hclust, [27](#), [47](#)  
Heatmap, [40](#)  
HeatmapList, [45](#)  
  
identifier, [55](#)  
isotope\_list, [3](#), [12](#), [14](#), [53](#)  
isotope\_list (data), [15](#)  
  
marker\_classes (SCE-accessors), [59](#)  
marker\_classes, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
mergeClusters, [21](#), [60](#)  
merging\_table (data), [15](#)  
na\_cells (data), [15](#)  
  
n\_cells (SCE-accessors), [59](#)  
n\_cells, SingleCellExperiment-method  
    (SCE-accessors), [59](#)  
normCytot, [22](#)  
  
PBMC\_fs (data), [15](#)  
PBMC\_md (data), [15](#)  
PBMC\_panel (data), [15](#)  
pbMDS, [24](#)  
plotAbundances, [21](#), [26](#), [43](#), [47](#)  
plotClusterExprs, [28](#)  
plotClusterHeatmap, [29](#)  
plotCodes, [30](#)  
plotCounts, [31](#)  
plotDiffHeatmap, [32](#)  
plotDR, [35](#)  
plotEvents, [37](#)  
plotExprHeatmap, [38](#), [43](#), [45–47](#)  
plotExprs, [41](#)  
plotFreqHeatmap, [40](#), [42](#), [45–47](#)  
plotMahal, [44](#)  
plotMedExprs, [40](#), [47](#)

plotMedExprs (plotPbExprs), [49](#)  
plotMultiHeatmap, [21](#), [40](#), [43](#), [45](#)  
plotNRS, [48](#)  
plotPbExprs, [49](#)  
plotScatter, [51](#)  
plotSpillmat, [52](#)  
plotYields, [53](#)  
prepData, [55](#), [59](#)  
  
raw\_data (data), [15](#)  
read.FCS, [56](#)  
runDiffusionMap, [58](#)  
runDR, [57](#)  
runMDS, [58](#)  
runPCA, [58](#)  
runTSNE, [58](#)  
runUMAP, [58](#)  
  
sample\_ff (data), [15](#)  
sample\_ids (SCE-accessors), [59](#)  
sample\_ids, SingleCellExperiment-method  
(SCE-accessors), [59](#)  
sample\_key (data), [15](#)  
SCE-accessors, [59](#)  
sce2fcs, [61](#)  
SingleCellExperiment, [4](#), [5](#), [7](#), [9](#), [11](#), [13](#), [16](#),  
[18](#), [19](#), [21](#), [23](#), [25](#), [26](#), [28–31](#), [33](#), [35](#),  
[37](#), [39](#), [41](#), [43](#), [44](#), [46](#), [48](#), [49](#), [51](#), [53](#),  
[54](#), [56](#), [58](#), [59](#), [61](#)  
ss\_exp (data), [15](#)  
state\_markers (SCE-accessors), [59](#)  
state\_markers, SingleCellExperiment-method  
(SCE-accessors), [59](#)  
  
testDA\_edgeR, [33](#)  
testDA\_GLMM, [33](#)  
testDA\_voom, [33](#)  
testDS\_limma, [33](#)  
testDS\_LMM, [33](#)  
type\_markers (SCE-accessors), [59](#)  
type\_markers, SingleCellExperiment-method  
(SCE-accessors), [59](#)