

Package ‘CNVMetrics’

June 6, 2023

Type Package

Version 1.4.0

Date 2021-11-23

Title Copy Number Variant Metrics

Description The CNVMetrics package calculates similarity metrics to facilitate copy number variant comparison among samples and/or methods. Similarity metrics can be employed to compare CNV profiles of genetically unrelated samples as well as those with a common genetic background. Some metrics are based on the shared amplified/deleted regions while other metrics rely on the level of amplification/deletion. The data type used as input is a plain text file containing the genomic position of the copy number variations, as well as the status and/or the log2 ratio values. Finally, a visualization tool is provided to explore resulting metrics.

Encoding UTF-8

License Artistic-2.0

Depends R (>= 4.1)

Imports GenomicRanges, IRanges, S4Vectors, BiocParallel, methods, magrittr, stats, pheatmap, gridExtra, grDevices

Suggests BiocStyle, knitr, rmarkdown, testthat

biocViews BiologicalQuestion, Software, CopyNumberVariation

VignetteBuilder knitr

URL <https://github.com/krasnitzlab/CNVMetrics>,
<https://krasnitzlab.github.io/CNVMetrics/>

BugReports <https://github.com/krasnitzlab/CNVMetrics/issues>

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/CNVMetrics>

git_branch RELEASE_3_17

git_last_commit f240f40

git_last_commit_date 2023-04-25

Date/Publication 2023-06-06

Author Astrid Deschênes [aut, cre] (<<https://orcid.org/0000-0001-7846-6749>>),
 Pascal Belleau [aut] (<<https://orcid.org/0000-0002-0802-1071>>),
 David A. Tuveson [aut],
 Alexander Krasnitz [aut]

Maintainer Astrid Deschênes <adeschen@hotmail.com>

R topics documented:

CNVMetrics-package	2
calculateJaccard	3
calculateLog2ratioMetric	4
calculateOneLog2valueMetricT	6
calculateOneOverlapMetricT	8
calculateOverlapMetric	9
calculateSorensen	12
calculateSzymkiewicz	13
calculateWeightedEuclideanDistanceFor2Samples	14
createDisjoinSegmentsForTwoSamples	16
is.CNVMetric	17
plotMetric	17
plotOneMetric	19
print.CNVMetric	20
validatecalculateLog2ratioMetricParameters	21
validateCalculateOverlapMetricParameters	22
Index	23

CNVMetrics-package	<i>CNVMetrics: Copy number variant metrics</i>
--------------------	--

Description

The CNVMetrics package calculates similarity metrics to facilitate copy number variant comparison among samples and/or methods. Similarity metrics can be employed to compare CNV profiles of genetically unrelated samples as well as those with a common genetic background. Some metrics are based on the shared amplified/deleted regions while other metrics rely on the level of amplification/deletion. The data type used as input is a plain text file containing the genomic position of the copy number variations, as well as the status and/or the log2 ratio values. Finally, a visualization tool is provided to explore resulting metrics.

Author(s)

Astrid Deschênes, Pascal Belleau, David A. Tuveson and Alexander Krasnitz

Maintainer: Astrid Deschênes <adeschen@hotmail.com>

See Also

- [calculateOverlapMetric](#) for calculating metric using overlapping amplified/deleted regions
- [calculateLog2ratioMetric](#) for calculating metric using log2ratio values
- [plotMetric](#) for plotting metrics

calculateJaccard	<i>Calculate Jaccard metric</i>
------------------	---------------------------------

Description

Calculate Jaccard metric using overlapping regions between two samples.

Usage

```
calculateJaccard(sample01, sample02)
```

Arguments

sample01	a GRanges which contains a collection of genomic ranges representing copy number events for the first sample.
sample02	a GRanges which contains a collection of genomic ranges representing copy number events for the second sample.

Details

The method calculates the Jaccard metric using overlapping regions between the samples. All regions present in both samples are used for the calculation of the metric.

The Jaccard metric is calculated by dividing the size of the intersection by the size of the union of the two sets. If the the size of the union of the two sets is zero; the value NA is returned instead. The strand of the regions is not taken into account while calculating the intersection.

Value

a numeric, the value of the Jaccard metric. If the metric cannot be calculated, NA is returned.

Author(s)

Astrid Deschênes

References

Jaccard, P. (1912), The Distribution of the Flora in the Alpine Zone. New Phytologist, 11: 37-50.
DOI: <https://doi.org/10.1111/j.1469-8137.1912.tb05611.x>

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

## Generate two samples with identical sequence levels
sample01 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841),
    end=c(2004603, 4577608, 31695808)), strand="*")
sample02 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222),
    end=c(2204505, 31689898)), strand="*")

## Calculate Sorensen metric
CNVMetrics::calculateJaccard(sample01=sample01, sample02=sample02)
```

```
calculateLog2ratioMetric
```

Calculate metric using overlapping amplified/deleted regions

Description

Calculate a specific metric using overlapping amplified/deleted regions between two samples. The metric is calculated for the amplified and deleted regions separately. When more than 2 samples are present, the metric is calculated for each sample pair.

Usage

```
calculateLog2ratioMetric(
  segmentData,
  method = c("weightedEuclideanDistance"),
  minThreshold = 0.2,
  excludedRegions = NULL,
  nJobs = 1
)
```

Arguments

segmentData	a GRangesList that contains a collection of genomic ranges representing copy number events, including amplified/deleted status, from at least 2 samples. All samples must have a metadata column called 'log2ratio' with the log2ratio values.
method	a character string representing the metric to be used. This should be (an unambiguous abbreviation of) one of "weightedEuclideanDistance". Default: "weightedEuclideanDistance".
minThreshold	a single positive numeric setting the minimum value to consider two segments as different during the metric calculation. If the absolute difference is below or equal to threshold, the difference will be replaced by zero. Default: 0.2.

excludedRegions	an optional GRanges containing the regions that have to be excluded for the metric calculation. Default: NULL.
nJobs	a single positive integer specifying the number of worker jobs to create in case of distributed computation. Default: 1 and always 1 for Windows.

Details

The weighted euclidean distance is $(\sum((x_i - y_i)^2 * \log(nbrBases_i)))^{0.5}$ where x and y are the values of 2 samples for a specific segment i and nbrBases the number of bases of the segment i.

Value

an object of class "CNVMetric" which contains the calculated metric. This object is a list with the following components:

- LOG2RATIO a lower-triangular matrix with the results of the selected metric on the log2ratio values for each paired samples. The value NA is present when the metric cannot be calculated. The value NA is also present in the top-triangular section, as well as the diagonal, of the matrix.

The object has the following attributes (besides "class" equal to "CNVMetric"):

- metric the metric used for the calculation.
- names the names of the two matrix containing the metrics for the amplified and deleted regions.

Author(s)

Astrid Deschênes, Pascal Belleau

Examples

```
## Load required package to generate the samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
demo <- GRangesList()
demo[["sample01"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841),
    end=c(2004603, 4577608, 31695808)), strand="*",
  log2ratio=c(2.5555, 1.9932, -0.9999))

demo[["sample02"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222, 31690000),
    end=c(2204505, 31689898, 31895666)), strand=c("-", "+", "+"),
  log2ratio=c(0.3422, 0.5454, -1.4444))

## The amplified region in sample03 is a subset of the amplified regions
## in sample01
demo[["sample03"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1906069, 4558838),
```

```

end=c(1909505, 4570601)), strand="*",
log2ratio=c(3.2222, -1.3232))

## Calculating Sorensen metric
calculateLog2ratioMetric(demo, method="weightedEuclideanDistance", nJobs=1)

```

```
calculateOneLog2valueMetricT
```

Calculate metric using the log2ratio values between two samples.

Description

Calculate a specific metric using the level of amplification/deletion, in log2 ratio, between two samples.

Usage

```

calculateOneLog2valueMetricT(
  entry,
  segmentData,
  method,
  minThreshold,
  bedExclusion
)

```

Arguments

entry	a list which contains the row and column indexes (always in this order) of the metric in the final matrix. Those values correspond to the positions of the two samples used to calculate the metric in the GRangesList (segmentData).
segmentData	a GRangesList that contains a collection of genomic ranges representing copy number events, including amplified/deleted status, from at least 2 samples. All samples must have a metadata column called 'log2ratio' with the log2ratio values.
method	a character string representing the metric to be used ('weightedEuclideanDistance').
minThreshold	a single numeric setting the minimum value to consider two segments as different during the metric calculation. If the absolute difference is below or equal to threshold, the difference will be replaced by zero.
bedExclusion	an optional GRanges containing the regions that have to be excluded for the metric calculation or codeNULL.

Details

The method calculates a specified metric using overlapping regions between the samples. Only regions corresponding to the type specified by user are used in the calculation of the metric. The strand of the regions is not taken into account while calculating the metric.

The Sorensen metric is calculated by dividing twice the size of the intersection by the sum of the size of the two sets. If the sum of the size of the two sets is zero; the value NA is returned instead.

Value

a list containing 1 entry:

- metric a data.frame, which contains 3 columns. The 2 first columns, called row and column correspond to the indexes of the metric in the final matrix. Those 2 first columns match to the entry parameter. The third column, called metric, contains the values of the specified metric for each combination. If the metric cannot be calculated, NA is present.

Author(s)

Astrid Deschênes

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
demo <- GRangesList()

## Generate two samples with log2value information as a metadata column
demo[["sample01"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(100, 201, 400),
    end=c(200, 350, 500)), strand="*",
  log2ratio=c(1.1111, 2.2222, -0.9999))
demo[["sample02"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(150, 200, 450),
    end=c(250, 350, 500)), strand="*",
  log2ratio=c(2.2121, 1.1212, -1.3939))

## The 2 samples used to calculate the metric
entries <- data.frame(row=c(2), col=c(1))

## Calculate weighted Euclidean distance
CNVMetrics:::calculateOneLog2valueMetricT(entry=entries,
  segmentData=demo, method="weightedEuclideanDistance",
  minThreshold=0.2, bedExclusion=NULL)
```

```
calculateOneOverlapMetricT
```

Calculate metric using overlapping amplified/deleted regions between two samples.

Description

Calculate a specific metric using overlapping amplified/deleted regions between two samples.

Usage

```
calculateOneOverlapMetricT(entry, segmentData, method, type)
```

Arguments

entry	a list which contains the row and column indexes (always in this order) of the metric in the final matrix. Those values correspond to the positions of the two samples used to calculate the metric in the GRangesList (segmentData).
segmentData	a GRangesList that contains a collection of genomic ranges representing copy number events, including amplified/deleted status, from at least 2 samples. All samples must have a metadata column called 'state' with a state, in a character string format, specified for each region (ex: DELETION, LOH, AMPLIFICATION, NEUTRAL, etc.).
method	a character string representing the metric to be used ('sorensen' or 'szymkiewicz').
type	a character string representing the type of copy number events to be used ('AMPLIFICATION' or 'DELETION').

Value

a list containing 1 entry:

- metric a data.frame, which contains 3 columns. The 2 first columns, called row and column correspond to the indexes of the metric in the final matrix. Those 2 first columns match to the entry parameter. The third column, called metric, contains the values of the specified metric for each combination. If the metric cannot be calculated, NA is present.

Author(s)

Astrid Deschênes

Examples

```
## Load required package to generate the samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
```

```

demo <- GRangesList()
demo[["sample01"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841, 32686222),
    end=c(2004603, 4577608, 31695808, 32689222)), strand="*",
  state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION", "LOH"))

demo[["sample02"]] <- GRanges(seqnames="chr1",
  ranges= IRanges(start=c(1995066, 31611222, 31690000, 32006222),
    end=c(2204505, 31689898, 31895666, 32789233)),
  strand=c("-", "+", "+", "+"),
  state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION", "LOH"))

## The amplified region in sample03 is a subset of the amplified regions
## in sample01
demo[["sample03"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1906069, 4558838),
    end=c(1909505, 4570601)), strand="*",
  state=c("AMPLIFICATION", "DELETION"))

## The 2 samples used to calculate the metric
entries <- data.frame(row=c(2, 3), col=c(1, 1))

## Calculate Sorensen metric for the amplified regions on samples 2 and 3
CNVMetrics::calculateOneOverlapMetricT(entry=entries, segmentData=demo,
  method="sorensen", type="AMPLIFICATION")

## Calculate Szymkiewicz-Simpson metric for the amplified regions
## in samples 1 and 2
## Amplified regions of sample02 are a subset of the amplified
## regions in sample01
CNVMetrics::calculateOneOverlapMetricT(entry=entries, segmentData=demo,
  method="szymkiewicz", type="AMPLIFICATION")

## Calculate Sorensen metric for the deleted regions in samples 1 and 2
CNVMetrics::calculateOneOverlapMetricT(entry=entries, segmentData=demo,
  method="sorensen", type="DELETION")

```

calculateOverlapMetric

Calculate metric using overlapping amplified/deleted regions

Description

Calculate a specific metric using overlapping regions of specific state between to samples. The metric is calculated for each state separately. When more than 2 samples are present, the metric is calculated for each sample pair. By default, the function is calculating metrics for the AMPLIFICATION and DELETION states. However, the user can specify the list of states to be analyzed.

Usage

```
calculateOverlapMetric(
  segmentData,
  states = c("AMPLIFICATION", "DELETION"),
  method = c("sorensen", "szymkiewicz", "jaccard"),
  nJobs = 1
)
```

Arguments

<code>segmentData</code>	a <code>GRangesList</code> that contains a collection of genomic ranges representing copy number events, including amplified/deleted status, from at least 2 samples. All samples must have a metadata column called 'state' with a state, in a character string format, specified for each region (ex: DELETION, LOH, AMPLIFICATION, NEUTRAL, etc.).
<code>states</code>	a vector of character string with at least one entry. The strings are representing the states that will be analyzed. Default: <code>c('AMPLIFICATION', 'DELETION')</code> .
<code>method</code>	a character string representing the metric to be used. This should be (an unambiguous abbreviation of) one of "sorensen", "szymkiewicz" or "jaccard". Default: "sorensen".
<code>nJobs</code>	a single positive integer specifying the number of worker jobs to create in case of distributed computation. Default: 1 and always 1 for Windows.

Details

The two methods each estimate the overlap between paired samples. They use different metrics, all in the range [0, 1] with 0 indicating no overlap. The NA is used when the metric cannot be calculated.

The available metrics are (written for two `GRanges`):

sorensen:

This metric is calculated by dividing twice the size of the intersection by the sum of the size of the two sets. With this metric, an overlap metric value of 1 is only obtained when the two samples are identical.

szymkiewicz:

This metric is calculated by dividing the size of the intersection by the size of the smallest set. With this metric, if one set is a subset of the other set, the overlap metric value is 1.

jaccard:

This metric is calculated by dividing the size of the intersection by the size of the union of the two sets. With this metric, an overlap metric value of 1 is only obtained when the two samples are identical.

Value

an object of class "CNVMetric" which contains the calculated metric. This object is a list where each entry corresponds to one state specified in the 'states' parameter. Each entry is a matrix:

- state a lower-triangular matrix with the results of the selected metric on the amplified regions for each paired samples. The value NA is present when the metric cannot be calculated. The value NA is also present in the top-triangular section, as well as the diagonal, of the matrix.

The object has the following attributes (besides "class" equal to "CNVMetric"):

- metric the metric used for the calculation.
- names the names of the two matrix containing the metrics for the amplified and deleted regions.

Author(s)

Astrid Deschênes, Pascal Belleau

References

Sørensen, Thorvald. n.d. "A Method of Establishing Groups of Equal Amplitude in Plant Sociology Based on Similarity of Species and Its Application to Analyses of the Vegetation on Danish Commons." *Biologiske Skrifter*, no. 5: 1–34.

Vijaymeena, M. K, and Kavitha K. 2016. "A Survey on Similarity Measures in Text Mining." *Machine Learning and Applications: An International Journal* 3 (1): 19–28. doi: <https://doi.org/10.5121/mlaij.2016.3103>

Jaccard, P. (1912), The Distribution of the Flora in the Alpine Zone. *New Phytologist*, 11: 37-50. doi: <https://doi.org/10.1111/j.1469-8137.1912.tb05611.x>

Examples

```
## Load required package to generate the samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
demo <- GRangesList()
demo[["sample01"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841, 32686222),
    end=c(2004603, 4577608, 31695808, 32689222)), strand="*",
  state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION", "LOH"))

demo[["sample02"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222, 31690000, 32006222),
    end=c(2204505, 31689898, 31895666, 32789233)),
  strand=c("-", "+", "+", "+"),
  state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION", "LOH"))

## The amplified region in sample03 is a subset of the amplified regions
## in sample01
demo[["sample03"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1906069, 4558838),
    end=c(1909505, 4570601)), strand="*",
  state=c("AMPLIFICATION", "DELETION"))
```

```
## Calculating Sorensen metric for both AMPLIFICATION and DELETION
calculateOverlapMetric(demo, method="sorensen", nJobs=1)

## Calculating Szymkiewicz-Simpson metric on AMPLIFICATION only
calculateOverlapMetric(demo, states="AMPLIFICATION", method="szymkiewicz",
  nJobs=1)

## Calculating Jaccard metric on LOH only
calculateOverlapMetric(demo, states="LOH", method="jaccard", nJobs=1)
```

calculateSorensen	<i>Calculate Sorensen metric</i>
-------------------	----------------------------------

Description

Calculate Sorensen metric using overlapping regions between two samples.

Usage

```
calculateSorensen(sample01, sample02)
```

Arguments

sample01	a GRanges which contains a collection of genomic ranges representing copy number events for the first sample.
sample02	a GRanges which contains a collection of genomic ranges representing copy number events for the second sample.

Details

The method calculates the Sorensen metric using overlapping regions between the samples. All regions present in both samples are used for the calculation of the metric.

The Sorensen metric is calculated by dividing twice the size of the intersection by the sum of the size of the two sets. If the sum of the size of the two sets is zero; the value NA is returned instead. The strand of the regions is not taken into account while calculating the intersection.

Value

a numeric, the value of the Sorensen metric. If the metric cannot be calculated, NA is returned.

Author(s)

Astrid Deschênes

References

Sørensen, Thorvald. n.d. "A Method of Establishing Groups of Equal Amplitude in Plant Sociology Based on Similarity of Species and Its Application to Analyses of the Vegetation on Danish Commons." Biologiske Skrifter, no. 5: 1–34.

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

## Generate two samples with identical sequence levels
sample01 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841),
    end=c(2004603, 4577608, 31695808)), strand="*")
sample02 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222),
    end=c(2204505, 31689898)), strand="*")

## Calculate Sorensen metric
CNVMetrics::calculateSorensen(sample01=sample01, sample02=sample02)
```

calculateSzymkiewicz	<i>Calculate Szymkiewicz-Simpson metric</i>
----------------------	---

Description

Calculate Szymkiewicz-Simpson metric using overlapping regions between two samples.

Usage

```
calculateSzymkiewicz(sample01, sample02)
```

Arguments

sample01	a GRanges which contains a collection of genomic ranges representing copy number events for the first sample.
sample02	a GRanges which contains a collection of genomic ranges representing copy number events for the second sample.

Details

The method calculates the Szymkiewicz-Simpson metric using overlapping regions between the samples. All regions present in both samples all used for the calculation of the metric.

The Szymkiewicz-Simpson metric is calculated by dividing the size of the intersection by the smaller of the size of the two sets. If one sample has a size of zero, the metric is not calculated; the value NA is returned instead. The strand of the regions is not taken into account while calculating the intersection.

Value

a numeric, the value of the Szymkiewicz-Simpson metric. If the metric cannot be calculated, NA is returned.

Author(s)

Astrid Deschênes

References

Vijaymeena, M. K, and Kavitha K. 2016. "A Survey on Similarity Measures in Text Mining." Machine Learning and Applications: An International Journal 3 (1): 19–28. doi: <https://doi.org/10.5121/mlaij.2016.3103>

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

## Generate two samples with identical sequence levels
sample01 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841),
    end=c(2004603, 4577608, 31695808)), strand="*")
sample02 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222),
    end=c(2204505, 31689898)), strand=c("+", "-"))

## Calculate Szymkiewicz-Simpson metric
CNVMetrics:::calculateSzymkiewicz(sample01=sample01, sample02=sample02)
```

calculateWeightedEuclideanDistanceFor2Samples

Calculate Weighted Euclidean distance-based metric between samples.

Description

The weighted Euclidean distance-based metric corresponds to the euclidean distance between 2 samples multiplied by the natural logarithm of the number of bases of the analyzed segment. The final metric is 1 over 1 added to the squared sum of the values obtained for all segments that are not excluded of the analysis.

Usage

```
calculateWeightedEuclideanDistanceFor2Samples(segmentData, minThreshold)
```

Arguments

segmentData	a list marked as a preMetricSegments class that contains the disjoint segment information from 2 samples and the log2ratio values of the samples in the metadata columns.
-------------	---

minThreshold a single numeric setting the minimum value to consider two segments as different for the metric calculation. If the absolute difference is below or equal to threshold, the value will be replaced by zero.

Details

The weighted euclidean distance is $1/(1 + (\sum((x_i - y_i)^2 * \log_2(nbrBases_i))^0.5)$ where x and y are the values of 2 samples for a specific segment i and nbrBases the number of bases of the segment i.

Value

a numeric representing the weighted euclidean distance between the two samples. If the distance cannot be calculated as the two samples don't share any segments with log2ratio value, the value NA is assigned.

Author(s)

Astrid Deschênes

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

# Create first Granges representing first sample
sample01 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(100, 201, 400), end=c(200, 350, 500)),
  strand="*", log2ratio=c(0.3091175, 0.4582058, -0.3798390))

# Create second Granges representing second sample
sample02 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(150, 200, 450), end=c(250, 350, 500)),
  strand="*", log2ratio=c(0.222174, 0.3282156, -0.2728292))

# Create disjoint segment using the 2 samples and without any region
# excluded from the analysis (parameter bedExclusion set to null)
disjoinGRange <- CNVMetrics::createDisjoinSegmentsForTwoSamples(
  segmentDataSample1=sample01, segmentDataSample2=sample02,
  bedExclusion=NULL)

## Calculate the weighted euclidean distance between the two samples
CNVMetrics::calculateWeightedEuclideanDistanceFor2Samples(
  segmentData=disjoinGRange, minThreshold=0.2)
```

```
createDisjoinSegmentsForTwoSamples
```

Generate common segments to enable calculation of metrics on two segmented samples.

Description

The two segments are gathered together, including excluded regions when specified, and a disjoint operation is done to create a collection of non-overlapping ranges. The ranges overlapping the excluded regions are marked as so to be removed from future analysis. The log2value of each samples are assigned to the new disjointed segments for each sample in the metadata columns.

Usage

```
createDisjoinSegmentsForTwoSamples(
  segmentDataSample1,
  segmentDataSample2,
  bedExclusion = NULL
)
```

Arguments

```
segmentDataSample1
    a GRanges, the segments from the first sample.
segmentDataSample2
    a GRanges, the segments from the second sample.
bedExclusion
    a GRanges, the regions that must be excluded from the analysis. Default: NULL.
```

Value

a GRanges containing the common segment information for the two samples. The log2ration value are present, for the two samples, in the metadata columns. When there is not log2ratio value for one sample, NA is the assigned value. A metadata column also specifies if the segments should be included in the analysis.

Author(s)

Astrid Deschênes

Examples

```
## Load required package to generate the two samples
require(GenomicRanges)

# Create first Granges representing first sample
sample01 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(100, 201, 400), end=c(200, 350, 500)),
  strand="*", log2ratio=c(0.3091175, 0.4582058, -0.3798390))
```

```
# Create second Granges representing second sample
sample02 <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(150, 200, 450), end=c(250, 350, 500)),
  strand="*", log2ratio=c(0.222174, 0.3282156, -0.2728292))

# Create disjoint segment using the 2 samples and without any region
# excluded from the analysis (parameter bedExclusion set to null)
CNVMetrics::createDisjoinSegmentsForTwoSamples(segmentDataSample1=sample01,
  segmentDataSample2=sample02, bedExclusion=NULL)
```

is.CNVMetric	<i>Is an object of class CNVMetric</i>
--------------	--

Description

Functions to test inheritance relationships between an object and class CNVMetric.

Usage

```
## S3 method for class 'CNVMetric'
is(x, ...)
```

Arguments

x	an object.
...	further arguments passed to or from other methods.

Value

a logical.

plotMetric	<i>Plot metrics present in a CNVMetric object.</i>
------------	--

Description

Plot one heatmap (or two heatmaps) of the metrics present in a CNVMetric object. For the overlapping metrics, the user can select to print the heatmap related to amplified or deleted regions or both. The NA values present in the metric matrix are transformed into zero for the creation of the heatmap.

Usage

```
plotMetric(
  metric,
  type = "ALL",
  colorRange = c(c("white", "darkblue")),
  show_colnames = FALSE,
  silent = TRUE,
  ...
)
```

Arguments

<code>metric</code>	a CNVMetric object containing the metrics calculated by <code>calculateOverlapMetric</code> or by <code>calculateLog2ratioMetric</code> .
<code>type</code>	a single character string indicating which graph to generate. This should be a type present in the CNVMetric object or "ALL". This is useful for the overlapping metrics that have multiple types specified by the user. Default: "ALL".
<code>colorRange</code>	a vector of 2 character string representing the 2 colors that will be assigned to the lowest (0) and highest value (1) in the heatmap. Default: <code>c("white", "darkblue")</code> .
<code>show_colnames</code>	a boolean specifying if column names are to be shown. Default: FALSE.
<code>silent</code>	a boolean specifying if the plot should not be drawn. Default: TRUE.
<code>...</code>	further arguments passed to <code>pheatmap::pheatmap()</code> method. Beware that the <code>filename</code> argument cannot be used when <code>type</code> is "ALL".

Value

a `gtable` object containing the heatmap(s) of the specified metric(s).

Author(s)

Astrid Deschênes

See Also

The default method `pheatmap::pheatmap()`.

Examples

```
## Load required package to generate the samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
demo <- GRangesList()
demo[["sample01"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1905048, 4554832, 31686841),
    end=c(2004603, 4577608, 31695808)), strand="*")
```

```

state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION"))

demo[["sample02"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1995066, 31611222, 31690000),
    end=c(2204505, 31689898, 31895666)), strand=c("-", "+", "+"),
  state=c("AMPLIFICATION", "AMPLIFICATION", "DELETION"))

## The amplified region in sample03 is a subset of the amplified regions
## in sample01
demo[["sample03"]] <- GRanges(seqnames="chr1",
  ranges=IRanges(start=c(1906069, 4558838),
    end=c(1909505, 4570601)), strand="*",
  state=c("AMPLIFICATION", "DELETION"))

## Calculating Sorensen metric
metric <- calculateOverlapMetric(demo, method="sorensen")

## Plot both amplification and deletion metrics
plotMetric(metric, type="ALL")

## Extra parameters, used by pheatmap(), can also be passed to the function
## Here, we have the metric values print to the cell while the
## row names and column names are removed
plotMetric(metric, type="DELETION", show_rownames=FALSE,
  show_colnames=FALSE, main="deletion", display_numbers=TRUE,
  number_format="%.2f")

```

plotOneMetric

Plot one graph related to one set of metrics.

Description

Plot one heatmap of one set of metrics present in a a CNVMetric object.

Usage

```
plotOneMetric(metric, type, colorRange, show_colnames, silent, ...)
```

Arguments

metric	a CNVMetric object containing the metrics calculated by calculateOverlapMetric.
type	a character string indicating which graph to generate. This should be (an unambiguous abbreviation of) one of "AMPLIFICATION" or "DELETION" or "LOG2RATIO".
show_colnames	a boolean specifying if column names are be shown.
silent	a boolean specifying if the plot should not be drawn.
...	further arguments passed to pheatmap::pheatmap() method.

Value

a gtable object containing the heatmap for the specified metric.

Author(s)

Astrid Deschênes

See Also

The default method `pheatmap::pheatmap()`.

Examples

```
#' ## Load required package to generate the samples
require(GenomicRanges)

## Create a GRangesList object with 3 samples
## The stand of the regions doesn't affect the calculation of the metric
demo <- GRangesList()
demo[["sample01"]] <- GRanges(seqnames = "chr1",
  ranges = IRanges(start = c(1905048, 4554832, 31686841),
    end = c(2004603, 4577608, 31695808)), strand = "*",
  state = c("AMPLIFICATION", "AMPLIFICATION", "DELETION"))

demo[["sample02"]] <- GRanges(seqnames = "chr1",
  ranges = IRanges(start = c(1995066, 31611222, 31690000),
    end = c(2204505, 31689898, 31895666)), strand = c("-", "+", "+"),
  state = c("AMPLIFICATION", "AMPLIFICATION", "DELETION"))

## The amplified region in sample03 is a subset of the amplified regions
## in sample01
demo[["sample03"]] <- GRanges(seqnames = "chr1",
  ranges = IRanges(start = c(1906069, 4558838),
    end = c(1909505, 4570601)), strand = "*",
  state = c("AMPLIFICATION", "DELETION"))

## Calculating Sorensen metric
metric <- calculateOverlapMetric(demo, method="sorensen")

## Plot amplification metrics using darkorange color
CNVMetrics::plotOneMetric(metric, type="AMPLIFICATION",
  colorRange=c("white", "darkorange"), show_colnames=FALSE, silent=TRUE)
```

print.CNVMetric

Print CNVMetric object

Description

Print a CNVMetric object and returns it invisibly.

Usage

```
## S3 method for class 'CNVMetric'
print(x, ...)
```

Arguments

`x` the output object from `calculateOverlapRegionsMetric` function to be printed.
`...` further arguments passed to or from other methods.

Value

the argument `x`.

See Also

The default method `print.default`.

```
validatecalculateLog2ratioMetricParameters
```

Parameters validation for the `calculateLog2ratioMetric` function

Description

Validation of all parameters needed by the public `calculateLog2ratioMetric` function.

Usage

```
validatecalculateLog2ratioMetricParameters(
  minThreshold,
  excludedRegions,
  nJobs
)
```

Arguments

`minThreshold` a single positive numeric setting the minimum value to consider two segments as different during the metric calculation. If the absolute difference is below or equal to threshold, the difference will be replaced by zero.

`excludedRegions` an optional `GRanges` containing the regions that have to be excluded for the metric calculation or `NULL`.

`nJobs` a single positive integer specifying the number of worker jobs to create in case of distributed computation.

Value

0.

Author(s)

Astrid Deschênes

Examples

```
## Return zero as all parameters are valid
CNVMetrics::validatecalculateLog2ratioMetricParameters(
  minThreshold=0.9, excludedRegions=NULL, nJobs=1)
```

validateCalculateOverlapMetricParameters

Parameters validation for the [calculateOverlapMetric](#) function

Description

Validation of all parameters needed by the public [calculateOverlapMetric](#) function.

Usage

```
validateCalculateOverlapMetricParameters(states, nJobs)
```

Arguments

states	a vector of character string with at least one entry. The strings are representing the states that will be analyzed.
nJobs	a single positive integer specifying the number of worker jobs to create in case of distributed computation.

Value

0.

Author(s)

Astrid Deschênes

Examples

```
## Return zero as all parameters are valid
CNVMetrics::validateCalculateOverlapMetricParameters(
  states="GAIN", nJobs=1)
```

Index

- * **internal**
 - calculateJaccard, [3](#)
 - calculateOneLog2valueMetricT, [6](#)
 - calculateOneOverlapMetricT, [8](#)
 - calculateSorensen, [12](#)
 - calculateSzymkiewicz, [13](#)
 - calculateWeightedEuclideanDistanceFor2Samples, [14](#)
 - createDisjoinSegmentsForTwoSamples, [16](#)
 - plotOneMetric, [19](#)
 - validatecalculateLog2ratioMetricParameters, [21](#)
 - validateCalculateOverlapMetricParameters, [22](#)
- * **package**
 - CNVMetrics-package, [2](#)
- calculateJaccard, [3](#)
- calculateLog2ratioMetric, [3](#), [4](#), [21](#)
- calculateOneLog2valueMetricT, [6](#)
- calculateOneOverlapMetricT, [8](#)
- calculateOverlapMetric, [3](#), [9](#), [22](#)
- calculateSorensen, [12](#)
- calculateSzymkiewicz, [13](#)
- calculateWeightedEuclideanDistanceFor2Samples, [14](#)
- CNVMetrics (CNVMetrics-package), [2](#)
- CNVMetrics-package, [2](#)
- createDisjoinSegmentsForTwoSamples, [16](#)
- is.CNVMetric, [17](#)
- heatmap::heatmap(), [18–20](#)
- plotMetric, [3](#), [17](#)
- plotOneMetric, [19](#)
- print.CNVMetric, [20](#)
- print.default, [21](#)
- validatecalculateLog2ratioMetricParameters, [21](#)
- validateCalculateOverlapMetricParameters, [22](#)