

Package ‘MicrobiomeProfiler’

May 9, 2023

Title An R/shiny package for microbiome functional enrichment analysis

Version 1.6.0

Description

This is an R/shiny package to perform functional enrichment analysis for microbiome data. This package was based on clusterProfiler. Moreover, MicrobiomeProfiler support KEGG enrichment analysis, COG enrichment analysis, Microbe-Disease association enrichment analysis, Metabo-Pathway analysis.

License GPL-2

URL <https://github.com/YuLab-SMU/MicrobiomeProfiler/>

BugReports <https://github.com/YuLab-SMU/MicrobiomeProfiler/issues>

Imports clusterProfiler (>= 4.5.2), config, DT, enrichplot, golem, gson, methods, magrittr, shiny (>= 1.6.0), shinyWidgets, shinycustomloader, htmltools, ggplot2, graphics, stats, utils

Encoding UTF-8

biocViews Microbiome, Software, Visualization,KEGG

RoxygenNote 7.2.3

Depends R (>= 4.2.0)

Suggests rmarkdown, knitr, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/MicrobiomeProfiler>

git_branch RELEASE_3_17

git_last_commit 31f72ea

git_last_commit_date 2023-04-25

Date/Publication 2023-05-09

Author Meijun Chen [aut, cre] (<<https://orcid.org/0000-0003-2486-8106>>),
Guangchuang Yu [aut, ths] (<<https://orcid.org/0000-0002-6485-8781>>)

Maintainer Meijun Chen <mjchen1996@outlook.com>

R topics documented:

MicrobiomeProfiler-package	2
enrichCOG	2
enrichHMDB	3
enrichKO	4
enrichMBKEGG	5
enrichMDA	6
enrichSMPDB	7
gson_cpd	8
gson_KO	8
microbiota_taxlist	8
Psoriasis_data	9
Rat_data	9
run_MicrobiomeProfiler	10
Index	11

MicrobiomeProfiler-package	<i>Functional enrichment analysis for microbiome data</i>
----------------------------	---

Description

The package implements an shiny application for functional enrichment analysis and visualization of microbiome studies.

enrichCOG	<i>COG enrichment analysis for microbiome data</i>
-----------	--

Description

COG enrichment analysis for microbiome data

Usage

```
enrichCOG(  
  gene,  
  dtype = "category",  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2  
)
```

Arguments

gene	a vector of COG ids.
dtype	one of "category", "pathway"
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
universe	universe background genes. If missing, use the all COGs.
minGSSize	minimal size of genes annotated by KEGG term for testing.
maxGSSize	maximal size of genes annotated for testing.
qvalueCutoff	qvalue cutoff on enrichment tests to report.

Value

A `enrichResult` instance.

Examples

```
data(Psoriasis_data)
cog <- enrichCOG(Psoriasis_data, dtype="category")
```

`enrichHMDB`*Metabolism enrichment analysis for microbiome data*

Description

Metabolism enrichment analysis for microbiome data

Usage

```
enrichHMDB(  
  metabo_list,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2  
)
```

Arguments

metabo_list	a vector of metabolites in HMDB.ID
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
universe	universe background genes. If missing, use HMDB db.
minGSSize	minimal size of genes annotated by KEGG term for testing.
maxGSSize	maximal size of genes annotated for testing.
qvalueCutoff	qvalue cutoff on enrichment tests to report.

Value

A enrichResult instance.

Examples

```
x1 <- c("HMDB00000001", "HMDB00000005", "HMDB00000008")
x2 <- enrichHMDB(x1)
```

enrichKO	<i>KO enrichment for microbiome data</i>
----------	--

Description

KO enrichment for microbiome data

Usage

```
enrichKO(
  gene,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2
)
```

Arguments

gene	a vector of K gene id (e.g. K00001).
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
universe	universe background genes. If missing, use all K genes.
minGSSize	minimal size of genes annotated by KEGG term for testing.
maxGSSize	maximal size of genes annotated for testing.
qvalueCutoff	qvalue cutoff on enrichment tests to report.

Value

A `enrichResult` instance.

Examples

```
data(Rat_data)
ko <- enrichKO(Rat_data)
head(ko)
```

`enrichMBKEGG`*Metabolism enrichment analysis for microbiome data*

Description

Metabolism enrichment analysis for microbiome data

Usage

```
enrichMBKEGG(
  metabo_list,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2
)
```

Arguments

<code>metabo_list</code>	a vector of metabolites in KEGG.ID
<code>pvalueCutoff</code>	adjusted pvalue cutoff on enrichment tests to report.
<code>pAdjustMethod</code>	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
<code>universe</code>	universe background genes. If missing, use KEGG as default.
<code>minGSSize</code>	minimal size of genes annotated by KEGG term for testing.
<code>maxGSSize</code>	maximal size of genes annotated for testing.
<code>qvalueCutoff</code>	qvalue cutoff on enrichment tests to report.

Value

A `enrichResult` instance.

Examples

```
mblist3 <- c("C00019", "C00020", "C00022")
mb3 <- enrichMBKEGG(mblist3)
head(mb3)
```

enrichMDA

Microbe-Disease associations enrichment analysis

Description

Microbe-Disease associations enrichment analysis

Usage

```
enrichMDA(
  microbe_list,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2
)
```

Arguments

microbe_list	a vector of microbe ncbi tax ids.
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
universe	universe background genes. If missing, use disbiome as default.
minGSSize	minimal size of genes annotated by KEGG term for testing.
maxGSSize	maximal size of genes annotated for testing.
qvalueCutoff	qvalue cutoff on enrichment tests to report.

Value

A enrichResult instance.

Examples

```
data(microbiota_taxlist)
mda <- enrichMDA(microbiota_taxlist)
head(mda)
```

enrichSMPDB*Metabolism enrichment analysis for microbiome data*

Description

Metabolism enrichment analysis for microbiome data

Usage

```
enrichSMPDB(  
  metabo_list,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  universe,  
  minGSSize = 10,  
  maxGSSize = 500,  
  qvalueCutoff = 0.2  
)
```

Arguments

metabo_list	a vector of metabolites in smpdb Metabolite.ID
pvalueCutoff	adjusted pvalue cutoff on enrichment tests to report.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
universe	universe background genes. If missing, use SMPDB db.
minGSSize	minimal size of genes annotated by KEGG term for testing.
maxGSSize	maximal size of genes annotated for testing.
qvalueCutoff	qvalue cutoff on enrichment tests to report.

Value

A `enrichResult` instance.

Examples

```
smp <- enrichSMPDB(c("PW_C000164", "PW_C000078", "PW_C000040"))  
head(smp)
```

`gson_cpd`*gson_cpd*

Description

download compound annotation of the latest version of KEGG pathway and stored in a 'GSON' object

Usage

```
gson_cpd()
```

Value

a 'GSON' object

`gson_KO`*gson_KO*

Description

download KO annotation of the latest version of KEGG pathway and stored in a 'GSON' object

Usage

```
gson_KO()
```

Value

a 'GSON' object

`microbiota_taxlist`*Example data: a vector of 54 bacterial genera tested for significantly between T2D metformin samples*

Description

This example data was reported on Forslund K,et al.2016 (doi: 10.1038/nature15766) and used for Microbe-Disease Association analysis.

Format

a vector with 54 genera tax ids

References

<https://www.nature.com/articles/nature15766>

Examples

```
data(microbiota_taxlist)
```

Psoriasis_data	<i>Example data: a vector of 134 significantly different functional COGs between Psoriasis patients and controls</i>
----------------	--

Description

This example data was reported on Xiao S,et al.2021 (doi:10.3389/fcimb.2021.605825) and used for COG enrichment analysis.

Format

a vector with 134 COGs

Value

<https://www.frontiersin.org/articles/10.3389/fcimb.2021.605825/full>

Examples

```
data(Psoriasis_data)
```

Rat_data	<i>Example data: a vector of 91 KEGG Orthologies (KOs) showing significant associations with weaning weight</i>
----------	---

Description

This example data was reported on Fang S,et al.2019 (doi: 10.1111/1751-7915.13485) and used for KEGG enrichment analysis.

Format

a vector with 91 KEGG Orthologies (KOs)

References

<https://sfamjournals.onlinelibrary.wiley.com/doi/10.1111/1751-7915.13485>

Examples

```
data(Rat_data)
```

run_MicrobiomeProfiler

Run the Shiny Application

Description

Run the Shiny Application

Usage

```
run_MicrobiomeProfiler(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

onStart	A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global.R file can be used for this purpose.
options	Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app.
enableBookmarking	Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app.
uiPattern	A regular expression that will be applied to each GET request to determine whether the ui should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
...	arguments to pass to golem_opts. See <code>'?golem::get_golem_options'</code> for more details.

Value

Shiny application object.

Examples

```
if (interactive()) {run_MicrobiomeProfiler()}
```

Index

* **data**

- microbiota_taxlist, [8](#)
- Psoriasis_data, [9](#)
- Rat_data, [9](#)

enableBookmarking(), [10](#)

enrichCOG, [2](#)

enrichHMDB, [3](#)

enrichKO, [4](#)

enrichMBKEGG, [5](#)

enrichMDA, [6](#)

enrichSMPDB, [7](#)

gson_cpd, [8](#)

gson_KO, [8](#)

MicrobiomeProfiler

(MicrobiomeProfiler-package), [2](#)

MicrobiomeProfiler-package, [2](#)

microbiota_data (microbiota_taxlist), [8](#)

microbiota_taxlist, [8](#)

Psoriasis_data, [9](#)

Rat_data, [9](#)

run_MicrobiomeProfiler, [10](#)