

# Package ‘ProtGenerics’

May 30, 2023

**Title** Generic infrastructure for Bioconductor mass spectrometry packages

**Description** S4 generic functions and classes needed by Bioconductor proteomics packages.

**Version** 1.32.0

**Author** Laurent Gatto <[laurent.gatto@uclouvain.be](mailto:laurent.gatto@uclouvain.be)>,  
Johannes Rainer <[johannes.rainer@eurac.edu](mailto:johannes.rainer@eurac.edu)>

**Maintainer** Laurent Gatto <[laurent.gatto@uclouvain.be](mailto:laurent.gatto@uclouvain.be)>

**biocViews** Infrastructure, Proteomics, MassSpectrometry

**URL** <https://github.com/RforMassSpectrometry/ProtGenerics>

**Depends** methods

**Suggests** testthat

**License** Artistic-2.0

**NeedsCompilation** no

**RoxygenNote** 7.2.1

**git\_url** <https://git.bioconductor.org/packages/ProtGenerics>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** 30c6458

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-05-30

## R topics documented:

Param	2
ProcessingStep	2
ProtGenerics	3

## Index

6

---

Param	<i>Generic parameter class</i>
-------	--------------------------------

---

## Description

The ‘Param’ class is a virtual class which can be used as \*base\* class from which \*parameter\* classes can inherit.

The methods implemented for the ‘Param’ class are:

- ‘as.list’: coerces the ‘Param’ class to a ‘list’ with list elements representing the object’s slot values, names the slot names. \*Hidden\* slots (i.e. those with a name starting with ‘.’) are not returned. In addition, a ‘Param’ class can be coerced to a ‘list’ using ‘as(object, "list")’.
- ‘show’: prints the content of the ‘Param’ object (i.e. the individual slots and their value).

## Usage

```
## S4 method for signature 'Param'
as.list(x, ...)

## S4 method for signature 'Param'
show(object)
```

## Arguments

x	‘Param’ object.
...	ignored.
object	‘Param’ object.

## Author(s)

Johannes Rainer

---

ProcessingStep	<i>Processing step</i>
----------------	------------------------

---

## Description

Class containing the function and arguments to be applied in a lazy-execution framework.

Objects of this class are created using the `ProcessingStep()` function. The processing step is executed with the `executeProcessingStep()` function.

**Usage**

```
ProcessingStep(FUN = character(), ARGS = list())  
  
## S4 method for signature 'ProcessingStep'  
show(object)  
  
executeProcessingStep(object, ...)
```

**Arguments**

FUN	function or character representing a function name.
ARGS	list of arguments to be passed along to FUN.
object	ProcessingStep object.
...	optional additional arguments to be passed along.

**Details**

This object contains all relevant information of a data analysis processing step, i.e. the function and all of its arguments to be applied to the data. This object is mainly used to record possible processing steps of a Spectra or OnDiskMSnExp object (from the Spectra and MSnbase packages, respectively).

**Value**

The ProcessingStep function returns and object of type ProcessingStep.

**Author(s)**

Johannes Rainer

**Examples**

```
## Create a simple processing step object  
ps <- ProcessingStep(sum)  
  
executeProcessingStep(ps, 1:10)
```

**Description**

These generic functions provide basic interfaces to operations on and data access to proteomics and mass spectrometry infrastructure in the Bioconductor project.

For the details, please consult the respective methods' manual pages.

## Usage

```
psms(object, ...)
peaks(object, ...)
modifications(object, ...)
database(object, ...)
rtime(object, ...)
tic(object, ...)
spectra(object, ...)
intensity(object, ...)
mz(object, ...)
peptides(object, ...)
proteins(object, ...)
accessions(object, ...)
scans(object, ...)
mass(object, ...)
ions(object, ...)
chromatograms(object, ...)
chromatogram(object, ...)
isCentroided(object, ...)
writeMSData(object, file, ...)
## and many more
```

## Arguments

object	Object of class for which methods are defined.
file	for writeMSData
: the name of the file to which the data should be exported.	
...	Further arguments, possibly used by downstream methods.

## Details

### When should one define a generics?:

Generics are appropriate for functions that have *generic* names, i.e. names that occur in multiple circumstances, (with different input classes, most often defined in different packages) or, when (multiple) dispatching is better handled by the generics mechanism rather than the developer. The dispatching mechanism will then automatically call the appropriate method and save the user from explicitly calling package::method or the developer to handle the multiple input types cases. When no such conflict exists or is unlikely to happen (for example when the name of the function is specific to a package or domain, or for class slots accessors and replacement methods), the usage of a generic is arguably questionable, and in most of these cases, simple, straightforward functions would be perfectly valid.

### When to define a generic in ProtGenerics?:

ProtGenerics is not meant to be the central package for generics, nor should it stop developers from defining the generics they need. It is a means to centralise generics that are defined in different packages (for example mzR::psms and mzID::psms, or IRanges::score and mzR::score,

now `BioGenerics::score`) or generics that live in a rather big package (say `mzR`) on which one wouldn't want to depend just for the sake of that generics' definition.

The goal of `ProtGenerics` is to step in when namespace conflicts arise so as to facilitate inter-operability of packages. In case such conflict appears due to multiple generics, we would (1) add these same definitions in `ProtGenerics`, (2) remove the definitions from the packages they stem from, which then (3) only need to import `ProtGenerics`. This would be very minor/straightforward changes for the developers and would resolve issues when they arise.

More generics can be added on request by opening an issue or sending a pull request on:

<https://github.com/lgatto/ProtGenerics>

## Author(s)

Laurent Gatto

## See Also

- The `BiocGenerics` package for S4 generic functions needed by many Bioconductor packages.
- `showMethods` for displaying a summary of the methods defined for a given generic function.
- `selectMethod` for getting the definition of a specific method.
- `setGeneric` and `setMethod` for defining generics and methods.

## Examples

```
## List all the symbols defined in this package:  
ls('package:ProtGenerics')  
  
## Not run:  
## What methods exists for 'peaks'  
showMethods("peaks")  
  
## To look at one method in particular  
getMethod("peaks", "mzRpwiz")  
  
## End(Not run)
```

# Index

\* **methods**

- ProtGenerics, 3
- accessions (ProtGenerics), 3
- acquisitionNum (ProtGenerics), 3
- addProcessing (ProtGenerics), 3
- adjacencyMatrix (ProtGenerics), 3
- aggregateFeatures (ProtGenerics), 3
- alignRt (ProtGenerics), 3
- analyser (ProtGenerics), 3
- analyserDetails (ProtGenerics), 3
- analyzer (ProtGenerics), 3
- analyzerDetails (ProtGenerics), 3
- as.list,Param-method (Param), 2
- bin (ProtGenerics), 3
- calculateFragments (ProtGenerics), 3
- centroided (ProtGenerics), 3
- centroided<- (ProtGenerics), 3
- characterOrFunction-class
  - (ProcessingStep), 2
- chromatogram (ProtGenerics), 3
- chromatograms (ProtGenerics), 3
- collisionEnergy (ProtGenerics), 3
- collisionEnergy<- (ProtGenerics), 3
- combineFeatures (ProtGenerics), 3
- compareChromatograms (ProtGenerics), 3
- compareSpectra (ProtGenerics), 3
- compounds (ProtGenerics), 3
- database (ProtGenerics), 3
- dataOrigin (ProtGenerics), 3
- dataOrigin<- (ProtGenerics), 3
- dataStorage (ProtGenerics), 3
- dataStorage<- (ProtGenerics), 3
- detectorType (ProtGenerics), 3
- executeProcessingStep (ProcessingStep), 2
- expemail (ProtGenerics), 3
- exptitle (ProtGenerics), 3
- filterAcquisitionNum (ProtGenerics), 3
- filterDataOrigin (ProtGenerics), 3
- filterDataStorage (ProtGenerics), 3
- filterEmptySpectra (ProtGenerics), 3
- filterIntensity (ProtGenerics), 3
- filterIsolationWindow (ProtGenerics), 3
- filterMsLevel (ProtGenerics), 3
- filterMz (ProtGenerics), 3
- filterNA (ProtGenerics), 3
- filterPolarity (ProtGenerics), 3
- filterPrecursorCharge (ProtGenerics), 3
- filterPrecursorMz (ProtGenerics), 3
- filterPrecursorScan (ProtGenerics), 3
- filterProductMz (ProtGenerics), 3
- filterRt (ProtGenerics), 3
- impute (ProtGenerics), 3
- instrumentCustomisations
  - (ProtGenerics), 3
- instrumentManufacturer (ProtGenerics), 3
- instrumentModel (ProtGenerics), 3
- intensity (ProtGenerics), 3
- intensity<- (ProtGenerics), 3
- ionCount (ProtGenerics), 3
- ions (ProtGenerics), 3
- ionSource (ProtGenerics), 3
- ionSourceDetails (ProtGenerics), 3
- isCentroided (ProtGenerics), 3
- isolationWindowLowerMz (ProtGenerics), 3
- isolationWindowLowerMz<-
  - (ProtGenerics), 3
- isolationWindowTargetMz (ProtGenerics), 3
- isolationWindowTargetMz<-
  - (ProtGenerics), 3
- isolationWindowUpperMz (ProtGenerics), 3
- isolationWindowUpperMz<-
  - (ProtGenerics), 3

mass (ProtGenerics), 3  
modifications (ProtGenerics), 3  
msInfo (ProtGenerics), 3  
msLevel (ProtGenerics), 3  
msLevel<- (ProtGenerics), 3  
mz (ProtGenerics), 3  
mz<- (ProtGenerics), 3  
  
Param, 2  
Param-class (Param), 2  
peaks (ProtGenerics), 3  
peaks<- (ProtGenerics), 3  
peptides (ProtGenerics), 3  
polarity (ProtGenerics), 3  
polarity<- (ProtGenerics), 3  
precAcquisitionNum (ProtGenerics), 3  
precScanNum (ProtGenerics), 3  
precursorCharge (ProtGenerics), 3  
precursorCharge<- (ProtGenerics), 3  
precursorIntensity (ProtGenerics), 3  
precursorIntensity<- (ProtGenerics), 3  
precursorMz (ProtGenerics), 3  
precursorMz<- (ProtGenerics), 3  
processingData (ProtGenerics), 3  
processingData<- (ProtGenerics), 3  
ProcessingStep, 2  
ProcessingStep-class (ProcessingStep), 2  
productMz (ProtGenerics), 3  
productMz<- (ProtGenerics), 3  
proteins (ProtGenerics), 3  
ProtGenerics, 3  
ProtGenerics-package (ProtGenerics), 3  
psms (ProtGenerics), 3  
  
quantify (ProtGenerics), 3  
  
rtime (ProtGenerics), 3  
rtime<- (ProtGenerics), 3  
  
scanIndex (ProtGenerics), 3  
scans (ProtGenerics), 3  
selectMethod, 5  
setGeneric, 5  
setMethod, 5  
show, Param-method (Param), 2  
show, ProcessingStep-method  
(ProcessingStep), 2  
showMethods, 5  
smooth (ProtGenerics), 3  
smoothed (ProtGenerics), 3  
smoothed<- (ProtGenerics), 3  
spectra (ProtGenerics), 3  
spectra<- (ProtGenerics), 3  
spectraData (ProtGenerics), 3  
spectraData<- (ProtGenerics), 3  
spectraNames (ProtGenerics), 3  
spectraNames<- (ProtGenerics), 3  
spectrapply (ProtGenerics), 3  
spectraVariables (ProtGenerics), 3  
  
tic (ProtGenerics), 3  
tolerance (ProtGenerics), 3  
  
uniqueMsLevel (ProtGenerics), 3  
  
writeMSData (ProtGenerics), 3