

Package ‘hyperdraw’

June 4, 2023

Version 1.52.0

Depends R (>= 2.9.0)

Imports methods, grid, graph, hypergraph, Rgraphviz, stats4

SystemRequirements graphviz

Title Visualizing Hypergraphs

Author Paul Murrell

Maintainer Paul Murrell <p.murrell@auckland.ac.nz>

Description Functions for visualizing hypergraphs.

License GPL (>= 2)

Collate AllClasses.R affine.R draw.R graphBPH.R grid.R hypergraph.R
legacy.R node.R RagraphBPH.R

biocViews Visualization, GraphAndNetwork

git_url <https://git.bioconductor.org/packages/hyperdraw>

git_branch RELEASE_3_17

git_last_commit 861cb7b

git_last_commit_date 2023-04-25

Date/Publication 2023-06-04

R topics documented:

| | |
|----------------------------|---|
| graphBPH | 2 |
| graphBPH-class | 3 |
| graphLayout | 4 |
| RagraphBPH-class | 6 |

Index

8

`graphBPH`*Constructor for graphBPH objects*

Description

A convenience constructor for [graphBPH-class](#) objects. This is a generic function.

Usage

```
graphBPH(graph, edgeNodePattern, ...)
```

Arguments

| | |
|------------------------------|---|
| <code>graph</code> | Some form of graph that is to be converted into a graphBPH object. |
| <code>edgeNodePattern</code> | A regular expression used to distinguish between normal nodes and edge nodes. |
| <code>...</code> | Potential arguments to other methods. |

Value

An object of class [graphBPH-class](#)

Methods

graphBPH `signature(graph = "graphNEL", edgeNodePattern = "character")`: create a graphBPH object from a (directed) graphNEL object.

graphBPH `signature(graph = "Hypergraph", edgeNodePattern = "missing")`: create a graphBPH object from a Hypergraph object (where all Hyperedges are DirectedHyperedges).

Author(s)

Paul Murrell

References

Falcon, S. and Gentleman, R. **hypergraph**: A package providing hypergraph data structures.
 Gentleman, R. and Whalen, E. and Huber, W. and Falcon, S. **graph**: A package to handle graph data structures.

See Also

[graphBPH-class](#)

| | |
|----------------|-------------------------|
| graphBPH-class | <i>Class "graphBPH"</i> |
|----------------|-------------------------|

Description

A bipartite representation of a hypergraph. The purpose of this class is to support visualization of the hypergraph; it is not intended for analysis or manipulation of the hypergraph.

Objects from the Class

Objects can be created by calls of the form `new("graphBPH", graph, edgeNodePattern, ...)`. There is also a convenience function `graphBPH()`.

A `graphBPH` object consists of a `graphNEL` object, which must obey some strict rules:

- nodes in the graph are divided into two sets: normal nodes and edge-nodes,
- all edges in the graph must connect a normal node to an edge node,
- the graph must be a directed graph.

The `edgeNodePattern` is a regular expression that is used to define the set of edge-nodes.

Slots

`graph`: Object of class `graphNEL`. This graph must obey the constraints described above.

`edgeNodePattern`: Object of class `character`. The regular expression used to define edge-nodes.

`nodes`: Object of class `character`. Records which nodes in the graph are normal nodes.

`edgeNodes`: Object of class `character`. Records which nodes in the graph are edge-nodes.

`edgeNodeIO`: Object of class `list`. Records information about which edges enter and exit each edge-node.

Methods

plot `signature(x = "graphBPH", y = "ANY")`: draw a representation of the hypergraph where edges between normal nodes in the graph pass through an intermediate edge-node in a nice smooth curve.

graphLayout `signature(graph = "graphBPH", layoutType = "missing")`: convert the `graphBPH` object to a `RgraphBPH` object (using a default layout method).

graphLayout `signature(graph = "graphBPH", layoutType = "character")`: convert the `graphBPH` object to a `RgraphBPH` object (using the specified layout method).

Author(s)

Paul Murrell

References

Gansner, E.R. and and North, S.C. (1999) An open graph visualization system and its applications to software engineering, *Software - Practice and Experience*, 30:1203–1233.

Gentleman, R. and Whalen, E. and Huber, W. and Falcon, S. **graph**: A package to handle graph data structures.

Gentry, J. and Long, L. and Gentleman, R. and Falcon, S. and Hahne, F. and Sarkar, D. and Hansen, K. **Rgraphviz**: Provides plotting capabilities for R graph objects.

See Also

[agopen](#), [graphLayout](#) and [graphNEL](#) [RgraphBPH](#)

Examples

```
nodes <- c(LETTERS[1:5], paste("R", 1:3, sep=""))
testgnel <- new("graphNEL",
  nodes=nodes,
  edgeL=list(
    A=list(edges=c("R1", "R2")),
    B=list(edges="R2"),
    C=list(),
    D=list(edges="R3"),
    E=list(),
    R1=list(edges="B"),
    R2=list(edges=c("C", "D")),
    R3=list(edges="E")),
  edgemode="directed")
testbph <- graphBPH(testgnel, "R")
plot(testbph)

# A Hypergraph equivalent
require(hypergraph)
dh1 <- DirectedHyperedge("A", "B", "R1")
dh2 <- DirectedHyperedge(c("A", "B"), c("C", "D"), "R2")
dh3 <- DirectedHyperedge("D", "E", "R3")
hg <- Hypergraph(LETTERS[1:5], list(dh1, dh2, dh3))
plot(graphBPH(hg))
```

graphLayout

Layout a graph.

Description

This function is designed to layout a graph using the **Rgraphviz** package. The **hyperdraw** package makes this a generic function with a method for graphBPH objects. The function of the same name in the **Rgraphviz** package is used as a method for Rgraph objects.

Usage

```
graphLayout(graph, layoutType, ...)
```

Arguments

| | |
|------------|--|
| graph | An graphBPH object, which is to be laid out. |
| layoutType | The layout method (e.g., dot or neato). |
| ... | These arguments will be passed to the agopen() function. |

Value

An RgraphBPH object.

Author(s)

Paul Murrell

References

Gansner, E.R. and North, S.C. (1999) An open graph visualization system and its applications to software engineering, *Software - Practice and Experience*, 30:1203–1233.

Gentry, J. and Long, L. and Gentleman, R. and Falcon, S. and Hahne, F. and Sarkar, D. and Hansen, K. **Rgraphviz**: Provides plotting capabilities for R graph objects.

See Also

[agopen](#) and [GraphvizLayouts](#)

Examples

```
nodes <- c(LETTERS[1:5], paste("R", 1:3, sep=""))
testgnel <- new("graphNEL",
                 nodes=nodes,
                 edgeL=list(
                   A=list(edges=c("R1", "R2")),
                   B=list(edges="R2"),
                   C=list(),
                   D=list(edges="R3"),
                   E=list(),
                   R1=list(edges="B"),
                   R2=list(edges=c("C", "D")),
                   R3=list(edges="E")),
                 edgeMode="directed")
testbph <- new("graphBPH", testgnel, "R")
testrabph <- graphLayout(testbph)
```

| | |
|-----------------|--------------------------|
| RgraphBPH-class | <i>Class "RgraphBPH"</i> |
|-----------------|--------------------------|

Description

The purpose of this class is to represent a laid out version of a graphBPH object. The laying out is performed by the **Rgraphviz** package. This is an intermediate step in the process of drawing a graphBPH object.

Objects from the Class

Objects of this class should be created via the `graphLayout()` function.

Slots

graph: Object of class `Rgraph`. The laid out graph.
allNodes: Object of class `character`. The names of all nodes in the graph.
nodes: Object of class `character`. Records normal nodes in the graph.
edgeNodes: Object of class `character`. Records edge-nodes in the graph.
edgeNodeIO: Object of class `list`. Records which edges enter and exit each edge-node.

Methods

plot `signature(x = "RgraphBPH", y = "ANY")`: draw a representation of the hypergraph where edges between normal nodes in the graph pass through an intermediate edge-node in a nice smooth curve.
edgeDataDefaults<- `signature(self = "RgraphBPH", attr = "character", value = "ANY")`: set the default drawing attributes for all edges.
edgeData<- `signature(self = "RgraphBPH", from = "character", to = "character", attr = "character", value = "ANY")`: set a specific drawing attribute for one or more edges.
nodeDataDefaults<- `signature(self = "RgraphBPH", attr = "character", value = "ANY")`: set the default drawing attributes for all nodes.
nodeData<- `signature(self = "RgraphBPH", n = "character", attr = "character", value = "ANY")`: set a specific attribute for one or more nodes.
graphDataDefaults<- `signature(self = "RgraphBPH", attr = "character", value = "ANY")`: set the default drawing attributes for the graph.
graphData<- `signature(self = "RgraphBPH", n = "character", attr = "character", value = "ANY")`: set a specific attribute for the graph.

Author(s)

Paul Murrell

See Also

[graphLayout](#), [graphBPH](#), and [Ragraph](#)

Examples

```
nodes <- c(LETTERS[1:5], paste("R", 1:3, sep=""))
testgnel <- new("graphNEL",
                 nodes=nodes,
                 edgeL=list(
                   A=list(edges=c("R1", "R2")),
                   B=list(edges="R2"),
                   C=list(),
                   D=list(edges="R3"),
                   E=list(),
                   R1=list(edges="B"),
                   R2=list(edges=c("C", "D")),
                   R3=list(edges="E")),
                 edgemode="directed")
testbph <- graphBPH(testgnel, "^R")
testrabph <- graphLayout(testbph)
edgeDataDefaults(testrabph, "lwd") <- 1
edgeData(testrabph, c("A", "R1"), c("R1", "B"), "lwd") <- c("3", 5)
edgeDataDefaults(testrabph, "color") <- "black"
edgeData(testrabph, c("A", "R1"), c("R1", "B"), "color") <- "red"
nodeDataDefaults(testrabph, "margin") <- 'unit(2, "mm")'
nodeDataDefaults(testrabph, "shape") <- "circle"
plot(testrabph)
graphDataDefaults(testrabph, "arrowLoc") <- "middle"
graphData(testrabph, "arrowLoc") <- "end"
plot(testrabph)
graphData(testrabph, "arrowLoc") <- "none"
plot(testrabph)
```

Index

* **classes**
graphBPH, 2
graphBPH-class, 3
RagraphBPH-class, 6

* **dplot**
graphLayout, 4

agopen, 4, 5

edgeData<-, RagraphBPH, character, character, character, ANY-method
(RagraphBPH-class), 6

edgeDataDefaults<-, RagraphBPH, character, ANY-method
(RagraphBPH-class), 6

graphBPH, 2, 7
graphBPH, graphNEL, character-method
(graphBPH), 2

graphBPH, Hypergraph, missing-method
(graphBPH), 2

graphBPH-class, 3

graphData<-, RagraphBPH, character, ANY-method
(RagraphBPH-class), 6

graphDataDefaults<-, RagraphBPH, character, ANY-method
(RagraphBPH-class), 6

graphLayout, 4, 4, 7
graphLayout, graphBPH, character-method
(graphBPH-class), 3

graphLayout, graphBPH, missing-method
(graphBPH-class), 3

graphNEL, 4
GraphvizLayouts, 5

nodeData<-, RagraphBPH, character, character, ANY-method
(RagraphBPH-class), 6

nodeDataDefaults<-, RagraphBPH, character, ANY-method
(RagraphBPH-class), 6

plot, graphBPH, ANY-method
(graphBPH-class), 3

plot, RagraphBPH, ANY-method
(RagraphBPH-class), 6