

# Package ‘MSMB’

June 1, 2023

**Title** Data sets for the book 'Modern Statistics for Biology'

**Version** 1.18.0

**Author** Wolfgang Huber, Andrzej Oles, Mike Smith

**Description** Data sets for the book 'Modern Statistics for Modern Biology',  
S.P. Holmes and W. Huber.

**Maintainer** Wolfgang Huber <wolfgang.huber@embl.org>

**License** LGPL

**Depends** R (>= 3.5), tibble

**Suggests** knitr, BiocStyle

**VignetteBuilder** knitr

**biocViews** ExperimentData

**git\_url** <https://git.bioconductor.org/packages/MSMB>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** d139b53

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-06-01

## R topics documented:

|                         |          |
|-------------------------|----------|
| brcalymphnode . . . . . | 2        |
| ukraine_dists . . . . . | 2        |
| <b>Index</b>            | <b>4</b> |

---

|               |                                                                                                     |
|---------------|-----------------------------------------------------------------------------------------------------|
| brcalymphnode | <i>Coordinates and cell types in a histopathology slide of a breast cancer patient's lymph node</i> |
|---------------|-----------------------------------------------------------------------------------------------------|

---

### Description

Coordinates and cell types in a histopathology slide of a breast cancer patient's lymph node.

### Usage

```
data("brcalymphnode")
```

### Format

A data.frame.

### Details

This dataset is used as an example in the 'Image data' chapter. See there for more details about it.

### Examples

```
data("brcalymphnode")
plot(x = brcalymphnode$x, y = brcalymphnode$y, pch=".", col = brcalymphnode$class)
```

---

|               |                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------|
| ukraine_dists | <i>Coordinates of and pairwise distances between hero cities and oblast capitals in Ukraine</i> |
|---------------|-------------------------------------------------------------------------------------------------|

---

### Description

This dataset is used as an example in the 'Multivariate methods for heterogeneous data' chapter.

### Usage

```
data("ukraine_dists")
data("ukraine_coords")
```

### Format

ukraine\_dists is an object of S3 class dist. ukraine\_coords is a tibble.

### Details

The two datasets were constructed using the R code in the file 'ukraine-dists.R' in the 'scripts' directory of this package. Briefly, the city and place names are hardcoded in the script, coordinates were queried from OpenStreetMap using the geo function in the **tidygeocoder**, and pairwise geodesic distances computed using the geodist function from the eponymous package.

**Examples**

```
data("ukraine_coords")
plot(x = ukraine_coords$lon, y = ukraine_coords$lat, pch = 16, cex = 0.7, col = "#0057b7", asp = 1 / cos(pi / 180 *
text(x = ukraine_coords$lon, y = ukraine_coords$lat, labels = ukraine_coords$city, adj = c(0.5, -0.2))
```

# Index

## \* **datasets**

brcalymphnode, [2](#)

ukraine\_dists, [2](#)

brcalymphnode, [2](#)

ukraine\_coords(ukraine\_dists), [2](#)

ukraine\_dists, [2](#)