

# Package ‘geneLenDataBase’

June 6, 2023

**Version** 1.36.0

**Date** 2019/04/26

**Title** Lengths of mRNA transcripts for a number of genomes

**Author** Matthew Young

**Maintainer**

Matthew Young <my4@sanger.ac.uk>, Nadia Davidson <nadia.davidson@mcri.edu.au>

**Depends** R (>= 2.11.0)

**Imports** utils, rtracklayer, GenomicFeatures (>= 1.3.15)

**LazyLoad** yes

**Description** Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser

**biocViews** ExperimentData, Genome

**License** LGPL (>= 2)

**NeedsCompilation** no

**git\_url** <https://git.bioconductor.org/packages/geneLenDataBase>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** e8f37dd

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-06-06

## R topics documented:

anoCar1.ensGene.LENGTH . . . . .	9
anoCar1.genscan.LENGTH . . . . .	9
anoCar1.xenoRefGene.LENGTH . . . . .	10
anoGam1.ensGene.LENGTH . . . . .	10
anoGam1.geneid.LENGTH . . . . .	11
anoGam1.genscan.LENGTH . . . . .	11
apiMel1.genscan.LENGTH . . . . .	12
apiMel2.ensGene.LENGTH . . . . .	12

apiMel2.geneid.LENGTH	13
apiMel2.genscan.LENGTH	13
aplCal1.xenoRefGene.LENGTH	14
bosTau2.geneid.LENGTH	14
bosTau2.geneSymbol.LENGTH	15
bosTau2.genscan.LENGTH	15
bosTau2.refGene.LENGTH	16
bosTau2.sgpGene.LENGTH	16
bosTau3.ensGene.LENGTH	17
bosTau3.geneid.LENGTH	17
bosTau3.geneSymbol.LENGTH	18
bosTau3.genscan.LENGTH	18
bosTau3.refGene.LENGTH	19
bosTau3.sgpGene.LENGTH	19
bosTau4.ensGene.LENGTH	20
bosTau4.geneSymbol.LENGTH	20
bosTau4.genscan.LENGTH	21
bosTau4.nscanGene.LENGTH	21
bosTau4.refGene.LENGTH	22
braFlo1.xenoRefGene.LENGTH	22
caeJap1.xenoRefGene.LENGTH	23
caePb1.xenoRefGene.LENGTH	23
caePb2.xenoRefGene.LENGTH	24
caeRem2.xenoRefGene.LENGTH	24
caeRem3.xenoRefGene.LENGTH	25
calJac1.genscan.LENGTH	25
calJac1.nscanGene.LENGTH	26
calJac1.xenoRefGene.LENGTH	26
canFam1.ensGene.LENGTH	27
canFam1.geneSymbol.LENGTH	27
canFam1.genscan.LENGTH	28
canFam1.nscanGene.LENGTH	28
canFam1.refGene.LENGTH	29
canFam1.xenoRefGene.LENGTH	29
canFam2.ensGene.LENGTH	30
canFam2.geneSymbol.LENGTH	30
canFam2.genscan.LENGTH	31
canFam2.nscanGene.LENGTH	31
canFam2.refGene.LENGTH	32
canFam2.xenoRefGene.LENGTH	32
cavPor3.ensGene.LENGTH	33
cavPor3.genscan.LENGTH	33
cavPor3.nscanGene.LENGTH	34
cavPor3.xenoRefGene.LENGTH	34
cb1.xenoRefGene.LENGTH	35
cb3.xenoRefGene.LENGTH	35
ce2.geneid.LENGTH	36
ce2.geneSymbol.LENGTH	36

ce2.refGene.LENGTH . . . . .	37
ce4.geneSymbol.LENGTH . . . . .	37
ce4.refGene.LENGTH . . . . .	38
ce4.xenoRefGene.LENGTH . . . . .	38
ce6.ensGene.LENGTH . . . . .	39
ce6.geneSymbol.LENGTH . . . . .	39
ce6.refGene.LENGTH . . . . .	40
ce6.xenoRefGene.LENGTH . . . . .	40
ci1.geneSymbol.LENGTH . . . . .	41
ci1.refGene.LENGTH . . . . .	41
ci1.xenoRefGene.LENGTH . . . . .	42
ci2.ensGene.LENGTH . . . . .	42
ci2.geneSymbol.LENGTH . . . . .	43
ci2.refGene.LENGTH . . . . .	43
ci2.xenoRefGene.LENGTH . . . . .	44
danRer3.ensGene.LENGTH . . . . .	44
danRer3.geneSymbol.LENGTH . . . . .	45
danRer3.refGene.LENGTH . . . . .	45
danRer4.ensGene.LENGTH . . . . .	46
danRer4.geneSymbol.LENGTH . . . . .	46
danRer4.genscan.LENGTH . . . . .	47
danRer4.nscanGene.LENGTH . . . . .	47
danRer4.refGene.LENGTH . . . . .	48
danRer5.ensGene.LENGTH . . . . .	48
danRer5.geneSymbol.LENGTH . . . . .	49
danRer5.refGene.LENGTH . . . . .	49
danRer5.vegaGene.LENGTH . . . . .	50
danRer5.vegaPseudoGene.LENGTH . . . . .	50
danRer6.ensGene.LENGTH . . . . .	51
danRer6.geneSymbol.LENGTH . . . . .	51
danRer6.refGene.LENGTH . . . . .	52
danRer6.xenoRefGene.LENGTH . . . . .	52
dm1.geneSymbol.LENGTH . . . . .	53
dm1.genscan.LENGTH . . . . .	53
dm1.refGene.LENGTH . . . . .	54
dm2.geneid.LENGTH . . . . .	54
dm2.geneSymbol.LENGTH . . . . .	55
dm2.genscan.LENGTH . . . . .	55
dm2.nscanGene.LENGTH . . . . .	56
dm2.refGene.LENGTH . . . . .	56
dm3.geneSymbol.LENGTH . . . . .	57
dm3.nscanPasaGene.LENGTH . . . . .	57
dm3.refGene.LENGTH . . . . .	58
dp2.genscan.LENGTH . . . . .	58
dp2.xenoRefGene.LENGTH . . . . .	59
dp3.geneid.LENGTH . . . . .	59
dp3.genscan.LENGTH . . . . .	60
dp3.xenoRefGene.LENGTH . . . . .	60

droAna1.geneid.LENGTH . . . . .	61
droAna1.genscan.LENGTH . . . . .	61
droAna1.xenoRefGene.LENGTH . . . . .	62
droAna2.genscan.LENGTH . . . . .	62
droAna2.xenoRefGene.LENGTH . . . . .	63
droEre1.genscan.LENGTH . . . . .	63
droEre1.xenoRefGene.LENGTH . . . . .	64
droGri1.genscan.LENGTH . . . . .	64
droGri1.xenoRefGene.LENGTH . . . . .	65
droMoj1.geneid.LENGTH . . . . .	65
droMoj1.genscan.LENGTH . . . . .	66
droMoj1.xenoRefGene.LENGTH . . . . .	66
droMoj2.genscan.LENGTH . . . . .	67
droMoj2.xenoRefGene.LENGTH . . . . .	67
droPer1.genscan.LENGTH . . . . .	68
droPer1.xenoRefGene.LENGTH . . . . .	68
droSec1.genscan.LENGTH . . . . .	69
droSec1.xenoRefGene.LENGTH . . . . .	69
droSim1.geneid.LENGTH . . . . .	70
droSim1.genscan.LENGTH . . . . .	70
droSim1.xenoRefGene.LENGTH . . . . .	71
droVir1.geneid.LENGTH . . . . .	71
droVir1.genscan.LENGTH . . . . .	72
droVir1.xenoRefGene.LENGTH . . . . .	72
droVir2.genscan.LENGTH . . . . .	73
droVir2.xenoRefGene.LENGTH . . . . .	73
droYak1.geneid.LENGTH . . . . .	74
droYak1.genscan.LENGTH . . . . .	74
droYak1.xenoRefGene.LENGTH . . . . .	75
droYak2.genscan.LENGTH . . . . .	75
droYak2.xenoRefGene.LENGTH . . . . .	76
equCab1.geneid.LENGTH . . . . .	76
equCab1.geneSymbol.LENGTH . . . . .	77
equCab1.nscanGene.LENGTH . . . . .	77
equCab1.refGene.LENGTH . . . . .	78
equCab1.sgpGene.LENGTH . . . . .	78
equCab2.ensGene.LENGTH . . . . .	79
equCab2.geneSymbol.LENGTH . . . . .	79
equCab2.nscanGene.LENGTH . . . . .	80
equCab2.refGene.LENGTH . . . . .	80
equCab2.xenoRefGene.LENGTH . . . . .	81
felCat3.ensGene.LENGTH . . . . .	81
felCat3.geneid.LENGTH . . . . .	82
felCat3.geneSymbol.LENGTH . . . . .	82
felCat3.genscan.LENGTH . . . . .	83
felCat3.nscanGene.LENGTH . . . . .	83
felCat3.refGene.LENGTH . . . . .	84
felCat3.sgpGene.LENGTH . . . . .	84

felCat3.xenoRefGene.LENGTH . . . . .	85
fr1.ensGene.LENGTH . . . . .	85
fr1.genscan.LENGTH . . . . .	86
fr2.ensGene.LENGTH . . . . .	86
galGal2.ensGene.LENGTH . . . . .	87
galGal2.geneid.LENGTH . . . . .	87
galGal2.geneSymbol.LENGTH . . . . .	88
galGal2.genscan.LENGTH . . . . .	88
galGal2.refGene.LENGTH . . . . .	89
galGal2.sgpGene.LENGTH . . . . .	89
galGal3.ensGene.LENGTH . . . . .	90
galGal3.geneSymbol.LENGTH . . . . .	90
galGal3.genscan.LENGTH . . . . .	91
galGal3.nscanGene.LENGTH . . . . .	91
galGal3.refGene.LENGTH . . . . .	92
galGal3.xenoRefGene.LENGTH . . . . .	92
gasAcu1.ensGene.LENGTH . . . . .	93
gasAcu1.nscanGene.LENGTH . . . . .	93
hg16.acembly.LENGTH . . . . .	94
hg16.ensGene.LENGTH . . . . .	94
hg16.exoniphy.LENGTH . . . . .	95
hg16.geneid.LENGTH . . . . .	95
hg16.geneSymbol.LENGTH . . . . .	96
hg16.genscan.LENGTH . . . . .	96
hg16.knownGene.LENGTH . . . . .	97
hg16.refGene.LENGTH . . . . .	97
hg16.sgpGene.LENGTH . . . . .	98
hg17.acembly.LENGTH . . . . .	98
hg17.acescan.LENGTH . . . . .	99
hg17.ccdsGene.LENGTH . . . . .	99
hg17.ensGene.LENGTH . . . . .	100
hg17.exoniphy.LENGTH . . . . .	100
hg17.geneid.LENGTH . . . . .	101
hg17.geneSymbol.LENGTH . . . . .	101
hg17.genscan.LENGTH . . . . .	102
hg17.knownGene.LENGTH . . . . .	102
hg17.refGene.LENGTH . . . . .	103
hg17.sgpGene.LENGTH . . . . .	103
hg17.vegaGene.LENGTH . . . . .	104
hg17.vegaPseudoGene.LENGTH . . . . .	104
hg17.xenoRefGene.LENGTH . . . . .	105
hg18.acembly.LENGTH . . . . .	105
hg18.acescan.LENGTH . . . . .	106
hg18.ccdsGene.LENGTH . . . . .	106
hg18.ensGene.LENGTH . . . . .	107
hg18.exoniphy.LENGTH . . . . .	107
hg18.geneid.LENGTH . . . . .	108
hg18.geneSymbol.LENGTH . . . . .	108

hg18.genscan.LENGTH . . . . .	109
hg18.knownGene.LENGTH . . . . .	109
hg18.knownGeneOld3.LENGTH . . . . .	110
hg18.refGene.LENGTH . . . . .	110
hg18.sgpGene.LENGTH . . . . .	111
hg18.sibGene.LENGTH . . . . .	111
hg18.xenoRefGene.LENGTH . . . . .	112
hg19.ccdsGene.LENGTH . . . . .	112
hg19.ensGene.LENGTH . . . . .	113
hg19.exoniphy.LENGTH . . . . .	113
hg19.geneSymbol.LENGTH . . . . .	114
hg19.knownGene.LENGTH . . . . .	114
hg19.nscanGene.LENGTH . . . . .	115
hg19.refGene.LENGTH . . . . .	115
hg19.xenoRefGene.LENGTH . . . . .	116
loxAfr3.xenoRefGene.LENGTH . . . . .	116
mm7.ensGene.LENGTH . . . . .	117
mm7.geneid.LENGTH . . . . .	117
mm7.geneSymbol.LENGTH . . . . .	118
mm7.genscan.LENGTH . . . . .	118
mm7.knownGene.LENGTH . . . . .	119
mm7.refGene.LENGTH . . . . .	119
mm7.sgpGene.LENGTH . . . . .	120
mm7.xenoRefGene.LENGTH . . . . .	120
mm8.ccdsGene.LENGTH . . . . .	121
mm8.ensGene.LENGTH . . . . .	121
mm8.geneid.LENGTH . . . . .	122
mm8.geneSymbol.LENGTH . . . . .	122
mm8.genscan.LENGTH . . . . .	123
mm8.knownGene.LENGTH . . . . .	123
mm8.nscanGene.LENGTH . . . . .	124
mm8.refGene.LENGTH . . . . .	124
mm8.sgpGene.LENGTH . . . . .	125
mm8.sibGene.LENGTH . . . . .	125
mm8.xenoRefGene.LENGTH . . . . .	126
mm9.acembly.LENGTH . . . . .	126
mm9.ccdsGene.LENGTH . . . . .	127
mm9.ensGene.LENGTH . . . . .	127
mm9.exoniphy.LENGTH . . . . .	128
mm9.geneid.LENGTH . . . . .	128
mm9.geneSymbol.LENGTH . . . . .	129
mm9.genscan.LENGTH . . . . .	129
mm9.knownGene.LENGTH . . . . .	130
mm9.nscanGene.LENGTH . . . . .	130
mm9.refGene.LENGTH . . . . .	131
mm9.sgpGene.LENGTH . . . . .	131
mm9.xenoRefGene.LENGTH . . . . .	132
monDom1.genscan.LENGTH . . . . .	132

monDom4.ensGene.LENGTH	133
monDom4.geneSymbol.LENGTH	133
monDom4.genscan.LENGTH	134
monDom4.nscanGene.LENGTH	134
monDom4.refGene.LENGTH	135
monDom4.xenoRefGene.LENGTH	135
monDom5.ensGene.LENGTH	136
monDom5.geneSymbol.LENGTH	136
monDom5.genscan.LENGTH	137
monDom5.nscanGene.LENGTH	137
monDom5.refGene.LENGTH	138
monDom5.xenoRefGene.LENGTH	138
ornAna1.ensGene.LENGTH	139
ornAna1.geneSymbol.LENGTH	139
ornAna1.refGene.LENGTH	140
ornAna1.xenoRefGene.LENGTH	140
oryLat2.ensGene.LENGTH	141
oryLat2.geneSymbol.LENGTH	141
oryLat2.refGene.LENGTH	142
oryLat2.xenoRefGene.LENGTH	142
panTro1.ensGene.LENGTH	143
panTro1.geneid.LENGTH	143
panTro1.genscan.LENGTH	144
panTro1.xenoRefGene.LENGTH	144
panTro2.ensGene.LENGTH	145
panTro2.geneSymbol.LENGTH	145
panTro2.genscan.LENGTH	146
panTro2.nscanGene.LENGTH	146
panTro2.refGene.LENGTH	147
panTro2.xenoRefGene.LENGTH	147
petMar1.xenoRefGene.LENGTH	148
ponAbe2.ensGene.LENGTH	148
ponAbe2.geneSymbol.LENGTH	149
ponAbe2.genscan.LENGTH	149
ponAbe2.nscanGene.LENGTH	150
ponAbe2.refGene.LENGTH	150
ponAbe2.xenoRefGene.LENGTH	151
priPac1.xenoRefGene.LENGTH	151
rheMac2.ensGene.LENGTH	152
rheMac2.geneid.LENGTH	152
rheMac2.geneSymbol.LENGTH	153
rheMac2.nscanGene.LENGTH	153
rheMac2.refGene.LENGTH	154
rheMac2.sgpGene.LENGTH	154
rheMac2.xenoRefGene.LENGTH	155
rn3.ensGene.LENGTH	155
rn3.geneid.LENGTH	156
rn3.geneSymbol.LENGTH	156

rn3.genscan.LENGTH . . . . .	157
rn3.knownGene.LENGTH . . . . .	157
rn3.nscanGene.LENGTH . . . . .	158
rn3.refGene.LENGTH . . . . .	158
rn3.sgpGene.LENGTH . . . . .	159
rn3.xenoRefGene.LENGTH . . . . .	159
rn4.ensGene.LENGTH . . . . .	160
rn4.geneid.LENGTH . . . . .	160
rn4.geneSymbol.LENGTH . . . . .	161
rn4.genscan.LENGTH . . . . .	161
rn4.knownGene.LENGTH . . . . .	162
rn4.nscanGene.LENGTH . . . . .	162
rn4.refGene.LENGTH . . . . .	163
rn4.sgpGene.LENGTH . . . . .	163
rn4.xenoRefGene.LENGTH . . . . .	164
sacCer1.ensGene.LENGTH . . . . .	164
sacCer2.ensGene.LENGTH . . . . .	165
strPur1.geneSymbol.LENGTH . . . . .	165
strPur1.genscan.LENGTH . . . . .	166
strPur1.refGene.LENGTH . . . . .	166
strPur1.xenoRefGene.LENGTH . . . . .	167
strPur2.geneSymbol.LENGTH . . . . .	167
strPur2.genscan.LENGTH . . . . .	168
strPur2.refGene.LENGTH . . . . .	168
strPur2.xenoRefGene.LENGTH . . . . .	169
supportedGeneIDs . . . . .	169
supportedGenomes . . . . .	170
taeGut1.ensGene.LENGTH . . . . .	171
taeGut1.geneSymbol.LENGTH . . . . .	171
taeGut1.genscan.LENGTH . . . . .	172
taeGut1.nscanGene.LENGTH . . . . .	172
taeGut1.refGene.LENGTH . . . . .	173
taeGut1.xenoRefGene.LENGTH . . . . .	173
tetNig1.ensGene.LENGTH . . . . .	174
tetNig1.geneid.LENGTH . . . . .	174
tetNig1.genscan.LENGTH . . . . .	175
tetNig1.nscanGene.LENGTH . . . . .	175
tetNig2.ensGene.LENGTH . . . . .	176
unfactor . . . . .	176
xenTro1.genscan.LENGTH . . . . .	177
xenTro2.ensGene.LENGTH . . . . .	178
xenTro2.geneSymbol.LENGTH . . . . .	178
xenTro2.genscan.LENGTH . . . . .	179
xenTro2.refGene.LENGTH . . . . .	179



---

`anoCar1.ensGene.LENGTH`*Transcript length data for the organism anoCar*

---

**Description**

anoCar1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(anoCar1.ensGene.LENGTH)
head(anoCar1.ensGene.LENGTH)
```

---

`anoCar1.genscan.LENGTH`*Transcript length data for the organism anoCar*

---

**Description**

anoCar1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(anoCar1.genscan.LENGTH)
head(anoCar1.genscan.LENGTH)
```

---

```
anoCar1.xenoRefGene.LENGTH
```

*Transcript length data for the organism anoCar*

---

### Description

anoCar1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.xenoRefGene.LENGTH)
head(anoCar1.xenoRefGene.LENGTH)
```

---

```
anoGam1.ensGene.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.ensGene.LENGTH)
head(anoGam1.ensGene.LENGTH)
```

---

anoGam1.geneid.LENGTH *Transcript length data for the organism anoGam*

---

### Description

anoGam1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.geneid.LENGTH)
head(anoGam1.geneid.LENGTH)
```

---

anoGam1.genscan.LENGTH  
*Transcript length data for the organism anoGam*

---

### Description

anoGam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.genscan.LENGTH)
head(anoGam1.genscan.LENGTH)
```

---

`apiMel1.genscan.LENGTH`*Transcript length data for the organism apiMel*

---

**Description**

`apiMel1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(apiMel1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(apiMel1.genscan.LENGTH)
head(apiMel1.genscan.LENGTH)
```

---

`apiMel2.ensGene.LENGTH`*Transcript length data for the organism apiMel*

---

**Description**

`apiMel2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(apiMel2.ensGene.LENGTH)
head(apiMel2.ensGene.LENGTH)
```

---

apiMel2.geneid.LENGTH *Transcript length data for the organism apiMel*

---

### Description

apiMel2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel2.geneid.LENGTH)
head(apiMel2.geneid.LENGTH)
```

---

apiMel2.genscan.LENGTH  
*Transcript length data for the organism apiMel*

---

### Description

apiMel2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(apiMel2.genscan.LENGTH)
head(apiMel2.genscan.LENGTH)
```

---

`aplCal1.xenoRefGene.LENGTH`*Transcript length data for the organism aplCal*

---

**Description**

`aplCal1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(aplCal1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(aplCal1.xenoRefGene.LENGTH)
head(aplCal1.xenoRefGene.LENGTH)
```

---

`bosTau2.geneid.LENGTH` *Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau2.geneid.LENGTH)
head(bosTau2.geneid.LENGTH)
```

---

`bosTau2.geneSymbol.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.geneSymbol.LENGTH)
head(bosTau2.geneSymbol.LENGTH)
```

---

`bosTau2.genscan.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.genscan.LENGTH)
head(bosTau2.genscan.LENGTH)
```

---

`bosTau2.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau2.refGene.LENGTH)
head(bosTau2.refGene.LENGTH)
```

---

`bosTau2.sgpGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau2.sgpGene.LENGTH)
head(bosTau2.sgpGene.LENGTH)
```



---

`bosTau3.ensGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau3.ensGene.LENGTH)
head(bosTau3.ensGene.LENGTH)
```

---

`bosTau3.geneid.LENGTH` *Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau3.geneid.LENGTH)
head(bosTau3.geneid.LENGTH)
```

---

`bosTau3.geneSymbol.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau3.geneSymbol.LENGTH)
head(bosTau3.geneSymbol.LENGTH)
```

---

`bosTau3.genscan.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau3.genscan.LENGTH)
head(bosTau3.genscan.LENGTH)
```

---

`bosTau3.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau3.refGene.LENGTH)
head(bosTau3.refGene.LENGTH)
```

---

`bosTau3.sgpGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, sgpGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau3.sgpGene.LENGTH)
head(bosTau3.sgpGene.LENGTH)
```

---

`bosTau4.ensGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.ensGene.LENGTH)
head(bosTau4.ensGene.LENGTH)
```

---

`bosTau4.geneSymbol.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.geneSymbol.LENGTH)
head(bosTau4.geneSymbol.LENGTH)
```

---

`bosTau4.genscan.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.genscan.LENGTH)
head(bosTau4.genscan.LENGTH)
```

---

`bosTau4.nscanGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.nscanGene.LENGTH)
head(bosTau4.nscanGene.LENGTH)
```

---

`bosTau4.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(bosTau4.refGene.LENGTH)
head(bosTau4.refGene.LENGTH)
```

---

`braFlo1.xenoRefGene.LENGTH`*Transcript length data for the organism braFlo*

---

**Description**

`braFlo1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(braFlo1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(braFlo1.xenoRefGene.LENGTH)
head(braFlo1.xenoRefGene.LENGTH)
```

---

`caeJap1.xenoRefGene.LENGTH`*Transcript length data for the organism caeJap*

---

**Description**

caeJap1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeJap1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(caeJap1.xenoRefGene.LENGTH)
head(caeJap1.xenoRefGene.LENGTH)
```

---

`caePb1.xenoRefGene.LENGTH`*Transcript length data for the organism caePb*

---

**Description**

caePb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(caePb1.xenoRefGene.LENGTH)
head(caePb1.xenoRefGene.LENGTH)
```

---

`caePb2.xenoRefGene.LENGTH`*Transcript length data for the organism caePb*

---

### Description

caePb2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caePb2.xenoRefGene.LENGTH)
head(caePb2.xenoRefGene.LENGTH)
```

---

`caeRem2.xenoRefGene.LENGTH`*Transcript length data for the organism caeRem*

---

### Description

caeRem2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeRem2.xenoRefGene.LENGTH)
head(caeRem2.xenoRefGene.LENGTH)
```



---

`caeRem3.xenoRefGene.LENGTH`*Transcript length data for the organism caeRem*

---

**Description**

caeRem3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem3, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(caeRem3.xenoRefGene.LENGTH)
head(caeRem3.xenoRefGene.LENGTH)
```

---

`calJac1.genscan.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.genscan.LENGTH)
head(calJac1.genscan.LENGTH)
```

---

`calJac1.nscanGene.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.nscanGene.LENGTH)
head(calJac1.nscanGene.LENGTH)
```

---

`calJac1.xenoRefGene.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.xenoRefGene.LENGTH)
head(calJac1.xenoRefGene.LENGTH)
```

---

`canFam1.ensGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.ensGene.LENGTH)
head(canFam1.ensGene.LENGTH)
```

---

`canFam1.geneSymbol.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.geneSymbol.LENGTH)
head(canFam1.geneSymbol.LENGTH)
```

---

`canFam1.genscan.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.genscan.LENGTH)
head(canFam1.genscan.LENGTH)
```

---

`canFam1.nscanGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.nscanGene.LENGTH)
head(canFam1.nscanGene.LENGTH)
```

---

`canFam1.refGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.refGene.LENGTH)
head(canFam1.refGene.LENGTH)
```

---

`canFam1.xenoRefGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam1.xenoRefGene.LENGTH)
head(canFam1.xenoRefGene.LENGTH)
```

---

`canFam2.ensGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam2.ensGene.LENGTH)
head(canFam2.ensGene.LENGTH)
```

---

`canFam2.geneSymbol.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam2.geneSymbol.LENGTH)
head(canFam2.geneSymbol.LENGTH)
```

---

`canFam2.genscan.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam2.genscan.LENGTH)
head(canFam2.genscan.LENGTH)
```

---

`canFam2.nscanGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(canFam2.nscanGene.LENGTH)
head(canFam2.nscanGene.LENGTH)
```

---

`canFam2.refGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam2.refGene.LENGTH)
head(canFam2.refGene.LENGTH)
```

---

`canFam2.xenoRefGene.LENGTH`*Transcript length data for the organism canFam*

---

**Description**

canFam2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(canFam2.xenoRefGene.LENGTH)
head(canFam2.xenoRefGene.LENGTH)
```



---

`cavPor3.ensGene.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.ensGene.LENGTH)
head(cavPor3.ensGene.LENGTH)
```

---

`cavPor3.genscan.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.genscan.LENGTH)
head(cavPor3.genscan.LENGTH)
```

---

`cavPor3.nscanGene.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.nscanGene.LENGTH)
head(cavPor3.nscanGene.LENGTH)
```

---

`cavPor3.xenoRefGene.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.xenoRefGene.LENGTH)
head(cavPor3.xenoRefGene.LENGTH)
```

---

`cb1.xenoRefGene.LENGTH`*Transcript length data for the organism cb*

---

**Description**

cb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(cb1.xenoRefGene.LENGTH)
head(cb1.xenoRefGene.LENGTH)
```

---

`cb3.xenoRefGene.LENGTH`*Transcript length data for the organism cb*

---

**Description**

cb3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb3, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(cb3.xenoRefGene.LENGTH)
head(cb3.xenoRefGene.LENGTH)
```

---

ce2.geneid.LENGTH	<i>Transcript length data for the organism ce</i>
-------------------	---

---

**Description**

ce2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ce2.geneid.LENGTH)
head(ce2.geneid.LENGTH)
```

---

ce2.geneSymbol.LENGTH	<i>Transcript length data for the organism ce</i>
-----------------------	---

---

**Description**

ce2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ce2.geneSymbol.LENGTH)
head(ce2.geneSymbol.LENGTH)
```

---

ce2.refGene.LENGTH	<i>Transcript length data for the organism ce</i>
--------------------	---

---

### Description

ce2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce2.refGene.LENGTH)
head(ce2.refGene.LENGTH)
```

---

ce4.geneSymbol.LENGTH	<i>Transcript length data for the organism ce</i>
-----------------------	---

---

### Description

ce4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.geneSymbol.LENGTH)
head(ce4.geneSymbol.LENGTH)
```

---

ce4.refGene.LENGTH	<i>Transcript length data for the organism ce</i>
--------------------	---

---

### Description

ce4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.refGene.LENGTH)
head(ce4.refGene.LENGTH)
```

---

ce4.xenoRefGene.LENGTH	<i>Transcript length data for the organism ce</i>
------------------------	---

---

### Description

ce4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.xenoRefGene.LENGTH)
head(ce4.xenoRefGene.LENGTH)
```

---

ce6.ensGene.LENGTH	<i>Transcript length data for the organism ce</i>
--------------------	---

---

### Description

ce6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.ensGene.LENGTH)
head(ce6.ensGene.LENGTH)
```

---

ce6.geneSymbol.LENGTH	<i>Transcript length data for the organism ce</i>
-----------------------	---

---

### Description

ce6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce6, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.geneSymbol.LENGTH)
head(ce6.geneSymbol.LENGTH)
```

---

ce6.refGene.LENGTH	<i>Transcript length data for the organism ce</i>
--------------------	---

---

**Description**

ce6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ce6.refGene.LENGTH)
head(ce6.refGene.LENGTH)
```

---

ce6.xenoRefGene.LENGTH	<i>Transcript length data for the organism ce</i>
------------------------	---

---

**Description**

ce6.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ce6.xenoRefGene.LENGTH)
head(ce6.xenoRefGene.LENGTH)
```



---

ci1.geneSymbol.LENGTH    *Transcript length data for the organism ci*

---

### Description

ci1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.geneSymbol.LENGTH)
head(ci1.geneSymbol.LENGTH)
```

---

ci1.refGene.LENGTH    *Transcript length data for the organism ci*

---

### Description

ci1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.refGene.LENGTH)
head(ci1.refGene.LENGTH)
```

---

`ci1.xenoRefGene.LENGTH`*Transcript length data for the organism ci*

---

**Description**

ci1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ci1.xenoRefGene.LENGTH)
head(ci1.xenoRefGene.LENGTH)
```

---

`ci2.ensGene.LENGTH`*Transcript length data for the organism ci*

---

**Description**

ci2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ci2.ensGene.LENGTH)
head(ci2.ensGene.LENGTH)
```

---

ci2.geneSymbol.LENGTH    *Transcript length data for the organism ci*

---

### Description

ci2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.geneSymbol.LENGTH)
head(ci2.geneSymbol.LENGTH)
```

---

ci2.refGene.LENGTH    *Transcript length data for the organism ci*

---

### Description

ci2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.refGene.LENGTH)
head(ci2.refGene.LENGTH)
```

---

`ci2.xenoRefGene.LENGTH`*Transcript length data for the organism ci*

---

**Description**

`ci2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(ci2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ci2.xenoRefGene.LENGTH)
head(ci2.xenoRefGene.LENGTH)
```

---

`danRer3.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer3.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer3.ensGene.LENGTH)
head(danRer3.ensGene.LENGTH)
```

---

`danRer3.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer3.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer3.geneSymbol.LENGTH)
head(danRer3.geneSymbol.LENGTH)
```

---

`danRer3.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer3.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer3.refGene.LENGTH)
head(danRer3.refGene.LENGTH)
```

---

`danRer4.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer4.ensGene.LENGTH)
head(danRer4.ensGene.LENGTH)
```

---

`danRer4.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer4.geneSymbol.LENGTH)
head(danRer4.geneSymbol.LENGTH)
```

---

`danRer4.genscan.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.genscan.LENGTH)
head(danRer4.genscan.LENGTH)
```

---

`danRer4.nscanGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.nscanGene.LENGTH)
head(danRer4.nscanGene.LENGTH)
```

---

`danRer4.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.refGene.LENGTH)
head(danRer4.refGene.LENGTH)
```

---

`danRer5.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer5.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.ensGene.LENGTH)
head(danRer5.ensGene.LENGTH)
```



---

`danRer5.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer5.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.geneSymbol.LENGTH)
head(danRer5.geneSymbol.LENGTH)
```

---

`danRer5.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.refGene.LENGTH)
head(danRer5.refGene.LENGTH)
```

---

`danRer5.vegaGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer5.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.vegaGene.LENGTH)
head(danRer5.vegaGene.LENGTH)
```

---

`danRer5.vegaPseudoGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer5.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaPseudoGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.vegaPseudoGene.LENGTH)
head(danRer5.vegaPseudoGene.LENGTH)
```

---

`danRer6.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer6.ensGene.LENGTH)
head(danRer6.ensGene.LENGTH)
```

---

`danRer6.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer6.geneSymbol.LENGTH)
head(danRer6.geneSymbol.LENGTH)
```

---

`danRer6.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer6.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer6.refGene.LENGTH)
head(danRer6.refGene.LENGTH)
```

---

`danRer6.xenoRefGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer6.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(danRer6.xenoRefGene.LENGTH)
head(danRer6.xenoRefGene.LENGTH)
```

---

dm1.geneSymbol.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.geneSymbol.LENGTH)
head(dm1.geneSymbol.LENGTH)
```

---

dm1.genscan.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.genscan.LENGTH)
head(dm1.genscan.LENGTH)
```

---

dm1.refGene.LENGTH	<i>Transcript length data for the organism dm</i>
--------------------	---

---

### Description

dm1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.refGene.LENGTH)
head(dm1.refGene.LENGTH)
```

---

dm2.geneid.LENGTH	<i>Transcript length data for the organism dm</i>
-------------------	---

---

### Description

dm2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneid.LENGTH)
head(dm2.geneid.LENGTH)
```

---

dm2.geneSymbol.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneSymbol.LENGTH)
head(dm2.geneSymbol.LENGTH)
```

---

dm2.genscan.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.genscan.LENGTH)
head(dm2.genscan.LENGTH)
```

---

dm2.nscanGene.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.nscanGene.LENGTH)
head(dm2.nscanGene.LENGTH)
```

---

dm2.refGene.LENGTH    *Transcript length data for the organism dm*

---

### Description

dm2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.refGene.LENGTH)
head(dm2.refGene.LENGTH)
```



---

dm3.geneSymbol.LENGTH *Transcript length data for the organism dm*

---

### Description

dm3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm3.geneSymbol.LENGTH)
head(dm3.geneSymbol.LENGTH)
```

---

dm3.nscanPasaGene.LENGTH  
*Transcript length data for the organism dm*

---

### Description

dm3.nscanPasaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanPasaGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, nscanPasaGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm3.nscanPasaGene.LENGTH)
head(dm3.nscanPasaGene.LENGTH)
```

---

dm3.refGene.LENGTH	<i>Transcript length data for the organism dm</i>
--------------------	---

---

### Description

dm3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm3.refGene.LENGTH)
head(dm3.refGene.LENGTH)
```

---

dp2.genscan.LENGTH	<i>Transcript length data for the organism dp</i>
--------------------	---

---

### Description

dp2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp2.genscan.LENGTH)
head(dp2.genscan.LENGTH)
```

---

`dp2.xenoRefGene.LENGTH`*Transcript length data for the organism dp*

---

**Description**

dp2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(dp2.xenoRefGene.LENGTH)
head(dp2.xenoRefGene.LENGTH)
```

---

`dp3.geneid.LENGTH`*Transcript length data for the organism dp*

---

**Description**

dp3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dp3, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(dp3.geneid.LENGTH)
head(dp3.geneid.LENGTH)
```

---

dp3.genscan.LENGTH	<i>Transcript length data for the organism dp</i>
--------------------	---

---

### Description

dp3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.genscan.LENGTH)
head(dp3.genscan.LENGTH)
```

---

dp3.xenoRefGene.LENGTH	<i>Transcript length data for the organism dp</i>
------------------------	---

---

### Description

dp3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.xenoRefGene.LENGTH)
head(dp3.xenoRefGene.LENGTH)
```

---

droAna1.geneid.LENGTH *Transcript length data for the organism droAna*

---

### Description

droAna1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.geneid.LENGTH)
head(droAna1.geneid.LENGTH)
```

---

droAna1.genscan.LENGTH  
*Transcript length data for the organism droAna*

---

### Description

droAna1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.genscan.LENGTH)
head(droAna1.genscan.LENGTH)
```

---

`droAna1.xenoRefGene.LENGTH`*Transcript length data for the organism droAna*

---

### Description

`droAna1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.xenoRefGene.LENGTH)
head(droAna1.xenoRefGene.LENGTH)
```

---

`droAna2.genscan.LENGTH`*Transcript length data for the organism droAna*

---

### Description

`droAna2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna2.genscan.LENGTH)
head(droAna2.genscan.LENGTH)
```

---

`droAna2.xenoRefGene.LENGTH`*Transcript length data for the organism droAna*

---

**Description**

droAna2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droAna2.xenoRefGene.LENGTH)
head(droAna2.xenoRefGene.LENGTH)
```

---

`droEre1.genscan.LENGTH`*Transcript length data for the organism droEre*

---

**Description**

droEre1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droEre1.genscan.LENGTH)
head(droEre1.genscan.LENGTH)
```

---

`droEre1.xenoRefGene.LENGTH`*Transcript length data for the organism droEre*

---

**Description**

`droEre1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droEre1.xenoRefGene.LENGTH)
head(droEre1.xenoRefGene.LENGTH)
```

---

`droGri1.genscan.LENGTH`*Transcript length data for the organism droGri*

---

**Description**

`droGri1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droGri1.genscan.LENGTH)
head(droGri1.genscan.LENGTH)
```



---

`droGri1.xenoRefGene.LENGTH`*Transcript length data for the organism droGri*

---

**Description**

droGri1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droGri1.xenoRefGene.LENGTH)
head(droGri1.xenoRefGene.LENGTH)
```

---

`droMoj1.geneid.LENGTH` *Transcript length data for the organism droMoj*

---

**Description**

droMoj1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj1.geneid.LENGTH)
head(droMoj1.geneid.LENGTH)
```

---

`droMoj1.genscan.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj1.genscan.LENGTH)
head(droMoj1.genscan.LENGTH)
```

---

`droMoj1.xenoRefGene.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj1.xenoRefGene.LENGTH)
head(droMoj1.xenoRefGene.LENGTH)
```

---

`droMoj2.genscan.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj2.genscan.LENGTH)
head(droMoj2.genscan.LENGTH)
```

---

`droMoj2.xenoRefGene.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj2.xenoRefGene.LENGTH)
head(droMoj2.xenoRefGene.LENGTH)
```

---

`droPer1.genscan.LENGTH`*Transcript length data for the organism droPer*

---

**Description**

droPer1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droPer1.genscan.LENGTH)
head(droPer1.genscan.LENGTH)
```

---

`droPer1.xenoRefGene.LENGTH`*Transcript length data for the organism droPer*

---

**Description**

droPer1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droPer1.xenoRefGene.LENGTH)
head(droPer1.xenoRefGene.LENGTH)
```

---

`droSec1.genscan.LENGTH`*Transcript length data for the organism droSec*

---

**Description**

droSec1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droSec1.genscan.LENGTH)
head(droSec1.genscan.LENGTH)
```

---

`droSec1.xenoRefGene.LENGTH`*Transcript length data for the organism droSec*

---

**Description**

droSec1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droSec1.xenoRefGene.LENGTH)
head(droSec1.xenoRefGene.LENGTH)
```

---

droSim1.geneid.LENGTH *Transcript length data for the organism droSim*

---

### Description

droSim1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.geneid.LENGTH)
head(droSim1.geneid.LENGTH)
```

---

droSim1.genscan.LENGTH  
*Transcript length data for the organism droSim*

---

### Description

droSim1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.genscan.LENGTH)
head(droSim1.genscan.LENGTH)
```

---

`droSim1.xenoRefGene.LENGTH`*Transcript length data for the organism droSim*

---

**Description**

`droSim1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droSim1.xenoRefGene.LENGTH)
head(droSim1.xenoRefGene.LENGTH)
```

---

`droVir1.geneid.LENGTH` *Transcript length data for the organism droVir*

---

**Description**

`droVir1.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir1.geneid.LENGTH)
head(droVir1.geneid.LENGTH)
```

---

`droVir1.genscan.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir1.genscan.LENGTH)
head(droVir1.genscan.LENGTH)
```

---

`droVir1.xenoRefGene.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir1.xenoRefGene.LENGTH)
head(droVir1.xenoRefGene.LENGTH)
```



---

`droVir2.genscan.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir2.genscan.LENGTH)
head(droVir2.genscan.LENGTH)
```

---

`droVir2.xenoRefGene.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir2.xenoRefGene.LENGTH)
head(droVir2.xenoRefGene.LENGTH)
```

---

droYak1.geneid.LENGTH *Transcript length data for the organism droYak*

---

### Description

droYak1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.geneid.LENGTH)
head(droYak1.geneid.LENGTH)
```

---

droYak1.genscan.LENGTH  
*Transcript length data for the organism droYak*

---

### Description

droYak1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.genscan.LENGTH)
head(droYak1.genscan.LENGTH)
```

---

`droYak1.xenoRefGene.LENGTH`*Transcript length data for the organism droYak*

---

**Description**

droYak1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droYak1.xenoRefGene.LENGTH)
head(droYak1.xenoRefGene.LENGTH)
```

---

`droYak2.genscan.LENGTH`*Transcript length data for the organism droYak*

---

**Description**

droYak2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droYak2.genscan.LENGTH)
head(droYak2.genscan.LENGTH)
```

---

`droYak2.xenoRefGene.LENGTH`*Transcript length data for the organism droYak*

---

**Description**

`droYak2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(droYak2.xenoRefGene.LENGTH)
head(droYak2.xenoRefGene.LENGTH)
```

---

`equCab1.geneid.LENGTH` *Transcript length data for the organism equCab*

---

**Description**

`equCab1.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(equCab1.geneid.LENGTH)
head(equCab1.geneid.LENGTH)
```

---

`equCab1.geneSymbol.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.geneSymbol.LENGTH)
head(equCab1.geneSymbol.LENGTH)
```

---

`equCab1.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.nscanGene.LENGTH)
head(equCab1.nscanGene.LENGTH)
```

---

`equCab1.refGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(equCab1.refGene.LENGTH)
head(equCab1.refGene.LENGTH)
```

---

`equCab1.sgpGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(equCab1.sgpGene.LENGTH)
head(equCab1.sgpGene.LENGTH)
```

---

`equCab2.ensGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.ensGene.LENGTH)
head(equCab2.ensGene.LENGTH)
```

---

`equCab2.geneSymbol.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.geneSymbol.LENGTH)
head(equCab2.geneSymbol.LENGTH)
```

---

`equCab2.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.nscanGene.LENGTH)
head(equCab2.nscanGene.LENGTH)
```

---

`equCab2.refGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.refGene.LENGTH)
head(equCab2.refGene.LENGTH)
```



---

`equCab2.xenoRefGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(equCab2.xenoRefGene.LENGTH)
head(equCab2.xenoRefGene.LENGTH)
```

---

`felCat3.ensGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

`felCat3.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(felCat3.ensGene.LENGTH)
head(felCat3.ensGene.LENGTH)
```

---

felCat3.geneid.LENGTH *Transcript length data for the organism felCat*

---

### Description

felCat3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.geneid.LENGTH)
head(felCat3.geneid.LENGTH)
```

---

felCat3.geneSymbol.LENGTH  
*Transcript length data for the organism felCat*

---

### Description

felCat3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.geneSymbol.LENGTH)
head(felCat3.geneSymbol.LENGTH)
```

---

`felCat3.genscan.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.genscan.LENGTH)
head(felCat3.genscan.LENGTH)
```

---

`felCat3.nscanGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.nscanGene.LENGTH)
head(felCat3.nscanGene.LENGTH)
```

---

`felCat3.refGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.refGene.LENGTH)
head(felCat3.refGene.LENGTH)
```

---

`felCat3.sgpGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, sgpGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.sgpGene.LENGTH)
head(felCat3.sgpGene.LENGTH)
```

---

`felCat3.xenoRefGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.xenoRefGene.LENGTH)
head(felCat3.xenoRefGene.LENGTH)
```

---

`fr1.ensGene.LENGTH`*Transcript length data for the organism fr*

---

**Description**

fr1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(fr1.ensGene.LENGTH)
head(fr1.ensGene.LENGTH)
```

---

fr1.genscan.LENGTH	<i>Transcript length data for the organism fr</i>
--------------------	---

---

### Description

fr1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(fr1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr1.genscan.LENGTH)
head(fr1.genscan.LENGTH)
```

---

fr2.ensGene.LENGTH	<i>Transcript length data for the organism fr</i>
--------------------	---

---

### Description

fr2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr2.ensGene.LENGTH)
head(fr2.ensGene.LENGTH)
```

---

`galGal2.ensGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.ensGene.LENGTH)
head(galGal2.ensGene.LENGTH)
```

---

`galGal2.geneid.LENGTH` *Transcript length data for the organism galGal*

---

**Description**

galGal2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.geneid.LENGTH)
head(galGal2.geneid.LENGTH)
```

---

`galGal2.geneSymbol.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.geneSymbol.LENGTH)
head(galGal2.geneSymbol.LENGTH)
```

---

`galGal2.genscan.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.genscan.LENGTH)
head(galGal2.genscan.LENGTH)
```



---

`galGal2.refGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.refGene.LENGTH)
head(galGal2.refGene.LENGTH)
```

---

`galGal2.sgpGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal2.sgpGene.LENGTH)
head(galGal2.sgpGene.LENGTH)
```

---

`galGal3.ensGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.ensGene.LENGTH)
head(galGal3.ensGene.LENGTH)
```

---

`galGal3.geneSymbol.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.geneSymbol.LENGTH)
head(galGal3.geneSymbol.LENGTH)
```

---

`galGal3.genscan.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.genscan.LENGTH)
head(galGal3.genscan.LENGTH)
```

---

`galGal3.nscanGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.nscanGene.LENGTH)
head(galGal3.nscanGene.LENGTH)
```

---

`galGal3.refGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.refGene.LENGTH)
head(galGal3.refGene.LENGTH)
```

---

`galGal3.xenoRefGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(galGal3.xenoRefGene.LENGTH)
head(galGal3.xenoRefGene.LENGTH)
```

---

`gasAcu1.ensGene.LENGTH`*Transcript length data for the organism gasAcu*

---

**Description**

gasAcu1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(gasAcu1.ensGene.LENGTH)
head(gasAcu1.ensGene.LENGTH)
```

---

`gasAcu1.nscanGene.LENGTH`*Transcript length data for the organism gasAcu*

---

**Description**

gasAcu1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(gasAcu1.nscanGene.LENGTH)
head(gasAcu1.nscanGene.LENGTH)
```

---

hg16.acembly.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg16.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg16, acembly)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.acembly.LENGTH)
head(hg16.acembly.LENGTH)
```

---

hg16.ensGene.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg16.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.ensGene.LENGTH)
head(hg16.ensGene.LENGTH)
```

---

hg16.exoniphy.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg16, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.exoniphy.LENGTH)
head(hg16.exoniphy.LENGTH)
```

---

hg16.geneid.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.geneid.LENGTH)
head(hg16.geneid.LENGTH)
```

---

`hg16.geneSymbol.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg16.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.geneSymbol.LENGTH)
head(hg16.geneSymbol.LENGTH)
```

---

`hg16.genscan.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg16.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg16, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.genscan.LENGTH)
head(hg16.genscan.LENGTH)
```



---

hg16.knownGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg16.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.knownGene.LENGTH)
head(hg16.knownGene.LENGTH)
```

---

hg16.refGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg16.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.refGene.LENGTH)
head(hg16.refGene.LENGTH)
```

---

hg16.sgpGene.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg16.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.sgpGene.LENGTH)
head(hg16.sgpGene.LENGTH)
```

---

hg17.acembly.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg17.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acembly)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.acembly.LENGTH)
head(hg17.acembly.LENGTH)
```

---

hg17.acescan.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg17.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acescan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.acescan.LENGTH)
head(hg17.acescan.LENGTH)
```

---

hg17.ccdsGene.LENGTH	<i>Transcript length data for the organism hg</i>
----------------------	---

---

**Description**

hg17.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ccdsGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.ccdsGene.LENGTH)
head(hg17.ccdsGene.LENGTH)
```

---

hg17.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.ensGene.LENGTH)
head(hg17.ensGene.LENGTH)
```

---

hg17.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg17, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.exoniphy.LENGTH)
head(hg17.exoniphy.LENGTH)
```

---

hg17.geneid.LENGTH	<i>Transcript length data for the organism hg</i>
--------------------	---

---

**Description**

hg17.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.geneid.LENGTH)
head(hg17.geneid.LENGTH)
```

---

hg17.geneSymbol.LENGTH	<i>Transcript length data for the organism hg</i>
------------------------	---

---

**Description**

hg17.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.geneSymbol.LENGTH)
head(hg17.geneSymbol.LENGTH)
```

---

hg17.genscan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.genscan.LENGTH)
head(hg17.genscan.LENGTH)
```

---

hg17.knownGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.knownGene.LENGTH)
head(hg17.knownGene.LENGTH)
```

---

hg17.refGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.refGene.LENGTH)
head(hg17.refGene.LENGTH)
```

---

hg17.sgpGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.sgpGene.LENGTH)
head(hg17.sgpGene.LENGTH)
```

---

hg17.vegaGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaGene.LENGTH)
head(hg17.vegaGene.LENGTH)
```

---

hg17.vegaPseudoGene.LENGTH  
                                  *Transcript length data for the organism hg*

---

### Description

hg17.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaPseudoGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaPseudoGene.LENGTH)
head(hg17.vegaPseudoGene.LENGTH)
```



---

`hg17.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg17.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg17.xenoRefGene.LENGTH)
head(hg17.xenoRefGene.LENGTH)
```

---

`hg18.acembly.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acembly)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg18.acembly.LENGTH)
head(hg18.acembly.LENGTH)
```

---

hg18.acescan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acescan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.acescan.LENGTH)
head(hg18.acescan.LENGTH)
```

---

hg18.ccdsGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ccdsGene.LENGTH)
head(hg18.ccdsGene.LENGTH)
```

---

hg18.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ensGene.LENGTH)
head(hg18.ensGene.LENGTH)
```

---

hg18.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg18, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.exoniphy.LENGTH)
head(hg18.exoniphy.LENGTH)
```

---

hg18.geneid.LENGTH	<i>Transcript length data for the organism hg</i>
--------------------	---

---

### Description

hg18.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneid.LENGTH)
head(hg18.geneid.LENGTH)
```

---

hg18.geneSymbol.LENGTH	<i>Transcript length data for the organism hg</i>
------------------------	---

---

### Description

hg18.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneSymbol.LENGTH)
head(hg18.geneSymbol.LENGTH)
```

---

hg18.genscan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.genscan.LENGTH)
head(hg18.genscan.LENGTH)
```

---

hg18.knownGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.knownGene.LENGTH)
head(hg18.knownGene.LENGTH)
```

---

`hg18.knownGeneOld3.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.knownGeneOld3.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGeneOld3 table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGeneOld3)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg18.knownGeneOld3.LENGTH)
head(hg18.knownGeneOld3.LENGTH)
```

---

`hg18.refGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg18.refGene.LENGTH)
head(hg18.refGene.LENGTH)
```

---

hg18.sgpGene.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg18.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.sgpGene.LENGTH)
head(hg18.sgpGene.LENGTH)
```

---

hg18.sibGene.LENGTH	<i>Transcript length data for the organism hg</i>
---------------------	---

---

**Description**

hg18.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sibGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.sibGene.LENGTH)
head(hg18.sibGene.LENGTH)
```

---

`hg18.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.xenoRefGene.LENGTH)
head(hg18.xenoRefGene.LENGTH)
```

---

`hg19.ccdsGene.LENGTH`    *Transcript length data for the organism hg*

---

**Description**

hg19.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ccdsGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg19.ccdsGene.LENGTH)
head(hg19.ccdsGene.LENGTH)
```



---

hg19.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg19.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.ensGene.LENGTH)
head(hg19.ensGene.LENGTH)
```

---

hg19.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg19.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg19, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.exoniphy.LENGTH)
head(hg19.exoniphy.LENGTH)
```

---

`hg19.geneSymbol.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg19.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg19, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg19.geneSymbol.LENGTH)
head(hg19.geneSymbol.LENGTH)
```

---

`hg19.knownGene.LENGTH` *Transcript length data for the organism hg*

---

**Description**

hg19.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, knownGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg19.knownGene.LENGTH)
head(hg19.knownGene.LENGTH)
```

---

hg19.nscanGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.nscanGene.LENGTH)
head(hg19.nscanGene.LENGTH)
```

---

hg19.refGene.LENGTH *Transcript length data for the organism hg*

---

### Description

hg19.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.refGene.LENGTH)
head(hg19.refGene.LENGTH)
```

---

`hg19.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg19.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg19.xenoRefGene.LENGTH)
head(hg19.xenoRefGene.LENGTH)
```

---

`loxAfr3.xenoRefGene.LENGTH`*Transcript length data for the organism loxAfr*

---

**Description**

loxAfr3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(loxAfr3, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(loxAfr3.xenoRefGene.LENGTH)
head(loxAfr3.xenoRefGene.LENGTH)
```

---

mm7.ensGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm7.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.ensGene.LENGTH)
head(mm7.ensGene.LENGTH)
```

---

mm7.geneid.LENGTH	<i>Transcript length data for the organism mm</i>
-------------------	---

---

### Description

mm7.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneid.LENGTH)
head(mm7.geneid.LENGTH)
```

---

mm7.geneSymbol.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneSymbol.LENGTH)
head(mm7.geneSymbol.LENGTH)
```

---

mm7.genscan.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm7, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.genscan.LENGTH)
head(mm7.genscan.LENGTH)
```

---

mm7.knownGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.knownGene.LENGTH)
head(mm7.knownGene.LENGTH)
```

---

mm7.refGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.refGene.LENGTH)
head(mm7.refGene.LENGTH)
```

---

mm7.sgpGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm7.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.sgpGene.LENGTH)
head(mm7.sgpGene.LENGTH)
```

---

mm7.xenoRefGene.LENGTH	<i>Transcript length data for the organism mm</i>
------------------------	---

---

### Description

mm7.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.xenoRefGene.LENGTH)
head(mm7.xenoRefGene.LENGTH)
```



---

mm8.ccdsGene.LENGTH	<i>Transcript length data for the organism mm</i>
---------------------	---

---

### Description

mm8.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ccdsGene.LENGTH)
head(mm8.ccdsGene.LENGTH)
```

---

mm8.ensGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm8.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ensGene.LENGTH)
head(mm8.ensGene.LENGTH)
```

---

mm8.geneid.LENGTH	<i>Transcript length data for the organism mm</i>
-------------------	---

---

### Description

mm8.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneid.LENGTH)
head(mm8.geneid.LENGTH)
```

---

mm8.geneSymbol.LENGTH	<i>Transcript length data for the organism mm</i>
-----------------------	---

---

### Description

mm8.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneSymbol.LENGTH)
head(mm8.geneSymbol.LENGTH)
```

---

mm8.genscan.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm8.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm8, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.genscan.LENGTH)
head(mm8.genscan.LENGTH)
```

---

mm8.knownGene.LENGTH	<i>Transcript length data for the organism mm</i>
----------------------	---

---

### Description

mm8.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.knownGene.LENGTH)
head(mm8.knownGene.LENGTH)
```

---

mm8.nscanGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm8.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.nscanGene.LENGTH)
head(mm8.nscanGene.LENGTH)
```

---

mm8.refGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm8.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.refGene.LENGTH)
head(mm8.refGene.LENGTH)
```

---

mm8.sgpGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

**Description**

mm8.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(mm8.sgpGene.LENGTH)
head(mm8.sgpGene.LENGTH)
```

---

mm8.sibGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

**Description**

mm8.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sibGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(mm8.sibGene.LENGTH)
head(mm8.sibGene.LENGTH)
```

---

`mm8.xenoRefGene.LENGTH`*Transcript length data for the organism mm*

---

**Description**

`mm8.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(mm8, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(mm8.xenoRefGene.LENGTH)
head(mm8.xenoRefGene.LENGTH)
```

---

`mm9.acembly.LENGTH`*Transcript length data for the organism mm*

---

**Description**

`mm9.acembly.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `acembly` table.

The data file was made by calling `downloadLengthFromUCSC(mm9, acembly)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(mm9.acembly.LENGTH)
head(mm9.acembly.LENGTH)
```

---

mm9.ccdsGene.LENGTH	<i>Transcript length data for the organism mm</i>
---------------------	---

---

### Description

mm9.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ccdsGene.LENGTH)
head(mm9.ccdsGene.LENGTH)
```

---

mm9.ensGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm9.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ensGene.LENGTH)
head(mm9.ensGene.LENGTH)
```

---

mm9.exoniphy.LENGTH	<i>Transcript length data for the organism mm</i>
---------------------	---

---

### Description

mm9.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(mm9, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.exoniphy.LENGTH)
head(mm9.exoniphy.LENGTH)
```

---

mm9.geneid.LENGTH	<i>Transcript length data for the organism mm</i>
-------------------	---

---

### Description

mm9.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneid.LENGTH)
head(mm9.geneid.LENGTH)
```



---

mm9.geneSymbol.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneSymbol.LENGTH)
head(mm9.geneSymbol.LENGTH)
```

---

mm9.genscan.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm9, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.genscan.LENGTH)
head(mm9.genscan.LENGTH)
```

---

mm9.knownGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.knownGene.LENGTH)
head(mm9.knownGene.LENGTH)
```

---

mm9.nscanGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.nscanGene.LENGTH)
head(mm9.nscanGene.LENGTH)
```

---

mm9.refGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm9.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.refGene.LENGTH)
head(mm9.refGene.LENGTH)
```

---

mm9.sgpGene.LENGTH	<i>Transcript length data for the organism mm</i>
--------------------	---

---

### Description

mm9.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.sgpGene.LENGTH)
head(mm9.sgpGene.LENGTH)
```

---

`mm9.xenoRefGene.LENGTH`*Transcript length data for the organism mm*

---

**Description**

`mm9.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(mm9, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(mm9.xenoRefGene.LENGTH)
head(mm9.xenoRefGene.LENGTH)
```

---

`monDom1.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(monDom1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom1.genscan.LENGTH)
head(monDom1.genscan.LENGTH)
```

---

`monDom4.ensGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.ensGene.LENGTH)
head(monDom4.ensGene.LENGTH)
```

---

`monDom4.geneSymbol.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.geneSymbol.LENGTH)
head(monDom4.geneSymbol.LENGTH)
```

---

`monDom4.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

monDom4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(monDom4.genscan.LENGTH)
head(monDom4.genscan.LENGTH)
```

---

`monDom4.nscanGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

monDom4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(monDom4.nscanGene.LENGTH)
head(monDom4.nscanGene.LENGTH)
```

---

`monDom4.refGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.refGene.LENGTH)
head(monDom4.refGene.LENGTH)
```

---

`monDom4.xenoRefGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.xenoRefGene.LENGTH)
head(monDom4.xenoRefGene.LENGTH)
```

---

`monDom5.ensGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.ensGene.LENGTH)
head(monDom5.ensGene.LENGTH)
```

---

`monDom5.geneSymbol.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.geneSymbol.LENGTH)
head(monDom5.geneSymbol.LENGTH)
```



---

`monDom5.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.genscan.LENGTH)
head(monDom5.genscan.LENGTH)
```

---

`monDom5.nscanGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.nscanGene.LENGTH)
head(monDom5.nscanGene.LENGTH)
```

---

`monDom5.refGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

monDom5.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.refGene.LENGTH)
head(monDom5.refGene.LENGTH)
```

---

`monDom5.xenoRefGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

monDom5.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.xenoRefGene.LENGTH)
head(monDom5.xenoRefGene.LENGTH)
```

---

`ornAna1.ensGene.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

`ornAna1.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ornAna1.ensGene.LENGTH)
head(ornAna1.ensGene.LENGTH)
```

---

`ornAna1.geneSymbol.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

`ornAna1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ornAna1.geneSymbol.LENGTH)
head(ornAna1.geneSymbol.LENGTH)
```

---

`ornAna1.refGene.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

`ornAna1.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ornAna1.refGene.LENGTH)
head(ornAna1.refGene.LENGTH)
```

---

`ornAna1.xenoRefGene.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

`ornAna1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ornAna1.xenoRefGene.LENGTH)
head(ornAna1.xenoRefGene.LENGTH)
```

---

`oryLat2.ensGene.LENGTH`*Transcript length data for the organism oryLat*

---

**Description**

oryLat2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(oryLat2.ensGene.LENGTH)
head(oryLat2.ensGene.LENGTH)
```

---

`oryLat2.geneSymbol.LENGTH`*Transcript length data for the organism oryLat*

---

**Description**

oryLat2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(oryLat2.geneSymbol.LENGTH)
head(oryLat2.geneSymbol.LENGTH)
```

---

`oryLat2.refGene.LENGTH`*Transcript length data for the organism oryLat*

---

**Description**

oryLat2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(oryLat2.refGene.LENGTH)
head(oryLat2.refGene.LENGTH)
```

---

`oryLat2.xenoRefGene.LENGTH`*Transcript length data for the organism oryLat*

---

**Description**

oryLat2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(oryLat2.xenoRefGene.LENGTH)
head(oryLat2.xenoRefGene.LENGTH)
```

---

`panTro1.ensGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(panTro1.ensGene.LENGTH)
head(panTro1.ensGene.LENGTH)
```

---

`panTro1.geneid.LENGTH` *Transcript length data for the organism panTro*

---

**Description**

panTro1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(panTro1.geneid.LENGTH)
head(panTro1.geneid.LENGTH)
```

---

`panTro1.genscan.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(panTro1.genscan.LENGTH)
head(panTro1.genscan.LENGTH)
```

---

`panTro1.xenoRefGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(panTro1.xenoRefGene.LENGTH)
head(panTro1.xenoRefGene.LENGTH)
```



---

`panTro2.ensGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.ensGene.LENGTH)
head(panTro2.ensGene.LENGTH)
```

---

`panTro2.geneSymbol.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.geneSymbol.LENGTH)
head(panTro2.geneSymbol.LENGTH)
```

---

`panTro2.genscan.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.genscan.LENGTH)
head(panTro2.genscan.LENGTH)
```

---

`panTro2.nscanGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.nscanGene.LENGTH)
head(panTro2.nscanGene.LENGTH)
```

---

`panTro2.refGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.refGene.LENGTH)
head(panTro2.refGene.LENGTH)
```

---

`panTro2.xenoRefGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.xenoRefGene.LENGTH)
head(panTro2.xenoRefGene.LENGTH)
```

---

`petMar1.xenoRefGene.LENGTH`*Transcript length data for the organism petMar*

---

**Description**

`petMar1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(petMar1, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(petMar1.xenoRefGene.LENGTH)
head(petMar1.xenoRefGene.LENGTH)
```

---

`ponAbe2.ensGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ponAbe2.ensGene.LENGTH)
head(ponAbe2.ensGene.LENGTH)
```

---

`ponAbe2.geneSymbol.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.geneSymbol.LENGTH)
head(ponAbe2.geneSymbol.LENGTH)
```

---

`ponAbe2.genscan.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.genscan.LENGTH)
head(ponAbe2.genscan.LENGTH)
```

---

`ponAbe2.nscanGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.nscanGene.LENGTH)
head(ponAbe2.nscanGene.LENGTH)
```

---

`ponAbe2.refGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.refGene.LENGTH)
head(ponAbe2.refGene.LENGTH)
```

---

`ponAbe2.xenoRefGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.xenoRefGene.LENGTH)
head(ponAbe2.xenoRefGene.LENGTH)
```

---

`priPac1.xenoRefGene.LENGTH`*Transcript length data for the organism priPac*

---

**Description**

`priPac1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(priPac1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(priPac1.xenoRefGene.LENGTH)
head(priPac1.xenoRefGene.LENGTH)
```

---

`rheMac2.ensGene.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

`rheMac2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rheMac2.ensGene.LENGTH)
head(rheMac2.ensGene.LENGTH)
```

---

`rheMac2.geneid.LENGTH` *Transcript length data for the organism rheMac*

---

**Description**

`rheMac2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rheMac2.geneid.LENGTH)
head(rheMac2.geneid.LENGTH)
```



---

`rheMac2.geneSymbol.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

rheMac2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(rheMac2.geneSymbol.LENGTH)
head(rheMac2.geneSymbol.LENGTH)
```

---

`rheMac2.nscanGene.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

rheMac2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(rheMac2.nscanGene.LENGTH)
head(rheMac2.nscanGene.LENGTH)
```

---

`rheMac2.refGene.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

rheMac2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rheMac2.refGene.LENGTH)
head(rheMac2.refGene.LENGTH)
```

---

`rheMac2.sgpGene.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

rheMac2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rheMac2.sgpGene.LENGTH)
head(rheMac2.sgpGene.LENGTH)
```

---

`rheMac2.xenoRefGene.LENGTH`*Transcript length data for the organism rheMac*

---

**Description**

`rheMac2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rheMac2.xenoRefGene.LENGTH)
head(rheMac2.xenoRefGene.LENGTH)
```

---

`rn3.ensGene.LENGTH`*Transcript length data for the organism rn*

---

**Description**

`rn3.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(rn3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rn3.ensGene.LENGTH)
head(rn3.ensGene.LENGTH)
```

---

rn3.geneid.LENGTH	<i>Transcript length data for the organism rn</i>
-------------------	---

---

**Description**

rn3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rn3.geneid.LENGTH)
head(rn3.geneid.LENGTH)
```

---

rn3.geneSymbol.LENGTH	<i>Transcript length data for the organism rn</i>
-----------------------	---

---

**Description**

rn3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rn3.geneSymbol.LENGTH)
head(rn3.geneSymbol.LENGTH)
```

---

rn3.genscan.LENGTH	<i>Transcript length data for the organism rn</i>
--------------------	---

---

### Description

rn3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.genscan.LENGTH)
head(rn3.genscan.LENGTH)
```

---

rn3.knownGene.LENGTH	<i>Transcript length data for the organism rn</i>
----------------------	---

---

### Description

rn3.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.knownGene.LENGTH)
head(rn3.knownGene.LENGTH)
```

---

rn3.nscanGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.nscanGene.LENGTH)
head(rn3.nscanGene.LENGTH)
```

---

rn3.refGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.refGene.LENGTH)
head(rn3.refGene.LENGTH)
```

---

rn3.sgpGene.LENGTH	<i>Transcript length data for the organism rn</i>
--------------------	---

---

### Description

rn3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.sgpGene.LENGTH)
head(rn3.sgpGene.LENGTH)
```

---

rn3.xenoRefGene.LENGTH	<i>Transcript length data for the organism rn</i>
------------------------	---

---

### Description

rn3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.xenoRefGene.LENGTH)
head(rn3.xenoRefGene.LENGTH)
```

---

rn4.ensGene.LENGTH	<i>Transcript length data for the organism rn</i>
--------------------	---

---

### Description

rn4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.ensGene.LENGTH)
head(rn4.ensGene.LENGTH)
```

---

rn4.geneid.LENGTH	<i>Transcript length data for the organism rn</i>
-------------------	---

---

### Description

rn4.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneid.LENGTH)
head(rn4.geneid.LENGTH)
```



---

rn4.geneSymbol.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneSymbol.LENGTH)
head(rn4.geneSymbol.LENGTH)
```

---

rn4.genscan.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.genscan.LENGTH)
head(rn4.genscan.LENGTH)
```

---

rn4.knownGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.knownGene.LENGTH)
head(rn4.knownGene.LENGTH)
```

---

rn4.nscanGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.nscanGene.LENGTH)
head(rn4.nscanGene.LENGTH)
```

---

rn4.refGene.LENGTH	<i>Transcript length data for the organism rn</i>
--------------------	---

---

### Description

rn4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.refGene.LENGTH)
head(rn4.refGene.LENGTH)
```

---

rn4.sgpGene.LENGTH	<i>Transcript length data for the organism rn</i>
--------------------	---

---

### Description

rn4.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.sgpGene.LENGTH)
head(rn4.sgpGene.LENGTH)
```

---

`rn4.xenoRefGene.LENGTH`*Transcript length data for the organism rn*

---

**Description**

`rn4.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(rn4, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(rn4.xenoRefGene.LENGTH)
head(rn4.xenoRefGene.LENGTH)
```

---

`sacCer1.ensGene.LENGTH`*Transcript length data for the organism sacCer*

---

**Description**

`sacCer1.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(sacCer1, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(sacCer1.ensGene.LENGTH)
head(sacCer1.ensGene.LENGTH)
```

---

`sacCer2.ensGene.LENGTH`*Transcript length data for the organism sacCer*

---

**Description**

sacCer2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(sacCer2.ensGene.LENGTH)
head(sacCer2.ensGene.LENGTH)
```

---

`strPur1.geneSymbol.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.geneSymbol.LENGTH)
head(strPur1.geneSymbol.LENGTH)
```

---

`strPur1.genscan.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.genscan.LENGTH)
head(strPur1.genscan.LENGTH)
```

---

`strPur1.refGene.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.refGene.LENGTH)
head(strPur1.refGene.LENGTH)
```

---

`strPur1.xenoRefGene.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.xenoRefGene.LENGTH)
head(strPur1.xenoRefGene.LENGTH)
```

---

`strPur2.geneSymbol.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur2.geneSymbol.LENGTH)
head(strPur2.geneSymbol.LENGTH)
```

---

`strPur2.genscan.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur2.genscan.LENGTH)
head(strPur2.genscan.LENGTH)
```

---

`strPur2.refGene.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur2.refGene.LENGTH)
head(strPur2.refGene.LENGTH)
```



---

strPur2.xenoRefGene.LENGTH
<i>Transcript length data for the organism strPur</i>

---

**Description**

strPur2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling downloadLengthFromUCSC(strPur2, xenoRefGene) on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(strPur2.xenoRefGene.LENGTH)
head(strPur2.xenoRefGene.LENGTH)
```

---

supportedGeneIDs	<i>Supported Gene IDs</i>
------------------	---------------------------

---

**Description**

Lists supported gene ID formats

**Usage**

```
supportedGeneIDs()
```

**Details**

Uses the supportedUCSCTables function from the GenomicFeatures package to obtain a list of gene ID formats available from the UCSC genome browser. The db column gives the gene ID formats which are provided to the id argument of various functions. The track and subtrack columns are the names of the UCSC track/subtrack from which information is fetched.

The GeneID column lists the "full name" of the gene ID format where available.

The final column, headed AvailableGenomes lists the genomes for which there is a local copy of the length information available for the gene ID format listed in the geneLenDataBase package.

**Value**

A data.frame containing supported gene ID formats.

**Author(s)**

Matthew D. Young <myoung@wehi.edu.au>

**Examples**

```
supportedGeneIDs()
```

---

supportedGenomes

*Supported Genomes*

---

**Description**

Lists supported genomes

**Usage**

```
supportedGenomes()
```

**Details**

Uses the `ucscGenomes()` function from the `rtracklayer` package to obtain a list of genomes available from the UCSC genome browser. The `db` column lists genomes as they are provided to the genome argument of various functions.

The final column, headed `AvailableGeneIDs` lists the gene ID formats for which there is a local copy of the length information available for the genome listed in the `geneLenDataBase` package.

**Value**

A `data.frame` containing supported genomes.

**Author(s)**

Matthew D. Young <myoung@wehi.edu.au>

**Examples**

```
supportedGenomes()
```

---

`taeGut1.ensGene.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.ensGene.LENGTH)
head(taeGut1.ensGene.LENGTH)
```

---

`taeGut1.geneSymbol.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.geneSymbol.LENGTH)
head(taeGut1.geneSymbol.LENGTH)
```

---

`taeGut1.genscan.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.genscan.LENGTH)
head(taeGut1.genscan.LENGTH)
```

---

`taeGut1.nscanGene.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.nscanGene.LENGTH)
head(taeGut1.nscanGene.LENGTH)
```

---

`taeGut1.refGene.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.refGene.LENGTH)
head(taeGut1.refGene.LENGTH)
```

---

`taeGut1.xenoRefGene.LENGTH`*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.xenoRefGene.LENGTH)
head(taeGut1.xenoRefGene.LENGTH)
```

---

`tetNig1.ensGene.LENGTH`*Transcript length data for the organism tetNig*

---

**Description**

tetNig1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(tetNig1.ensGene.LENGTH)
head(tetNig1.ensGene.LENGTH)
```

---

`tetNig1.geneid.LENGTH` *Transcript length data for the organism tetNig*

---

**Description**

tetNig1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(tetNig1.geneid.LENGTH)
head(tetNig1.geneid.LENGTH)
```

---

`tetNig1.genscan.LENGTH`*Transcript length data for the organism tetNig*

---

**Description**

tetNig1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(tetNig1.genscan.LENGTH)
head(tetNig1.genscan.LENGTH)
```

---

`tetNig1.nscanGene.LENGTH`*Transcript length data for the organism tetNig*

---

**Description**

tetNig1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(tetNig1.nscanGene.LENGTH)
head(tetNig1.nscanGene.LENGTH)
```

---

```
tetNig2.ensGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig2.ensGene.LENGTH)
head(tetNig2.ensGene.LENGTH)
```

---

```
unfactor
```

*Purge factors*

---

### Description

Removes all factors from a variable in a sensible way.

### Usage

```
unfactor(var)
```

### Arguments

`var`                      The variable from which you want the factors removed.

### Details

As factors are their own type, to remove factors we must convert each level into another type. This is currently done using "typeless" behaviour: a factor is converted to a numeric vector if this can be done without inducing NAs, otherwise it is coerced using `as.character`. Currently supported types are: `/codefactor`, `/codedata.frame` and `/codelist`.



**Value**

The variable with all factors converted to characters or numbers (see details).

**Author(s)**

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**Examples**

```
#A named factor
x <- factor(sample(1:6, 100, replace=TRUE))
names(x) <- paste("Roll.No", 1:100, sep='.')
x
unfactor(x)

#A data.frame
x <- data.frame(player <- c("Alice", "Bob", "Mary", "Fred"), score <- factor(c(9, 7, 8, 9)), stringsAsFactors=TRUE)
x$player
x$score
y <- unfactor(x)
y$player
y$score
```

---

xenTro1.genscan.LENGTH

*Transcript length data for the organism xenTro*

---

**Description**

xenTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro1, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro1.genscan.LENGTH)
head(xenTro1.genscan.LENGTH)
```

---

`xenTro2.ensGene.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

`xenTro2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.ensGene.LENGTH)
head(xenTro2.ensGene.LENGTH)
```

---

`xenTro2.geneSymbol.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

`xenTro2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, geneSymbol)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.geneSymbol.LENGTH)
head(xenTro2.geneSymbol.LENGTH)
```

---

`xenTro2.genscan.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.genscan.LENGTH)
head(xenTro2.genscan.LENGTH)
```

---

`xenTro2.refGene.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.refGene.LENGTH)
head(xenTro2.refGene.LENGTH)
```

# Index

## \* datasets

anoCar1.ensGene.LENGTH, 9  
anoCar1.genscan.LENGTH, 9  
anoCar1.xenoRefGene.LENGTH, 10  
anoGam1.ensGene.LENGTH, 10  
anoGam1.geneid.LENGTH, 11  
anoGam1.genscan.LENGTH, 11  
apiMel1.genscan.LENGTH, 12  
apiMel2.ensGene.LENGTH, 12  
apiMel2.geneid.LENGTH, 13  
apiMel2.genscan.LENGTH, 13  
aplCal1.xenoRefGene.LENGTH, 14  
bosTau2.geneid.LENGTH, 14  
bosTau2.geneSymbol.LENGTH, 15  
bosTau2.genscan.LENGTH, 15  
bosTau2.refGene.LENGTH, 16  
bosTau2.sgpGene.LENGTH, 16  
bosTau3.ensGene.LENGTH, 17  
bosTau3.geneid.LENGTH, 17  
bosTau3.geneSymbol.LENGTH, 18  
bosTau3.genscan.LENGTH, 18  
bosTau3.refGene.LENGTH, 19  
bosTau3.sgpGene.LENGTH, 19  
bosTau4.ensGene.LENGTH, 20  
bosTau4.geneSymbol.LENGTH, 20  
bosTau4.genscan.LENGTH, 21  
bosTau4.nscanGene.LENGTH, 21  
bosTau4.refGene.LENGTH, 22  
braFlo1.xenoRefGene.LENGTH, 22  
caeJap1.xenoRefGene.LENGTH, 23  
caePb1.xenoRefGene.LENGTH, 23  
caePb2.xenoRefGene.LENGTH, 24  
caeRem2.xenoRefGene.LENGTH, 24  
caeRem3.xenoRefGene.LENGTH, 25  
calJac1.genscan.LENGTH, 25  
calJac1.nscanGene.LENGTH, 26  
calJac1.xenoRefGene.LENGTH, 26  
canFam1.ensGene.LENGTH, 27  
canFam1.geneSymbol.LENGTH, 27

canFam1.genscan.LENGTH, 28  
canFam1.nscanGene.LENGTH, 28  
canFam1.refGene.LENGTH, 29  
canFam1.xenoRefGene.LENGTH, 29  
canFam2.ensGene.LENGTH, 30  
canFam2.geneSymbol.LENGTH, 30  
canFam2.genscan.LENGTH, 31  
canFam2.nscanGene.LENGTH, 31  
canFam2.refGene.LENGTH, 32  
canFam2.xenoRefGene.LENGTH, 32  
cavPor3.ensGene.LENGTH, 33  
cavPor3.genscan.LENGTH, 33  
cavPor3.nscanGene.LENGTH, 34  
cavPor3.xenoRefGene.LENGTH, 34  
cb1.xenoRefGene.LENGTH, 35  
cb3.xenoRefGene.LENGTH, 35  
ce2.geneid.LENGTH, 36  
ce2.geneSymbol.LENGTH, 36  
ce2.refGene.LENGTH, 37  
ce4.geneSymbol.LENGTH, 37  
ce4.refGene.LENGTH, 38  
ce4.xenoRefGene.LENGTH, 38  
ce6.ensGene.LENGTH, 39  
ce6.geneSymbol.LENGTH, 39  
ce6.refGene.LENGTH, 40  
ce6.xenoRefGene.LENGTH, 40  
ci1.geneSymbol.LENGTH, 41  
ci1.refGene.LENGTH, 41  
ci1.xenoRefGene.LENGTH, 42  
ci2.ensGene.LENGTH, 42  
ci2.geneSymbol.LENGTH, 43  
ci2.refGene.LENGTH, 43  
ci2.xenoRefGene.LENGTH, 44  
danRer3.ensGene.LENGTH, 44  
danRer3.geneSymbol.LENGTH, 45  
danRer3.refGene.LENGTH, 45  
danRer4.ensGene.LENGTH, 46  
danRer4.geneSymbol.LENGTH, 46  
danRer4.genscan.LENGTH, 47

danRer4.nscanGene.LENGTH, 47  
danRer4.refGene.LENGTH, 48  
danRer5.ensGene.LENGTH, 48  
danRer5.geneSymbol.LENGTH, 49  
danRer5.refGene.LENGTH, 49  
danRer5.vegaGene.LENGTH, 50  
danRer5.vegaPseudoGene.LENGTH, 50  
danRer6.ensGene.LENGTH, 51  
danRer6.geneSymbol.LENGTH, 51  
danRer6.refGene.LENGTH, 52  
danRer6.xenoRefGene.LENGTH, 52  
dm1.geneSymbol.LENGTH, 53  
dm1.genscan.LENGTH, 53  
dm1.refGene.LENGTH, 54  
dm2.geneid.LENGTH, 54  
dm2.geneSymbol.LENGTH, 55  
dm2.genscan.LENGTH, 55  
dm2.nscanGene.LENGTH, 56  
dm2.refGene.LENGTH, 56  
dm3.geneSymbol.LENGTH, 57  
dm3.nscanPasaGene.LENGTH, 57  
dm3.refGene.LENGTH, 58  
dp2.genscan.LENGTH, 58  
dp2.xenoRefGene.LENGTH, 59  
dp3.geneid.LENGTH, 59  
dp3.genscan.LENGTH, 60  
dp3.xenoRefGene.LENGTH, 60  
droAna1.geneid.LENGTH, 61  
droAna1.genscan.LENGTH, 61  
droAna1.xenoRefGene.LENGTH, 62  
droAna2.genscan.LENGTH, 62  
droAna2.xenoRefGene.LENGTH, 63  
droEre1.genscan.LENGTH, 63  
droEre1.xenoRefGene.LENGTH, 64  
droGri1.genscan.LENGTH, 64  
droGri1.xenoRefGene.LENGTH, 65  
droMoj1.geneid.LENGTH, 65  
droMoj1.genscan.LENGTH, 66  
droMoj1.xenoRefGene.LENGTH, 66  
droMoj2.genscan.LENGTH, 67  
droMoj2.xenoRefGene.LENGTH, 67  
droPer1.genscan.LENGTH, 68  
droPer1.xenoRefGene.LENGTH, 68  
droSec1.genscan.LENGTH, 69  
droSec1.xenoRefGene.LENGTH, 69  
droSim1.geneid.LENGTH, 70  
droSim1.genscan.LENGTH, 70  
droSim1.xenoRefGene.LENGTH, 71  
droVir1.geneid.LENGTH, 71  
droVir1.genscan.LENGTH, 72  
droVir1.xenoRefGene.LENGTH, 72  
droVir2.genscan.LENGTH, 73  
droVir2.xenoRefGene.LENGTH, 73  
droYak1.geneid.LENGTH, 74  
droYak1.genscan.LENGTH, 74  
droYak1.xenoRefGene.LENGTH, 75  
droYak2.genscan.LENGTH, 75  
droYak2.xenoRefGene.LENGTH, 76  
equCab1.geneid.LENGTH, 76  
equCab1.geneSymbol.LENGTH, 77  
equCab1.nscanGene.LENGTH, 77  
equCab1.refGene.LENGTH, 78  
equCab1.sgpGene.LENGTH, 78  
equCab2.ensGene.LENGTH, 79  
equCab2.geneSymbol.LENGTH, 79  
equCab2.nscanGene.LENGTH, 80  
equCab2.refGene.LENGTH, 80  
equCab2.xenoRefGene.LENGTH, 81  
felCat3.ensGene.LENGTH, 81  
felCat3.geneid.LENGTH, 82  
felCat3.geneSymbol.LENGTH, 82  
felCat3.genscan.LENGTH, 83  
felCat3.nscanGene.LENGTH, 83  
felCat3.refGene.LENGTH, 84  
felCat3.sgpGene.LENGTH, 84  
felCat3.xenoRefGene.LENGTH, 85  
fr1.ensGene.LENGTH, 85  
fr1.genscan.LENGTH, 86  
fr2.ensGene.LENGTH, 86  
galGal2.ensGene.LENGTH, 87  
galGal2.geneid.LENGTH, 87  
galGal2.geneSymbol.LENGTH, 88  
galGal2.genscan.LENGTH, 88  
galGal2.refGene.LENGTH, 89  
galGal2.sgpGene.LENGTH, 89  
galGal3.ensGene.LENGTH, 90  
galGal3.geneSymbol.LENGTH, 90  
galGal3.genscan.LENGTH, 91  
galGal3.nscanGene.LENGTH, 91  
galGal3.refGene.LENGTH, 92  
galGal3.xenoRefGene.LENGTH, 92  
gasAcu1.ensGene.LENGTH, 93  
gasAcu1.nscanGene.LENGTH, 93  
hg16.acembly.LENGTH, 94  
hg16.ensGene.LENGTH, 94  
hg16.exoniphy.LENGTH, 95

hg16.geneid.LENGTH, 95  
 hg16.geneSymbol.LENGTH, 96  
 hg16.genscan.LENGTH, 96  
 hg16.knownGene.LENGTH, 97  
 hg16.refGene.LENGTH, 97  
 hg16.sgpGene.LENGTH, 98  
 hg17.acembly.LENGTH, 98  
 hg17.acescan.LENGTH, 99  
 hg17.ccdsGene.LENGTH, 99  
 hg17.ensGene.LENGTH, 100  
 hg17.exoniphy.LENGTH, 100  
 hg17.geneid.LENGTH, 101  
 hg17.geneSymbol.LENGTH, 101  
 hg17.genscan.LENGTH, 102  
 hg17.knownGene.LENGTH, 102  
 hg17.refGene.LENGTH, 103  
 hg17.sgpGene.LENGTH, 103  
 hg17.vegaGene.LENGTH, 104  
 hg17.vegaPseudoGene.LENGTH, 104  
 hg17.xenoRefGene.LENGTH, 105  
 hg18.acembly.LENGTH, 105  
 hg18.acescan.LENGTH, 106  
 hg18.ccdsGene.LENGTH, 106  
 hg18.ensGene.LENGTH, 107  
 hg18.exoniphy.LENGTH, 107  
 hg18.geneid.LENGTH, 108  
 hg18.geneSymbol.LENGTH, 108  
 hg18.genscan.LENGTH, 109  
 hg18.knownGene.LENGTH, 109  
 hg18.knownGeneOld3.LENGTH, 110  
 hg18.refGene.LENGTH, 110  
 hg18.sgpGene.LENGTH, 111  
 hg18.sibGene.LENGTH, 111  
 hg18.xenoRefGene.LENGTH, 112  
 hg19.ccdsGene.LENGTH, 112  
 hg19.ensGene.LENGTH, 113  
 hg19.exoniphy.LENGTH, 113  
 hg19.geneSymbol.LENGTH, 114  
 hg19.knownGene.LENGTH, 114  
 hg19.nscanGene.LENGTH, 115  
 hg19.refGene.LENGTH, 115  
 hg19.xenoRefGene.LENGTH, 116  
 loxAfr3.xenoRefGene.LENGTH, 116  
 mm7.ensGene.LENGTH, 117  
 mm7.geneid.LENGTH, 117  
 mm7.geneSymbol.LENGTH, 118  
 mm7.genscan.LENGTH, 118  
 mm7.knownGene.LENGTH, 119  
 mm7.refGene.LENGTH, 119  
 mm7.sgpGene.LENGTH, 120  
 mm7.xenoRefGene.LENGTH, 120  
 mm8.ccdsGene.LENGTH, 121  
 mm8.ensGene.LENGTH, 121  
 mm8.geneid.LENGTH, 122  
 mm8.geneSymbol.LENGTH, 122  
 mm8.genscan.LENGTH, 123  
 mm8.knownGene.LENGTH, 123  
 mm8.nscanGene.LENGTH, 124  
 mm8.refGene.LENGTH, 124  
 mm8.sgpGene.LENGTH, 125  
 mm8.sibGene.LENGTH, 125  
 mm8.xenoRefGene.LENGTH, 126  
 mm9.acembly.LENGTH, 126  
 mm9.ccdsGene.LENGTH, 127  
 mm9.ensGene.LENGTH, 127  
 mm9.exoniphy.LENGTH, 128  
 mm9.geneid.LENGTH, 128  
 mm9.geneSymbol.LENGTH, 129  
 mm9.genscan.LENGTH, 129  
 mm9.knownGene.LENGTH, 130  
 mm9.nscanGene.LENGTH, 130  
 mm9.refGene.LENGTH, 131  
 mm9.sgpGene.LENGTH, 131  
 mm9.xenoRefGene.LENGTH, 132  
 monDom1.genscan.LENGTH, 132  
 monDom4.ensGene.LENGTH, 133  
 monDom4.geneSymbol.LENGTH, 133  
 monDom4.genscan.LENGTH, 134  
 monDom4.nscanGene.LENGTH, 134  
 monDom4.refGene.LENGTH, 135  
 monDom4.xenoRefGene.LENGTH, 135  
 monDom5.ensGene.LENGTH, 136  
 monDom5.geneSymbol.LENGTH, 136  
 monDom5.genscan.LENGTH, 137  
 monDom5.nscanGene.LENGTH, 137  
 monDom5.refGene.LENGTH, 138  
 monDom5.xenoRefGene.LENGTH, 138  
 ornAna1.ensGene.LENGTH, 139  
 ornAna1.geneSymbol.LENGTH, 139  
 ornAna1.refGene.LENGTH, 140  
 ornAna1.xenoRefGene.LENGTH, 140  
 oryLat2.ensGene.LENGTH, 141  
 oryLat2.geneSymbol.LENGTH, 141  
 oryLat2.refGene.LENGTH, 142  
 oryLat2.xenoRefGene.LENGTH, 142  
 panTro1.ensGene.LENGTH, 143

panTro1.geneid.LENGTH, 143  
 panTro1.genscan.LENGTH, 144  
 panTro1.xenoRefGene.LENGTH, 144  
 panTro2.ensGene.LENGTH, 145  
 panTro2.geneSymbol.LENGTH, 145  
 panTro2.genscan.LENGTH, 146  
 panTro2.nscanGene.LENGTH, 146  
 panTro2.refGene.LENGTH, 147  
 panTro2.xenoRefGene.LENGTH, 147  
 petMar1.xenoRefGene.LENGTH, 148  
 ponAbe2.ensGene.LENGTH, 148  
 ponAbe2.geneSymbol.LENGTH, 149  
 ponAbe2.genscan.LENGTH, 149  
 ponAbe2.nscanGene.LENGTH, 150  
 ponAbe2.refGene.LENGTH, 150  
 ponAbe2.xenoRefGene.LENGTH, 151  
 priPac1.xenoRefGene.LENGTH, 151  
 rheMac2.ensGene.LENGTH, 152  
 rheMac2.geneid.LENGTH, 152  
 rheMac2.geneSymbol.LENGTH, 153  
 rheMac2.nscanGene.LENGTH, 153  
 rheMac2.refGene.LENGTH, 154  
 rheMac2.sgpGene.LENGTH, 154  
 rheMac2.xenoRefGene.LENGTH, 155  
 rn3.ensGene.LENGTH, 155  
 rn3.geneid.LENGTH, 156  
 rn3.geneSymbol.LENGTH, 156  
 rn3.genscan.LENGTH, 157  
 rn3.knownGene.LENGTH, 157  
 rn3.nscanGene.LENGTH, 158  
 rn3.refGene.LENGTH, 158  
 rn3.sgpGene.LENGTH, 159  
 rn3.xenoRefGene.LENGTH, 159  
 rn4.ensGene.LENGTH, 160  
 rn4.geneid.LENGTH, 160  
 rn4.geneSymbol.LENGTH, 161  
 rn4.genscan.LENGTH, 161  
 rn4.knownGene.LENGTH, 162  
 rn4.nscanGene.LENGTH, 162  
 rn4.refGene.LENGTH, 163  
 rn4.sgpGene.LENGTH, 163  
 rn4.xenoRefGene.LENGTH, 164  
 sacCer1.ensGene.LENGTH, 164  
 sacCer2.ensGene.LENGTH, 165  
 strPur1.geneSymbol.LENGTH, 165  
 strPur1.genscan.LENGTH, 166  
 strPur1.refGene.LENGTH, 166  
 strPur1.xenoRefGene.LENGTH, 167  
 strPur2.geneSymbol.LENGTH, 167  
 strPur2.genscan.LENGTH, 168  
 strPur2.refGene.LENGTH, 168  
 strPur2.xenoRefGene.LENGTH, 169  
 taeGut1.ensGene.LENGTH, 171  
 taeGut1.geneSymbol.LENGTH, 171  
 taeGut1.genscan.LENGTH, 172  
 taeGut1.nscanGene.LENGTH, 172  
 taeGut1.refGene.LENGTH, 173  
 taeGut1.xenoRefGene.LENGTH, 173  
 tetNig1.ensGene.LENGTH, 174  
 tetNig1.geneid.LENGTH, 174  
 tetNig1.genscan.LENGTH, 175  
 tetNig1.nscanGene.LENGTH, 175  
 tetNig2.ensGene.LENGTH, 176  
 xenTro1.genscan.LENGTH, 177  
 xenTro2.ensGene.LENGTH, 178  
 xenTro2.geneSymbol.LENGTH, 178  
 xenTro2.genscan.LENGTH, 179  
 xenTro2.refGene.LENGTH, 179  
 anoCar1.ensGene.LENGTH, 9  
 anoCar1.genscan.LENGTH, 9  
 anoCar1.xenoRefGene.LENGTH, 10  
 anoGam1.ensGene.LENGTH, 10  
 anoGam1.geneid.LENGTH, 11  
 anoGam1.genscan.LENGTH, 11  
 apiMel1.genscan.LENGTH, 12  
 apiMel2.ensGene.LENGTH, 12  
 apiMel2.geneid.LENGTH, 13  
 apiMel2.genscan.LENGTH, 13  
 aplCal1.xenoRefGene.LENGTH, 14  
 bosTau2.geneid.LENGTH, 14  
 bosTau2.geneSymbol.LENGTH, 15  
 bosTau2.genscan.LENGTH, 15  
 bosTau2.refGene.LENGTH, 16  
 bosTau2.sgpGene.LENGTH, 16  
 bosTau3.ensGene.LENGTH, 17  
 bosTau3.geneid.LENGTH, 17  
 bosTau3.geneSymbol.LENGTH, 18  
 bosTau3.genscan.LENGTH, 18  
 bosTau3.refGene.LENGTH, 19  
 bosTau3.sgpGene.LENGTH, 19  
 bosTau4.ensGene.LENGTH, 20  
 bosTau4.geneSymbol.LENGTH, 20  
 bosTau4.genscan.LENGTH, 21  
 bosTau4.nscanGene.LENGTH, 21  
 bosTau4.refGene.LENGTH, 22

- braFlo1.xenoRefGene.LENGTH, 22
- caeJap1.xenoRefGene.LENGTH, 23
- caePb1.xenoRefGene.LENGTH, 23
- caePb2.xenoRefGene.LENGTH, 24
- caeRem2.xenoRefGene.LENGTH, 24
- caeRem3.xenoRefGene.LENGTH, 25
- calJac1.genscan.LENGTH, 25
- calJac1.nscanGene.LENGTH, 26
- calJac1.xenoRefGene.LENGTH, 26
- canFam1.ensGene.LENGTH, 27
- canFam1.geneSymbol.LENGTH, 27
- canFam1.genscan.LENGTH, 28
- canFam1.nscanGene.LENGTH, 28
- canFam1.refGene.LENGTH, 29
- canFam1.xenoRefGene.LENGTH, 29
- canFam2.ensGene.LENGTH, 30
- canFam2.geneSymbol.LENGTH, 30
- canFam2.genscan.LENGTH, 31
- canFam2.nscanGene.LENGTH, 31
- canFam2.refGene.LENGTH, 32
- canFam2.xenoRefGene.LENGTH, 32
- cavPor3.ensGene.LENGTH, 33
- cavPor3.genscan.LENGTH, 33
- cavPor3.nscanGene.LENGTH, 34
- cavPor3.xenoRefGene.LENGTH, 34
- cb1.xenoRefGene.LENGTH, 35
- cb3.xenoRefGene.LENGTH, 35
- ce2.geneid.LENGTH, 36
- ce2.geneSymbol.LENGTH, 36
- ce2.refGene.LENGTH, 37
- ce4.geneSymbol.LENGTH, 37
- ce4.refGene.LENGTH, 38
- ce4.xenoRefGene.LENGTH, 38
- ce6.ensGene.LENGTH, 39
- ce6.geneSymbol.LENGTH, 39
- ce6.refGene.LENGTH, 40
- ce6.xenoRefGene.LENGTH, 40
- ci1.geneSymbol.LENGTH, 41
- ci1.refGene.LENGTH, 41
- ci1.xenoRefGene.LENGTH, 42
- ci2.ensGene.LENGTH, 42
- ci2.geneSymbol.LENGTH, 43
- ci2.refGene.LENGTH, 43
- ci2.xenoRefGene.LENGTH, 44
- danRer3.ensGene.LENGTH, 44
- danRer3.geneSymbol.LENGTH, 45
- danRer3.refGene.LENGTH, 45
- danRer4.ensGene.LENGTH, 46
- danRer4.geneSymbol.LENGTH, 46
- danRer4.genscan.LENGTH, 47
- danRer4.nscanGene.LENGTH, 47
- danRer4.refGene.LENGTH, 48
- danRer5.ensGene.LENGTH, 48
- danRer5.geneSymbol.LENGTH, 49
- danRer5.refGene.LENGTH, 49
- danRer5.vegaGene.LENGTH, 50
- danRer5.vegaPseudoGene.LENGTH, 50
- danRer6.ensGene.LENGTH, 51
- danRer6.geneSymbol.LENGTH, 51
- danRer6.refGene.LENGTH, 52
- danRer6.xenoRefGene.LENGTH, 52
- dm1.geneSymbol.LENGTH, 53
- dm1.genscan.LENGTH, 53
- dm1.refGene.LENGTH, 54
- dm2.geneid.LENGTH, 54
- dm2.geneSymbol.LENGTH, 55
- dm2.genscan.LENGTH, 55
- dm2.nscanGene.LENGTH, 56
- dm2.refGene.LENGTH, 56
- dm3.geneSymbol.LENGTH, 57
- dm3.nscanPasaGene.LENGTH, 57
- dm3.refGene.LENGTH, 58
- downloadLengthFromUCSC, 9–169, 171–179
- dp2.genscan.LENGTH, 58
- dp2.xenoRefGene.LENGTH, 59
- dp3.geneid.LENGTH, 59
- dp3.genscan.LENGTH, 60
- dp3.xenoRefGene.LENGTH, 60
- droAna1.geneid.LENGTH, 61
- droAna1.genscan.LENGTH, 61
- droAna1.xenoRefGene.LENGTH, 62
- droAna2.genscan.LENGTH, 62
- droAna2.xenoRefGene.LENGTH, 63
- droEre1.genscan.LENGTH, 63
- droEre1.xenoRefGene.LENGTH, 64
- droGri1.genscan.LENGTH, 64
- droGri1.xenoRefGene.LENGTH, 65
- droMoj1.geneid.LENGTH, 65
- droMoj1.genscan.LENGTH, 66
- droMoj1.xenoRefGene.LENGTH, 66
- droMoj2.genscan.LENGTH, 67
- droMoj2.xenoRefGene.LENGTH, 67
- droPer1.genscan.LENGTH, 68
- droPer1.xenoRefGene.LENGTH, 68
- droSec1.genscan.LENGTH, 69



- droSec1.xenoRefGene.LENGTH, 69  
droSim1.geneid.LENGTH, 70  
droSim1.genscan.LENGTH, 70  
droSim1.xenoRefGene.LENGTH, 71  
droVir1.geneid.LENGTH, 71  
droVir1.genscan.LENGTH, 72  
droVir1.xenoRefGene.LENGTH, 72  
droVir2.genscan.LENGTH, 73  
droVir2.xenoRefGene.LENGTH, 73  
droYak1.geneid.LENGTH, 74  
droYak1.genscan.LENGTH, 74  
droYak1.xenoRefGene.LENGTH, 75  
droYak2.genscan.LENGTH, 75  
droYak2.xenoRefGene.LENGTH, 76
- equCab1.geneid.LENGTH, 76  
equCab1.geneSymbol.LENGTH, 77  
equCab1.nscanGene.LENGTH, 77  
equCab1.refGene.LENGTH, 78  
equCab1.sgpGene.LENGTH, 78  
equCab2.ensGene.LENGTH, 79  
equCab2.geneSymbol.LENGTH, 79  
equCab2.nscanGene.LENGTH, 80  
equCab2.refGene.LENGTH, 80  
equCab2.xenoRefGene.LENGTH, 81
- felCat3.ensGene.LENGTH, 81  
felCat3.geneid.LENGTH, 82  
felCat3.geneSymbol.LENGTH, 82  
felCat3.genscan.LENGTH, 83  
felCat3.nscanGene.LENGTH, 83  
felCat3.refGene.LENGTH, 84  
felCat3.sgpGene.LENGTH, 84  
felCat3.xenoRefGene.LENGTH, 85  
fr1.ensGene.LENGTH, 85  
fr1.genscan.LENGTH, 86  
fr2.ensGene.LENGTH, 86
- galGal2.ensGene.LENGTH, 87  
galGal2.geneid.LENGTH, 87  
galGal2.geneSymbol.LENGTH, 88  
galGal2.genscan.LENGTH, 88  
galGal2.refGene.LENGTH, 89  
galGal2.sgpGene.LENGTH, 89  
galGal3.ensGene.LENGTH, 90  
galGal3.geneSymbol.LENGTH, 90  
galGal3.genscan.LENGTH, 91  
galGal3.nscanGene.LENGTH, 91  
galGal3.refGene.LENGTH, 92
- galGal3.xenoRefGene.LENGTH, 92  
gasAcu1.ensGene.LENGTH, 93  
gasAcu1.nscanGene.LENGTH, 93
- hg16.acembly.LENGTH, 94  
hg16.ensGene.LENGTH, 94  
hg16.exoniphy.LENGTH, 95  
hg16.geneid.LENGTH, 95  
hg16.geneSymbol.LENGTH, 96  
hg16.genscan.LENGTH, 96  
hg16.knownGene.LENGTH, 97  
hg16.refGene.LENGTH, 97  
hg16.sgpGene.LENGTH, 98  
hg17.acembly.LENGTH, 98  
hg17.acescan.LENGTH, 99  
hg17.ccdsGene.LENGTH, 99  
hg17.ensGene.LENGTH, 100  
hg17.exoniphy.LENGTH, 100  
hg17.geneid.LENGTH, 101  
hg17.geneSymbol.LENGTH, 101  
hg17.genscan.LENGTH, 102  
hg17.knownGene.LENGTH, 102  
hg17.refGene.LENGTH, 103  
hg17.sgpGene.LENGTH, 103  
hg17.vegaGene.LENGTH, 104  
hg17.vegaPseudoGene.LENGTH, 104  
hg17.xenoRefGene.LENGTH, 105  
hg18.acembly.LENGTH, 105  
hg18.acescan.LENGTH, 106  
hg18.ccdsGene.LENGTH, 106  
hg18.ensGene.LENGTH, 107  
hg18.exoniphy.LENGTH, 107  
hg18.geneid.LENGTH, 108  
hg18.geneSymbol.LENGTH, 108  
hg18.genscan.LENGTH, 109  
hg18.knownGene.LENGTH, 109  
hg18.knownGeneOld3.LENGTH, 110  
hg18.refGene.LENGTH, 110  
hg18.sgpGene.LENGTH, 111  
hg18.sibGene.LENGTH, 111  
hg18.xenoRefGene.LENGTH, 112  
hg19.ccdsGene.LENGTH, 112  
hg19.ensGene.LENGTH, 113  
hg19.exoniphy.LENGTH, 113  
hg19.geneSymbol.LENGTH, 114  
hg19.knownGene.LENGTH, 114  
hg19.nscanGene.LENGTH, 115  
hg19.refGene.LENGTH, 115  
hg19.xenoRefGene.LENGTH, 116

loxAfr3.xenoRefGene.LENGTH, 116

mm7.ensGene.LENGTH, 117

mm7.geneid.LENGTH, 117

mm7.geneSymbol.LENGTH, 118

mm7.genscan.LENGTH, 118

mm7.knownGene.LENGTH, 119

mm7.refGene.LENGTH, 119

mm7.sgpGene.LENGTH, 120

mm7.xenoRefGene.LENGTH, 120

mm8.ccdsGene.LENGTH, 121

mm8.ensGene.LENGTH, 121

mm8.geneid.LENGTH, 122

mm8.geneSymbol.LENGTH, 122

mm8.genscan.LENGTH, 123

mm8.knownGene.LENGTH, 123

mm8.nscanGene.LENGTH, 124

mm8.refGene.LENGTH, 124

mm8.sgpGene.LENGTH, 125

mm8.sibGene.LENGTH, 125

mm8.xenoRefGene.LENGTH, 126

mm9.acembly.LENGTH, 126

mm9.ccdsGene.LENGTH, 127

mm9.ensGene.LENGTH, 127

mm9.exoniphy.LENGTH, 128

mm9.geneid.LENGTH, 128

mm9.geneSymbol.LENGTH, 129

mm9.genscan.LENGTH, 129

mm9.knownGene.LENGTH, 130

mm9.nscanGene.LENGTH, 130

mm9.refGene.LENGTH, 131

mm9.sgpGene.LENGTH, 131

mm9.xenoRefGene.LENGTH, 132

monDom1.genscan.LENGTH, 132

monDom4.ensGene.LENGTH, 133

monDom4.geneSymbol.LENGTH, 133

monDom4.genscan.LENGTH, 134

monDom4.nscanGene.LENGTH, 134

monDom4.refGene.LENGTH, 135

monDom4.xenoRefGene.LENGTH, 135

monDom5.ensGene.LENGTH, 136

monDom5.geneSymbol.LENGTH, 136

monDom5.genscan.LENGTH, 137

monDom5.nscanGene.LENGTH, 137

monDom5.refGene.LENGTH, 138

monDom5.xenoRefGene.LENGTH, 138

ornAna1.ensGene.LENGTH, 139

ornAna1.geneSymbol.LENGTH, 139

ornAna1.refGene.LENGTH, 140

ornAna1.xenoRefGene.LENGTH, 140

oryLat2.ensGene.LENGTH, 141

oryLat2.geneSymbol.LENGTH, 141

oryLat2.refGene.LENGTH, 142

oryLat2.xenoRefGene.LENGTH, 142

panTro1.ensGene.LENGTH, 143

panTro1.geneid.LENGTH, 143

panTro1.genscan.LENGTH, 144

panTro1.xenoRefGene.LENGTH, 144

panTro2.ensGene.LENGTH, 145

panTro2.geneSymbol.LENGTH, 145

panTro2.genscan.LENGTH, 146

panTro2.nscanGene.LENGTH, 146

panTro2.refGene.LENGTH, 147

panTro2.xenoRefGene.LENGTH, 147

petMar1.xenoRefGene.LENGTH, 148

ponAbe2.ensGene.LENGTH, 148

ponAbe2.geneSymbol.LENGTH, 149

ponAbe2.genscan.LENGTH, 149

ponAbe2.nscanGene.LENGTH, 150

ponAbe2.refGene.LENGTH, 150

ponAbe2.xenoRefGene.LENGTH, 151

priPac1.xenoRefGene.LENGTH, 151

rheMac2.ensGene.LENGTH, 152

rheMac2.geneid.LENGTH, 152

rheMac2.geneSymbol.LENGTH, 153

rheMac2.nscanGene.LENGTH, 153

rheMac2.refGene.LENGTH, 154

rheMac2.sgpGene.LENGTH, 154

rheMac2.xenoRefGene.LENGTH, 155

rn3.ensGene.LENGTH, 155

rn3.geneid.LENGTH, 156

rn3.geneSymbol.LENGTH, 156

rn3.genscan.LENGTH, 157

rn3.knownGene.LENGTH, 157

rn3.nscanGene.LENGTH, 158

rn3.refGene.LENGTH, 158

rn3.sgpGene.LENGTH, 159

rn3.xenoRefGene.LENGTH, 159

rn4.ensGene.LENGTH, 160

rn4.geneid.LENGTH, 160

rn4.geneSymbol.LENGTH, 161

rn4.genscan.LENGTH, 161

rn4.knownGene.LENGTH, 162

rn4.nscanGene.LENGTH, 162

rn4.refGene.LENGTH, 163

rn4.sgpGene.LENGTH, [163](#)  
rn4.xenoRefGene.LENGTH, [164](#)

sacCer1.ensGene.LENGTH, [164](#)  
sacCer2.ensGene.LENGTH, [165](#)  
strPur1.geneSymbol.LENGTH, [165](#)  
strPur1.genscan.LENGTH, [166](#)  
strPur1.refGene.LENGTH, [166](#)  
strPur1.xenoRefGene.LENGTH, [167](#)  
strPur2.geneSymbol.LENGTH, [167](#)  
strPur2.genscan.LENGTH, [168](#)  
strPur2.refGene.LENGTH, [168](#)  
strPur2.xenoRefGene.LENGTH, [169](#)  
supportedGeneIDs, [169](#)  
supportedGenomes, [170](#)

taeGut1.ensGene.LENGTH, [171](#)  
taeGut1.geneSymbol.LENGTH, [171](#)  
taeGut1.genscan.LENGTH, [172](#)  
taeGut1.nscanGene.LENGTH, [172](#)  
taeGut1.refGene.LENGTH, [173](#)  
taeGut1.xenoRefGene.LENGTH, [173](#)  
tetNig1.ensGene.LENGTH, [174](#)  
tetNig1.geneid.LENGTH, [174](#)  
tetNig1.genscan.LENGTH, [175](#)  
tetNig1.nscanGene.LENGTH, [175](#)  
tetNig2.ensGene.LENGTH, [176](#)

unfactor, [176](#)

xenTro1.genscan.LENGTH, [177](#)  
xenTro2.ensGene.LENGTH, [178](#)  
xenTro2.geneSymbol.LENGTH, [178](#)  
xenTro2.genscan.LENGTH, [179](#)  
xenTro2.refGene.LENGTH, [179](#)