

Package ‘ipdDb’

June 6, 2023

Title IPD IMGT/HLA and IPD KIR database for Homo sapiens

Description All alleles from the IPD IMGT/HLA

<<https://www.ebi.ac.uk/ipd/imgt/hla/>> and IPD KIR

<<https://www.ebi.ac.uk/ipd/kir/>> database for Homo sapiens.

Reference:

Robinson J, Maccari G, Marsh SGE, Walter L, Blokhuis J, Bimber B, Parham P,

De Groot NG, Bontrop RE, Guethlein LA, and Hammond JA

KIR Nomenclature in non-human species

Immunogenetics (2018), in preparation.

Version 1.19.0

Author Steffen Klasberg

Maintainer Steffen Klasberg <klasberg@dkms-lab.de>

Depends R (>= 3.5.0), methods, AnnotationDbi (>= 1.43.1),
AnnotationHub

Imports Biostrings, GenomicRanges, RSQLite, DBI, IRanges, stats,
assertthat

License Artistic-2.0

URL <https://github.com/DKMS-LSL/ipdDb>

BugReports <https://github.com/DKMS-LSL/ipdDb/issues/new>

organism Homo sapiens

species Homo sapiens

biocViews GenomicVariation, SequenceMatching, VariantAnnotation,
DataRepresentation,AnnotationHubSoftware

Suggests knitr, rmarkdown, testthat

RoxygenNote 6.1.0

Encoding UTF-8

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/ipdDb>

git_branch devel

git_last_commit 35dfef9

git_last_commit_date 2023-04-25

Date/Publication 2023-06-06

R topics documented:

| | |
|---|----------|
| getAlleles,Ipddb-method | 2 |
| getClosestComplete,Ipddb-method | 3 |
| getLoci,Ipddb-method | 3 |
| getReference,Ipddb-method | 4 |
| getStructure,Ipddb-method | 5 |
| Ipddb-class | 5 |
| ipddbPackage | 7 |
| loadHlaData | 7 |
| loadKirData | 8 |
| Index | 9 |

getAlleles, Ipddb-method

Get alleles

Description

Get all alleles of a given locus.

Usage

```
getAlleles(x, locus)
```

Arguments

| | |
|-------|---|
| x | The database connection; an Ipddb object. |
| locus | A single locus as a string. |

Value

A character vector with all alleles of the give locus.

Examples

```
## Load the database
hla <- loadHlaData()
## Get the loci
loci <- getLoci(hla)
## Get alleles of a locus
alleles <- getAlleles(hla, loci[1])
```

getClosestComplete, IpdDb-method
Get closest full-length sequence

Description

Get the sequence of the closest allele which for which a full-length sequence is available.

Usage

```
getClosestComplete(x, allele, locus = NULL)
```

Arguments

| | |
|--------|--|
| x | The database connection; an IpdDb object. |
| allele | A single allele as a string. |
| locus | optional parameter used if the allele identifier is not found. |

Value

A [Biostrings:DNAStringSet](#) object with the sequence of the closest full-length allele.

Examples

```
## Load the database
hla <- loadHlaData()
## Get the loci
loci <- getLoci(hla)
## Get alleles of a locus
alleles <- getAlleles(hla, loci[1])
alleleOfInterest <- alleles[1]
## Get the closest complete sequence
seqs <- getClosestComplete(hla, alleleOfInterest, loci[1])
```

getLoci, IpdDb-method *Get loci*

Description

Get all available loci of the KIR or HLA database

Usage

```
getLoci(x)
```

Arguments

x The database connection; an [IpdDb](#) object.

Value

A vector of available loci in the database.

Examples

```
## Load the database
hla <- loadHlaData()
## Get the loci
loci <- getLoci(hla)
```

getReference, IpdDb-method

Get reference sequences

Description

Get the reference sequences for alleles.

Usage

```
getReference(x, allele)
```

Arguments

x The database connection; an [IpdDb](#) object.
allele The alleles of interest as a character vector.

Value

A [Biostrings:DNAStringSet](#) object with all references.

Examples

```
## Load the database
hla <- loadHlaData()
## Get the loci
loci <- getLoci(hla)
## Get alleles of a locus
alleles <- getAlleles(hla, loci[1])
allelesOfInterest <- alleles[1:10]
## Get the sequences
seqs <- getReference(hla, allelesOfInterest)
```

getStructure, IpdDb-method
Get gene structures

Description

Get the gene structures for alleles.

Usage

```
getStructure(x, allele)
```

Arguments

x The database connection; an [IpdDb](#) object.
allele The alleles of interest as a character vector.

Value

A [GenomicRanges:GRanges](#) object with all gene structures.

Examples

```
## Load the database  
hla <- loadHlaData()  
## Get the loci  
loci <- getLoci(hla)  
## Get alleles of a locus  
alleles <- getAlleles(hla, loci[1])  
allelesOfInterest <- alleles[1:10]  
## Get the structures  
seqs <- getStructure(hla, allelesOfInterest)
```

IpdDb-class *The database class for storing allele data from IPD.*

Description

This class extends the [AnnotationDbi::AnnDbObj-class](#) object by higher level methods for sequence and annotation retrieval. blubb

Usage

```

columns(x)

keytypes(x)

keys(x, keytype, ...)

select(x, keys, columns, keytype, ...)

```

Arguments

| | |
|---------|---|
| x | the IpdDb object |
| keytype | The keytype for which the keys are retrieved |
| ... | Additional arguments. Not used now. |
| keys | The keys for which columns should be selected by select() |
| columns | The columns to retrieve by select |

Value

character vector (keys, columns, keytypes) or a data.frame (select).

Slots

```

getDbVersion() Get the version of the original ipd database
getLoci() get all loci from a database, see getLoci.
getReference(alleles) Get the reference sequence for alleles, see getReference.
getStructure(alleles) Get the structures of alleles, see getStructure.
getClosestComplete(allele) Get the closest full-length reference sequence of one allele, see getClosestComplete.
getAlleles(locus) Get all alleles of a locus, see getAlleles.

```

See Also

[AnnotationDbi::AnnDbObj-class](#)

Examples

```

## load the data
hla <- loadHlaData()
## get all valid keytypes
kts <- keytypes(hla)
## get all valid columns
cols <- columns(hla)
## get the keys of one keytype
kt <- kts[1]
keys <- keys(hla, kt)
## Get data of the two first columns for the first 10 keys

```

```
cols <- cols[1:10]
res <- select(hla, keys, cols, kt)
```

| | |
|--------------|--|
| ipdDbPackage | <i>Get allele information from IPD</i> |
|--------------|--|

Description

This package holds the IPD IMGT/HLA and IPD KIR database. All alleles are accessible using the `select`, `columns`, `keys` and `keytypes` methods of the `AnnotationDbi` package of `bioconductor`.

Details

Included data are:

Allele names

p-groups

g-groups

cwd_status

completeness status

gene structure

reference sequences

closest full-length allele

| | |
|-------------|---------------------------------------|
| loadHlaData | <i>Load the IPD IMGT/HLA database</i> |
|-------------|---------------------------------------|

Description

Load the IPD IMGT/HLA database

Usage

```
loadHlaData(version = "Latest")
```

Arguments

| | |
|---------|---|
| version | Either a valid version of the IPD IMGT/HLA database or "Latest" to fetch the latest version |
|---------|---|

Value

an `IpdDb` object containing the database.

Examples

```
## Load the HLA database  
hla <- loadHlaData()
```

| | |
|-------------|----------------------------------|
| loadKirData | <i>Load the IPD KIR database</i> |
|-------------|----------------------------------|

Description

Load the IPD KIR database

Usage

```
loadKirData(version = "Latest")
```

Arguments

| | |
|---------|--|
| version | Either a valid version of the IPD KIR database or "Latest" to fetch the latest version |
|---------|--|

Value

an [IpdDb](#) object containing the database.

Examples

```
## Load the KIR database  
kir <- loadKirData()
```

Index

.IpdDb (IpdDb-class), 5

Biostrings:DNAStrngSet, 3, 4

columns (IpdDb-class), 5
columns, IpdDb-method (IpdDb-class), 5

GenomicRanges:GRanges, 5
getAlleles, 6
getAlleles (getAlleles, IpdDb-method), 2
getAlleles, IpdDb-method, 2
getClosestComplete, 6
getClosestComplete
 (getClosestComplete, IpdDb-method),
 3
getClosestComplete, IpdDb-method, 3
getLoci, 6
getLoci (getLoci, IpdDb-method), 3
getLoci, IpdDb-method, 3
getReference, 6
getReference
 (getReference, IpdDb-method), 4
getReference, IpdDb-method, 4
getStructure, 6
getStructure
 (getStructure, IpdDb-method), 5
getStructure, IpdDb-method, 5

IpdDb, 2–5, 7, 8
IpdDb (IpdDb-class), 5
IpdDb-class, 5
ipdDbPackage, 7
ipdDbPackage-package (ipdDbPackage), 7

keys (IpdDb-class), 5
keys, IpdDb-method (IpdDb-class), 5
keytypes (IpdDb-class), 5
keytypes, IpdDb-method (IpdDb-class), 5

loadHlaData, 7
loadKirData, 8

select (IpdDb-class), 5
select, IpdDb-method (IpdDb-class), 5