

Pre-Processing for the Zebrafish RNA-Seq Gene-Level Counts

Davide Rissò

Modified: April 13, 2014. Compiled: April 27, 2023.

This vignette describes the pre-processing steps that were followed for the generation of the gene-level read counts contained in the *Bioconductor* package `zebrafishRNASeq`.

Contents

1	Sample preparation and sequencing	1
2	Read alignment and expression quantitation	1
3	Loading the zebrafish data into <i>R</i>	2
4	Session info	2

1 Sample preparation and sequencing

Olfactory sensory neurons were isolated from three pairs of gallein-treated and control embryonic zebrafish pools and purified by fluorescence activated cell sorting (FACS) [1]. Each RNA sample was enriched in poly(A)+ RNA from 10–30 ng total RNA and 1 μ L (1:1000 dilution) of Ambion ExFold RNA Spike-in Control Mix 1 was added to 30 ng of total RNA before mRNA isolation. cDNA libraries were prepared according to manufacturer's protocol. The six libraries were sequenced in two multiplex runs on an Illumina HiSeq2000 sequencer, yielding approximately 50 million 100bp paired-end reads per library.

2 Read alignment and expression quantitation

We made use of a custom reference sequence, defined as the union of the zebrafish reference genome (Zv9, downloaded from Ensembl [2], v. 67) and the ERCC spike-in sequences (<http://tools.invitrogen.com/downloads/ERCC92.fa>). Reads were mapped with TopHat [3] (v. 2.0.4), with the following parameters,

```
--library-type=fr-unstranded -G ensembl.gtf --transcriptome-index=transcript --no-novel-juncs
```

where `ensembl.gtf` is a GTF file containing Ensembl gene annotation.

Gene-level read counts were obtained using the `htseq-count` python script [4] in the “union” mode and Ensembl (v. 67) gene annotation.

After verifying that there were no run-specific biases, we used the sums of the counts of the two runs as the expression measures for each library.

3 Loading the zebrafish data into *R*

To load the gene-level read counts into *R*, simply type

```
library(zebrafishRNASeq)
data(zfGenes)

head(zfGenes)

##          Ctl1 Ctl3 Ctl5 Trt9 Trt11 Trt13
## ENSDARG000000000001 304 129 339 102   16   617
## ENSDARG000000000002 605 637 406  82   230 1245
## ENSDARG000000000018 391 235 217 554   451 565
## ENSDARG000000000019 2979 4729 7002 7309 9395 3349
## ENSDARG000000000068   89 356   41 149    45   44
## ENSDARG000000000069  312 184  844 269   513 243
```

The ERCC spike-in read counts are in the last rows of the same matrix and can be retrieved in the following way.

```
spikes <- zfGenes[grep("ERCC", rownames(zfGenes)),]
head(spikes)

##          Ctl1 Ctl3 Ctl5 Trt9 Trt11 Trt13
## ERCC-00002 97227 38556 68367 148331 169360 100974
## ERCC-00003 10925 6240 11156 36652 21184 21841
## ERCC-00004 379182 179870 256130 679783 529085 311169
## ERCC-00009 2452 1183 1042 1895 3520 1252
## ERCC-00012    0    0    0    0    0    0
## ERCC-00013   89    8    0   205    21     3
```

The typical use of this dataset is the identification of differentially expressed genes between control (Ctl) and treated (Trt) samples. For additional details, exploratory analysis, and normalization of the zebrafish data see [5, 6]. The data are used as a case study for the *Bioconductor* package *RUVSeq*.

4 Session info

```
toLatex(sessionInfo())
```

- R version 4.3.0 RC (2023-04-18 r84287), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_GB, LC_COLLATE=C, LC_MONETARY=en_US.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_US.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_US.UTF-8, LC_IDENTIFICATION=C
- Time zone: America/New_York
- TZcode source: system (glibc)
- Running under: Ubuntu 22.04.2 LTS
- Matrix products: default

Pre-Processing for the Zebrafish RNA-Seq Gene-Level Counts

- BLAS: /home/biocbuild/bbs-3.18-bioc/R/lib/libRblas.so
- LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.10.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: zebrafishRNASeq 1.21.0
- Loaded via a namespace (and not attached): BiocManager 1.30.20, BiocStyle 2.29.0, cli 3.6.1, compiler 4.3.0, digest 0.6.31, evaluate 0.20, fastmap 1.1.1, highr 0.10, htmltools 0.5.5, knitr 1.42, rlang 1.1.0, rmarkdown 2.21, tools 4.3.0, xfun 0.39, yaml 2.3.7

References

- [1] T. Ferreira, S. R. Wilson, Y. G. Choi, D. Risso, S. Dudoit, T. P. Speed, and J. Ngai. Silencing of odorant receptor genes by G Protein $\beta\gamma$ signaling ensures the expression of one odorant receptor per olfactory sensory neuron. *Neuron*, 81:847–859, 2014.
- [2] P. Flicek, M. R. Amode, D. Barrell, K. Beal, S. Brent, D. Carvalho-Silva, P. Clapham, G. Coates, S. Fairley, S. Fitzgerald, et al. Ensembl 2012. *Nucleic Acids Research*, 40(D1):D84–D90, 2012.
- [3] C. Trapnell, L. Pachter, and S. L. Salzberg. TopHat: discovering splice junctions with RNA-Seq. *Bioinformatics*, 25(9):1105–1111, 2009.
- [4] S. Anders, P. T. Pyl, and W. Huber. HTSeq – A Python framework to work with high-throughput sequencing data. *bioRxiv preprint*, 2014. doi:10.1101/002824.
- [5] D. Risso, J. Ngai, T.P. Speed, and S. Dudoit. Using controls for the normalization of RNA-Seq data. *Nature Biotechnology*, 2014. Accepted.
- [6] D. Risso, J. Ngai, T.P. Speed, and S. Dudoit. The role of spike-in standards in the normalization of RNA-seq. In D. Nettleton and S. Datta, editors, *Statistical Analysis of Next Generation Sequence Data*. Springer, 2014.